

PRATTO

STM-SL

Overview

High-quality fixture with die-cast aluminum body, efficient LED module, and anti-glare design. Available in various wattages, beam angles, and color temperatures for versatile applications.




Family Range


| Code        | Power | Dimension   |
|-------------|-------|-------------|
| SLM-2820-SL | 12W   | Ø120*H152mm |

Parameters

|                       |                    |
|-----------------------|--------------------|
| Efficiency            | 110lm/W            |
| CRI                   | 95                 |
| Adjustable            | Yes                |
| Power Factor          | 0.5                |
| Input Voltage         | AC220-240V 50/60Hz |
| Operating Temperature | -20° to 60°        |
| Working Hours         | 50,000 Hrs.        |
| IP RATING             | IP66               |



Specification

|                      |                                                                                                                                                                                                                                                                   |
|----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| LED CHIP             | CREE                                                                                                                                                                                                                                                              |
| FINISH               | BK                                                                                                                                                                                                                                                                |
| MATERIAL DESCRIPTION | HOUSING: DIE CAST ALUMINIUM<br>DIFFUSER: TEMPERED CLEAR GLASS WITH OPTICAL LENS                                                                                                                                                                                   |
| BEAM ANGLE           | 30°,60°,90°                                                                                                                                                                                                                                                       |
| DIMMING OPTION       |    |
| PHOTOMETRIC          |                                                                                                                                                                              |

Application

- 1. Garden Beds and Flower Borders
- 2. Pathways and Walkways
- 3. Lawn and Grass Areas
- 4. Trees and Shrubs
- 5. Outdoor Seating Areas
- 6. Water Features
- 7. Statues and Sculptures
- 8. Architectural Features
- 9. Perimeter Lighting
- 10. Outdoor Kitchen and Cooking Areas
- 11. Deck and Deck Stairs

Drawing

Unit: MM

