



STELLMORE
Italia



TERRA-2

STM-SL

Overview

High-quality fixture with die-cast aluminum body, efficient LED module, and anti-glare design. Available in various wattages, beam angles, and color temperatures for versatile applications.



Family Range


Code	Power	Dimension
SLM-2821-SL	12W	Ø115*H170mm

Parameters

Efficiency	110lm/W
CRI	95
Adjustable	Yes
Power Factor	0.5
Input Voltage	AC220-240V 50/60Hz
Operating Temperature	-20° to 60°
Working Hours	50,000 Hrs.
IP RATING	IP66



Specification

LED CHIP	CREE
FINISH	BK
MATERIAL DESCRIPTION	HOUSING: DIE CAST ALUMINIUM WITH ABS PLASTIC (SPIKE) AND ALUMINIUM BASE DIFFUSER: TENPERED CLEAR GLASS WITH OPTICAL LENS
BEAM ANGLE	40°,60°,90°
DIMMING OPTION	-
PHOTOMETRIC	

Application

- 1. Garden Beds and Flower Borders
- 2. Pathways and Walkways
- 3. Lawn and Grass Areas
- 4. Trees and Shrubs
- 5. Outdoor Seating Areas
- 6. Water Features
- 7. Statues and Sculptures
- 8. Architectural Features
- 9. Perimeter Lighting
- 10. Outdoor Kitchen and Cooking Areas
- 11. Deck and Deck Stairs

Drawing

Unit: MM

