F · direct p-html in the PDF template (no partial)

Direct **bold** p-html in the PDF template itself — no partial involved.

Template directive matrix

A · direct p-for + interpolation

- Alpha
- Beta
- Gamma

B · template p-for + interpolation

- Alpha
- Beta
- Gamma

C · single element p-html (no loop)

One line with **bold** and *italic* spans.

D · template p-for + p-html

- Alpha — **bold** emphasis
- Beta — **bold** emphasis
- Gamma — **bold** emphasis

E · direct p-for + p-html (co-located)

- Alpha — **bold** emphasis
- Beta — **bold** emphasis
- Gamma — **bold** emphasis

G · inline span inside a block (control)

Prefix text **inline span** then suffix — should stay on one line.

H · flex: plain text item + flex-grow rule

Section label

I · flex: nested inline span + text + rule (the CV heading pattern)

Experience

J · flex row: label + right-aligned value (the CV aside pattern)

Organisation name Right-aligned date

K · raw inline <svg>

green dot via raw inline svg

L · piko:svg inlined from an asset

S · p-html wrapping multi-word bold in a flex column

- Created a golden path for developers by standardising Helm charts and CI/CD pipelines, which enabled **developer self-service** and reduced deployment friction across the team.

aside

M · p-if (show / hide)

VISIBLE — p-if true rendered this line.

N · :class bound from state

Coloured via a state-bound class binding.

O · p-class object syntax

Coloured via a toggled p-class.

P · flex gap

One Two Three

Q · CSS variable for size + border colour

Sized 18px and blue-bordered via CSS variables.

R · literal inline <b> / (written in template, not p-html)

Plain text with **literal bold** and *literal italic* in the template.