

BEATE OLDENDORFF - Bulk carrier

Shipbuilder: Oshima Shipbuilding Co., Ltd	S
Vessel's name:Beate Oldendorff	V
Owner/Operator: Oldendorff Carriers GmbH &	C
Co. KG	
Designer: Oshima Shipbuilding Co., Ltd.	D
Country:Japan	
Flag:Madeira	
IMO number: 9853022	IN
Total number of sister ships already completed	T
(excluding ship presented):2	(6
Total number of sister ships still on order:Nil	

Beate Oldendorff was ordered from Japan's Oshima shipyard in March 2016 by German bulker specialist Oldendorff Carriers as one of three ships, all for virtually simultaneous delivery in 2020. They form part of an extensive fleet renewal programme with new vessels being built in Chinese and Japanese yards.

The three ships in the series, Beate Oldendorff, Benjamin Oldendorff and Britta Oldendorff (all of which are 62,500dwt), and larger vessel Dietrich

The three ships in the series, Beate Oldendorff, Benjamin Oldendorff and Britta Oldendorff (all of which are 62,500dwt), and larger vessel Dietrich Oldendorff were christened in a joint naming ceremony in January 2020. All four vessels were delivered on time two to three months later.

Oldendorff describes the vessel as a 'super-eco Ultramax', which is based on the popular Oshima-

Oldendorff describes the vessel as a 'super-eco Ultramax', which is based on the popular Oshima-62k design modified with several upgrades to suit the owners operating strategies. Typical in the profiles of this highly versatile type of vessel, there are five holds and hatches. The ship has an loa of 200m, a Panamax beam of 32.26m, depth of 18.97m and draught of 13.35m.

The holds are CO₂ fitted and have strengthened tanktops allowing 25tonnes/m² in holds 1 to 4 and 26tonnes/m² in hold 5. When carrying heavy cargoes, holds 2 and 4 can be empty. There are cement ports in the hatches allowing for loading of grain or cement by pumps. Cargo handling gear consists of four electro-hydraulic cranes with a capacity of 30tonnes and a radius of 26m. Total grain capacity is 79,506m³.

capacity is 79,506m³.


Power to move the ship at a service speed of 14knots is provided by a Kawasaki-built MAN B&W 6S50ME-B9.5 engine series with a 7,220kW output at 94rpm. There are three Daihatsu gensets each producing 530kW at 900rpm. All gensets and the main engine can run on HFO and are connected to a Yara scrubber system allowing the vessel to meet the latest SOx regulations.

TECHNICAL PARTICULARS

Length oa:	199.995m
Length bp:	196m
Breadth moulded:	32.26m
Depth moulded	
to main deck:	18.97m
to upper deck:	18.97m
Width of double skin side: Single hull type for all	cargo hold
311	
Draught	
scantling:	13.35m
Gross:	34,909gt
Deadweight	
scantling:	62,623t
	20. 12
Speed, service:	.14.5knots
Cargo capacity (m3)	
Grain:	79,506
Bunkers (m³)	124210 2420 2420
Heavy oil:	1.652m
Diesel oil:	367
Diesel oil:	33.235
Classification society and notations:	Nippon
MC*/CCD DC A DC VII CDAD	alji Kyokai
WIDT FOR DO MC) (FCD) (IMI	20, PSPC-
NS*(CSR, BC-A, BC-XII, GRAB WBT, EQ C DG, NC) (ESP) (IW	S) (PSCM)
(IHM), (SOx(EGCS)), MNS*(M0), Str	engthened
(IHM), (SOx(EGCS)), MNS*(Mo), Str for heavy cargo loading where hold	engthened No.2 and
(IHM), (SOx(EGCS)), MNS*(M0), Str	engthened d No.2 and , G/E(Nos.
(IHM), (SOx(EGCS)), MNS*(M0), Str for heavy cargo loading where hole 4 may be empty, (SOx-EGCS-M/E	engthened No.2 and
(IHM), (SOx(EGCS)), MNS*(M0), Str for heavy cargo loading where hole 4 may be empty, (SOx-EGCS-M/E Propulsion	engthened d No.2 and , G/E(Nos.
(IHM), (SOx(EGCS)), MNS*(M0), Str for heavy cargo loading where hole 4 may be empty, (SOx-EGCS-M/E Propulsion Main engine(s)	engthened d No.2 and , G/E(Nos. 1,2,3))
(IHM), (SOx(EGCS)), MNS*(M0), Str for heavy cargo loading where hole 4 may be empty, (SOx-EGCS-M/E Propulsion Main engine(s) Design:	engthened d No.2 and , G/E(Nos. 1,2,3))
(IHM), (SOx(EGCS)), MNS*(M0), Str for heavy cargo loading where hole 4 may be empty, (SOx-EGCS-M/E Propulsion Main engine(s) Design:	engthened d No.2 and , G/E(Nos. 1,2,3)) Industries 60ME-B9.5
(IHM), (SOx(EGCS)), MNS*(M0), Str for heavy cargo loading where hole 4 may be empty, (SOx-EGCS-M/E Propulsion Main engine(s) Design:	engthened d No.2 and , G/E(Nos. 1,2,3)) Industries iOME-B9.5 Industries,
(IHM), (SOx(EGCS)), MNS*(M0), Str for heavy cargo loading where hole 4 may be empty, (SOx-EGCS-M/E Propulsion Main engine(s) Design:	engthened d No.2 and , G/E(Nos. 1,2,3)) Industries OME-B9.5 Industries, Ltd.
(IHM), (SOx(EGCS)), MNS*(M0), Str for heavy cargo loading where hole 4 may be empty, (SOx-EGCS-M/E Propulsion Main engine(s) Design:	engthened I No.2 and , G/E(Nos. 1,2,3)) Industries OME-B9.5 Industries, Ltd.
(IHM), (SOx(EGCS)), MNS*(M0), Str for heavy cargo loading where hole 4 may be empty, (SOx-EGCS-M/E Propulsion Main engine(s) Design:	engthened I No.2 and , G/E(Nos. 1,2,3)) Industries OME-B9.5 Industries, Ltd.
(IHM), (SOx(EGCS)), MNS*(M0), Str for heavy cargo loading where hole 4 may be empty, (SOx-EGCS-M/E Propulsion Main engline(s) Design:	engthened I No.2 and , G/E(Nos. 1,2,3)) Industries OME-B9.5 Industries, Ltd.
(IHM), (SOx(EGCS)), MNS*(M0), Str for heavy cargo loading where hole 4 may be empty, (SOx-EGCS-M/E Propulsion Main engine(s) Design:	engthened if No.2 and , G/E (Nos. 1,2,3)) Industries oME-B9.5 industries, Ltd
(IHM), (SOx(EGCS)), MNS*(M0), Str for heavy cargo loading where hole 4 may be empty, (SOx-EGCS-M/E Propulsion Main engine(s) Design:	engthened I No.2 and G/E(Nos. 1,2,3)) Industries 60ME-B9.5 Industries, Ltd. 1
(IHM), (SOx(EGCS)), MNS*(M0), Str for heavy cargo loading where hole 4 may be empty, (SOx-EGCS-M/E Propulsion Main engine(s) Design:	engthened I No.2 and G/E(Nos. 1,2,3)) Industries 60ME-B9.5 Industries, Ltd. 1
(IHM), (SOx(EGCS)), MNS*(M0), Str for heavy cargo loading where hole 4 may be empty, (SOx-EGCS-M/E Propulsion Main engline(s) Design:	engthened i No.2 and , G/E (Nos. 1,2,3)) Industries oME-B9.5 industries, Ltd
(IHM), (SOx(EGCS)), MNS*(M0), Str for heavy cargo loading where hole 4 may be empty, (SOx-EGCS-M/E Propulsion Main engine(s) Design:	engthened if No.2 and Control of No.2 and Cont
(IHM), (SOx(EGCS)), MNS*(M0), Str for heavy cargo loading where hole 4 may be empty, (SOx-EGCS-M/E Propulsion Main engine(s) Design:	engthened if No.2 and Control of No.2 and Cont
(IHM), (SOx(EGCS)), MNS*(M0), Str for heavy cargo loading where hole 4 may be empty, (SOx-EGCS-M/E Propulsion Main engine(s) Design:	engthened if No.2 and Control No.2 and C
(IHM), (SOx(EGCS)), MNS*(M0), Str for heavy cargo loading where hole 4 may be empty, (SOx-EGCS-M/E Propulsion Main engine(s) Design:	engthened i No.2 and , G/E (Nos. 1,2,3)) Industries oME-B9.5 industries, Ltd
(IHM), (SOx(EGCS)), MNS*(M0), Str for heavy cargo loading where hole 4 may be empty, (SOx-EGCS-M/E Propulsion Main engine(s) Design:	engthened i No.2 and , G/E (Nos. 1,2,3)) Industries oME-B9.5 industries, Ltd

Type of fuel:HFO Alternator make/type:Nishishiba Electric
Exhaust-gas scrubbing equipment Manufacturer:Yara Marine Technologies AS Type:
Boilers Number: 1 Type: Vertical cylindrical composite type Make: Osaka Boiler Mfg.
Deck machinery Cargo cranes/cargo gear Number: 4 Make: Iknow Machinery Type: Jib type Performance: 30t x 26m
Mooring equipment Number: 2 mooring winch, 2 windlass/ mooring winch Make:
Type:Electro-hydraulic
Special lifesaving equipment Number of each and capacity: 1 free-fall lifeboat / 25 persons Make:Shigi Shipbuilding Type:F.R.P. totally enclosed
Hatch covers Design: Iknow Machinery Manufacturer: Iknow Machinery Type: Weather-tight folding type
Ballast control system Make:Nakakita Seisakusyo Type:Multi control panel
Ballast water treatment system Make:Techross Inc.
Complement 8 Crew: 13 Supernumaries/Spare: 4
Navigation and other equipment Bridge control system Make:
Radars Number: 2 Make: Furuno Electric
Fire detection system Make:
Make/Type: Air Water Safety Service Inc. / CO ₂ fire extinguishing system Engine room:
Make/Type: Air Water Safety Service Inc. / CO ₂ fire extinguishing system Cabins: As per rule requirement Public spaces: As per rule requirement
Waste disposal plant Waste handled: Garbage and waste oil
Incinerator Make:Sunflame
Waste shredder/crusher Make:Mitsuboshi Chuki Mfq.
Sewage plant Make:Taiko Kikai Industries
Efficiency Attained EEDI value:29.5%
Contract date: March 2016 Delivery date:

BEATE OLDENDORFF



SIGNIFICANT SHIPS OF 2020