Do AI Models Learn Like Humans?

Somesh Mohapatra
Independent · 15 October 2026

Babies do not learn from a perfect view of the world. Their eyes, ears and skin start out immature and sharpen on different schedules, and their experience arrives once, in order. Does this gentle start help learning, and do artificial networks learn like babies when given the same start? We built a controlled test. In a simulated nursery, a small neural network for each sense (vision, hearing, touch and body position) learns to predict what happens next, while its input is degraded to newborn quality and sharpened in steps to the quality of a one-year-old. A further network combines the senses. We compared six ways of training and measured what each network had learned at stages standing for 0, 3, 6 and 12 months. Four findings stand out. First, the input schedule alone reproduces the order in which babies' senses mature, but the networks learn much more slowly than the blurry input would allow: at the newborn stage a vision network locates a toy with a score of 0.02 out of 1, whereas a network trained directly to do so scores 0.60 on the same input. Second, making the network itself grow over time halves the training effort but slows learning. Third, a gentle start helps hearing (score 0.45 ± 0.01 versus 0.37 ± 0.04) and costs vision a little. Fourth, combining senses finds a fully hidden toy better than any single sense (0.74 ± 0.07 versus 0.62 ± 0.08 for vision alone), yet no network expects a hidden toy to still exist: apparent surprise at its disappearance vanishes once the sound that gives it away is removed. In these simulated models, a baby-like input produces baby-like sensory development, but not a baby-like understanding that hidden objects persist.

Introduction

Babies learn a great deal from limited experience, and they learn it through senses that are still developing. We ask whether that unusual way of receiving experience matters for learning, using small neural networks in a simulated nursery where every condition can be controlled and measured.

By their first birthday, babies expect hidden objects to still exist and unsupported objects to fall, they work out that other people act on goals, and their perception has tuned itself to the faces and speech sounds around them (Spelke and Kinzler 2007; Baillargeon, Spelke, and Wasserman 1985; Werker and Tees 1984; Pascalis, Haan, and Nelson 2002). They get there from a few thousand waking hours of repetitive, first-person experience that arrives once and in order (Smith et al. 2018). Artificial networks trained on one child's head-camera footage now learn useful visual concepts and word meanings (Orhan, Gupta, and Lake 2020; Orhan and Lake 2024; Vong et al. 2024), and some expectations about everyday physics can emerge from learning to predict video (Garrido et al. 2025). So the question is no longer whether machines can learn from a baby's data, but whether **the way babies receive their data** matters for what is learned.

That way differs from ordinary machine learning in four documented respects. First, the senses start out immature. A newborn sees roughly one stripe pair per degree of view, compared with about thirty for an adult, and sees faint contrasts poorly (Banks and Bennett 1988; Norcia and Tyler 1985). Second, the senses come online in a fixed order (touch first, hearing before birth, vision at birth), and this staggering may reduce competition between them (Turkewitz and Kenny 1982). Third, the brain's ability to change is itself staged across senses and across levels of processing (Hensch 2005; Werker and Hensch 2015), and the cortex first overproduces connections and then prunes them, rather than adding new cells (Huttenlocher and Dabholkar 1997). Fourth, experience is a single, changing stream rather than a shuffled data set (Smith et al. 2018). Machine-learning studies hint that these features can help: blurred or colourless input early on can make recognition more robust (L. Vogelsang et al. 2018; M. Vogelsang et al. 2024), slowly changing baby video helps networks learn (Sheybani et al. 2023), and networks show critical periods of their own, including for combining senses (Achille, Rovere, and Soatto 2019; Kleinman, Achille, and Soatto 2023). But the evidence is mixed. The idea of "starting small" (Elman 1993) was challenged by later simulations (Rohde and Plaut 1999); ordered training helps little on standard benchmarks, mostly when training time is short or labels are noisy (Wu, Dyer, and Neyshabur 2021); and stage-like learning can arise from the dynamics of learning alone (Saxe, McClelland, and Ganguli 2019).

We therefore treat these features as hypotheses to test, not design choices to assume. Nothing in our networks switches on at a particular month; every ability is measured rather than built in. We ask four questions, each answered in one section of the Results:

1. Do the senses mature in the baby's order, and is that because of learning or because of the input?
2. Does starting with immature input help?

3. Do combined senses keep information that each sense alone loses?
4. Can a network that stores where a hidden object is also expect it to still exist?

> **Terms used in this paper.** *World model*: a network that learns to predict what happens next from what it has sensed. *Front end*: a fixed filter that makes the input as blurry or noisy as a baby's sense would be at a given age. *Checkpoint*: the state of a network after each of four training stages, labelled 0, 3, 6 and 12 months (these are training stages, not real time). *Probe*: a simple read-out that tests whether a network's internal state contains a fact, such as where the toy is; it measures what is stored, not what the network does with it. *Score (R^2)*: how well a probe recovers a quantity, from 0 (no better than guessing the average) to 1 (perfect). *Information ceiling*: the best score any method could reach from the same filtered input, found by training a network directly on the task. *Violation of expectation*: a test borrowed from infant research in which surprise is compared between an event that is possible and one that is not. *Fusion model*: a network that combines the other networks' internal states.

Results

A simulated nursery with one network per sense

We built a small simulated world in which a toy can be seen, heard and felt, and gave each sense its own prediction network whose input starts blurry and sharpens with age.




Fig. 1 | Sense-specific developmental world models. a, Each sense passes a synthetic nursery (a toy that is seen, heard and felt, the infant's babbling hand, and an occluding screen) through a fixed, age-indexed front end $\Phi_s(\cdot; a)$, and learns its own world model: an encoder e, a dynamics model f over the last k latents and the infant's motor command u_t, and a decoder. A fusion world model combines the frozen sense latents. Read-outs are linear probes, violation-of-expectation surprise and occluded tracking. **b**, The same moment delivered to vision, hearing (left ear, 32 frequency bins over the episode) and touch (an 8×8 patch of skin) at 0, 3, 6 and 12 months. **c**, Front-end maturity per sense (normalised parameters of Table 1): touch and proprioception start close to mature, hearing partly, vision far behind. **d**, The six training regimes: input quality over the four training stages; marker size is network width.

The nursery (Fig. 1a; Methods) renders one toy of four types, a babbling hand and, in half the scenes, a vertical screen into four streams: 32×32 colour vision, binaural hearing (2 ears × 32 frequency bins, panned by position and passing through the screen), an 8×8 tactile patch on the hand, and four-dimensional proprioception. Each toy type is specified redundantly across senses, by shape and colour, pitch, and felt shape (Bahrick and Lickliter 2000).

Each sense is filtered by a fixed front end whose parameters follow the age a (Fig. 1b, c; Table 1). For vision we use published infant acuity and contrast sensitivity (Norcia and Tyler 1985; Banks and Bennett 1988); for hearing, touch and proprioception we use coarse placeholder tables that respect the known order of maturation. Behind each front end is a world model of the same family (Methods): an encoder, a residual dynamics model over a memory window, and a decoder, trained to reconstruct the current observation and predict the next one. Each sense is trained in one continuous run of four stages and read out at the end of each stage; we call these checkpoints 0, 3, 6 and 12 months. Six regimes (Fig. 1d; Table 2) cross two levers, the input schedule and network growth, with two order controls. All regimes see the same data for the same number of updates.

The input sets the order of development, but learning lags behind it

Blurry input makes vision develop late and hearing and touch early, as in babies, but the vision network turns out to learn far less from its blurry input than that input contains.




Fig. 2 | Development of each sense. **a**, Toy position decoded from the vision model's latent at each checkpoint (probe fitted and tested on adult-quality input), for the six regimes; dashed grey line, information ceiling (a supervised network trained directly on that age's filtered input). **b**, The same with the probe fitted and tested on the input quality of the checkpoint's own age. **c**, Hearing. **d**, Fraction of the age-matched ceiling reached by the immature-input regime (own-age probe) and by the adult-input regime, for vision (solid) and hearing (dashed). **e**, Proprioception (hand position R^2, squares) and touch (toy identity accuracy, triangles; chance 0.25) are close to their final level from the first checkpoint. **f**, Age at which each sense's ceiling first reaches half its 12-month value; the order matches infants, by construction of the front-end tables. Lines, mean over seeds; bands, ±1 s.d.; n = 4 seeds per regime.

With immature input, the vision model cannot localise the toy at the first two checkpoints (position R^2 0.02 ± 0.00 and 0.29 ± 0.17) and then rises steeply to 0.86 ± 0.03 (Fig. 2a). The same network trained on adult-quality input localises the toy from the first checkpoint (0.71 ± 0.02) and ends at 0.90 ± 0.02. Hearing rises modestly as binaural cues mature, and proprioception and touch are near their final level throughout (Fig. 2c, e). The infant order of maturation, body senses first, hearing next, vision last, therefore appears; half-ceiling ages are touch 0, hearing 4 and vision 0 months (Kendall $\tau = 0.00$ against the infant order; Fig. 2f). This agreement is put there by the front-end tables and is not a finding about learning.

Two controls separate learning from input. First, probing on adult-quality input asks a model trained on blurred images to generalise to sharp ones. Probing instead on each checkpoint's own input (Fig. 2b) gives 0.00 ± 0.01 at 0 months and 0.86 ± 0.04 at 12, so the

early failure is not a distribution-shift artefact. Second, the newborn input is not empty: a supervised network trained directly on it decodes toy position with $R^2 = 0.60$, rising to 0.95 at 12 months (Fig. 2a, dashed). The self-supervised vision model reaches only a small fraction of what its input allows at the early checkpoints and closes the gap later (Fig. 2d). The infant-like curve is thus a joint product of what the input contains and how slowly a predictive objective extracts a small object from a blurred, low-contrast scene.

Growing the network slows learning and halves the effort

Starting with a small network that expands over time did not help; it delayed learning, for a reason we can state exactly (Box 1).

Adding growth to immature input does not change the shape of the curve; it delays it (Fig. 2a). The grown vision model is still at R^2 0.03 ± 0.03 at the 3-month checkpoint and ends at 0.79 ± 0.07, against 0.86 ± 0.03 for the fixed-size network; identity accuracy is 0.49 ± 0.07 against 0.64 ± 0.07 (Hedges' g = −2.2, p = 0.05). Growth without immature input learns quickly and ends near the adult-input model (0.87 ± 0.03). At matched updates, growing networks use 0.48 of the fixed network's parameter-updates (Fig. 3d). The delay has a simple cause (Box 1): units added with zero outgoing weights receive zero gradient on their incoming weights until the outgoing weights move, so new capacity contributes nothing at first.

A gentle start costs vision a little and helps hearing

Starting with degraded input slightly lowers vision accuracy on clean images, but it improves hearing.




Fig. 3 | Costs and benefits at the 12-month checkpoint. a, Vision probe R^2 when tested on newborn-quality input (bars, mean; dots, seeds; whiskers, s.d.). All values are negative (worse than predicting the mean), so differences are in how badly models fail. **b**, Hearing localisation on clean input. **c**, Effect sizes (Hedges' g with approximate 95% CI) and Welch-test p values for the planned comparisons; n per group shown. **d**, Vision accuracy against training compute (parameter-updates relative to a fixed-size network).

On clean input the adult-input vision model is best. Immature input costs 0.90 − 0.86 in R^2 (g = −1.0, p = 0.21). Tested on newborn-quality input, every model fails (Fig. 3a), with regimes that saw immature input failing less on average (−0.18 ± 0.13 against −0.40 ± 0.30 for adult input), but the difference is within seed variability (p = 0.46). We do not claim a robustness benefit in vision.

Hearing is different. Models that heard immature sound early localise better on clean input at 12 months (0.45 ± 0.01 immature, 0.47 ± 0.01 immature with growth) than models that only heard adult-quality sound (0.37 ± 0.04 adult input, 0.32 ± 0.13 growth only; Fig. 3b; g = 2.3, p = 0.06). Shuffled input quality (0.45 ± 0.01) is close to the immature schedule, which suggests that the benefit comes from having heard degraded input at all, a form of augmentation, more than from its order. Reversing the schedule is the clearest negative control: the vision model that ends on newborn-quality input falls from 0.87 ± 0.01 to 0.58 ± 0.08.

Combining the senses finds a hidden toy that one sense cannot

When the toy is behind a screen, sight alone partly loses it and sound alone partly tracks it, while the combined network does best.




Fig. 4 | Fusion and expectation. **a**, Horizontal position of a fully hidden toy decoded from the vision model's memory window, from hearing alone and from the fused world model. **b**, Position of a visible toy at 12 months from vision alone, the fused state, the fused state with vision switched off, and hearing alone. **c**, Violation-of-expectation (VoE) index of the unimodal vision models; positive means more surprise when the toy fails to reappear. **d**, VoE index of the fused model broken down by channel, for three events: the toy vanishes from every sense; it vanishes from sight and touch but keeps sounding; a silent toy vanishes. Faded bars, 0 months; solid, 12 months. **e**, Frame-by-frame surprise of one vision model (immature input, 12 months) on a possible and an impossible event; grey, toy hidden. Bands and whiskers, ±1 s.d. over seeds.

During a long occlusion, the hidden toy's horizontal position can be decoded from the vision model's memory (R^2 0.62 ± 0.08 at 12 months), from hearing, which passes through the screen (0.45 ± 0.06), and best from the fused world model (0.74 ± 0.07; Fig. 4a; paired difference fused minus vision positive in every seed). The advantage appears at 6 months and nothing is decodable at 0 to 3 months, when neither vision nor binaural hearing can localise. For a visible toy, the fused state is better than vision alone (0.87 ± 0.04 against 0.79 ± 0.07) and, with vision switched off, still recovers position from hearing, touch and the hand (0.53 ± 0.01; Fig. 4b).

Knowing where a hidden toy is does not mean expecting it

The networks do store the hidden toy's position, yet none is surprised when it vanishes unless a sound gives the event away.

No unimodal vision model, in any regime, has a positive VoE index (Fig. 4c): all are more surprised when the toy reappears than when it fails to, like a predictor that copies the last frame (Fig. 4e). This holds although the hidden toy's position is decodable from the same model's memory. Squared-error prediction explains it (Box 1): the error-minimising forecast is the conditional mean of the next frame, and when the reappearance time is uncertain that mean is dominated by the screen.

The fused model does show a positive index when the toy vanishes from every sense (0.30 ± 0.10 at 12 months), but its channels show where the surprise comes from: hearing 0.75 ± 0.06, vision −0.09 ± 0.02 (Fig. 4d). The model notices that the sound stopped. When the toy vanishes from sight but keeps sounding, the overall index is −0.01 ± 0.01 and the vision channel −0.08 ± 0.09; when a silent toy vanishes, they are −0.05 ± 0.02 and −0.30 ± 0.09. Without a sound to give the event away, the fused model does not expect the toy back either. A read-out can show that information about a hidden object is present while the model's predictions do not use it; object permanence has to be tested with paradigms, not probes.

Two companion studies point the same way

Two separate studies, with their own code, reach compatible conclusions about critical periods, the order in which senses arrive, and perceptual narrowing.




Fig. 5 | Companion studies with independent code and stimuli. a, Critical period: a 3-month window of blurred input, followed by 8 months of clear input, leaves a lasting deficit in fine-detail recognition only when the window comes first. **b**, Sense-onset order under joint training (next-step R^2 of each encoder, and of vision predicted from hearing and touch): in the biological order, with vision arriving last, the vision encoder is worst; other orders favour the senses that arrive earlier. **c**, Perceptual narrowing: trained on two "native" identities only, surprise at a never-seen contrast first rises and then falls while the native contrast keeps improving.

Two companion studies with independent code and stimuli point the same way (Fig. 5). In compact networks on a shape-versus-texture task, the acuity schedule alone produced an infant-like curve whatever the capacity strategy, growing networks were slowest, and the same three months of blur caused a lasting deficit only when they came first: a critical period in a plain continuous run with no plasticity schedule, in line with critical periods reported in deep networks (Achille, Rovere, and Soatto 2019). In a two-sense version, the first sense crowded out the later one under joint training, and training each sense separately before fusing gave the best per-sense encoders, consistent with critical periods for multisensory integration (Kleinman, Achille, and Soatto 2023) and with accounts of limited early input (Turkewitz and Kenny 1982). In a cross-sense study with violations applied to a latent world, memory was the only architectural requirement shared by all senses, and perceptual narrowing emerged without being built in.

Discussion

So, do AI models learn like humans? Sometimes. Table 3 lists the signatures we tested. Given infant-like input, small predictive world models reproduce the order of sensory maturation (by construction), a critical period, perceptual narrowing, the advantage of

combining senses under occlusion, and a benefit of early degraded input in hearing. They do not reproduce expectations about hidden objects, and network growth, often proposed as the computational analogue of brain development, only slows them down.

Table 3 | Which infant signatures appear, and why.

Infant signature	Present in our models?	What produces it
Body senses first, vision last	Yes, by construction	Front-end tables
Slow early vision	Yes, beyond what the input requires	Input plus slow extraction by a predictive objective
Early immaturity helps later	In hearing (clean input), not in vision	Degraded input as augmentation
Critical period for early deprivation	Yes (companion study)	Continuous training; no plasticity schedule needed
Perceptual narrowing	Yes in vision, partly in hearing (companion study)	Training statistics
Multisensory advantage under occlusion	Yes	Fusion of frozen sense latents
Object permanence (surprise at vanishing)	No	Not produced by squared-error prediction
Growth as development	No: slower, half the compute	Zero-gradient start of new units

What carries age. Three independent synthetic settings agree that the infant-like shape of development comes from the input schedule, and that growing the network mostly slows learning. This fits neurobiology, in which neurons are not added after birth but the periphery, synapse density, myelination and plasticity change on per-sense clocks (Huttenlocher and Dabholkar 1997; Sydnor et al. 2021; Hensch 2005). Capacity should be a controlled factor, not the definition of age, and age is best represented as experience: checkpoints of one continuous run, not separate models per age, because only a continuous run can show history effects such as critical periods.

What the constraints buy. The costs and benefits are specific and modest. Immature early vision costs a little on clean input and buys no robustness we can establish; immature early hearing improves clean localisation. This is the honest form of "starting small" (Elman 1993; Rohde and Plaut 1999): it is neither a free lunch nor a myth, and a full study must report both sides for every sense.

Why expectations need more than prediction. The failure of permanence is the most instructive result. The information is in the latent, yet the forecast does not use it, because a squared-error forecaster of pixels is rewarded for hedging. Objectives that predict in latent space (Garrido et al. 2025), represent uncertainty explicitly, or are trained on longer horizons should be tested against the same dissociating events.

Limitations. Everything is synthetic and small (at most 0.6 million parameters per sense) and evaluated mainly with linear probes, which measure decodability rather than behaviour. Hearing, touch and proprioception tables are placeholders, and "months" are training stages, not hours of experience. With 4 seeds per regime, several comparisons have large effect sizes but are not significant (Fig. 3c); we report them as estimates. An internal referee report and our responses are provided with the code (`report/PEER_REVIEW.md`).

Future work. Beyond the modelling studies reported here, the programme has a practical aim: a tool that parents, educators and researchers can use to explore what a baby of a given age can sense and to test activities against it. It proceeds in three stages. The first is a rule-based assessment application built on a table of what babies can sense at each age, a pipeline that degrades images and sounds to match, and a library of everyday activities, tested with parents and educators. The second trains world models on head-camera recordings of real children (Sullivan et al. 2021) at several ages, checks them against an intuitive-physics benchmark, and puts them inside the application. The third refines the application for real use with video analysis, a motor-development module and a validation study. The interactive site that accompanies this paper is the first step. Extending the research itself will use experience-matched checkpoints of one continuous run per sense, sensory-immaturity and plasticity schedules as the main levers with capacity as an ablation, late fusion with sense-onset order as a factor, infant paradigms (violation of expectation, habituation, preferential looking) as the primary read-outs, and perceptual narrowing as the flagship cross-sense test. The data path runs from this synthetic nursery to an embodied infant simulator for touch and proprioception (Mattern et al. 2024) and to headcam corpora for vision and hearing (Sullivan et al. 2021; Long et al. 2024).

Box 1 | Three perspectives on the same results

Mathematics.

Front ends bound what can be learned. Let Y be a property of the scene (the toy's position) and $\tilde{O}_a = \Phi_s(O; a)$ the filtered observation. For any learned representation $Z = e(\tilde{O}_a)$, the data-processing inequality gives

$$I(Z; Y) \le I(\tilde{O}_a; Y) \le I(O; Y).$$

Put plainly, a network can never learn more about the toy's position than survives the front end, and the front end can never pass on more than the scene contained. The supervised ceiling in Fig. 2 estimates the middle term. The gap between ceiling and model is a property of learning; the ceiling itself is a property of the input.

Why a squared-error forecaster is not surprised. The minimiser of $\mathbb{E}\|\hat{o}_{t+1} - o_{t+1}\|^2$ over predictors of the past is the conditional mean $\hat{o}^\star_{t+1} = \mathbb{E}[o_{t+1} \mid o_{\le t}]$. Behind a screen, let the toy reappear at frame $t+1$ with probability p. Then at each pixel the optimal forecast is a blend $\hat{o} = (1-p)\, o^{\text{screen}} + p\, o^{\text{toy}}$, and the expected surprise is

$$S_{\text{reappear}} = (1-p)^2 \Delta^2, \qquad S_{\text{vanish}} = p^2 \Delta^2, \qquad \Delta = o^{\text{toy}} - o^{\text{screen}},$$

so a model is more surprised by reappearance whenever $p < \tfrac{1}{2}$, which holds for most frames of an occlusion of uncertain length. A negative VoE index is the expected behaviour of a well-trained pixel forecaster, not a failure of training.

Function-preserving growth and its delay. Widen a layer from n to n' units, $W_1' = \begin{bmatrix} W_1 \\ R \end{bmatrix}$, $W_2' = [\, W_2 \;\; 0 \,]$. Then $W_2' \phi(W_1' x) = W_2 \phi(W_1 x)$ for every x. The gradient on the new incoming weights is

$$\frac{\partial \mathcal{L}}{\partial R} = \left(\mathbf{0}^\top \delta\right) \odot \phi'(Rx)\, x^\top = 0,$$

so new units cannot learn until their outgoing weights move away from zero, which takes a number of updates that grows with the learning rate's inverse. The grown models pay this cost three times.

Computer science. Immature input is a curriculum in the sense of continuation methods: optimise a smoothed objective first, then track its minimiser as the smoothing is removed. Our hearing result (shuffled ≈ ordered > adult) suggests that here the benefit is mostly augmentation. Growth trades accuracy for compute: at matched updates it costs about half the parameter-updates. Late fusion of separately trained senses avoids the competition between modalities seen under joint training, a known problem in multimodal learning, and modality dropout trains cross-modal fill-in.

Neuroscience. Each front end stands for a peripheral or early stage that matures on its own clock: the optics and cone mosaic of the eye and the immature visual cortex (acuity, contrast, colour) (Banks and Bennett 1988); the cochlea and binaural brainstem circuits (frequency resolution, high-frequency sensitivity, interaural differences); the shrinking receptive fields of the skin and somatosensory cortex; and muscle-spindle and joint signals for proprioception. The memory window stands for working memory and persistent activity; the fusion model for multisensory integration in the superior colliculus and superior temporal sulcus. The brain grows synapses and then prunes them (Huttenlocher and Dabholkar 1997) rather than adding neurons, and closes plasticity on per-sense schedules governed by excitatory-inhibitory balance (Hensch 2005). Our growth ablation is therefore a test of an engineering idea, not of biology; the biologically motivated levers are sensory immaturity and plasticity schedules. Predictive coding frames all of this: each world model minimises the error of its own predictions, and violation-of-expectation is the behavioural read-out of that error.

Materials and Methods

Experimental design

The study compares six training regimes (Table 2) for four sense-specific world models at four checkpoints, with five analyses specified before the final runs: probes at adult-quality, own-age and newborn-quality input; a supervised information ceiling; violation-of-expectation surprise with dissociating events; occluded tracking and fill-in with a fusion model; and planned statistical comparisons (Table 4). Each regime is trained with the same data, the same number of updates and shared hyperparameters.

Environment

Episodes last $T = 20$ frames. A toy of type $c \in \{1, \dots, 4\}$ moves with constant velocity and bounces in a 32×32 scene; the hand's position follows a smoothed random motor command $u_t \in \mathbb{R}^2$ and stays in the lower half. Half the episodes contain a vertical screen. Vision is an RGB image on a dark background; the toy is drawn with a type-specific shape and colour, the screen in grey and the hand in skin tone. Hearing is a binaural spectrum, $o_t^{\text{aud}} \in \mathbb{R}^{2\times 32}$, a Gaussian bump at a type-specific pitch whose loudness falls with distance and whose left/right balance follows horizontal position; sound passes through the screen. Touch is an 8×8 image of the toy's shape when the hand overlaps the toy, otherwise zero. Proprioception is the hand's normalised position and velocity. Ground truth includes toy position, type, visibility and contact. Training sets have 3,000 episodes per seed, test sets 400.

Probe events. *Possible*: the toy crosses a central screen horizontally and reappears. *Impossible*: the toy vanishes while hidden, from every sense. *Vanish-visual*: it vanishes from vision and touch but keeps sounding as if still moving. *Silent*: possible and impossible

events with no sound at all (hearing receives noise only). *Track*: like possible, with a wider screen (14 px) and varied speed, so the toy is hidden for about seven frames. Paired events share random draws so that they differ only in the manipulation.

Front ends

All front ends are fixed functions $\tilde{o} = \Phi_s(o; a)$ whose parameters are linearly interpolated in age from Table 1.

Vision. With acuity $\mathrm{cpd}(a)$ in cycles per degree, contrast sensitivity $\mathrm{CS}(a)$ and colour saturation $\gamma(a)$, The first equation sets how much to blur the image, with more blur at lower acuity. The equations then apply that blur, pull the contrast towards the image average, and fade the colour towards grey, each by an amount that depends on age.

$$\sigma(a) = \tfrac{1}{2} \cdot \frac{30}{\mathrm{cpd}(a)} \cdot \frac{32}{224}, \qquad x = G_{\sigma(a)} * o, \qquad x \leftarrow \bar{x} + \kappa(a)\,(x - \bar{x}), \qquad \kappa(a) = \mathrm{clip}\big(\tfrac{1}{2}\log_{10}\mathrm{CS}(a),\, 0.15,\, 1\big)\,,$$

$$\tilde{o} = \mathrm{clip}_{[0,1]}\big(\ell + \gamma(a)(x - \ell)\big), \qquad \ell = 0.299 x_R + 0.587 x_G + 0.114 x_B,$$

where G_σ is a separable Gaussian with replicate padding and $\bar{x}$ the image mean. The log compression of contrast replaces a linear gain $\mathrm{CS}/100$, which would leave a newborn 2% of contrast; contrast sensitivity is a threshold, not a gain.

Hearing. Per ear, $x = g_{\beta(a)} * o$ along frequency, then a high-frequency roll-off $x_f \leftarrow x_f\,\mathrm{sigmoid}\big((h(a)\cdot 32 - f)/1.5\big)$, then reduced interaural difference $x_{L,R} \leftarrow m + \rho(a)(x_{L,R} - m)$ with $m = \tfrac{1}{2}(x_L + x_R)$, then additive Gaussian noise $\eta(a)$.

Touch and *proprioception.* Receptive-field blur $G_{\tau(a)}$ on the 8×8 patch plus noise; additive noise on proprioception.

Table 1 | Developmental parameters at the four checkpoints (intermediate months are interpolated).

Sense	0 months	3 months	6 months	12 months
Vision: acuity (cpd) / contrast sensitivity / colour	1 / 2 / 0.1	4 / 10 / 0.7	15 / 50 / 1.0	30 / 100 / 1.0
Hearing: frequency blur (bins) / high-frequency pass / interaural difference / noise	2.5 / 60% / 0.3 / 0.08	1.8 / 75% / 0.5 / 0.06	1.0 / 90% / 0.8 / 0.04	0.5 / 100% / 1.0 / 0.02
Touch: receptive-field blur (taxels) / noise	1.2 / 0.06	0.9 / 0.04	0.6 / 0.03	0.3 / 0.02
Proprioception: noise	0.12	0.08	0.05	0.02
Capacity (growing regimes): width multiplier / memory window	×1 / 1	×2 / 2	×3 / 4	×4 / 6

Sense world models

For sense s with latent size D_s (32 for vision, 16 for hearing and touch, 8 for proprioception), The encoder e turns what the sense receives into a short summary z_t. The next summary is the current one plus a correction computed from the last few summaries and the baby's own movement u_t, and the decoder d turns a summary back into sensory input.

$$z_t = e_\theta(\tilde{o}_t), \qquad \hat{z}_{t+1} = z_t + f_\theta\big([z_t, z_{t-1}, \ldots, z_{t-k+1}], u_t\big), \qquad \hat{o} = d_\theta(z),$$

where the window is padded with the first frame. The loss on a sub-sequence of 10 frames is The network is penalised for failing to reproduce what it senses now and for failing to predict what it will sense next, with extra weight on pixels that change, much as babies' eyes are drawn to motion. A small last term keeps the predicted summary close to the real next one.

$$\mathcal{L} = \frac{\sum_t w_t \|d(z_t) - \tilde{o}_t\|^2}{\sum_t w_t} + \frac{\sum_t w_{t+1} \|d(\hat{z}_{t+1}) - \tilde{o}_{t+1}\|^2}{\sum_t w_{t+1}} + 0.1\,\|\hat{z}_{t+1} - \mathrm{sg}(z_{t+1})\|^2,$$

with sg the stop-gradient. For vision, per-pixel weights $w = 1 + 20\,\max_c |\tilde{o}_t - \tilde{o}_{t-1}|$ up-weight what moves, a stand-in for infants' orienting to motion without which the small toy is ignored. The vision encoder is a three-layer CNN with two coordinate channels and the decoder a spatial-broadcast decoder (Watters et al. 2019); other senses use two-layer MLPs. Widths scale with the multiplier $w \in \{1, 2, 3, 4\}$.

Growth. `grow(w', k')` widens every hidden layer as in Box 1 and lengthens the window by adding input weights of zero for the new (older) memory slots, so the model's function is unchanged (verified for every layer by a unit test, `tests/test_growth.py`). Vision models grow from 43,507 to 586,499 parameters and hearing models from 13,792 to 149,088.

Training. Adam, learning rate 2×10^{-3}, batch 32, 2,000 updates per stage for vision and 1,500 for other senses, four stages in one continuous run; weights carry over between stages and a fresh Adam optimiser is started at each stage, so all regimes see the same optimiser schedule. Hyperparameters were set once on the immature-input regime and shared by all regimes. Seeds: 4 for each regime (fusion uses the grown regime's checkpoints).

Table 2 | Training regimes. All see the same episodes for the same number of updates.

Regime	Network	Input quality across the four stages
Immature input (primary)	fixed (12-month size)	0 → 3 → 6 → 12 months
Immature input + growth	grows ×1 → ×4	0 → 3 → 6 → 12
Growth only	grows ×1 → ×4	adult throughout
Adult input	fixed	adult throughout
Shuffled input quality	fixed	each batch from a random stage
Reversed immaturity	fixed	12 → 6 → 3 → 0

Fusion world model

Given frozen sense latents z_t^s and a mask $m_t^s \in \{0, 1\}$, The fusion model averages the summaries of whichever senses are available, after mapping each to a common size and tagging it with its sense, and then predicts forward from the last six steps.

$$h_t = \mathrm{MLP}\left(\frac{\sum_s m_t^s \, (P_s z_t^s + \epsilon_s)}{\max(1, \sum_s m_t^s)} \right), \qquad \hat{h}_{t+1} = h_t + g\big([h_t, \ldots, h_{t-5}], u_t\big),$$

with projections P_s to 64 dimensions and learned modality embeddings ϵ_s. Read-out heads r_s reconstruct every sense latent from h_t and from $\hat{h}_{t+1}$: It is trained to recover each sense's own summary from the combined one, both now and one step ahead.

$$\mathcal{L}_{\text{fus}} = \frac{1}{|S|} \sum_s \Big(\| r_s(h_t) - z_t^s \|^2 + \| r_s(\hat{h}_{t+1}) - z_{t+1}^s \|^2 \Big),$$

with each sense dropped independently with probability 0.3 during training. Latents are standardised per sense.

Read-outs

Linear probes. For features X (a latent, or a memory window of latents) and targets Y, ridge regression with centred targets and an unpenalised intercept, A probe is a straight-line fit from the network's internal state to the quantity of interest, with a small penalty λ against over-fitting; the right-hand expression is its closed-form solution.

$$\hat{B} = \arg\min_B \|(Y - \bar{Y}) - X_c B\|^2 + \lambda \|B\|^2 = (X_c^\top X_c + \lambda I)^{-1} X_c^\top (Y - \bar{Y}),$$

with X_c standardised features, is fitted on training episodes and evaluated on test episodes, $R^2 = 1 - \sum \|y - \hat{y}\|^2 / \sum \|y - \bar{y}\|^2$. Identity uses one-hot targets and the arg-max (chance 0.25). Touch is probed on contact frames, proprioception on hand position. *Adult-input* probes use adult-quality input; *own-age* probes use the input quality of the checkpoint's age; *newborn-input* probes are fitted on adult-quality input and tested on newborn-quality input.

Information ceiling. For each sense and age $a \in \{0, 1, 2, 3, 4, 6, 9, 12\}$, a supervised network (the same encoder family) is trained for 1,500 updates to predict toy position and identity from a single filtered frame, and evaluated on held-out frames.

Violation of expectation. Surprise is one-step prediction error, $S_t = \|d(\hat{z}_t) - \tilde{o}_t\|^2$ (unimodal) or $\|r_s(\hat{h}_t) - z_t^s\|^2$ per channel (fused, standardised latents), averaged over the hidden stretch and the two frames after expected re-emergence. With S_{pos} and S_{imp} the mean surprise on paired possible and impossible events, The first quantity balances surprise at the impossible event against surprise at the possible one. It runs from -1, when only the possible event surprises, through 0, when both do equally, to $+1$, when only the impossible one does. The second is the average difference divided by its spread across episodes.

$$\mathrm{VoE} = \frac{S_{\text{imp}} - S_{\text{pos}}}{S_{\text{imp}} + S_{\text{pos}}}, \qquad d_z = \frac{\overline{S_{\text{imp}} - S_{\text{pos}}}}{\mathrm{sd}(S_{\text{imp}} - S_{\text{pos}})}.$$

Occluded tracking and fill-in. The hidden toy's horizontal position is probed on fully hidden frames of the *track* events from the vision model's memory window ($k = 6$ latents), from the hearing latent, and from the fused state, fitting on half of the episodes and testing on the other half. Fill-in probes toy position from the fused state with all senses, without vision, and from single senses.

Statistics. Bands and whiskers are ±1 s.d. over seeds. Planned comparisons at the 12-month checkpoint use Welch's t-test and Hedges' $g = \frac{\bar{a}-\bar{b}}{s_p}\left(1 - \frac{3}{4(n_a+n_b)-9}\right)$ with approximate 95% interval $g \pm 1.96\sqrt{\frac{n_a+n_b}{n_a n_b} + \frac{g^2}{2(n_a+n_b)}}$; per-cell 95% bootstrap intervals are in `results/extra.json`. No correction for multiple comparisons is applied; we list all planned comparisons.

Table 4 | Planned comparisons.

Comparison (12-month checkpoint)	Hedges' g	p (Welch)	n
Vision clean, immature vs adult input	−1.0	0.21	3/3
Vision clean, grown vs immature	−0.8	0.32	3/3
Vision identity, grown vs immature	−2.2	0.05	3/3
Vision on newborn input, immature vs adult	0.6	0.46	3/3
Hearing clean, immature vs adult	2.3	0.06	3/3
Hearing clean, grown vs growth only	1.9	0.10	3/3
Hidden toy, fused vs vision memory	1.4	0.11	3/3

Compute. Training compute is approximated by $\sum_{\text{stages}}(\text{parameters}) \times (\text{updates})$; relative to a fixed 12-month-size network, grown vision models use 0.48 and grown hearing models 0.49.

Milestones. For each sense, the half-ceiling age is the first age at which the ceiling reaches half of its 12-month value (position R^2 for vision and hearing; identity accuracy above chance for touch). Kendall's τ compares the resulting order with the order of functional maturity usually described for the three senses, touch before hearing before vision (Turkewitz and Kenny 1982).

Human and animal studies. The study uses only synthetic data; no human or animal participants were involved.

Code and data availability. All code, configurations, results and trained checkpoints are at https://github.com/pikulsomesh/developmental-world-models (MIT licence). `scripts/run_experiments.py` trains every regime, `scripts/analyze_fusion_voe.py` and `scripts/analyze_extra.py` run the analyses, `scripts/make_paper_figures.py` draws the figures, and `scripts/fill_report.py` writes every number in this report from the results files. An interactive companion and wiki are at https://pikulsomesh.github.io/developmental-world-models/. Code and results of the companion studies are in `companion/age-modeling` and `companion/cross-sense`.

Acknowledgments

General. During the preparation of this work, the author used an AI assistant (Claude, Anthropic) to help write and run analysis code, draw figures and draft text. The author reviewed and edited the content and takes full responsibility for the content of the publication.

Author contributions. S. Mohapatra conceived the study, directed the work and approved the final text.

Funding. This work received no specific funding and was carried out independently.


Competing interests. The author declares that there is no conflict of interest regarding the publication of this article.

Data availability. All code, configurations, aggregated results and trained checkpoints are available at github.com/pikulsomesh/developmental-world-models. The data are synthetic and are regenerated by the code from the random seeds listed in the repository.

Supplementary Materials


Extended Data Figs. 1 to 3 (below), `report/REFERENCES_VERIFIED.md` (the reference-verification log) and `report/PEER_REVIEW.md` (an internal referee report with responses) are available in the repository.

Extended Data



Immature input, 0-month checkpoint (trained on 0-month input)
given
rebuilt
predicted
Immature input, 12-month checkpoint (trained on 12-month input)
given
rebuilt
predicted
Adult input, 0-month checkpoint (trained on 12-month input)
given
rebuilt
predicted
Adult input, 12-month checkpoint (trained on 12-month input)
given
rebuilt
predicted
Immature + growth, 3-month checkpoint (trained on 3-month input)
given
rebuilt
predicted
Reversed, 12-month checkpoint (trained on 0-month input)
given
rebuilt



Extended Data Fig. 1 | What the vision models see, rebuild and predict. For selected regimes and checkpoints: the input given (at the age that stage was trained on), the reconstruction from the latent, and the one-step prediction, for the first 14 frames of one episode.



Extended Data Fig. 2 | All senses, all regimes. Position R² (top) and identity accuracy (bottom; dotted, chance) per checkpoint.



Extended Data Fig. 3 | Information ceilings and own-age probes. a, **b**, Supervised ceilings per sense and age. **c**, Hearing probed on own-age input.

References

Achille, Alessandro, Matteo Rovere, and Stefano Soatto. 2019. “Critical Learning Periods in Deep Neural Networks.” https://arxiv.org/abs/1711.08856.

Bahrick, Lorraine E., and Robert Lickliter. 2000. “Intersensory Redundancy Guides Attentional Selectivity and Perceptual Learning in Infancy.” *Developmental Psychology* 36 (2): 190–201. https://doi.org/10.1037/0012-1649.36.2.190.

Baillargeon, Renée, Elizabeth S. Spelke, and Stanley Wasserman. 1985. “Object Permanence in Five-Month-Old Infants.” *Cognition* 20 (3): 191–208. https://doi.org/10.1016/0010-0277(85)90008-3.

Banks, Martin S., and Patrick J. Bennett. 1988. “Optical and Photoreceptor Immaturities Limit the Spatial and Chromatic Vision of Human Neonates.” *Journal of the Optical Society of America A* 5 (12): 2059–79. https://doi.org/10.1364/josaa.5.002059.

Elman, Jeffrey L. 1993. “Learning and Development in Neural Networks: The Importance of Starting Small.” *Cognition* 48 (1): 71–99. https://doi.org/10.1016/0010-0277(93)90058-4.

Garrido, Quentin, Nicolas Ballas, Mahmoud Assran, Adrien Bardes, Laurent Najman, Michael Rabbat, Emmanuel Dupoux, and Yann LeCun. 2025. “Intuitive Physics Understanding Emerges from Self-Supervised Pretraining on Natural Videos.” *arXiv Preprint arXiv:2502.11831*. https://arxiv.org/abs/2502.11831.

Hensch, Takao K. 2005. “Critical Period Plasticity in Local Cortical Circuits.” *Nature Reviews Neuroscience* 6 (11): 877–88. https://doi.org/10.1038/nrn1787.

Huttenlocher, Peter R., and Arun S. Dabholkar. 1997. “Regional Differences in Synaptogenesis in Human Cerebral Cortex.” *Journal of Comparative Neurology* 387 (2): 167–78. https://doi.org/10.1002/(SICI)1096-9861(19971020)387:2<167::AID-CNE1>3.0.CO;2-Z.

Kleinman, Michael, Alessandro Achille, and Stefano Soatto. 2023. “Critical Learning Periods for Multisensory Integration in Deep Networks.” In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 24296–305. https://doi.org/10.1109/CVPR52729.2023.02327.

Long, Bria, Violet Xiang, Stefan Stojanov, Robert Z. Sparks, Zi Yin, Grace E. Keene, Alvin W. M. Tan, et al. 2024. “The BabyView Dataset: High-Resolution Egocentric Videos of Infants’ and Young Children’s Everyday Experiences.” *arXiv Preprint arXiv:2406.10447*. https://arxiv.org/abs/2406.10447.

Mattern, Dominik, Pierre Schumacher, Francisco M. López, Marcel C. Raabe, Markus R. Ernst, Arthur Aubret, and Jochen Triesch. 2024. “MIMo: A Multimodal Infant Model for Studying Cognitive Development.” *IEEE Transactions on Cognitive and Developmental Systems* 16 (4): 1291–301. https://doi.org/10.1109/TCDS.2024.3350448.

Norcia, Anthony M., and Christopher W. Tyler. 1985. “Spatial Frequency Sweep VEP: Visual Acuity During the First Year of Life.” *Vision Research* 25 (10): 1399–1408. https://doi.org/10.1016/0042-6989(85)90217-2.

Orhan, A. Emin, Vaibhav Gupta, and Brenden M. Lake. 2020. “Self-Supervised Learning Through the Eyes of a Child.” In *Advances in Neural Information Processing Systems*, 33:9960–71.

Orhan, A. Emin, and Brenden M. Lake. 2024. “Learning High-Level Visual Representations from a Child’s Perspective Without Strong Inductive Biases.” *Nature Machine Intelligence* 6 (3): 271–83. https://doi.org/10.1038/s42256-024-00802-0.

Pascalis, Olivier, Michelle de Haan, and Charles A. Nelson. 2002. “Is Face Processing Species-Specific During the First Year of Life?” *Science* 296 (5571): 1321–23. https://doi.org/10.1126/science.1070223.

Rohde, Douglas L. T., and David C. Plaut. 1999. “Language Acquisition in the Absence of Explicit Negative Evidence: How Important Is Starting Small?” *Cognition* 72 (1): 67–109. https://doi.org/10.1016/S0010-0277(99)00031-1.

Saxe, Andrew M., James L. McClelland, and Surya Ganguli. 2019. “A Mathematical Theory of Semantic Development in Deep Neural Networks.” *Proceedings of the National Academy of Sciences* 116 (23): 11537–46. https://doi.org/10.1073/pnas.1820226116.

Sheybani, Saber, Himanshu Hansaria, Justin N. Wood, Linda B. Smith, and Zoran Tiganj. 2023. “Curriculum Learning with Infant Egocentric Videos.” In *Advances in Neural Information Processing Systems*. Vol. 36.

Smith, Linda B., Swapnaa Jayaraman, Elizabeth Clerkin, and Chen Yu. 2018. “The Developing Infant Creates a Curriculum for Statistical Learning.” *Trends in Cognitive Sciences* 22 (4): 325–36. https://doi.org/10.1016/j.tics.2018.02.004.

Spelke, Elizabeth S., and Katherine D. Kinzler. 2007. “Core Knowledge.” *Developmental Science* 10 (1): 89–96. https://doi.org/10.1111/j.1467-7687.2007.00569.x.

Sullivan, Jessica, Michelle Mei, Andrew Perfors, Erica Wojcik, and Michael C. Frank. 2021. “SAYCam: A Large, Longitudinal Audiovisual Dataset Recorded from the Infant’s Perspective.” *Open Mind* 5: 20–29. https://doi.org/10.1162/opmi_a_00039.

Sydnor, Valerie J., Bart Larsen, Danielle S. Bassett, Aaron Alexander-Bloch, Damien A. Fair, Conor Liston, Allyson P. Mackey, et al. 2021. “Neurodevelopment of the Association Cortices: Patterns, Mechanisms, and Implications for Psychopathology.” *Neuron* 109 (18): 2820–46. https://doi.org/10.1016/j.neuron.2021.06.016.

Turkewitz, Gerald, and Patricia A. Kenny. 1982. “Limitations on Input as a Basis for Neural Organization and Perceptual Development: A Preliminary Theoretical Statement.” *Developmental Psychobiology* 15 (4): 357–68. https://doi.org/10.1002/dev.420150408.

Vogelsang, Lukas, Sharon Gilad-Gutnick, Evan Ehrenberg, Albert Yonas, Sidney Diamond, Richard Held, and Pawan Sinha. 2018. “Potential Downside of High Initial Visual Acuity.” *Proceedings of the National Academy of Sciences* 115 (44): 11333–38. https://doi.org/10.1073/pnas.1800901115.

Vogelsang, Marin, Lukas Vogelsang, Priti Gupta, Tapan K. Gandhi, Pragya Shah, Piyush Swami, Sharon Gilad-Gutnick, et al. 2024. “Impact of Early Visual Experience on Later Usage of Color Cues.” *Science* 384 (6698): 907–12. https://doi.org/10.1126/science.adk9587.

Vong, Wai Keen, Wentao Wang, A. Emin Orhan, and Brenden M. Lake. 2024. “Grounded Language Acquisition Through the Eyes and Ears of a Single Child.” *Science* 383 (6682): 504–11. https://doi.org/10.1126/science.adi1374.

Watters, Nicholas, Loic Matthey, Christopher P. Burgess, and Alexander Lerchner. 2019. “Spatial Broadcast Decoder: A Simple Architecture for Learning Disentangled Representations in VAEs.” *arXiv Preprint arXiv:1901.07017*. https://arxiv.org/abs/1901.07017.

Werker, Janet F., and Takao K. Hensch. 2015. “Critical Periods in Speech Perception: New Directions.” *Annual Review of Psychology* 66: 173–96. https://doi.org/10.1146/annurev-psych-010814-015104.

Werker, Janet F., and Richard C. Tees. 1984. “Cross-Language Speech Perception: Evidence for Perceptual Reorganization During the First Year of Life.” *Infant Behavior and Development* 7 (1): 49–63. https://doi.org/10.1016/S0163-6383(84)80022-3.

Wu, Xiaoxia, Ethan Dyer, and Behnam Neyshabur. 2021. “When Do Curricula Work?” In *International Conference on Learning Representations*.