



LED

A NEW STEP
TOWARDS
A NEW WORLD



Bulb | Spot Light | Panel Light | Down Light | Batten

LED BULB

Input Voltage: AC 220-240V, 50/60Hz

Driver Type: Integral

P.F ≥ 0.5 for 3W, P.F ≥ 0.9 for 5W, 7W, 9W, 12W, 15W, 18W & 23W

Voltage Operating Range: 100-300 VAC

High Surge Protection: Upto 3.5 KV

CRI: Ra>80

LED Life: 25,000 BH

Optics: Polycarbonate Diffuser for better light distribution



| Wattage | Product Description | CCT | Lumen Output | Cutout Dimension mm | Dimension (DxH) mm | Product Code | MRP ₹ | Std. Pkg. |
|---------|---------------------|--------|--------------|---------------------|--------------------|--------------|-------|-----------|
| 3W | LED Bulb | 3000K | 270 | NA | 50 x 94 | ABUM01033 | 125 | 50 |
| 3W | LED Bulb | 6500K | 276 | NA | 50 x 94 | ABUM01037 | 125 | 50 |
| 5W | LED Bulb | 3000K | 450 | NA | 57 x 101 | ABUM01053 | 140 | 50 |
| 5W | LED Bulb | 6500K | 500 | NA | 57 x 101 | ABUM01057 | 140 | 50 |
| 7W | LED Bulb | 3000K | 630 | NA | 57 x 101 | ABUM01073 | 145 | 50 |
| 7W | LED Bulb | 6500K | 700 | NA | 57 x 101 | ABUM01077 | 145 | 50 |
| 9W | LED Bulb | 3000K | 810 | NA | 57 x 101 | ABUM01093 | 170 | 50 |
| 9W | LED Bulb | 6500K | 900 | NA | 57 x 101 | ABUM01097 | 170 | 50 |
| 12W | LED Bulb | 3000K | 1080 | NA | 60 x 110 | ABUM01123 | 255 | 50 |
| 12W | LED Bulb | 6500K | 1104 | NA | 60 x 110 | ABUM01127 | 255 | 50 |
| 12W | LED Bulb | 3000K | 1080 | NA | 60 x 110 | ABUM01123R2 | 220 | 50 |
| 12W | LED Bulb | 6500K | 1104 | NA | 60 x 110 | ABUM01127R2 | 220 | 50 |
| 15W | LED Bulb | 3000K | 1350 | NA | 65 x 122 | ABUM01153 | 280 | 30 |
| 15W | LED Bulb | 6500K | 1380 | NA | 65 x 122 | ABUM01157 | 280 | 30 |
| 18W | LED Bulb | 3000K | 1656 | NA | 75 x 140 | ABUM01183 | 350 | 30 |
| 18W | LED Bulb | 6500K | 1800 | NA | 75 x 140 | ABUM01187 | 350 | 30 |
| 23W | LED Bulb | 3000K | 2070 | NA | 80 x 154 | ABUM01233 | 540 | 20 |
| 23W | LED Bulb | 6500K | 2300 | NA | 80 x 154 | ABUM01237 | 540 | 20 |
| 30W | LED Bulb | 6500K | 3000 | NA | 115 x 220 | ABUM01307 | 850 | 10 |
| 40W | LED Bulb | 3000K | 4000 | NA | 135 x 255 | ABUM01407 | 950 | 10 |
| 50W | LED Bulb | 6500K | 5000 | NA | 135 x 255 | ABUM01507 | 1250 | 10 |
| 7W | Emergency Lamp | 6500K | 700 | NA | 75 x 140 | ABUM03077 | 600 | 10 |
| 9W | Emergency Lamp | 6500K | 700 | NA | 75 x 140 | ABUM03097R1 | 650 | 10 |
| 0.5 W | Night Bulb | Blue | NA | NA | 45 x 70 | ABUM0201B | 55 | 60 |
| | Night Bulb | Green | NA | NA | 45 x 70 | ABUM0201G | 55 | 60 |
| | Night Bulb | Orange | NA | NA | 45 x 70 | ABUM0201O | 55 | 60 |
| | Night Bulb | Pink | NA | NA | 45 x 70 | ABUM0201P | 55 | 60 |
| | Night Bulb | Red | NA | NA | 45 x 70 | ABUM0201R | 55 | 60 |
| | Night Bulb | White | NA | NA | 45 x 70 | ABUM0201W | 55 | 60 |
| | Night Bulb | Yellow | NA | NA | 45 x 70 | ABUM0201Y | 55 | 60 |



LED PANEL

Input Voltage: AC 220-240V, 50/60Hz

Driver Type: Non Integral

P.F ≥ 0.9

Voltage Operating Range: 100-300 VAC

High Surge Protection: 2.5 KV

CRI: Ra>80

LED Life: 30,000 BH

Optics: Polycarbonate Diffuser



| Wattage | Product Description | CCT | Lumen Output | Cutout Dimension (mm) | Dimension (DxH) mm | Product Code | MRP ₹ | Std. Pkg. |
|---------|-----------------------------|------|--------------|-----------------------|--------------------|--------------|-------|-----------|
| 5W | LED Slim Panel Light Round | 3000 | 260lm | Ø 108 | 120x25 | APAM01053 | 700 | 10 |
| | LED Slim Panel Light Round | 4000 | 275lm | Ø 108 | 120x25 | APAM01054 | 700 | 10 |
| | LED Slim Panel Light Round | 6500 | 275lm | Ø 108 | 120x25 | APAM01057 | 700 | 10 |
| 10W | LED Slim Panel Light Round | 3000 | 670lm | Ø 132 | 145x20 | APAM01103 | 900 | 10 |
| | LED Slim Panel Light Round | 4000 | 700lm | Ø 132 | 145x20 | APAM01104 | 900 | 10 |
| | LED Slim Panel Light Round | 6500 | 700lm | Ø 132 | 145x20 | APAM01107 | 900 | 10 |
| 15W | LED Slim Panel Light Round | 3000 | 1000lm | Ø 156 | 170x25 | APAM01153 | 1000 | 10 |
| | LED Slim Panel Light Round | 4000 | 1050lm | Ø 156 | 170x25 | APAM01154 | 1000 | 10 |
| | LED Slim Panel Light Round | 6500 | 1400lm | Ø 177 | 190x25 | APAM01157 | 1000 | 10 |
| 20W | LED Slim Panel Light Round | 3000 | 1340lm | Ø 177 | 190x25 | APAM01203 | 1200 | 10 |
| | LED Slim Panel Light Round | 4000 | 1400lm | Ø 177 | 190x25 | APAM01204 | 1200 | 10 |
| | LED Slim Panel Light Round | 6500 | 1400lm | Ø 177 | 190x25 | APAM01207 | 1200 | 10 |
| 5W | LED Slim Panel Light Square | 3000 | 260lm | Ø 108X108 | 120x120x25 | APAM02053 | 700 | 10 |
| | LED Slim Panel Light Square | 4000 | 275lm | Ø 108X108 | 120x120x25 | APAM02054 | 700 | 10 |
| | LED Slim Panel Light Square | 6500 | 275lm | Ø 108X108 | 120x120x25 | APAM02057 | 700 | 10 |
| 10W | LED Slim Panel Light Square | 3000 | 670lm | Ø 132x132 | 145x145x25 | APAM02103 | 900 | 10 |
| | LED Slim Panel Light Square | 4000 | 700lm | Ø 132x132 | 145x145x25 | APAM02104 | 900 | 10 |
| | LED Slim Panel Light Square | 6500 | 700lm | Ø 132x132 | 145x145x25 | APAM02107 | 900 | 10 |
| 15W | LED Slim Panel Light Square | 3000 | 1000lm | Ø 156x156 | 170x170x25 | APAM02153 | 1000 | 10 |
| | LED Slim Panel Light Square | 4000 | 1050lm | Ø 156x156 | 170x170x25 | APAM02154 | 1000 | 10 |
| | LED Slim Panel Light Square | 6500 | 1050lm | Ø 156x156 | 170x170x25 | APAM02157 | 1000 | 10 |
| 20W | LED Slim Panel Light Square | 3000 | 1340lm | Ø 177x177 | 190x190x25 | APAM02203 | 1200 | 10 |
| | LED Slim Panel Light Square | 4000 | 1400lm | Ø 177x177 | 190x190x25 | APAM02204 | 1200 | 10 |
| | LED Slim Panel Light Square | 6500 | 1400lm | Ø 177x177 | 190x190x25 | APAM02207 | 1200 | 10 |

LED SPOT LIGHT

Input Voltage: AC 220-240V, 50/60Hz

Driver Type: Constant Current. Non-Integral

P.F ≥ 0.4

Voltage Operating Range: 100-300 VAC

High Surge Protection: 2.5 KV

CRI: Ra>75

LED Life: 30,000 BH

Optics: PMMA lens for better light distribution



| Wattage | Product Description | CCT | Lumen Output | Cutout Dimension mm | Dimension (LxWxH) mm | Product Code | MRP ₹ | Std. Pkg. |
|---------|---------------------|-------|--------------|---------------------|----------------------|--------------|-------|-----------|
| 2W | LED SPOT LIGHT | 3000K | 108lm | Ø 33 | 41.6 x 16.5 | ASPM01023 | 180 | 50 |
| | LED SPOT LIGHT | 6500K | 120lm | Ø 33 | 41.6 x 16.5 | ASPM01027 | 180 | 50 |
| | LED SPOT LIGHT | RED | NA | Ø 33 | 41.6 x 16.5 | ASPM0102R | 180 | 50 |
| | LED SPOT LIGHT | GREEN | NA | Ø 33 | 41.6 x 16.5 | ASPM0102G | 180 | 50 |
| | LED SPOT LIGHT | BLUE | NA | Ø 33 | 41.6 x 16.5 | ASPM0102B | 180 | 50 |

LED PC PANEL

Non - Integrated Driver

Input Voltage: AC 220-240V, 50Hz
Driver Type: Non Integral
P.F > 0.9
Voltage Operating Range: 140-275 VAC
High Surge Protection: >3 KV
CRI: Ra>80
LED Life: >25,000 BH
Optics: Polycarbonate Diffuser



| Wattage | Product Description | CCT | Lumen Output | Cutout Dimension (mm) | Dimension (DxH) mm | Product Code | MRP ₹ | Std. Pkg. |
|---------|---------------------------|------|--------------|-----------------------|--------------------|--------------|-------|-----------|
| 3W | LED PC Panel Light Round | 3000 | 180lm | Ø 68 | 86x20 | APAM03033 | 155 | 20 |
| | LED PC Panel Light Round | 4000 | 186lm | Ø 68 | 86x20 | APAM03034 | 155 | 20 |
| | LED PC Panel Light Round | 6500 | 240lm | Ø 68 | 86x20 | APAM03037 | 155 | 20 |
| 6W | LED PC Panel Light Round | 3000 | 370lm | Ø 97 | 120x20 | APAM03063 | 222 | 20 |
| | LED PC Panel Light Round | 4000 | 390lm | Ø 97 | 120x20 | APAM03064 | 222 | 20 |
| | LED PC Panel Light Round | 6500 | 510lm | Ø 97 | 120x20 | APAM03067 | 222 | 20 |
| 10W | LED PC Panel Light Round | 3000 | 700lm | Ø 129 | 144x20 | APAM03103 | 255 | 20 |
| | LED PC Panel Light Round | 4000 | 720lm | Ø 129 | 144x20 | APAM03104 | 255 | 20 |
| | LED PC Panel Light Round | 6500 | 850lm | Ø 129 | 144x20 | APAM03107 | 255 | 20 |
| 15W | LED PC Panel Light Round | 3000 | 1050lm | Ø 145 | 170x20 | APAM03153 | 340 | 10 |
| | LED PC Panel Light Round | 4000 | 1080lm | Ø 145 | 170x20 | APAM03154 | 340 | 10 |
| | LED PC Panel Light Round | 6500 | 1350lm | Ø 145 | 170x20 | APAM03157 | 340 | 10 |
| 20W | LED PC Panel Light Round | 3000 | 1400lm | Ø 195 | 220x20 | APAM03203 | 470 | 10 |
| | LED PC Panel Light Round | 4000 | 1440lm | Ø 195 | 220x20 | APAM03204 | 470 | 10 |
| | LED PC Panel Light Round | 6500 | 1800lm | Ø 195 | 220x20 | APAM03207 | 470 | 10 |
| 3W | LED PC Panel Light Square | 3000 | 180lm | Ø 68x68 | 86 x 86 x 20 | APAM03033 | 155 | 20 |
| | LED PC Panel Light Square | 4000 | 186lm | Ø 68x68 | 86 x 86 x 20 | APAM03034 | 155 | 20 |
| | LED PC Panel Light Square | 6500 | 240lm | Ø 68x68 | 86 x 86 x 20 | APAM03037 | 155 | 20 |
| 6W | LED PC Panel Light Square | 3000 | 370lm | Ø 97x97 | 120 x 120 x 20 | APAM03063 | 222 | 20 |
| | LED PC Panel Light Square | 4000 | 390lm | Ø 97x97 | 120 x 120 x 20 | APAM03064 | 222 | 20 |
| | LED PC Panel Light Square | 6500 | 510lm | Ø 97x97 | 120 x 120 x 20 | APAM03067 | 222 | 20 |
| 10W | LED PC Panel Light Square | 3000 | 700lm | Ø 129x129 | 144 x 144 x 20 | APAM03103 | 255 | 20 |
| | LED PC Panel Light Square | 4000 | 720lm | Ø 129x129 | 144 x 144 x 20 | APAM03104 | 255 | 20 |
| | LED PC Panel Light Square | 6500 | 850lm | Ø 129x129 | 144 x 144 x 20 | APAM03107 | 255 | 20 |
| 15W | LED PC Panel Light Square | 3000 | 1050lm | Ø 145x145 | 170 x 170 x 20 | APAM03153 | 340 | 10 |
| | LED PC Panel Light Square | 4000 | 1080lm | Ø 145x145 | 170 x 170 x 20 | APAM03154 | 340 | 10 |
| | LED PC Panel Light Square | 6500 | 1350lm | Ø 145x145 | 170 x 170 x 20 | APAM03157 | 340 | 10 |
| 20W | LED PC Panel Light Square | 3000 | 1400lm | Ø 195x195 | 220 x 220 x 20 | APAM03203 | 470 | 10 |
| | LED PC Panel Light Square | 4000 | 1440lm | Ø 195x195 | 220 x 220 x 20 | APAM03204 | 470 | 10 |
| | LED PC Panel Light Square | 6500 | 1800lm | Ø 195x195 | 220 x 220 x 20 | APAM03207 | 470 | 10 |



LED FLOOD LIGHT

Input Voltage: AC 220-240V, 50/60Hz

Driver Type: Integral

P.F ≥ 0.95

Voltage Operating Range: 100-300VAC

High Surge Protection: 4 KV

CRI: Ra>80

LED Life: 30,000 BH



| Wattage | Product Description | CCT | Lumen Output | Cutout Dimension mm | Dimension (LxWxH) mm | Product Code | MRP ₹ | Std. Pkg. |
|---------|--------------------------|-------|--------------|---------------------|----------------------|--------------|-------|-----------|
| 30W | FLOOD LIGHT IP 65, IK 07 | 6500K | 3000lm | - | 225 x 159 x 41 | ASTM01157 | 1900 | 5 |
| 50W | FLOOD LIGHT IP 65, IK 07 | 6500K | 5000lm | - | 225 x 159 x 41 | ASTM01257 | 2200 | 5 |
| 100W | FLOOD LIGHT IP 65, IK 07 | 6500K | 10000lm | - | 332 x 289 x 53 | ASTM01457 | 4000 | 2 |

LED STREET LIGHT

Input Voltage: AC 220-240V, 50/60Hz

Driver Type: Integral

P.F ≥ 0.9

Voltage Operating Range: 100-300VAC

High Surge Protection: 2.5 KV

CRI: Ra>80

LED Life: 30,000 BH



| Wattage | Product Description | CCT | Lumen Output | Cutout Dimension mm | Dimension (LxWxH) mm | Product Code | MRP ₹ | Std. Pkg. |
|---------|---------------------------|-------|--------------|---------------------|----------------------|--------------|-------|-----------|
| 15W | STREET LIGHT IP 66, IK 07 | 6500K | 1500lm | - | 284 x 115 x 55 | ASTM01157 | 1500 | 10 |
| 25W | STREET LIGHT IP 66, IK 07 | 6500K | 2500lm | - | 284 x 115 x 55 | ASTM01257 | 1700 | 10 |
| 45W | STREET LIGHT IP 66, IK 07 | 6500K | 4500lm | - | 353 x 137 x 55 | ASTM01457 | 2200 | 10 |



LED DOWN LIGHT

Input Voltage: AC 220-240V, 50/60Hz

Driver Type: Integral

P.F ≥ 0.9

Voltage Operating Range: 100-300VAC

High Surge Protection: 2.5 KV

CRI: Ra>80

LED Life: 30,000 BH

Optics: Polycarbonate diffuser for better light distribution



| Wattage | Product Description | CCT | Lumen Output | Cutout Dimension mm | Dimension (LxWxH) mm | Product Code | MRP ₹ | Std. Pkg. |
|---------|----------------------------|-------|--------------|---------------------|----------------------|--------------|-------|-----------|
| 5W | CONCEALED DOWN LIGHT 3000K | 3000K | 360lm | Ø 75 | 110 x 50 | ADLM03053 | 300 | 20 |
| | CONCEALED DOWN LIGHT 4000K | 4000K | 380lm | Ø 75 | 110 x 50 | ADLM03054 | 300 | 20 |
| | CONCEALED DOWN LIGHT 6500K | 6500K | 400lm | Ø 75 | 110 x 50 | ADLM03057 | 300 | 20 |
| | CONCEALED DOWN LIGHT RED | RED | NA | Ø 75 | 110 x 50 | ADLM0305R | 300 | 20 |
| | CONCEALED DOWN LIGHT GREEN | GREEN | NA | Ø 75 | 110 x 50 | ADLM0305G | 300 | 20 |
| | CONCEALED DOWN LIGHT BLUE | BLUE | NA | Ø 75 | 110 x 50 | ADLM0305B | 300 | 20 |
| 7W | CONCEALED DOWN LIGHT 3000K | 3000K | 505lm | Ø 85 | Ø 105 x 60 | ADLM03073 | 350 | 20 |
| | CONCEALED DOWN LIGHT 6500K | 6500K | 560lm | Ø 85 | Ø 105 x 60 | ADLM03077 | 350 | 20 |
| | CONCEALED DOWN LIGHT RED | RED | NA | Ø 85 | Ø 105 x 60 | ADLM0307R | 350 | 20 |
| | CONCEALED DOWN LIGHT GREEN | GREEN | NA | Ø 85 | Ø 105 x 60 | ADLM0307G | 350 | 20 |
| | CONCEALED DOWN LIGHT BLUE | BLUE | NA | Ø 85 | Ø 105 x 60 | ADLM0307B | 350 | 20 |

LED BATTEN

Input Voltage: AC 220-240V, 50/60Hz

Driver Type: Integral

P.F ≥ 0.9

Voltage Operating Range: 90-305 VAC

High Surge Protection: 2.5 KV

CRI: Ra>80

LED Life: 30,000 BH

Optics: Polycarbonate Diffuser



| Wattage | Product Description | CCT | Lumen Output | Cutout Dimension mm | Dimension (LxWxH) mm | Product Code | MRP ₹ | Std. Pkg. |
|---------|---------------------|------|--------------|---------------------|----------------------|--------------|-------|-----------|
| 10W | LED Batten Round | 3000 | 900lm | NA | 590x22x34 | ABTM01103 | 375 | 20 |
| | LED Batten Round | 6500 | 1000lm | NA | 590x22x34 | ABTM01107 | 375 | 20 |
| 20W | LED Batten Round | 3000 | 1800lm | NA | 1190x22x34 | ABTM01203 | 560 | 20 |
| | LED Batten Round | 6500 | 2000lm | NA | 1190x22x34 | ABTM01207 | 560 | 20 |
| 20W | LED Batten Square | 6500 | 2000lm | NA | 1186x22x37 | ABTM02207 | 560 | 20 |
| 20W | Anmol LED Batten | 3000 | 1800lm | NA | 1100x25x35 | ABTM04203 | 499 | 25 |
| | Anmol LED Batten | 6500 | 2000lm | NA | 1100x25x35 | ABTM04207 | 499 | 25 |
| 24W | LED Batten Oval | 3000 | 2160lm | NA | 1130x25x35 | ABTM03243 | 630 | 20 |
| | LED Batten Oval | 6500 | 2640lm | NA | 1130x25x35 | ABTM03247 | 630 | 20 |

PANASONIC LIFE SOLUTIONS INDIA PVT. LTD.

12th Floor, Ambience Tower, Ambience Island, NH-48, Gurugram -122 002, Haryana.

In case of consumer complaints contact: Customer Care Executive 3rd Floor, B Wing,
I-Think Techno Campus, Pokharan Road No.2, Thane (W) - 400 607, Maharashtra.

Customer care no.: 022-41304130, WhatsApp no.: 91360 28606,

Email: wecare@in.panasonic.com

Panasonic Life Solutions India Pvt. Ltd is having exclusive right
to use "Anchor" Brand in Lighting Products

Panasonic

All Rights Reserved © 2015 COPYRIGHT Anchor Electricals Pvt. Ltd.
Specifications are subjected to change without notice
Printed in India

The duplication and transfer of images from this catalogue
without permission is strictly prohibited.