

myCompiler

Enter a title...

English Recent Login Sign up

FILES

main.m

```
1 clear;
2 close all;
3 clc;
4
5 %% Parameters
6 Fs = 1000;           % Sampling frequency (Hz)
7 T = 1;               % Total duration (1 second)
8 N = 3;               % Number of users
9
10 t = 0:1/Fs:T-1/Fs; % Time vector
11
12 %% User Signals
13 user1 = sin(2*pi*5*t); % User 1 (5 Hz)
14 user2 = sin(2*pi*10*t); % User 2 (10 Hz)
15 user3 = sin(2*pi*15*t); % User 3 (15 Hz)
16
17 %% TDMA Signal
18 L = length(t);
19 slot_length = floor(L/N);
20
21 tdma_signal = zeros(size(t));
22
23 % User 1 Slot
24 tdma_signal(1:slot_length) = user1(1:slot_length);
25
26 % User 2 Slot
27 tdma_signal(slot_length+1:2*slot_length) = ...
28     user2(slot_length+1:2*slot_length);
29
30 % User 3 Slot
31 tdma_signal(2*slot_length+1:end) = ...
32     user3(2*slot_length+1:end);
33
34 %% Plot User 1
35 subplot(4,1,1)
36 plot(t,user1,'b','LineWidth',1.5)
37 title('User 1 Signal (5 Hz)')
```

Run Save Output Input

[Execution complete with exit code 0]

User 1 Signal (5 Hz)

User 2 Signal (10 Hz)

User 3 Signal (15 Hz)

Combined TDMA Signal


Reach your agent anywhere. No inbound ports, no DNS, no static IP, any device, behind NAT. **Blocks.ai** →
blocks.ai
Ads by EthicalAds

