Utrecht University

TU/e EINDHOVEN UNIVERSITY OF TECHNOLOGY

25 April, 2025

Introducing formalization of mathematics with Tutte's theorem

Pim Otte
PhD Candidate

Outline

Introduction

Motivation

Concepts

Tutte’s theorem

Demo

Conclusion

Outline

Introduction

Motivation

Concepts

Tutte’s theorem

Demo

Conclusion

About me

- Pim Otte
- PhD candidate at Utrecht University & Technical University of Eindhoven
- Topic “Type Theory for Education”
- Webpage: `https://pim.otte.dev`

Topic

- Formalization of mathematics: What and Why?
- Demo: Formalizing Tutte’s theorem

Outline

Introduction

Motivation

Concepts

Tutte’s theorem

Demo

Conclusion

Formalization

- What: Encoding mathematics in a formal system

Formalization

- What: Encoding mathematics in a formal system
- Why: To teach mathematics to computers

Formalization

- What: Encoding mathematics in a formal system
- Why: To teach mathematics to computers
- Why: To create proof assistants (Interactive Theorem Provers)

Why do we want proof assistants?

- Verification

Why do we want proof assistants?

- Verification
- To build tools to help mathematicians

Why do we want proof assistants?

- Verification
- To build tools to help mathematicians
- To scale mathematical collaboration

Verification

- Computer assisted proofs: The four colour theorem [G$^+$08]

Verification

- Computer assisted proofs: The four colour theorem [G$^+$08]
- Mathematical doubt: The Liquid Tensor Experiment [Buz22] [Com21]

Tools for mathematicians

- Proof *assistant*

Tools for mathematicians

- Proof *assistant*
  - Interactive theorem proving

Tools for mathematicians

- Proof *assistant*
  - Interactive theorem proving
  - Theorem search

Tools for mathematicians

- Proof *assistant*
  - Interactive theorem proving
  - Theorem search
  - Automated theorem proving

Tools for mathematicians

- Proof *assistant*
  - Interactive theorem proving
  - Theorem search
  - Automated theorem proving
- Teaching tools

Scaling mathematical collaboration

- What's the biggest mathematical collaboration in the room?

Scaling mathematical collaboration

- What's the biggest mathematical collaboration in the room?
- Liquid Tensor Experiment (29 contributors)

Scaling mathematical collaboration

- What's the biggest mathematical collaboration in the room?
- Liquid Tensor Experiment (29 contributors)
- Busy Beaver 5 (28 contributors)

Scaling mathematical collaboration

- What's the biggest mathematical collaboration in the room?
- Liquid Tensor Experiment (29 contributors)
- Busy Beaver 5 (28 contributors)
- Fermat's Last Theorem (ongoing) (44 contributors)

Scaling mathematical collaboration

- What's the biggest mathematical collaboration in the room?
- Liquid Tensor Experiment (29 contributors)
- Busy Beaver 5 (28 contributors)
- Fermat's Last Theorem (ongoing) (44 contributors)
- Equational Theories (56 contributors)

Scaling mathematical collaboration

- What's the biggest mathematical collaboration in the room?
- Liquid Tensor Experiment (29 contributors)
- Busy Beaver 5 (28 contributors)
- Fermat's Last Theorem (ongoing) (44 contributors)
- Equational Theories (56 contributors)
- Mathlib (413 contributors)

Bonus: Interaction with Generative AI

- Problem: Generative AI is hit or miss

Bonus: Interaction with Generative AI

- Problem: Generative AI is hit or miss
- A formal (intermediate) language allows verification

Bonus: Interaction with Generative AI

- Problem: Generative AI is hit or miss
- A formal (intermediate) language allows verification
- Positive feedback loop (during training and at runtime)

Bonus: Interaction with Generative AI

- Problem: Generative AI is hit or miss
- A formal (intermediate) language allows verification
- Positive feedback loop (during training and at runtime)
- Examples: AlphaProof [AA24], Deepseek Prover [XGS$^+$24]

Outline

Introduction

Motivation

Concepts

Tutte’s theorem

Demo

Conclusion

Curry-Howard correspondence

- Core idea: Encode mathematical statements as types in a programming language

Curry-Howard correspondence

- Core idea: Encode mathematical statements as types in a programming language
- With A, B propositions, A implies B: $A \implies B$

Curry-Howard correspondence

- Core idea: Encode mathematical statements as types in a programming language
- With A, B propositions, A implies B: $A \implies B$
- A function $f : \mathbb{R} \to \mathbb{Z}$ turns a real number into an integer

Curry-Howard correspondence

- Core idea: Encode mathematical statements as types in a programming language
- With A, B propositions, A implies B: $A \implies B$
- A function $f : \mathbb{R} \to \mathbb{Z}$ turns a real number into an integer
- A function $f : A \to B$ turns a proof of A into a proof of B.

Curry-Howard correspondence

- Core idea: Encode mathematical statements as types in a programming language
- With A, B propositions, A implies B: $A \implies B$
- A function $f : \mathbb{R} \to \mathbb{Z}$ turns a real number into an integer
- A function $f : A \to B$ turns a proof of A into a proof of B.
- Similarly: for $P : \mathbb{R} \to \mathbf{Prop}$, $\forall x : \mathbb{R}, P(x)$ corresponds to a function that provides a proof of $P(x)$ on an input x.

Curry-Howard correspondence

```
theorem example1 {A : Prop} : A → A := fun (a : A) => a

theorem example2 {P : ℕ → Prop} : (∀ (n : ℕ), P n) → P 37
    :=
    fun Pforall => Pforall 37
```

Tactics

```
import Mathlib

theorem rearranging (x y z : ℝ) : (5*x + y) * z + (3*z)*y =
    5*x*z + 4*y*z := by ring

theorem integer_inequalities (n m : ℤ) (h : n < 5 * m) (h2 :
    5 + n > -m) : m > -1 := by omega

theorem linear_inequalities (a b : ℝ) (h : 5*a + b < 10) (h2
    : 9*a - 5*b > -20) :  b < 6 := by linarith
```

Outline

Introduction

Motivation


Concepts

Tutte’s theorem

Demo

Conclusion

Perfect Matching



Perfect Matching

Definition (Perfect matching).


A perfect matching of G is a subgraph M, such that every vertex in G is connected in M to exactly one other vertex.

Tutte's theorem


Theorem (Tutte, 1947).

A graph G has a perfect matching if and only if for any subset $U \subseteq V$ the graph $G - U$ has at most $|U|$ components of odd size.


Alternating cycles




Alternating cycles



Alternating cycles



Alternating cycles



Alternating graph

Definition (Alternating).

A graph G is alternating with respect to some other graph G′ if exactly every other edge in G is in G′.

Symmetric difference

Definition (Symmetric difference).

The symmetric difference of G and G' (denoted by $G \Delta G'$) is the graph consisting of edges that are in exactly one of G and G'.

Symmetric difference of perfect matchings is alternating

Lemma.

Let M, M' be perfect matchings of a graph G, then the symmetric difference $M \Delta M'$ is alternating with respect to M.

Symmetric difference of perfect matchings is alternating

Lemma.

Let M, M' be perfect matchings of a graph G, then the symmetric difference $M \Delta M'$ is alternating with respect to M.

Proof.

It suffices to show that for any vertex v in $M \Delta M'$ and two edges including v, exactly of these edges is in M. By definition of $M \Delta M'$, both of these edges must be in M or M'. Since M and M' are perfect matchings, each edge must be in exactly one of the two. So in particular, exactly one of these edges is in M. □

Outline

Introduction

Motivation

Concepts

Tutte’s theorem

Demo

Conclusion

Demo

Demo

```
lemma
  Subgraph.IsPerfectMatching.isAlternating_symmDiff_left
    {M' : Subgraph G'} (hM : M.IsPerfectMatching)
    (hM' : M'.IsPerfectMatching) :
    (M.spanningCoe △ M'.spanningCoe).IsAlternating
  M.spanningCoe := by
  sorry
```

Outline

Introduction

Motivation

Concepts

Tutte’s theorem

Demo

Conclusion

Conclusion

- Teaching computers mathematics: verification, tools and collaboration

Conclusion

- Teaching computers mathematics: verification, tools and collaboration
- How to get started?
  - Lean, Rocq, Isabelle, Agda

Conclusion

- Teaching computers mathematics: verification, tools and collaboration
- How to get started?
  - Lean, Rocq, Isabelle, Agda
  - Natural number game: https://adam.math.hhu.de/

Conclusion

- Teaching computers mathematics: verification, tools and collaboration
- How to get started?
  - Lean, Rocq, Isabelle, Agda
  - Natural number game: https://adam.math.hhu.de/
  - Do/join/supervise a project

References

- AlphaProof and AlphaGeometry, *Ai achieves silver-medal standard solving international mathematical olympiad problems*, 2024.
- Kevin Buzzard, *Beyond the liquid tensor experiment*, 2022.
- Johan Commelin, *Liquid tensor experiment*, Nieuw Archief voor Wiskunde **22** (2021), no. 4, 231–234.
- Georges Gonthier et al., *Formal proof–the four-color theorem*, Notices of the AMS **55** (2008), no. 11, 1382–1393.
- Huajian Xin, Daya Guo, Zhihong Shao, Zhizhou Ren, Qihao Zhu, Bo Liu, Chong Ruan, Wenda Li, and Xiaodan Liang, *Deepseek-prover: Advancing theorem proving in llms through large-scale synthetic data*, 2024.



Utrecht University

Sharing science,
shaping tomorrow

Thanks to Yaël Dillies, Bhavik Mehta, Kyle Miller and other mathlib reviewers.

TU/e EINDHOVEN UNIVERSITY OF TECHNOLOGY



pim.otte.dev



Utrecht University

Sharing science,
shaping tomorrow

Thanks to Yaël Dillies, Bhavik Mehta, Kyle Miller and other mathlib reviewers.

TU/e EINDHOVEN UNIVERSITY OF TECHNOLOGY

TU/e EINDHOVEN UNIVERSITY OF TECHNOLOGY



pim.otte.dev