

```

#include<stdio.h>
#include<conio.h>
#include<stdlib.h>
#include <windows.h>

int board[10] = {2,2,2,2,2,2,2,2,2,2};
int turn = 1,flag = 0;
int player,comp;

void menu();
void go(int n);
void start_game();
void check_draw();
void draw_board();
void player_first();
void put_X_O(char ch,int pos);
COORD coord= {0,0}; // this is global variable
//center of axis is set to the top left corner of the screen
void gotoxy(int x,int y)
{
    coord.X=x;
    coord.Y=y;
    SetConsoleCursorPosition(GetStdHandle(STD_OUTPUT_HANDLE),coord);
}

void main()
{
    system("cls");
    menu();
    getch();
}

void menu()
{
    int choice;
    system("cls");
    printf("\n-----MENU-----");
    printf("\n1 : Play with X");
    printf("\n2 : Play with O");
    printf("\n3 : Exit");
    printf("\nEnter your choice:>");
    scanf("%d",&choice);
    turn = 1;
    switch (choice)
    {
        case 1:
            player = 1;
            comp = 0;
            player_first();
    }
}

```

```

        break;
    case 2:
        player = 0;
        comp = 1;
        start_game();
        break;
    case 3:
        exit(1);
    default:
        menu();
    }
}

int make2()
{
    if(board[5] == 2)
        return 5;
    if(board[2] == 2)
        return 2;
    if(board[4] == 2)
        return 4;
    if(board[6] == 2)
        return 6;
    if(board[8] == 2)
        return 8;
    return 0;
}

int make4()
{
    if(board[1] == 2)
        return 1;
    if(board[3] == 2)
        return 3;
    if(board[7] == 2)
        return 7;
    if(board[9] == 2)
        return 9;
    return 0;
}

int posswin(int p)
{
    // p==1 then X   p==0 then 0
    int i;
    int check_val,pos;

    if(p == 1)
        check_val = 18;
    else

```

```

    check_val = 50;

i = 1;
while(i<=9)//row check
{
    if(board[i] * board[i+1] * board[i+2] == check_val)
    {
        if(board[i] == 2)
            return i;
        if(board[i+1] == 2)
            return i+1;
        if(board[i+2] == 2)
            return i+2;
    }
    i+=3;
}

i = 1;
while(i<=3)//column check
{
    if(board[i] * board[i+3] * board[i+6] == check_val)
    {
        if(board[i] == 2)
            return i;
        if(board[i+3] == 2)
            return i+3;
        if(board[i+6] == 2)
            return i+6;
    }
    i++;
}

if(board[1] * board[5] * board[9] == check_val)
{
    if(board[1] == 2)
        return 1;
    if(board[5] == 2)
        return 5;
    if(board[9] == 2)
        return 9;
}

if(board[3] * board[5] * board[7] == check_val)
{
    if(board[3] == 2)
        return 3;
    if(board[5] == 2)
        return 5;
    if(board[7] == 2)
        return 7;
}

```

```

    }
    return 0;
}

void go(int n)
{
    if(turn % 2)
        board[n] = 3;
    else
        board[n] = 5;
    turn++;
}

void player_first()
{
    int pos;

    check_draw();
    draw_board();
    gotoxy(30,18);
    printf("Your Turn :> ");
    scanf("%d",&pos);

    if(board[pos] != 2)
        player_first();

    if(pos == posswin(player))
    {
        go(pos);
        draw_board();
        gotoxy(30,20);
        //textcolor(128+RED);
        printf("Player Wins");
        getch();
        exit(0);
    }

    go(pos);
    draw_board();
    start_game();
}

void start_game()
{
    // p==1 then X   p==0   then   0
    if(posswin(comp))
    {
        go(posswin(comp));
        flag = 1;
    }
}

```

```

else if(posswin(player))
    go(posswin(player));
else if(make2())
    go(make2());
else
    go(make4());
draw_board();

if(flag)
{
    gotoxy(30,20);
    //textcolor(128+RED);
    printf("Computer wins");
    getch();
}
else
    player_first();
}

void check_draw()
{
    if(turn > 9)
    {
        gotoxy(30,20);
        //textcolor(128+RED);
        printf("Game Draw");
        getch();
        exit(0);
    }
}

void draw_board()
{
    int j;

    for(j=9; j<17; j++)
    {
        gotoxy(35,j);
        printf("|          |");
    }
    gotoxy(28,11);
    printf("-----");
    gotoxy(28,14);
    printf("-----");

    for(j=1; j<10; j++)
    {
        if(board[j] == 3)
            put_X_0('X',j);
        else if(board[j] == 5)

```

```

        put_X_0('0',j);
    }
}

void put_X_0(char ch,int pos)
{
    int m;
    int x = 31, y = 10;

    m = pos;

    if(m > 3)
    {
        while(m > 3)
        {
            y += 3;
            m -= 3;
        }
    }
    if(pos % 3 == 0)
        x += 16;
    else
    {
        pos %= 3;
        pos--;
        while(pos)
        {
            x+=8;
            pos--;
        }
    }
    gotoxy(x,y);
    printf("%c",ch);
}

```