

Case Study 10 — Wavelength Grid

Working grid bounds and density

Contents

1	Case Study 10 — Wavelength Grid	1
1.1	What you will produce	1
1.2	1. Prerequisites	1
1.3	2. Inputs	1
1.4	3. Run with the CLI	2
1.5	4. Run with the HTTP API	2
1.6	5. Drive both interfaces from one Python script	2
1.7	6. Expected output layout	2
1.8	7. Related case studies	3

1 Case Study 10 — Wavelength Grid

Widen the working wavelength grid from the default 200..800 nm with 10000 points to 250..1100 nm with 20000 points. Use a wider grid when your dyes absorb (or your light sources emit) outside the default window — for instance NIR dyes, or solar spectra extending into the IR.

The user-selectable knobs are:

- CLI: `--wl-min FLOAT, --wl-max FLOAT, --num-points INT`
- API: form fields `wl_min, wl_max, num_points`

The grid is shared across all samples and all light sources in the same run.

1.1 What you will produce

Everything is written under one `output/` directory inside this case study folder:

Folder	By	Contents
<code>output/cli/tables/</code>	CLI	Result tables (CSV / JSON / XLSX)
<code>output/cli/plots/</code>	CLI	TIFF plots per sample, light source, and (sample, light) pair
<code>output/api/</code>	API	Same <code>tables/</code> and <code>plots/</code> tree, extracted from the ZIP
<code>output/api/analysis_outputs.zip</code>	API	Raw ZIP response

Light sources used: **AM1.5G + LED-B4**.

1.2 1. Prerequisites

If you have never run any case study before, follow [Case Study 01 §1 Prerequisites](#) once to install the package, the `requests` library, and either the Python or Docker option for the HTTP API. Every case study uses the same environment.

1.3 2. Inputs

The case-study `input.json` lists 2 Gaussian TD-DFT outputs. The manifest uses relative paths that point at the bundled data under `../input/files/`, so no files are copied or duplicated. To swap in your own data, replace `input.json` with a manifest of the same shape; you do not need to touch `submit.py`.

1.4 3. Run with the CLI

Open a terminal at the repository root, then run a single command:

```
overlap-calculator analyze --input case_studies/10_wavelength_grid/input.json --out
→ case_studies/10_wavelength_grid/output/cli --default-light-sources AM15G,LEDB4 --wl-min 250 --wl-max
→ 1100 --num-points 20000 --plot-dpi 400
```

After the run, `case_studies/10_wavelength_grid/output/cli/` contains a `tables/` directory (and a `plots/` directory unless plots were disabled). The `--default-light-sources` flag pins the bundled sources to AM1.5G + LED-B4; remove it to compare against the full default set (AM15G, LEDB4, LEDB2, LEDB3, CIEFL10).

1.5 4. Run with the HTTP API

Start the API as documented in [Case Study 01 §1](#) and verify with `curl http://localhost:8000/health` (or `:8080` if you started the API via `docker compose`). Then submit the same uploads in one `curl` command:

```
curl -X POST http://localhost:8000/analyze -F "files=@input/files/slurm-5473089.out" -F
→ "files=@input/files/slurm-5473178.out" -F "default_light_sources=AM15G,LEDB4" -F "wl_min=250" -F
→ "wl_max=1100" -F "num_points=20000" -F "plot_dpi=400" --output
→ case_studies/10_wavelength_grid/output/api/analysis_outputs.zip
```

Each `-F "files=@..."` is one upload. The form fields mirror the CLI flags. The response is a ZIP archive saved as `output/api/analysis_outputs.zip`.

1.6 5. Drive both interfaces from one Python script

Instead of typing the commands above, run `submit.py` from the repository root:

```
python case_studies/10_wavelength_grid/submit.py
```

The script reads `input.json`, runs the CLI step (writing to `output/cli/`), then POSTs the same uploads to `/analyze` and unpacks the response into `output/api/`. If the API is not reachable, it prints a hint and exits cleanly without failing the CLI step.

1.7 6. Expected output layout

```
case_studies/10_wavelength_grid/output/
+-- cli/
|   +-- tables/results.{csv,json,xlsx}          (2 samples × 2 light sources = 4 rows (250..1100 nm, 20000
→ pts))
|   +-- tables/results_timings.{csv,json,xlsx}
```

```

|  +-- tables/descriptor_summary.{csv,xlsx}
|  +-- tables/ranking_by_light_source__<metric>.{csv,json,xlsx}  (gaussian/lorentzian x
↪  absorbed_fraction/shape_overlap)
|  +-- tables/ranking_by_sample__<metric>.{csv,json,xlsx}        (same four metric variants)
|  +-- plots/                                                    (also
↪  plots/ranking/by_light_source/<metric>/ and plots/ranking/by_sample/<metric>/)
+-- api/
    +-- analysis_outputs.zip
    +-- tables/...
    +-- plots/...

```

API sample IDs are auto-generated from each upload's %chk header, while the CLI uses the `sample_id` you set in `input.json`. This is the only cosmetic difference between the two trees; the tables align row by row otherwise.

1.8 7. Related case studies

- [Case Study 08 — Broadening Sigma](#)
- [Case Study 09 — Beer–Lambert Tuning](#)
- [Case Study 01 — Theoretical Only](#)