



TOPLIS

TopSky plugin for Portugal vACC

User Manual
Version 2.0

October 2022

Contents

1 Introduction	5
1.1 Disclaimer	5
1.2 Foreword	5
2 System Description	7
2.1 Main Window	7
2.2 Global Menu	7
2.2.1 Setup Menu	8
2.2.2 AMS menu	12
2.2.3 FData menu	12
2.2.4 Tools menu	13
2.2.5 Tools menu	13
2.3 Track Presentation	15
2.4 Track Label Menus	15
2.5 Flight Leg	15
2.6 Windows	15
2.6.1 Airspace Management Window	15
2.7 Lists	17
2.7.1 NOTAM List	17
2.8 Safety Nets	18
2.9 Monitoring Aids	18
2.10 Flight Plan Conflict Probe	18
A Label field descriptions	19
B Color Values	21
C Keyboard Shortcuts	23
Bibliography	25

Introduction

1.1 Disclaimer


Although - as its name suggests - the plugin is based on TOPLIS and the TopSky ATM system, it is in no way affiliated with or endorsed by Thales Group or NAV Portugal. Similarities between plugin features and the real system are not entirely coincidental, but the plugin can not be used as a real world training aid. [1]

1.2 Foreword

EuroScope, a controller client developed by Gergely Csernák for the VATSIM network, was first released for public use in September 2007. One of the biggest changes in version 3.1 was the possibility for the user community to customize the program to an even higher degree than was possible before by writing their own plugins that can be used to alter the way information is presented and even create completely new functionality into the program. This allowed creating very detailed simulations of all kinds of ATC systems without making the main program overly complex. Version 3.2 expands on these possibilities, making it possible to create even better plugins. The TopSky plugin (a.k.a. The Plugin Formerly Known As “EUROCAT 2000 E”) started out as a very small project to create a couple of customized aircraft tag items, but as more information about the real system and the possibilities with the plugin development became available, it slowly grew to include an almost complete set of tag items, tag menus, graphical elements on the radar display and some additional functionality.

System Description


2.1 Main Window



Euroscope should load with some preplaced windows similar to the above configuration

Screen resolutions other than 1920x1080 will yield different results. Larger resolutions will bring preplaced windows towards the left and middle, while smaller resolutions may potentially place windows outside the screen. It is recommended for users experiencing difficulties related to their screen size to experiment and create custom settings in the TopSkySettingsLocal file containing revised window placements adjusted for their own screen. Refer to TopSky_Developer_Guide_Settings.xlsx for available settings.


2.2 Global Menu



The Global Menu is located on the top edge of the radar screen. It displays the current

UTC time and contains a number of submenus which are explained below.

2.2.1 Setup Menu



Setup Menu allows for various adjustments. Each position will load its defined settings based on the active Primary Frequency.

Most used options are CPDLC Setting for CPDLC operations and Default Setting to reset options.

- Unit Settings >	Opens the Unit Settings submenu
- Default Setting	Resets all settings to their default values (keeps login callsign specific ones if they are active at the time). When clicked, a confirmation window will open, asking to confirm the reset.
- Local Settings >	Opens the Local Settings submenu
- Brightness Control >	Opens the Brightness Control Window
- Sign In. . .	Loads personal settings. The settings are specified in the <code>TopSkySettingsLocal.txt</code> data file. When clicked, a confirmation window will open, asking to confirm the settings change.
- Sign Out. . .	Clears any personal settings and resets all settings to their default values. When clicked, a confirmation window will open, asking to confirm the settings change.
- CPDLC Setting. . .	Opens the CPDLC Setting Window
- FPASD	Toggles on/off the display of flight plan tracks
- PDC Audible alarm	Toggles on/off playing a sound for received PDC messages
- CPDLC Audible alarm	Toggles on/off playing a sound for received CPDLC messages
- STCA Audible alarm	Toggles on/off playing a sound for STCA alerts
- APW Audible alarm	Toggles on/off playing a sound for APW alerts
- AMID	Not implemented
- Flight Leg	Toggles on/off the automatic display of the Flight Leg for a specified time when a track becomes assumed
- DAPs in Menus	Toggles on/off the display of DAPs in menus
- DAPs in Labels	Toggles on/off the display of DAPs in track labels
- RR Main >	Opens the RR Main submenu
- Direction Finder >	Opens the Direction Finder submenu

Unit Settings submenu

This submenu can be used to change the units used in the plugin. Any changes to the settings are session- specific only, so they will be lost when exiting EuroScope.

- Altitude Selects the units used for altitudes and vertical rates - Nautical (feet, feet per minute) - Metric (meters, meters per second)
- Flight level Selects the units for flight levels – only applicable with metric altitudes - Nautical (hundreds of feet) - Metric (meters)
- Distance Selects the units used for distances - Nautical (nautical miles) - Metric (kilometers)
- Speed Selects the units used for speeds - Nautical (knots) - Metric (kilometers per hour)

Local Settings submenu

This submenu allows changing some of the plugin's settings. Any changes to the settings are session- specific only, so they will be lost when exiting EuroScope.

- Vertical reference	Selects the pressure reference to be used at or below the transition altitude: • QNH Altitude above mean sea level • QFE Height above the aerodrome elevation (set/check it in the adjacent box)
- Used equipment codes	Selects whether to use or disregard the equipment codes found in the flight plans: • All Use all codes • ICAO Use all codes when specified in ICAO format • ICAO-alt As ICAO, but force transponder to report altitude • None Disregard all codes
- ASSR codes	Selects the transponder code source: • Plugin Plugin data file (reverts to ESE if no codes found) • ESE ESE file • Range Fixed code range
- Groundspeed	Selects whether to use pilot client reported ground speed or a plugin calculated value. Normally the reported value should be used as it is more accurate and stable, but some clients report wrong values. If that causes problems, you can try selecting the plugin calculated value instead
- Transfer confirmation	Selects when to display the Transfer Confirmation Window: • On Always when CFL is not equal to XFL • NotRFL When CFL is not equal to XFL unless XFL = RFL • Off Never, any CFL value is OK
- CFL menu default value	Selects the default value for the CFL menu when it is opened: • XFL FSS or CTR: RFL if not yet reached, otherwise as below Other: The XFL value, or current CFL value with no XFL • CFL The current CFL value • RFL The RFL value
- FPCP inhibit	FPCP calculations start when tracks are within this time from entering active sector
- STCA alert	Selects which aircraft display the STCA alert: • All All aircraft • Own+Co Only assumed and coordinated aircraft • Own Only assumed aircraft
- STCA alert sound	Selects which STCA alerts trigger the alert sound: • All All alerts • Own+Co Only alerts with assumed and/or coordinated aircraft involved • Own Only alerts with assumed aircraft involved
- APW alert	Selects which aircraft display the APW alert: • All All aircraft • Own+Co Only assumed and coordinated aircraft • Own Only assumed aircraft
- APW alert sound	Selects which STCA alerts trigger the alert sound: • All All alerts • Own+Co Only alerts for assumed or coordinated aircraft • Own Only alerts for assumed aircraft
- METAR source	Selects the METAR data source for the plugin windows that display METAR data


RR Main submenu

- | | |
|--------------------|---|
| - [] Rings On/Off | Toggles the range rings on/off |
| - Point | Sets the rings centerpoint. Either click on the radar screen or enter the desired point in the text field. Fixes, VORs, NDBs and airports from the active sector file can be used as well as coordinates in the flight plan format (DD[N/S]DDD[E/W] or DDMM[N/S]DDDMM[E/W], e.g. 60N025E or 0811S00300W). Entering an empty text string resets the rings to be shown at the radar screen centerpoint. |
| - Separation | Sets the separation between adjacent rings |
| - Number | Sets the number of rings drawn |
| - [] Highlight | Toggles highlight (drawn with solid line) of specified rings |
| - Step | Sets interval of highlighted rings |

Direction Finder submenu


Not operational

2.2.2 AMS menu



Opens the *Airspace Management Window*.

2.2.3 FData menu



Opens the ?? and ??.

2.2.4 Tools menu

2.2.5 Tools menu

- | | |
|----------------------------|-------------------------------------|
| - Flight Plan Lists > | Opens the Flight Plan Lists submenu |
| - CARD. . . | Opens the ?? |
| - SAP. . . | Opens the ?? |
| - Vertical Aid Window. . . | Opens the ?? |
| - Message In. . . | Opens the ?? |
| - Message Out. . . | Opens the ?? |
| - CPDLC > | Opens the CPDLC submenu |
| - LAT/LONG. . . | Opens the ?? |

Flight Plan Lists submenu

- | | |
|-----------------------------|--|
| - [] List options bar | Toggles the display of list options on the Global Menu |
| - Sector List. . . | Opens the Sector List |
| - [] Informed | Toggles the display of informed aircraft |
| - [] Concerned | Toggles the display of concerned aircraft |
| - [] Redundant | Toggles the display of redundant aircraft |
| - Load Factor List. . . | Opens the ?? |
| - ETWR List. . . | Opens the ?? |
| - <adep> | ETWR List departure airports filter |
| - Uncont. List 1. . . | Opens the ?? |
| - <filter> | Uncontrolled 1 List state filter |
| - <units> | Uncontrolled 1 List units filter |
| - Uncont. List 2. . . | Opens the ?? |
| - <filter> | Uncontrolled 2 List state filter |
| - <units> | Uncontrolled 2 List units filter |
| - Lost List. . . | Opens the ?? |
| - Resectorisation List. . . | Opens the ?? |
| - <lfunc> | Resectorisation List LFUNC filter |
| - Traffic Mgmt. List 1. . . | Opens the ?? |
| - <state> | Traffic Management List 1 flight plan state filter |
| - <ades> | Traffic Management List 1 destination airports filter |
| - <via> | Traffic Management List 1 route points filter |
| - Traffic Mgmt. List 2. . . | Opens the ?? |
| - <state> | Traffic Management List 2 flight plan state filter |
| - <ades> | Traffic Management List 2 destination airports filter |
| - <via> | Traffic Management List 2 route points filter |

When enabled, the list options bar displays “Info Conc Redu Filter Filter” on the right edge of the Global Menu. The first three toggle the respective settings for the Sector List and are colored with the appropriate color when enabled, and the last two

are displayed in “VFR” color when the corresponding Uncontrolled list is somehow filtered. Clicking on them opens the Flight Plan Lists submenu to change the filtering options.

Left-clicking <filter> cycles through “ALL” (no filtering), “ON-CONTACT” (only tracks on-contact with anyone), “ON-CONTACT-PPOS” (only tracks on-contact with you) and “FREE” (only tracks in the free state).

Left-clicking <units> opens a text entry box to enter a comma-separated list of aerodrome ICAO codes to filter the list. When entered, the list will display a flight only if one of the entered codes is its departure or destination, or the code is found in its scratchpad (OP-TEXT2).

Left-clicking <lfunc>, <adep>, <ades> and <via> open text entry boxes to enter comma-separated lists for controlled ID's, ICAO codes and point names respectively to filter the affected lists.

Left-clicking <state> toggles between “ALL” (no filtering), “SIMUL+TERM” (not started flight plans filtered), “NOTST+SIMUL” (terminated flight plans filtered) and “SIMUL” (not started and terminated flight plans filtered).


2.3 Track Presentation

2.4 Track Label Menus

2.5 Flight Leg

2.6 Windows

2.6.1 Airspace Management Window



The screenshot shows a window titled "AIRSPACE MANAGEMENT". Inside, there is a table with columns: Name, Map Text, Start Date, Start Time, End Date, End Time, Lower, Upper, Auto, and User. The table contains several rows of data, including active areas (blue background) and pre-active areas (yellow background). At the bottom of the window are three buttons: "Ok", "Apply", and "Cancel".

Name	Map Text	Start Date	Start Time	End Date	End Time	Lower	Upper	Auto	User
D65	D65	221013	00:00	221013	23:59		10	A	
D28A	D28A	221013	03:00	221013	22:59		33	M	
LER86A	LER86A	221013	06:00	221013	18:30		450	A	MIL
LER86B	LER86B	221013	06:00	221013	18:30	50	245	A	MIL
LER86C	LER86C	221013	06:00	221013	18:30	245	450	A	MIL
063-2021	063-2021	221013	07:00	221013	18:00		15	A	
068-2021	068-2021	221013	07:00	221013	22:59		20	A	
AMENDOEIRA	AMENDOEIRA	221013	07:00	221013	18:00		55	A	
BRAGA	BRAGA	221013	07:00	221013	18:00		20	A	
EVORA	EVORA	221013	07:00	221013	18:00		150	A	

This window is used for the activation and deactivation of the areas for the APW and SAP functionality. Each area can have a start time and/or an end time defined for its activation, or it can be activated without any time limits, making it active until deactivated manually. Additionally, lower and upper altitude limits are given. An area can have activation schedules defined in the area data file. Such areas will be automatically activated as long as their “Auto” option is selected (“A” in the “Auto” column). The “Auto” option cannot be selected for areas that don’t have an activation schedule defined in the area data file.

Dates will be shown in the format “yymmdd” and times in “hh:mm” and they must be entered in the same format. Entering an empty string for a date will clear it and the related time value and vice versa. When entering a time or date value to an empty field, the other value is automatically set to the current time/date value. Entering an empty string to the Map Text, Lower or Upper fields will reset the value to the default one from the data file.

Altitudes are shown in hundreds of feet if at or below the transition altitude, otherwise in flight levels. They must be entered in the same format.

An area’s activation status can be inactive, pre-active or active. A pre-active area is an area that will become active within 30 minutes and is shown in yellow text on a gray background. An active area is shown with yellow text on a blue background. The

APW system will not alert for a pre-active area, but for the SAP system a pre-active area is considered as being active.

The mouse click areas of the Airspace Management Window:

- Sorting option text (e.g. “Start date/time”) Opens a pop-up menu to select a sorting option for the list
- Right-click to open an area pop-up menu
- Other fields Left-click to edit field (when edit function active)
- “Ok” button Applies the changes, closes the window
- “Apply” button Applies the changes
- “Cancel” button Cancels the changes

The sorting pop-up menu contains the following items:

- Start Date Sorts based on the Start Date/Time, earliest first
- Name Sorts alphabetically based on the Name field
- Map Text Sorts alphabetically based on the Map Text field

With the area pop-up menu opened, the area text row background changes to black. The menu contains the following items:

- ACTIVATE Clears any activation times and activates the area
- DEACTIVATE Clears any activation times and deactivates the area
- AUTO If an activation schedule is found in the area data file, sets the area to be activated automatically
- VALIDATE Not implemented
- EDIT Allows to change the area parameters
- COPY Not implemented
- DELETE Clears any activation times, returns label and altitude limits to their default values and deactivates the area


After any selection from the pop-up menu, “Ok”, “Apply” or “Cancel” must be selected to apply or cancel the selection.

Preactive and active areas are displayed on the radar screen. The area border is drawn using a predefined color and it may be filled as well. A predefined text label may also be displayed, showing information about the area. A very small “+” symbol will be drawn at that location. By holding the left mouse button down on that symbol, a full area label will be displayed, showing:

Name
Map text
Upper level limit
Start time — End time
Lower level limit
time in minutes until the area becomes active

2.7 Lists

2.7.1 NOTAM List



The NOTAM List is automatically displayed at startup in order to fetch the current FUA. It may be closed after loading.

2.8 Safety Nets

2.9 Monitoring Aids

2.10 Flight Plan Conflict Probe

Label field descriptions

Color Values

Keyboard Shortcuts

Bibliography

- [1] TopSky plugin for Portugal vACC. <https://github.com/pinatacolada/topskylppc#disclamer>.