

PingDirectory®

Time-based One-Time Password (TOTP) on Simple Bind Plugin v1.0.0

User Guide



© 2005-2018 Ping Identity ® Corporation. All rights reserved.

PingDirectory Time-based One-Time Password (TOTP) on Simple Bind Plugin User Guide
Version 1.0.0
February 2018

Ping Identity Corporation
1001 17th Street, Suite 100
Denver, CO 80202
USA

Phone: 877.898.2905 (+1 303.468.2882 outside North America)

Fax: 303.468.2909 E-mail: info@pingidentity.com

Web Site: <http://www.pingidentity.com>

Trademarks

Ping Identity, the Ping Identity logo and PingDirectory are registered trademarks of Ping Identity Corporation ("Ping Identity"). All other trademarks or registered trademarks are the property of their respective owners.

Disclaimer

This document is proprietary and not for general publication. It may be provided ad hoc for informational purposes only, and the information herein is subject to change without notice. Ping Identity does not provide any warranties and specifically disclaims any liability in connection with this document.

Note that Ping Identity may not provide support for any sample configurations provided in this document. The variability inherent among security environments prevents full testing and support for all possible platform configurations. If you need special assistance or would like to inquire about implementation or support programs, please contact Ping Identity Global Client Services (<http://support.pingidentity.com>).

Table of Contents

Purpose 4

Prerequisites 4

Installation..... 4

Purpose

The "Time-based One-Time Password (TOTP) on Simple Bind" Plugin allows PingDirectory to expect the password, provided in the bind request, to be immediately followed by the TOTP code.

Prerequisites

This document assumes that a functional PingDirectory, Version 6.*, has already been installed and configured.

Installation

1. Copy the included zip file to a temporary location on the server that is running PingDirectory.
2. Open a terminal window.
3. Change directories to the installation path of the target PingDirectory server.
4. Execute the "manage-extension" command in the bin directory of the installation path to install the zip file and follow any prompts to continue and restart the server:

```
bin/manage-extension --install <path to the zip file>
```

5. Execute the "dsconfig" command in the bin directory of the installation path to configure the plugin and press "f" at the prompt to finish the configuration of the plugin:

```
bin/dsconfig create-plugin \  
  --plugin-name "TOTP on Simple Bind" \  
  --type third-party \  
  --set enabled:true \  
  --set plugin-type:preoperationbind \  
  --set extension-class:com.pingidentity.ps.ds.plugin.TOTPSimple \  
  --set extension-argument:totp-length=6 \  
  --set extension-argument:totp-is-last=true
```

"totp-length" is an optional argument and specifies the length of the TOTP code. Default value is "6".

"totp-is-last" is an optional argument and specifies whether the TOTP code is immediately after the password. Default value is "true".

6. *Optional:* To enable Server Extension debug messages, execute the following command:

```
bin/dsconfig set-log-publisher-prop \  
  --publisher-name "Server SDK Extension Debug Logger" \  
  --set enabled:true
```

7. *Optional:* To delete the plugin, execute the following command:

```
bin/dsconfig delete-plugin --plugin-name "TOTP on Simple Bind"
```