

Application of Wavelet in Computer Graphics: Wavelet Radiosity

Pinkesh Barsopia (123079006)

Guide: Prof. V. M. Gadre
Department of Electrical Engineering
Indian Institute of Technology Bombay

May 26, 2015

Outline

Introduction

Image Synthesis in Computer Graphics

Radiosity Integral Equation (RIE)

Literature Survey

Test Scenes and Metric for Comparison

Radiosity in 2 and 3 Dimensions

Relative Error

Projection Methods for Radiosity

Choice of a Finite Space

Choice of a Basis

Experiments and Results

Conclusion and Future Work

Direct and Indirect Illumination

- ▶ Rendering-Image synthesis from closed scene given
 - ▶ Geometry of scene
 - ▶ Optical properties of surfaces (BRDF)
 - ▶ Location of Light Source
- ▶ Types of renderer
 - ▶ Direct illumination
 - ▶ Indirect Illumination (Global Illumination)
- ▶ Types of Indirect Illumination renderer
 - ▶ Ray-Tracing
 - ▶ Radiosity (Lambertian BRDF)

Direct and Indirect Illumination




Figure : Direct and Indirect Illumination¹

¹[www.wikipedia.org/wiki/Radiosity\(computer_graphics\)](http://www.wikipedia.org/wiki/Radiosity(computer_graphics)).

Radiosity Integral Equation (RIE)

Radiosity \rightarrow Power per unit area

$$B_i = E_i + \sum_j K_{i,j} B_j, \quad j \in \{Allsurfaces\} \quad (1)$$

$$K_{i,j} = \frac{\text{Radiosity received by } i \text{ from } j}{\text{Radiosity leaving from } j}$$

$E_i \rightarrow$ Non zero for light source

$p_i \rightarrow$ BRDF of surface

Domain, $M^2 \rightarrow L^2(\mathbb{R}^2)$, finite support

$$B(x) = B(x) + p(x) \int_{M^2} K(x, y) B(y) \quad \forall x \in M^2 \quad (2)$$

Literature Survey

- ▶ Cohen et al. solved with n patches (constant radiosity) and n^2 from factors, $K_{i,j}$, $i, j = 1, 2, \dots, n$.
- ▶ Kajia \rightarrow radiosity integral equation \rightarrow Projection methods (solve IE in finite space).
- ▶ Finite space
 - ▶ Heckbert \rightarrow Piecewise linear
 - ▶ Zatz \rightarrow Piecewise polynomial of higher order
 - ▶ Hanarahan et al. \rightarrow Hierarchy of basis (Haar wavelet basis)
- ▶ Gortler et al. \rightarrow used wavelet basis \rightarrow wavelet radiosity

Test Scenes: 3 Dimensional




Figure : 3D scene: Two parallel surfaces




Figure : 3D Geometry: Kernel calculation

$$K(x, y) = \frac{\cos \theta_x \cos \theta_y}{\pi r_{xy}^2} V(x, y) \quad (3)$$

Test Scenes: 2 Dimensional




Figure : Flatland scene 1:




Figure : Flatland scene 2:
perpendicular segments

Kernel Calculation: 2 Dimensional




Figure : Kernel for two line segments

$$K(x, y) = \frac{\cos \theta_x \cos \theta_y}{2r_{xy}} V(x, y) \quad (4)$$

Solution of Flatland Scenes 1




Figure : Radiosity $B_1(x)$




Figure : Radiosity $B_2(y)$



Solution of Flatland Scenes 2




Figure : Image of B_1





Figure : Image of B_2



Metric for Comparison

Relative error (L^2 norm) in K for comparison

$$\text{relative error} = \frac{\int \int (K(x, y) - \hat{K}(x, y))^2 dy dx}{\int \int K(x, y)^2 dy dx} \quad (5)$$

Relative error (L^2 norm) in B for comparison

$$\text{relative error} = \frac{\int (B(x) - \hat{B}(x))^2 dx}{\int B(x)^2 dx} \quad (6)$$

Projection Methods for Radiosity

Choice of a Finite space

Space of Piecewise polynomial function of order m , over standard interval $(\frac{1}{n})$




Figure : Error in projection of $K(x,y)$ for Flatland scene 1




Figure : Error in projection of $K(x,y)$ for Flatland scene 2

Analytical Solution

$$B(x) = 1 + \int K(x, y)B(y)dy \quad (7)$$

$$K(x, y) = x^2 + xy, \quad x, y \in [0, 1]$$

$$\text{Degenerate kernel, } K(x, y) = \sum_{i=1}^n a_i(x)b_i(y)$$




Figure : Solution using




Figure : Solution using

Analytical Solution for $m = 1, 2$




Figure : Solution using $n = 2, m = 1$




Figure : Solution using $n = 4, m = 1$




Figure : Solution using $n = 1, m = 2$




Figure : Solution using $n = 2, m = 2$

Choice of a Basis: Wavelets

Choice of alternative basis for chosen space

- ▶ Haar
- ▶ Linear Legendre Multi-Wavelet
- ▶ Quadratic Legendre Multi-Wavelet

Advantages

- ▶ Vanishing Moments
- ▶ Negligible coefficients
- ▶ Sparse System of equation
- ▶ Faster Solution

Haar Wavelet: Alternate Basis

Haar Wavelet

$$\phi(x) = \begin{cases} 1 & \text{and if } 0 \leq x < 1 \\ 0 & \text{and elsewhere} \end{cases}$$

$$\psi^0(x) = \begin{cases} 1 & \text{and if } 0 \leq x < \frac{1}{2} \\ -1 & \text{and if } \frac{1}{2} \leq x < 1 \\ 0 & \text{and elsewhere} \end{cases}$$

Basis: Haar scaling function

$$\{\phi_{\frac{1}{n},k}(x)\},$$

$$k=0,1,\dots,n-1$$

$$\text{where, } \phi_{\frac{1}{n},k}(x) = \frac{1}{\sqrt{n}}\phi(nx - k)$$

Basis: Haar wavelet

$$\{\phi(x), \psi(x), \phi_{\frac{1}{L},k}(x)\},$$

$$k=0,1,\dots,n-1 \text{ and } k=0,1,\dots,L-1$$

$$\text{where, } \psi_{\frac{1}{n},k}(x) = \frac{1}{\sqrt{n}}\psi(nx - k)$$

Error vs n

Projection Methods for Radiosity