

Application of Wavelets in Computer Graphics: Wavelet Radiosity

Pinkesh Barsopia (123079006)

Guide: Prof. V. M. Gadre
Department of Electrical Engineering
Indian Institute of Technology Bombay

May 26, 2015

Outline

Introduction

Image Synthesis in Computer Graphics

Radiosity Integral Equation (RIE)

Literature Survey

Test Scenes and Metric for Comparison

Radiosity in 2 and 3 Dimensions

Relative Error

Projection Methods for Radiosity

Choice of a Finite Dimensional Space

Choice of a Basis

Experiments and Results

Conclusion and Future Work

Direct and Indirect Illumination

- ▶ Rendering-image synthesis from closed scene given,
 - ▶ Geometry of scene
 - ▶ Optical properties of surfaces (BRDF)
 - ▶ Location of light source
- ▶ Types of renderer
 - ▶ Direct illumination
 - ▶ Indirect illumination (global illumination)
- ▶ Types of indirect illumination renderer
 - ▶ Ray-tracing
 - ▶ Radiosity (Lambertian BRDF)

Direct and Indirect Illumination




Figure : Direct and Indirect Illumination¹

¹[www.wikipedia.org/wiki/Radiosity\(Computer Graphics\)](http://www.wikipedia.org/wiki/Radiosity(Computer_Graphics)).

Radiosity Integral Equation (RIE)

Radiosity \rightarrow Power (light) per unit area

$$B_i = E_i + \sum_j K_{i,j} B_j, \quad j \in \{All\ Surfaces\} \quad (1)$$

$$K_{i,j} = \frac{\text{Radiosity received by } i \text{ from } j}{\text{Radiosity leaving from } j}$$

$E_i \rightarrow$ Non zero for light source

$p_i \rightarrow$ BRDF of surface i

Domain of surfaces (M^2) is $L^2(\mathbb{R}^2)$ with finite support

$$B(x) = E(x) + p(x) \int_{M^2} K(x, y) B(y) dy \quad \forall x \in M^2 \quad (2)$$

Literature Survey

- ▶ Cohen et al. solved with n patches (constant radiosity) and n^2 from factors, K_{ij} , $i, j = 1, 2, \dots, n$.
- ▶ Kajia et al. \rightarrow radiosity integral equation \rightarrow Projection methods (solve RIE in finite dimensional space).
- ▶ Finite Dimensional space
 - ▶ Heckbert \rightarrow Piecewise linear
 - ▶ Zatz \rightarrow Piecewise polynomial of higher order
 - ▶ Hanarahan et al. \rightarrow Hierarchy of basis (Haar wavelet basis)
- ▶ Gortler et al. \rightarrow used wavelet basis \rightarrow wavelet radiosity

Test Scenes: 3 Dimensional




Figure : 3D scene: Two Parallel Surfaces




Figure : 3D Geometry: Kernel Calculation

$$K(x, y) = \frac{\cos \theta_x \cos \theta_y}{\pi r_{xy}^2} V(x, y) \quad (3)$$

Test Scenes: 2 Dimensional




Figure : Flatland Scene 1:
Parallel Segments




Figure : Flatland Scene 2:
Perpendicular Segments

Kernel Calculation: 2 Dimensional




Figure : Kernel for Any Two Line Segments X and Y

$$K(x, y) = \frac{\cos \theta_x \cos \theta_y}{2r_{xy}} V(x, y) \quad (4)$$

Solution for Flatland Scene 1




Figure : Radiosity $B_1(x)$



Figure : Image of B_1




Figure : Radiosity $B_2(y)$



Figure : Image of B_2

Solution of Flatland Scene 2




Figure : Radiosity $B_1(x)$



Figure : Image of B_1




Figure : Radiosity $B_2(y)$



Figure : Image of B_2

Metric for Comparison

Relative Error in Projection of K

$$\text{Relative Error} = \frac{\int \int (K(x, y) - \hat{K}(x, y))^2 dy dx}{\int \int K(x, y)^2 dy dx} \quad (5)$$

Relative Error in Projection of B

$$\text{Relative Error} = \frac{\int (B(x) - \hat{B}(x))^2 dx}{\int B(x)^2 dx} \quad (6)$$

Projection Methods for Radiosity

Discretization of Radiosity Integral Equation, using
Basis, $\{N_i(x)\}_{i=0,1,2,\dots}$, of the infinite dimensional space L^2

$$B_p(x) = \sum_{i=0}^{\infty} \langle B(x), \tilde{N}_i(x) \rangle N_i(x) \quad (7)$$

$$B_p(x) = E_p(x) + \int K(x, y) B_p(y) dy \quad (8)$$

$$B_p(x) = E_p(x) + KB_p(x) \quad (9)$$

where, $KB_p(x) = \int K(x, y) B_p(y) dy$

$$KB_p(x) = \sum_{i=0}^{\infty} \langle KB_p(x), \tilde{N}_i(x) \rangle N_i(x) \quad (10)$$

Projection Methods for Radiosity

$$\begin{bmatrix} B_1 \\ B_2 \\ \vdots \end{bmatrix} = \begin{bmatrix} E_1 \\ E_2 \\ \vdots \end{bmatrix} + \begin{bmatrix} k_{11} & k_{12} & \cdots \\ k_{21} & k_{22} & \cdots \\ \vdots & \vdots & \ddots \end{bmatrix} \begin{bmatrix} B_1 \\ B_2 \\ \vdots \end{bmatrix} \quad (11)$$

$$\mathbf{B} = \mathbf{E} + \mathbf{KB} \quad (12)$$

$$K_{i,j} = \langle \langle K(x, y), N_j(y) \rangle, \tilde{N}_i(x) \rangle = \int \int K(x, y) N_j(y) \tilde{N}_i(x) dy dx$$

- ▶ Discrete, but countably infinite no. of coefficients
- ▶ Project in finite dimensional space \rightarrow Finite no. of coefficients
- ▶ Error in Projection \rightarrow Choice of finite dimensional space
- ▶ Speed of solution \rightarrow Choice of a basis for the chosen space

Implementation of Algorithm

- ▶ Select finite dimensional function space
- ▶ Select Basis for that space
- ▶ Project $E(x)$ and $K(x)$ into chosen space \rightarrow inner product using Gauss-Legendre Quadrature rule for integration
- ▶ Solve System of linear equation using Jacobi iteration

Radiosity for scene with RGB colors can be calculated by solving this algorithm for 3 wavelength separately.

Choice of a Finite Dimensional Space

Space of piece-wise polynomial functions of order m , over standard interval $(1/n)$, using set of shifted Legendre polynomial up to order m




Figure : Error in Projection of

Pinkesh Barsopia (123079006)




Figure : Error in Projection of

Application of Wavelets in Computer Graphics: Wavelet Radiosity

Analytical Solution

$$B(x) = 1 + \int K(x, y)B(y)dy \quad (13)$$

$$K(x, y) = x^2 + xy, \quad x, y \in [0, 1]$$

$$\text{Degenerate kernel, } K(x, y) = \sum_{i=1}^n a_i(x)b_i(y)$$

Numerical Solution with $m = 0$




Figure : Solution Using
 $n = 4, m = 0$




Figure : Solution Using
 $n = 16, m = 0$

Numerical Solution with $m = 1$




Figure : Solution Using
 $n = 2, m = 1$




Figure : Solution Using
 $n = 4, m = 1$

Numerical Solution with $m = 2$




Figure : Solution Using
 $n = 1, m = 2$




Figure : Solution Using
 $n = 2, m = 2$

Choice of a Basis: Wavelets

Choice of alternative basis for chosen space

- ▶ Haar
- ▶ Linear Legendre Multi-Wavelet
- ▶ Quadratic Legendre Multi-Wavelet

Advantages

- ▶ Vanishing moments
- ▶ Negligible coefficients
- ▶ Sparse system of equation
- ▶ Faster solution

Haar Wavelet: As a Alternate Basis

$$\phi_0(x) = \begin{cases} 1 & \text{if } 0 \leq x < 1 \\ 0 & \text{elsewhere} \end{cases}$$

$$\psi_0(x) = \begin{cases} 1 & \text{if } 0 \leq x < \frac{1}{2} \\ -1 & \text{if } \frac{1}{2} \leq x < 1 \\ 0 & \text{elsewhere} \end{cases}$$

Basis: Haar scaling function

$$\{\phi_{\frac{1}{n},k}(x)\},$$

$$k = 0, 1, \dots, n-1$$

where, $\phi_{\frac{1}{n},k}(x) = \sqrt{n}\phi_0(nx - k)$

Basis: Haar wavelet

$$\{\phi_0(x), \psi_0(x), \psi_{\frac{1}{L},k}(x)\},$$

$$L = 2, 4, 8, \dots, 2^{n-1} \text{ and}$$

$$k = 0, 1, \dots, L-1$$

where, $\psi_{\frac{1}{n},k}(x) = \sqrt{n}\psi_0(nx - k)$

Sparsity of Kernel Projection Matrix

Flatland 1 using Haar wavelet and scaling functions. Radius of circle is proportional to absolute value of coefficient




Figure : Scaling Functions as basis




Figure : Wavelet Functions as basis

Linear Legendre Multi-wavelet (LLMW)

Two mother wavelet and scaling function




Figure : LLMW: $\phi^0(x)$




Figure : LLMW: $\phi^1(x)$

$$\phi^0(x) = \begin{cases} 1 & \text{if } 0 \leq x < 1 \\ 0 & \text{elsewhere} \end{cases}$$

$$\phi^1(x) = \begin{cases} \sqrt{3}(2x - 1) & \text{if } 0 \leq x < 1 \\ 0 & \text{elsewhere} \end{cases}$$

Linear Legendre Multi-wavelet (LLMW)




Figure : LLMW: $\psi^0(x)$

$$\psi^0(x) = \begin{cases} -\sqrt{3}(4x - 1) & \text{if } 0 \leq x < \frac{1}{2} \\ \sqrt{3}(4x - 1) & \text{if } \frac{1}{2} \leq x < 1 \\ 0 & \text{elsewhere} \end{cases}$$




Figure : LLMW: $\psi^1(x)$

$$\psi^1(x) = \begin{cases} (6x - 1) & \text{if } 0 \leq x < \frac{1}{2} \\ (6x - 5) & \text{if } \frac{1}{2} \leq x < 1 \\ 0 & \text{elsewhere} \end{cases}$$

Quadratic Legendre Multi-wavelet (QLMW)

Three mother wavelet and scaling function




Figure : QLMW: $\phi^0(x)$

$$\phi^0(x) = \begin{cases} 1 & \text{if } 0 \leq x < 1 \\ 0 & \text{elsewhere} \end{cases}$$




Figure : QLMW: $\phi^1(x)$

$$\phi^1(x) = \begin{cases} \sqrt{3}(2x - 1) & \text{if } 0 \leq x < 1 \\ 0 & \text{elsewhere} \end{cases}$$

Quadratic Legendre Multi-wavelet (QLMW)




Figure : QLMW: $\phi^2(x)$

$$\phi^2(x) = \begin{cases} \sqrt{5}(6x^2 - 6x + 1), & \text{if } 0 \leq x < 1 \\ 0 & \text{elsewhere} \end{cases}$$




Figure : QLMW: $\psi^0(x)$

$$\psi^0(x) = \begin{cases} -\frac{1}{3}(120x^2 - 72x + 7) & \text{if } 0 \leq x < \frac{1}{2} \\ \frac{1}{3}(120x^2 - 168x + 55) & \text{if } \frac{1}{2} \leq x < 1 \\ 0 & \text{elsewhere} \end{cases}$$

Quadratic Legendre Multi-wavelet (QLMW)




Figure : QLMW: $\psi^1(x)$

$$\psi^1(x) = \begin{cases} \sqrt{3}(30x^2 - 14x + 1) & \text{if } 0 \leq x < \frac{1}{2} \\ \sqrt{3}(30x^2 - 46x + 17) & \text{if } \frac{1}{2} \leq x < 1 \\ 0 & \text{elsewhere} \end{cases}$$




Figure : QLMW: $\psi^2(x)$

$$\psi^2(x) = \begin{cases} -\frac{\sqrt{5}}{3}(48x^2 - 18x + 1) & \text{if } 0 \leq x < \frac{1}{2} \\ \frac{\sqrt{5}}{3}(48x^2 - 78x + 31) & \text{if } \frac{1}{2} \leq x < 1 \\ 0 & \text{elsewhere} \end{cases}$$

Sparsity of Kernel Projection Matrix

Flatland 1 using Haar wavelet and scaling functions




Figure : Sorted Coefficients Based on Magnitude

Sparsity of Kernel Projection Matrix

Flatland 1 using LLMW wavelet and scaling functions




Figure : Sorted Coefficients Based on Magnitude

Sparsity of Kernel Projection Matrix

Flatland 1 using LLMW wavelet and scaling functions




Figure : Sorted Coefficients Based on Magnitude (Log Scale)

Sparsity of Kernel Projection Matrix

Flatland 1 using QLMW wavelet and scaling functions




Figure : Sorted Coefficients Based on Magnitude (Log Scale)

Error in Projection

Keeping top n coefficients (rest of the coefficient are set to zero)




Figure : Haar, $n = 256$

Error in Projection

Keeping top n coefficients (rest of the coefficient are set to zero)




Figure : LLMW, $n = 64$

Image Synthesis from 3D scene: Haar Wavelet

Solution of 3D scene with Haar wavelet and $n = 4$




Figure : Illumination of 3D scene (2 parallel surfaces) by square light source shown near center of one surface (left image)

Image Synthesis from 3D scene: Haar Wavelet

Solution of 3D scene with Haar wavelet and $n = 16$




Figure : Illumination of 3D scene (2 parallel surfaces) by square light source shown near center of one surface (left image)

Image Synthesis from 3D scene: Haar Wavelet

Solution of 3D scene with Haar wavelet, $n = 16$, retaining half of the 256 coefficients.




Figure : Illumination of 3D scene (2 parallel surfaces) by square light source shown near center of one surface (left image)

Image Synthesis from 3D scene: LLMW Wavelet

Solution of 3D scene with LLMW wavelet and $n = 16$




Figure : Illumination of 3D scene (2 parallel surfaces) by square light source shown near center of one surface (left image)

Image Synthesis from 3D scene: LLMW Wavelet

Solution of 3D scene with LLMW wavelet and $n = 16$, retaining quarter of the 1024 coefficients.




Figure : Illumination of 3D scene (2 parallel surfaces) by square light source shown near center of one surface (left image)

Image Synthesis from 3D scene: QLMW Wavelet

Solution of 3D scene with QLMW wavelet and $n = 4$.




Figure : Illumination of 3D scene (2 parallel surfaces) by square light source shown near center of one surface (left image)

Image Synthesis from 3D scene: QLMW Wavelet

Solution of 3D scene with LLMW wavelet and $n = 16$, retaining half of the 144 coefficients.




Figure : Illumination of 3D scene (2 parallel surfaces) by square light source shown near center of one surface (left image)

Conclusion and Future Work

- ▶ Projection methods are used to solve a radiosity integral equation.
- ▶ Different finite dimensional function space of piecewise polynomials of order 0, 1, 2 has been used for projection.
- ▶ Projection error decreases either when order of polynomials is increased or when interval size is decreased.
- ▶ Different basis like Haar wavelet, shifted Legendre polynomials, Legendre multi-wavelet (linear and quadratic) has been used for Comparison. In future other wavelets like Chebyshev multi-wavelet and other polynomial order wavelets can be used.
- ▶ Wavelet basis gives very sparse system of linear equations. Thus, setting negligible coefficients to zero increases speed of the algorithm.

- ▶ Different test scenes, 2D and 3D, has been used to test the algorithm. In future we can use more test scenes to verify results.
- ▶ Test scene under consideration are without occlusion, in future, testing performance of wavelets with scenes having occlusion can be done



Goral, Cindy M. and Torrance, Kenneth E. and Greenberg, Donald P. and Battaile, Bennett, "Modeling the Interaction of Light Between Diffuse Surfaces," *SIGGRAPH Comput. Graph.*, 1984.



Whitted, Turner, "An Improved Illumination Model for Shaded Display," *Commun. ACM*, June 1980.



Kajiya, James T., "The Rendering Equation," *SIGGRAPH Comput. Graph.*, Aug. 1986.



Ilias S., "A Survey on Solution Methods for Integral Equations," *Commun. ACM*, 2008.



Yury V. and Yury G. , "Integral Equations," 2002,



Stollnitz, Eric J. and Deroose, Tony D. and Salesin, David H., "Wavelets for Computer Graphics: Theory and Applications," 1996, isbn = 1-55860-375-1, Morgan Kaufmann Publishers Inc..



Stoer J. , Bulirsch R., "Introduction to Numerical Analysis," 1980, Springer Verlag, New York.



Lakestani, Mehrdad and Saray, Behzad Nemati and Dehghan, Mehdi, "Numerical Solution for the Weakly Singular Fredholm Integro-differential Equations Using Legendre Multiwavelets," *J. Comput. Appl. Math.*, April, 2011.



Alpert, Bradley K., "A Class of Bases in L_2 for the Sparse Representations of Integral Operators", *SIAM J. Math. Anal.*, Jan. 1993.



Hanrahan, Pat and Salzman, David and Aupperle, Larry, "A Rapid Hierarchical Radiosity Algorithm" *SIGGRAPH Comput. Graph.*, July 1991.



Heckbert, Paul Seagrave, "Simulating Global Illumination Using Adaptive Meshing, ", 1992.



Zatz, Harold R., "Galerkin Radiosity A Higher Order Solution Method for Global Illumination," *SIGGRAPH '93*, 1993.



Gortler, Steven J. and Schrder, Peter and Cohen, Michael F. and Hanrahan, Pat, "Wavelet Radiosity," *SIGGRAPH '93*, 1993.

