

PRODUCT-DETAILS

EM44304TS-4

General Purpose Motor 300 Hp 460 V (EM44304TS-4)



General Information	
Global Commercial Alias	EM44304TS-4
Product ID	7BEM44304TS-4
ABB Type Designation	300HP,1780RPM,3PH,60HZ,449TS,TEFC,F
Catalog Description	General Purpose Motor 300 Hp 460 V (EM44304TS-4)

Additional Information	
ABB Type Designation	300HP,1780RPM,3PH,60HZ,449TS,TEFC,F
Ambient Temperature	40 °C
Brake Present	No
Brand / Label	Baldor-Reliance
Catalog Number	EM44304TS-4
Certification Agency	CCSA US CSA EEV
Country of Origin	United States (US)
Customs Tariff Number	85015381
Dimension Diagram	617427-445
Drive End Flange Type	Standard
ETIM 7	EC001851 - Electric motor

Efficiency Level	Premium Efficiency (NEMA 12-12)
Electrical Data	

Current	Freq	Power	Speed	Voltage			
327 A	60 Hz	300 Hp	1780 r/min	460 V			
Enclosure Type					TEFC		
Explosion Proof Group Class					NONE		
Frame Material					Iron		
Frame Size					449		
Frequency (f)					60 Hz		
Global Commercial Alias			EM44304TS-				
Gross Volume					79178 in ³		
Gross Weight					1253.729 kg		
IDEA Granular Category Code (IGCC)			1325 >> General purpose motor AC				
Invoice Description			300HP,1780	RPM,3PH,60HZ,449	TS,TEFC,F1		
Made To Order					No		
Medium Description			General Purpose 3PH Enclosed, 300 HP, 1800 RPM, Frame Size 449Ts, Standard Mounting, 3 Phase, TEFC Enclosure, 460 V, 60 Hz (EM44304T				
Minimum Order Quantity					1 piece		
Motor Base Type				F	oot Mounted		
Motor Frame Size					449TS		
NEMA Design Code					В		
Number of Phases					3		
Number of Poles					4		
Number of Poles (High)					4		
Number of Speeds				S	ingle Speed		
Order Multiple					1 piece		
Output Power					300 Hp		
Product Name				General Purpose 3F	PH Enclosed		
Product Net Depth / Length					61 in		
Product Net Height					29.5 in		
Product Net Weight					1253.729 kg		
Product Net Width					44 in		
Product Type					Undefined		
Quote Only					No		
Selling Unit of Measure					piece		
Service Factor					1.15		
Shaft Diameter					2.375 in		
Short Description		300 HP, 18	00 RPM, Frame Size 449	Ts, Standard, 3 PH, 1	TEFC, 460 V		
Standards					NEMA		
Starting of Motor				Y-Sta	rt/Delta Run		
Stocked At (Warehouses)					China		
					Inited States Inited States		
					1800 r/min		
UNSPSC					26101112		
Voltage Rating					460 V		

EM44304TS-4 3/3

Categories

 $\textbf{Motors and Generators} \rightarrow \textbf{NEMA Low Voltage AC Motors} \rightarrow \textbf{General Purpose Motors} \rightarrow \textbf{Three Phase Enclosed}$





