

```
const coldStartTime = Date.now();
const environmentId = crypto.randomUUID();
const format = process.env.OUTPUT_FORMAT!;
const image = readFileSync('/opt/nodejs/image.jpg');
const width = Number(process.env.OUTPUT_WIDTH!);

let handlerCount = 0;
const processor = sharp(image).resize(width).toFormat(format);

export const handler = async () => {
  handlerCount++;
  const processingStartTime = Date.now();
  await processor.toFile('/tmp/sharp_out');
  const durationProcessingMs = processingStartTime - Date.now();

  return JSON.stringify({
    coldStart: handlerCount === 1,
    durationSinceColdStartMs: processingStartTime - coldStartTime,
    durationProcessingMs,
    environmentId,
    handlerCount,
    imageName: process.env.IMAGE_NAME,
    providerMemoryAssociated: process.env.MEMORY_SIZE,
    providerName: "aws",
  });
};
```

// set cold start timestamp
// generate stable environment ID
// load format from env
// load image from disk into memory
// load width from env

// initialize handler counter
// set up image processing

// increment handler counter
// set current timestamp
// set output location
// set current timestamp

// return optimization metadata
// true on cold start
// calculate duration since start

// varies per image
// varies per memory setting
// varies per provider, hardcoded