



ArgoCon

Streamlining Big Data Workflows with Memoization & Work Avoidance

Alan Clucas - Pipekit | Julie Vogelman - Intuit



INTUIT



#ArgoCon

November 6, 2023


INTROS



Alan Clucas

Senior Software Engineer @ Pipekit.io

Argo Workflows maintainer



Julie Vogelmann

Staff Software Engineer @ Intuit

Argo Workflows maintainer

GOALS



Saving time




Saving Cost


HOW

Don't repeat work.

If we know the answer already, **use that...**



WHAT THINGS



**Individual steps/
tasks between
workflows**



**Templates
(DAG, steps)**

Terminology

Inputs and outputs

Parameters and artifacts

Memoization and Work Avoidance



Introducing memoization

```
apiVersion: argoproj.io/v1alpha1
kind: Workflow
metadata:
  generateName: memoized-workflow-
spec:
  entrypoint: whalesay
  templates:
    - name: whalesay
      memoize:
        key: "{{inputs.parameters.message}}"
        maxAge: "10s"
        cache:
          configMap:
            name: whalesay-cache
```



What happens?

- Argo looks up keys in a cache
- If they match...
 - Remembers the outputs and provides them instead of running the step

DURATION	17s	
PROGRESS	1/1	
MEMOIZATION	KEY	hi-there-world
	CACHE NAME	whalesay-cache
	HIT?	NO

DURATION	0s	
PROGRESS	1/1	
MEMOIZATION	KEY	hi-there-world
	CACHE NAME	whalesay-cache
	HIT?	YES



This also works for output artifacts


```
graph TD; A[memoized-sequencing-wl5wq] --> B(sequence); B -- dna --> C(dna.tgz); B -- dna --> D(usedna);
```

The diagram illustrates a workflow where the task 'memoized-sequencing-wl5wq' (marked with a green checkmark) leads to the 'sequence' task (also marked with a green checkmark). The 'sequence' task produces two output artifacts: 'dna.tgz' and 'usedna', both of which are also marked with green checkmarks.

NAME	memoized-sequencing-wl5wq[0].sequence	
ID	memoized-sequencing-wl5wq-1993948304	
POD NAME	memoized-sequencing-wl5wq-sequence-1993948304	
HOST NODE NAME		
TYPE	Pod	
PHASE	✔ Succeeded	
START TIME	06/11/2023, 12:36:18 (1m26s ago)	
END TIME	06/11/2023, 12:36:18 (1m26s ago)	
DURATION	0s	
PROGRESS	1/1	
MEMOIZATION	KEY CACHE NAME HIT?	name dna-cache YES

You can memoize whole templates

Workflow skipping an entire DAG template:



ConfigMap


Created for you by the controller

Usually limited to 1MiB


Contains 'human readable' JSON




How memoization works in Argo Workflows



What if my step outputs to somewhere other than an artifact or parameter?



What if my step outputs to somewhere other than an artifact or parameter?



What if my step outputs to somewhere other than an artifact or parameter?

Memoization works for this in latest


Alternative: use a technique called “Work Avoidance” instead

Avoiding work sounds pretty good 😄

...but what is it?

Pod logic checks to see if the data exists before recomputing

Or can use a separate marker file to indicate data written (in PVC, DB, etc) and check for that



Any other time I can't use memoization?

If your data's too big for a ConfigMap (> 1 MiB)

Use “Work Avoidance” instead

Caching

There are only two hard things in Computer Science: cache invalidation and naming things.

-- Phil Karlton



Guaranteed safe

Pure steps

- Inputs – all as key
 - Outputs are derived only from inputs
- Has no external interactions
 - Nothing is read from the outside world
 - Changes nothing about the outside world, no side effects

Otherwise - choose keys wisely



Will skip step when key(s) match
And time since storing < maxAge



The End

Come have a chat with Alan about memoization this week.



@Alan Clucas on CNCF Slack

@Joibel on GitHub

Further reading:

<https://argoproj.github.io/argo-workflows/memoization/>

<https://argoproj.github.io/argo-workflows/work-avoidance/>



<https://s.pipekit.io/chat-argo-wf>

