

Stereo – Correspondence Matching


Andrew Calway

andrew@cs.bris.ac.uk

COMS30030 IPCV Stereo 4

1


Stereo Correspondence



COMS30030 IPCV Stereo 4

2

Stereo Matching is Hard




COMS30030 Stereo Lec 4

3

Region-Based Methods

- Compare pixel values within regions in two views.
- For region in left image, compute similarity with regions of same size in right image.
- Corresponding point - centre of most similar region



COMS30030 IPCV Stereo 4

4


Region Matching

- Stereo image pair: $I_L(x, y)$ and $I_R(x, y)$
- For each pixel, find disparity $\mathbf{d} = (d_x, d_y)$ which minimises (or maximises) cost function

$$c(\mathbf{d}) = \sum_{(i,j) \in W(x,y)} s[I_L(i, j), I_R(i + d_x, j + d_y)]$$

$W(x, y) \Rightarrow$ window of pixels around (x, y)

similarity measure



COMS30030 IPCV Stereo 4

5

Similarity Measures

- **Sum of squared differences:** $s(u, v) = (u - v)^2$
- **Similar pixel count:**

$$s(u, v) = \begin{cases} 1 & \text{if } |u - v| < T \\ 0 & \text{else} \end{cases}$$

- **Normalised cross correlation:**

$$s(u, v) = (u - u)(v - v) / N_u N_v$$

$$u = \frac{1}{|W|} \sum_{u \in W} u \quad \text{mean} \quad N_u = \sqrt{\sum_{u \in W} (u - u)^2} \quad \text{Std deviation}$$


COMS30030 IPCV Stereo 4

6

5

6

Example



Real time correlation-based stereo, Faugeras et al, 1993

COMS30030 IPCV Stereo 4

7

7

Feature-Based Methods

- Restrict search to sparse set of features
 - reduces mis-matches caused by texture-less regions
- Find salient (distinct) points in each view and match points by comparing pixels or image descriptors in local regions about each point



- Examples
 - Harris corner detector (salient points)
 - Scale-Invariant Feature Transform (SIFT)

COMS30030 IPCV Stereo 4

8

8

Harris Corner Detector

- Detects salient (distinct, interesting) image points
- Covariance of spatial gradient vectors within region W

$$A = \sum_{x,y \in W} \begin{bmatrix} I_x^2 & I_x I_y \\ I_x I_y & I_y^2 \end{bmatrix}$$
- Eigenvalues λ_1 and λ_2 of A indicate 'spread' of gradients in region, e.g. 2 high values \rightarrow 'busy' region.
- Example saliency metric: $sal = \lambda_1 \lambda_2 / (\lambda_1 + \lambda_2)$
- Properties:
 - if eigenvalues both large $\rightarrow sal$ large
 - if either eigenvalue small $\rightarrow sal$ small

COMS30030 IPCV Stereo 4

9

9

SIFT Matching


- **Two main elements:**
 - scale invariant detection of salient (key) points
 - matching by highly distinct local descriptors
- **Key point detection:**
 - extrema (max or min) in difference of Gaussian blurred versions of image \rightarrow Difference-of-Gaussians (DoG) tree
 - points imaged at different resolutions appear at different levels of DoG tree \rightarrow scale invariance
- **Spatial gradient descriptors:**
 - built from histograms of spatial gradients in local neighbourhood
 - invariant to rotation and perspective warp (almost)

COMS30030 IPCV Stereo 4

10

10

Difference of Gaussians




COMS30030 IPCV Stereo 4

11

11

Spatial Gradient Descriptor




Distinctive Image Features from Scale-Invariant Keypoints, David G. Lowe, International Journal of Computer Vision, 2004.

COMS30030 IPCV Stereo 4

12

12

SIFT Example – Selected Key Points




Each key point shown with circle indicating scale

COMS30030 IPCV Stereo 4

13

13

SIFT Example – Matched Key Points




COMS30030 IPCV Stereo 4

14

14

Where to look - Calibrated

- For calibrated stereo set up, corresponding points lie on epipolar lines
- Hence, given point in left image, search for point in right image along band about epipolar line:
- Increases speed, reduces mismatches



COMS30030 IPCV Stereo 4

15

15

Where to look - Uncalibrated


- When geometry unknown, can only match points using pixel values – region or feature based approach.
- Often leads to mismatches amongst true matches, known as **outliers** and **inliers**.
- We know that inliers will be related by epipolar constraint equation $\hat{\mathbf{p}}_R^T F \hat{\mathbf{p}}_L = 0$
- We can use **R**ANdom **S**Ample **C**onsensus to sort out:
 - select subset of matches at random (minimum 4)
 - compute fundamental matrix F from subset (lecture 8, slide 7)
 - assess support for F amongst other correspondences
 - repeat until best F found

COMS30030 IPCV Stereo 4

16

16

RANSAC Matching




2. Compute subset of potential matches

COMS30030 IPCV Stereo 4

17

17

RANSAC Matching




3. Compute support for fundamental matrix

COMS30030 IPCV Stereo 4

18

18

RANSAC Matching



1. Random selection of potential matches

..... and so on


F with most support defines outliers and inliers → most likely correspondences

COMS30030 IPCV Stereo 4

19

19

SIFT Matching – Keypoint Matches





COMS30030 IPCV Stereo 4

20

20

SIFT Matching – Epipolar Lines




COMS30030 IPCV Stereo 4

21

21

SIFT Matching – Keypoint Matches




COMS30030 IPCV Stereo 4

22

22

SIFT Matching – Epipolar Lines



COMS30030 IPCV Stereo 4

23

23