



**Post Office Protocol Version 3 Client
For NetX
(NetX POP3 Client)
User Guide**

Express Logic, Inc.

858.613.6640

Toll Free 888.THREADX

FAX 858.521.4259

www.expresslogic.com

©2002-2016 by Express Logic, Inc.

All rights reserved. This document and the associated NetX software are the sole property of Express Logic, Inc. Each contains proprietary information of Express Logic, Inc. Reproduction or duplication by any means of any portion of this document without the prior written consent of Express Logic, Inc. is expressly forbidden. Express Logic, Inc. reserves the right to make changes to the specifications described herein at any time and without notice in order to improve design or reliability of NetX. The information in this document has been carefully checked for accuracy; however, Express Logic, Inc. makes no warranty pertaining to the correctness of this document.

Trademarks

NetX, Piconet, and UDP Fast Path are trademarks of Express Logic, Inc. ThreadX is a registered trademark of Express Logic, Inc.

All other product and company names are trademarks or registered trademarks of their respective holders.

Warranty Limitations

Express Logic, Inc. makes no warranty of any kind that the NetX products will meet the USER's requirements, or will operate in the manner specified by the USER, or that the operation of the NetX products will operate uninterrupted or error free, or that any defects that may exist in the NetX products will be corrected after the warranty period. Express Logic, Inc. makes no warranties of any kind, either expressed or implied, including but not limited to the implied warranties of merchantability and fitness for a particular purpose, with respect to the NetX products. No oral or written information or advice given by Express Logic, Inc., its dealers, distributors, agents, or employees shall create any other warranty or in any way increase the scope of this warranty, and licensee may not rely on any such information or advice.

Part Number: 000-1054

Revision 5.10

Contents

Chapter 1	3
Introduction to NetX POP3.....	3
NetX POP3 Client Requirements	3
NetX POP3 Client Creation.....	4
NetX POP3 Client Constraints	5
NetX POP3 Client Login	5
The POP3 Client Maildrop	6
The POP3 Protocol State Machine	6
POP3 Server Reply Codes	7
Sample POP3 Client - Server Session	7
RFCs Supported by NetX POP3 Client.....	8
Chapter 2 Installation and Use of NetX POP3 Client	9
Using NetX POP3 Client	9
Small Example of the NetX POP3 Client.....	9
POP3 Client Configuration Options.....	14
Chapter 3 Description of POP3 Client Services	16
nx_pop3_client_create	17
nx_pop3_client_delete	19
nx_pop3_client_mail_item_delete	20
nx_pop3_client_mail_item_get.....	21
nx_pop3_client_mail_items_get	22
nx_pop3_client_mail_item_message_get	23
nx_pop3_client_mail_item_size_get	24

Chapter 1

Introduction to NetX POP3

The Post Office Protocol Version 3 (POP3) is a protocol designed to provide a mail transport system for small workstations to access Client maildrops on POP3 Servers for retrieving Client mail. POP3 utilizes Transmission Control Protocol (TCP) services to perform mail transfer. Because of this, POP3 is a highly reliable content transfer protocol. However, POP3 does not provide extensive operations on mail handling. Typically, mail is downloaded by the Client and then deleted from the Server's maildrop.

NetX POP3 Client Requirements

Client Requirements

The NetX POP3 Client API requires a previously created NetX IP instance using *nx_ip_create* and a previously created NetX packet pool using *nx_packet_pool_create*. Because the NetX POP3 Client utilizes TCP services, TCP must be enabled with the *nx_tcp_enable* call prior to using the NetX POP3 Client services on that same IP instance. The POP3 Client uses a TCP socket to connect to a POP3 Server on the Server's POP3 port. This is typically set at the well-known port 110, though neither POP3 Client nor Server is required to use this port.

The size of the packet pool used in creating the POP3 Client is user configurable in terms of packet payload and number of packets available. If the packet is used only in the POP3 Client create service, the packet payload need not be more than 100-120 bytes depending on the length of username and password, or APOP digest. The USER command with the local host's user name is probably the largest message sent by the POP3 Client. It is possible to share the same packet pool in the *nx_ip_create* (IP default packet pool) since the IP internal operations do not require a very large packet payload for sending and receiving TCP control data.

However, it may not be advantageous for the network driver to use the same packet pool as the POP3 Client packet pool. Generally, the payload of the receive packet pool is set the IP instance MTU (typically 1500 bytes) of the network interface which is much larger than POP3 Client messages. Incoming POP3 messages would usually be much larger data than outgoing POP3 Client messages.

NetX POP3 Client Creation

The POP3 Client create service, *nx_pop3_client_create* create the TCP socket and connect with the POP3 server.

After connecting with the POP3 server, the POP3 Client application can call *nx_pop3_client_mail_items_get* to obtain the number of mail items sitting in its maildrop box:

```
UINT nx_pop3_client_mail_items_get(NX_POP3_CLIENT *client_ptr,
                                   UINT *number_mail_items,
                                   ULONG *maildrop_total_size)
```

If one or more items are in the Client maildrop, the application can obtain the size of a specific mail item, using the *nx_pop3_client_get_mail_item* service:

```
UINT nx_pop3_client_mail_item_get(NX_POP3_CLIENT *client_ptr,
                                   UINT mail_item,
                                   ULONG *item_size)
```

The first mail item in the maildrop is at index 1.

To get the actual mail message, the application can call the *nx_pop3_client_mail_item_get_message_data* service to retrieve the mail message packets until the service indicates the last packet is received by the *final_packet* input argument:

```
UINT nx_pop3_client_mail_item_message_get(
    NX_POP3_CLIENT *client_ptr,
    NX_PACKET **recv_packet_ptr,
    ULONG *bytes_retrieved,
    UINT *final_packet)
```

To delete a specific mail item, the application calls *nx_pop3_client_mail_item_delete* with the same index as used in the preceding *nx_pop3_client_get_mail_item* call.

The Client can be deleted using the *nx_pop3_client_delete* service. Note it is up to the application to delete the POP3 Client packet pool using the *nx_packet_pool_delete* service there is no longer has any use for it.

NetX POP3 Client Constraints

There are some constraints in the NetX POP3 Client implementation:

1. The NetX POP3 Client does not support the AUTH command although it does implement APOP authentication using DIGEST-MD5 for the Client Server authentication exchange.
2. NetX POP3 Client does not implement all POP3 commands (e.g. the TOP or UIDL commands). Below is a list of commands it does support:

NOOP
RSET

NetX POP3 Client Login

A NetX POP3 Client must authenticate itself (login) to a POP3 Server to access a maildrop. It can do so either by using the USER/PASS commands and providing a username and password known to the POP3 Server, or by using the APOP command and MD5 digest described below.

The username is typically a fully qualified domain name (contains a local-part and a domain name, separated by an '@' character). When using the POP3 commands USER and PASS, the Client is sending its username and password unencrypted over the Internet.

To avoid the security risk of clear texting username and password, the NetX POP3 Client can be configured to use APOP authentication by setting the *APOP_authentication* parameter in the *nx_pop3_client_create* service:

```
UINT nx_pop3_client_create(NX_POP3_CLIENT *client_ptr,  
                           UINT APOP_authentication,  
                           NX_IP *ip_ptr,  
                           NX_PACKET_POOL *packet_pool_ptr,  
                           ULONG server_ip_address,  
                           ULONG server_port, CHAR *client_name,  
                           CHAR *client_password)
```

When the Client sends the APOP command, it takes an MD5 digest containing the server domain, local time and process ID extracted from the Server greeting, plus the Client password. The POP3 Server will create an MD5 digest containing the same information and if its MD5 digest matches the Client's MD5 digest, the Client is authenticated.

If APOP authentication fails, NetX POP3 Client will attempt USER/PASS authentication.

The POP3 Client Maildrop

Client mail is stored on a POP3 Server in a mailbox or "maildrop." A Client maildrop on a POP3 Server is represented as a 1 based list of mail items. That is, each mail is referred to by its index in the maildrop list with the first mail item at index 1 (not zero). POP3 commands refer to specific mail items by their index in this list.

The POP3 Protocol State Machine

The POP3 protocol requires that both Client and Server maintain the state of the POP3 session. First, the Client attempts to connect to the POP3 Server. If successful it enters into the POP3 protocol which has three distinct states defined by RFC 1939. The initial state is the Authorization state in which it must identify itself to the Server. In the Authorization state, the POP3 Client can only issue the USER and the PASS commands, and in that order, or the APOP command.

Once the POP3 Client is authenticated, the Client session enters the Transaction state. In this state, the Client can download and request mail deletion. The commands allowed in the Transaction state are LIST, STAT, RETR, DELE, RSET and QUIT. Typically the POP3 Client sends a STAT command followed by a series of RETR commands (one for each mail item in its maildrop).

Once the Client issues the QUIT command, the POP3 session enters the Update state in which it initiates the TCP disconnect from the Server. To download mail later, the POP3 Client application may call `nx_pop3_client_mail_items_get` at any time to check for new mail in the maildrop.

POP3 Server Reply Codes

- +OK** The Server uses this reply to accept a Client command. The Server can include additional information after the '+OK' but cannot assume the Client will process this information, except in the case of downloading mail message data or the LIST or DELE commands. In the latter case, the 'argument' after the command references the index of the mail item in the Client maildrop.
- ERR** The Server uses this reply to reject a Client command. The Server may send additional information following the '-ERR' but cannot assume the Client will process this information.

Sample POP3 Client - Server Session

Basic POP3 example using USER/PASS:

```
S: <wait for connection on TCP port 110>
C: <open connection>
S: +OK POP3 server ready <1896.697170952@dbc.mtview.ca.us>
C: USER mrose
S: +OK mrose is valid
C: PASS mvan99
S: +OK mrose is logged in
C: STAT
S: +OK 2 320
C: RETR 1
S: +OK 120 octets
S: <the POP3 server sends message 1>
S: .
C: DELE 1
S: +OK message 1 deleted
C: RETR 2
S: +OK 200 octets
S: <the POP3 server sends message 2>
S: .
C: DELE 2
S: +OK message 2 deleted
C: QUIT
S: +OK POP3 server signing off (maildrop empty)
C: <close connection>
S: <wait for next connection>
```

Basic POP3 example using APOP (and LIST instead of STAT):

```
S: <wait for connection on TCP port 110>
C: <open connection>
S: +OK POP3 server ready <1896.697170952@dbc.mtview.ca.us>
C: APOP mrose c4c9334bac560ecc979e58001b3e22fb
```

```
S: +OK mrose's maildrop has 2 messages (320 octets)
C: LIST
S: +OK 2 messages (320 octets)
S: 1 120
S: 2 200
S: .
C: RETR 1
S: +OK 120 octets
S: <the POP3 server sends message 1>
S: .
C: DELE 1
S: +OK message 1 deleted
C: RETR 2
S: +OK 200 octets
S: <the POP3 server sends message 2>
S: .
C: DELE 2
S: +OK message 2 deleted
C: QUIT
S: +OK dewey POP3 server signing off (maildrop empty)
C: <close connection>
S: <wait for next connection>
```

RFCs Supported by NetX POP3 Client

NetX Client POP3 is compliant with RFC 1939.

Chapter 2 Installation and Use of NetX POP3 Client

NetX POP3 Client includes one source file, one header file, and a demo file. There are two additional files for MD5 digest services. There is also a User Guide PDF file (this document).

`nx_pop3_client.c` C Source file for NetX POP3 Client API

`nx_pop3_client.h` C Header file for NetX POP3 Client API

`demo_netxdue_pop3_client.c` Demo file for POP3 Client creation and session initiation

`nx_md5.c` C Source file defining MD5 digest services

`nx_md5.h` C Header file defining MD5 digest services

`nx_pop3_client.pdf` NetX POP3 Client User Guide

To use NetX POP3 Client, the entire distribution mentioned previously can be copied to the same directory where NetX is installed. For example, if NetX is installed in the directory “`\threadx\mcf5272\green`” then the `nx_md5.h`, `nx_md5.c`, `nx_pop3_client.h`, and `nx_pop3_client.c` files should be copied into this directory.

Using NetX POP3 Client

To use the NetX POP3 Client service, the application must add `nx_pop3_client.c` to its build project. The application code must include `nx_md5.h`, `nx_pop3.h` and `nx_pop3_client.h` after `tx_api.h` and `nx_api.h`, in order to use ThreadX and NetX.

These files must be compiled in the same manner as other application files and the object code must be linked along with the files of the application. This is all that is required to use the NetX POP3 Client.

Small Example of the NetX POP3 Client

An example of how to use NetX POP3 Client services is described in Figure 1 that appears below. This demo sets up the two callbacks for notification of mail download and session completion on lines 37 and 38. The POP3 Client packet pool is created on line 76. The IP thread task is created on line 88. Note that this packet pool is also used for the POP3 Client packet pool. TCP is enabled on the IP task in line 107.

The POP3 Client is created on line 133 inside the application thread entry function, `demo_thread_entry`. This is because the

nx_pop3_client_create service also attempts to make a TCP connection with the POP3 server. If successful, the application queries the POP3 server for the number of items in its maildrop on line 149 using the *nx_pop3_client_mail_items_get* service.

If there are one or more items, the application iterates through the while loop for each mail item to download the mail message. The RETR request is made on line 149 in the *nx_pop3_client_mail_item_get* call. If successful, the application downloads packets using the *nx_pop3_client_mail_item_message_get* service on line 177 till it detects the last packet in the message has been received on line 196. Lastly, the application deletes the mail item, assuming a successful download has occurred on line 199 in the *nx_pop3_client_mail_item_delete* call. The RFC 1939 recommends that POP3 Clients instruct the Server to delete downloaded mail items to prevent mail accumulating in the Client's maildrop. The Server may automatically do so anyway.

Once all the mail items are downloaded, or if a POP3 Client service call fails, the application exits of the loop and deletes the POP3 Client on line 217 using the *nx_pop3_client_delete* service.

```
1  /*
2      demo_netxduo_pop3.c
3
4      This is a small demo of POP3 Client on the NetX TCP/IP stack.
5      This demo relies on Thread, NetX and POP3 Client API to conduct
6      a POP3 mail session.
7  */
8
9  #include "tx_api.h"
10 #include "nx_api.h"
11 #include "nx_pop3_client.h"
12
13 #define DEMO_STACK_SIZE          4096
14 #define CLIENT_ADDRESS           IP_ADDRESS(192,2,2,61)
15 #define SERVER_ADDRESS          IP_ADDRESS(192,2,2,89)
16 #define SERVER_PORT              110
17
18
19 /* Replace the 'ram' driver with your own Ethernet driver. */
20 void _nx_ram_network_driver(struct NX_IP_DRIVER_STRUCT *driver_req);
21
22
23 /* Set up the POP3 Client. */
24
25 TX_THREAD          demo_client_thread;
26 NX_POP3_CLIENT     demo_client;
27 NX_PACKET_POOL     client_packet_pool;
28 NX_IP              client_ip;
29
30 #define PAYLOAD_SIZE 500
31
32 /* Set up Client thread entry point. */
33 void demo_thread_entry(ULONG info);
34
35
36 /* Shared secret is the same as password. */
37
38 #define LOCALHOST          "recipient@domain.com"
39 #define LOCALHOST_PASSWORD "testpwd"
40
41
42
43 /* Define main entry point. */
44 int main()
```

```

45 {
46     /* Enter the ThreadX kernel. */
47     tx_kernel_enter();
48 }
49
50
51 /* Define what the initial system looks like. */
52 void tx_application_define(void *first_unused_memory)
53 {
54
55     UINT      status;
56     UCHAR     *free_memory_pointer;
57
58
59     /* Setup the working pointer. */
60     free_memory_pointer = first_unused_memory;
61
62     /* Create a client thread. */
63     tx_thread_create(&demo_client_thread, "Client", demo_thread_entry, 0,
64                     free_memory_pointer, DEMO_STACK_SIZE, 1, 1,
65                     TX_NO_TIME_SLICE, TX_AUTO_START);
66
67     free_memory_pointer = free_memory_pointer + DEMO_STACK_SIZE;
68
69     /* Initialize the NetX system. */
70     nx_system_initialize();
71
72     /* The demo client username and password is the authentication
73        data used when the server attempts to authentication the client. */
74
75     /* Create Client packet pool. */
76     status = nx_packet_pool_create(&client_packet_pool, "POP3 Client Packet Pool",
77                                   PAYLOAD_SIZE, free_memory_pointer,
78                                   (PAYLOAD_SIZE * 10));
79
80     if (status != NX_SUCCESS)
81     {
82         return;
83     }
84
85     /* Update pointer to unallocated (free) memory. */
86     free_memory_pointer = free_memory_pointer + (PAYLOAD_SIZE * 10);
87
88     /* Create IP instance for demo Client */
89     status = nx_ip_create(&client_ip, "POP3 Client IP Instance",
90                          CLIENT_ADDRESS, 0xFFFFFFFFUL, &client_packet_pool,
91                          _nx_ram_network_driver, free_memory_pointer,
92                          2048, 1);
93
94     if (status != NX_SUCCESS)
95     {
96         return;
97     }
98
99     /* Update pointer to unallocated (free) memory. */
100    free_memory_pointer = free_memory_pointer + 2048;
101
102    /* Enable ARP and supply ARP cache memory. */
103    nx_arp_enable(&client_ip, (void **) free_memory_pointer, 1024);
104
105    /* Update pointer to unallocated (free) memory. */
106    free_memory_pointer = free_memory_pointer + 1024;
107
108    /* Enable TCP and ICMP for Client IP. */
109    nx_tcp_enable(&client_ip);
110    nx_icmp_enable(&client_ip);
111
112    return;
113 }
114
115 /* Define the application thread entry function. */
116 void demo_thread_entry(ULONG info)
117 {
118
119
120     UINT      status;
121     UINT      mail_item, number_mail_items;
122     UINT      bytes_downloaded = 0;
123     UINT      final_packet = NX_FALSE;

```

```

124 ULONG      total_size, mail_item_size, bytes_retrieved;
125 NX_PACKET  *packet_ptr;
126
127 /* Let the IP instance get initialized with driver parameters. */
128 tx_thread_sleep(40);
129
130
131 /* Create a NetX POP3 Client instance with no byte or block memory pools.
132    Note that it uses its password for its APOP shared secret. */
133 status = nx_pop3_client_create(&demo_client,
134                                NX_TRUE,
135                                &client_ip, &client_packet_pool, SERVER_ADDRESS,
136                                SERVER_PORT, LOCALHOST, LOCALHOST_PASSWORD);
137
138 /* Check for error. */
139 if (status != NX_SUCCESS)
140 {
141
142     status = nx_pop3_client_delete(&demo_client);
143
144     /* Abort. */
145     return;
146 }
147
148 /* Find out how many items are in our mailbox. */
149 status = nx_pop3_client_mail_items_get(&demo_client, &number_mail_items,
                                         &total_size);
150
151 printf("Got %d mail items, total size%d \n", number_mail_items, total_size);
152
153 /* If nothing in the mailbox, disconnect. */
154 if (number_mail_items == 0)
155 {
156
157     nx_pop3_client_delete(&demo_client);
158
159     return;
160 }
161
162 /* Download all mail items. */
163 mail_item = 1;
164
165 while (mail_item <= number_mail_items)
166 {
167
168     /* This submits a RETR request and gets the mail message size. */
169     status = nx_pop3_client_mail_item_get(&demo_client, mail_item,
170                                           &mail_item_size);
171
172     /* Loop to get all mail message packets until the mail item is completely
173        downloaded. */
174     while((final_packet == NX_FALSE) && (status == NX_SUCCESS))
175     {
176
177         status = nx_pop3_client_mail_item_message_get(&demo_client, &packet_ptr,
178                                                       &bytes_retrieved,
179                                                       &final_packet);
180
181         if (status != NX_SUCCESS)
182         {
183
184             break;
185         }
186
187         if (bytes_retrieved != 0)
188         {
189
190             printf("Received %d bytes of data for item %d: %s\n",
191                   packet_ptr -> nx_packet_length,
192                   mail_item, packet_ptr -> nx_packet_prepend_ptr);
193
194             nx_packet_release(packet_ptr);
195
196             /* Determine if this is the last data packet. */
197             if (final_packet)
198             {
199                 /* It is. Let the server know it can delete this mail item. */
200                 status = nx_pop3_client_mail_item_delete(&demo_client, mail_item);

```

```

201
202         /* Keep track of how much mail message data is left. */
203         bytes_downloaded += bytes_retrieved;
204     }
205
206     /* Get the next mail item. */
207     mail_item++;
208
209     tx_thread_sleep(100);
210
211 }
212
213 /* Disconnect from the POP3 server. */
214 status = nx_pop3_client_quit(&demo_client);
215
216 /* Delete the POP3 client. This will not delete the client packet pool. */
217 status = nx_pop3_client_delete(&demo_client);
218
219 }

```

Figure 1. Example of a NetX POP3 Client application

POP3 Client Configuration Options

There are several configuration options with the NetX POP3 Client. Following is a list of all options described in detail:

Define

Meaning

NX_POP3_CLIENT_PACKET_TIMEOUT

This defines the wait option in seconds for the POP3 Client to allocate a packet. The default value is 1 second.

NX_POP3_CLIENT_CONNECTION_TIMEOUT

This defines the wait option in seconds for the POP3 Client to connect with the POP3 Server. The default value is 30 seconds.

NX_POP3_CLIENT_DISCONNECT_TIMEOUT

This defines the wait option in seconds for the POP3 Client to disconnect from the POP3 Server. The default value is 2 seconds.

NX_POP3_TCP_SOCKET_SEND_WAIT

This option sets the wait option in seconds in *nx_tcp_socket_send* service calls. The default value is 2 seconds.

NX_POP3_SERVER_REPLY_TIMEOUT

This option sets the wait option in *nx_tcp_socket_receive* service calls for the Server reply to a Client request. The default value is 10 seconds.

NX_POP3_CLIENT_TCP_WINDOW_SIZE

This option sets the size of the Client TCP receive window. This should be set to the IP instance MTU size minus the IP and TCP header. The default value is 1460.

NX_POP3_MAX_USERNAME

This option sets the size of the buffer of the POP3 Client user name. The default value is 40 bytes.

NX_POP3_MAX_PASSWORD

This option sets the size of the buffer of the POP3 Client password. The default value is 20 bytes.

Chapter 3 Description of POP3 Client Services

This chapter contains a description of all NetX POP3 Client services (listed below) in alphabetical order.

In the “Return Values” section in the following API descriptions, values in **BOLD** are not affected by the **NX_DISABLE_ERROR_CHECKING** define that is used to disable API error checking, while non-bold values are completely disabled.

`nx_pop3_client_create`

Create a POP3 Client Instance

`nx_pop3_client_delete`

Delete a POP3 Client instance

`nx_pop3_client_mail_item_get`

Delete a Client mail item from Server maildrop

`nx_pop3_client_mail_item_get`

Retrieve a specific mail message size

`nx_pop3_client_mail_items_get`

Obtain the number of mail items in maildrop

`nx_pop3_client_mail_item_message_get`

Download a specific mail message

`nx_pop3_client_mail_item_size_get`

Obtain the size of a specific mail item

nx_pop3_client_create

Create a POP3 Client instance

Prototype

```
UINT nx_pop3_client_create(NX_POP3_CLIENT *client_ptr,  
                           UINT APOP_authentication, NX_IP *ip_ptr,  
                           NX_PACKET_POOL *packet_pool_ptr,  
                           ULONG server_ip_address,  
                           ULONG server_port,  
                           CHAR *client_name, CHAR *client_password);
```

Description

This service creates an instance of the POP3 Client and sets up its configuration with the input parameters.

Input Parameters

client_ptr	Pointer to Client to create
APOP_authentication	Enable APOP authentication
ip_ptr	Pointer to IP instance
packet_pool_ptr	Pointer to Client packet pool
server_ip_address	POP3 server address
server_port	POP3 server port
client_name	Pointer to Client name
client_password	Pointer to Client password

Return Values

NX_SUCCESS	(0x00)	Client successfully created
status		Status completion of NetX and ThreadX service calls
NX_PTR_ERROR	(0x07)	Invalid input pointer parameter
NX_POP3_PARAM_ERROR	(0xB1)	Invalid non pointer input

Allowed From

Application code

Example

```
/* Create the POP3 Client. */  
  
/* Create username and password for our POP3 client mail drop. */  
#define LOCALHOST "recipient@expresslogic.com"  
#define LOCALHOST_PASSWORD "pass"  
#define POP3_SERVER_PORT 110  
  
/* Create a NetX POP3 Client instance. */
```

```
ULONG server_ip_address = IP_ADDRESS(1,2,3,4);  
status = nx_pop3_client_create(&demo_client,  
                                NX_FALSE /* disable APOP authentication */,  
                                &client_ip, &client_packet_pool,  
                                server_ip_address, POP3_SERVER_PORT,  
                                LOCALHOST, LOCALHOST_PASSWORD);  
/* If the Client was successfully created, status = NX_SUCCESS. */
```

nx_pop3_client_delete

Delete a POP3 Client instance

Prototype

```
UINT nx_pop3_client_delete(NX_POP3_CLIENT *client_ptr)
```

Description

This service deletes a previously created POP3 Client. Not that this service does not delete the POP3 Client packet pool. The device application must delete this resource separately if it no longer has use for the packet pool.

Input Parameters

client_ptr	Pointer to Client to delete
-------------------	-----------------------------

Return Values

NX_SUCCESS	(0x00)	Client successfully deleted
NX_PTR_ERROR	(0x07)	Invalid input pointer parameter

Allowed From

Application code

Example

```
/* Delete the POP3 Client. */  
status = nx_pop3_client_delete (&demo_client);  
/* If the Client was successfully deleted, status = NX_SUCCESS. */
```

nx_pop3_client_mail_item_delete

Delete a specified mail item from the Client maildrop

Prototype

```
UINT nx_pop3_client_mail_items_delete(NX_POP3_CLIENT *client_ptr,  
                                       UINT mail_index)
```

Description

This service deletes the specified mail item from the Client maildrop. It is intended for after downloading the mail item, although some POP3 servers may automatically delete mail items after being requested by the Client.

Input Parameters

client_ptr	Pointer to Client instance
mail_index	Index into Client maildrop

Return Values

NX_SUCCESS	(0x00)	Delete request successful
NX_POP3_INVALID_MAIL_ITEM	(0xB2)	Invalid mail item index
NX_POP3_INSUFFICIENT_PACKET_PAYLOAD	(0xB6)	Client packet payload too small for POP3 request.
NX_POP3_SERVER_ERROR_STATUS	(0xB4)	Server replies with error status
NX_POP3_CLIENT_INVALID_INDEX	(0xB8)	Invalid mail index input
NX_PTR_ERROR	(0x07)	Invalid input pointer parameter

Allowed From

Application code

Example

```
ULONG item_index;  
  
/* Delete the POP3 Client mail item. */  
status = nx_pop3_client_mail_item_delete(&demo_client, item_index);  
  
/* If the server accepts the DELE request (and deletes the mail item), status =  
   NX_SUCCESS. */
```

nx_pop3_client_mail_item_get

Retrieve a specified mail item

Prototype

```
UINT nx_pop3_client_mail_item_get(NX_POP3_CLIENT *client_ptr,  
                                  UINT mail_item, ULONG *item_size)
```

Description

This service makes a RETR request to retrieve a mail item from the Client maildrop specified by the index mail_item. After making a RETR request, and receiving a positive response from the Server, the Client can start downloading the mail message using the *nx_pop3_client_mail_item_message_get* service. Note that the service also supplies the size of the requested mail item extracted from the Server reply.

Input Parameters

client_ptr	Pointer to Client instance
mail_item	Index into Client maildrop
item_size	Pointer to size of mail message

Return Values

NX_SUCCESS	(0x00)	Mail item successfully retrieved
NX_POP3_INVALID_MAIL_ITEM	(0xB2)	Invalid mail item index
NX_POP3_INSUFFICIENT_PACKET_PAYLOAD	(0xB6)	Client packet payload too small for POP3 request.
NX_POP3_SERVER_ERROR_STATUS	(0xB4)	Server replies with error status
NX_POP3_CLIENT_INVALID_INDEX	(0xB8)	Invalid mail index input
NX_PTR_ERROR	(0x07)	Invalid input pointer parameter

Allowed From

Application code

Example

```
ULONG item_size;  
  
/* Retrieve the POP3 Client mail item. */  
status = nx_pop3_client_mail_item_get (&demo_client, 1, &item_size);  
  
/* If the mail item was successfully obtained, status = NX_SUCCESS. */
```

nx_pop3_client_mail_items_get

Retrieve the number of mail items in maildrop

Prototype

```
UINT nx_pop3_client_mail_items_get(NX_POP3_CLIENT *client_ptr,  
                                   UINT *number_mail_items,  
                                   ULONG *maildrop_total_size)
```

Description

This service makes a STAT request to retrieve the number of mail items and total size of mail message data from the Client maildrop.

Input Parameters

client_ptr	Pointer to Client instance
number_mail_item	Number of mail in Client maildrop
maildrop_total_size	Pointer to size of all mail message

Return Values

NX_SUCCESS	(0x00)	Mail item successfully retrieved
NX_POP3_INVALID_MAIL_ITEM	(0xB2)	Invalid mail item index
NX_POP3_INSUFFICIENT_PACKET_PAYLOAD	(0xB6)	Client packet payload too small for POP3 request.
NX_POP3_SERVER_ERROR_STATUS	(0xB4)	Server replies with error status
NX_PTR_ERROR	(0x07)	Invalid input pointer parameter

Allowed From

Application code

Example

```
UINT number_mail_items;  
ULONG maildrop_total_size;  
  
/* Retrieve the size and number of items in POP3 Client maildrop. */  
status = nx_pop3_client_mail_item_get (&demo_client, 1, &number_mail_items,  
                                       &maildrop_total_size);  
  
/* If the maildrop data was successfully obtained, status = NX_SUCCESS. */
```


nx_pop3_client_mail_item_message_get

Retrieve the specified mail item message

Prototype

```
UINT    nx_pop3_client_mail_item_message_get(  
                                                NX_POP3_CLIENT *client_ptr,  
                                                NX_PACKET **recv_packet_ptr,  
                                                ULONG *bytes_retrieved,  
                                                UINT *final_packet)
```

Description

This service retrieves the mail item message, size of the mail message, and if it is the last packet in the mail message. If `final_packet` is `NX_TRUE` the packet pointed to by `recv_packet_ptr` is the final packet in the mail item message.

Input Parameters

client_ptr	Pointer to Client instance
recv_packet_ptr	Received packet of message data
number_mail_item	Number of mail in Client maildrop
maildrop_total_size	Pointer to size of all mail message

Return Values

NX_SUCCESS	(0x00)	Mail item successfully retrieved
NX_POP3_CLIENT_INVALID_STATE	(0xB7)	Client packet payload too small for POP3 request.
NX_PTR_ERROR	(0x07)	Invalid input pointer parameter

Allowed From

Application code

Example

```
NX_PACKET    *recv_packet_ptr;  
ULONG        bytes_retrieved;  
UINT         final_packet;  
  
/* Retrieve the size and number of items in POP3 Client maildrop. */  
status = nx_pop3_client_mail_item_message_get (&demo_client, &recv_packet_ptr,  
                                                bytes_retrieved, final_packet);  
  
/* If the maildrop message packet was successfully obtained, status = NX_SUCCESS. */
```

nx_pop3_client_mail_item_size_get

Retrieve the size of the specified mail item

Prototype

```
UINT    nx_pop3_client_mail_item_size_get(  
        NX_POP3_CLIENT *client_ptr,  
        UINT mail_item, ULONG *size)
```

Description

This service makes a LIST request to obtain the size of the specified mail item.

Input Parameters

client_ptr	Pointer to Client instance
mail_item	Index into Client maildrop
size	Pointer to size of mail message

Return Values

NX_SUCCESS	(0x00)	Mail item successfully retrieved
NX_POP3_INVALID_MAIL_ITEM	(0xB2)	Invalid mail item index
NX_POP3_INSUFFICIENT_PACKET_PAYLOAD	(0xB6)	Client packet payload too small for POP3 request.
NX_POP3_SERVER_ERROR_STATUS	(0xB4)	Server replies with error status
NX_POP3_CLIENT_INVALID_INDEX	(0xB8)	Invalid mail index input
NX_PTR_ERROR	(0x07)	Invalid input pointer parameter

Allowed From

Application code

Example

```
ULONG    size;  
UINT     mail_item;  
  
/* Retrieve the size of the specified mail item in POP3 Client maildrop. */  
status = nx_pop3_client_mail_item_size_get (&demo_client, mail_item, &size);  
  
/* If the maildrop message packet was successfully obtained, status = NX_SUCCESS. */
```