DalmiaBHARAT CEMENT

DALMIA CEMENT (B) LIMITED - Ariyalur

MECHANICAL SOP

Issue No. 02 Rev. No: 00 Effective Date: 1.11.2019 SOP/MEC/030

Issued By: M.R Approved By: HOD - MECHANICAL

Truck tippler operation

SOP FOR TRUCK TRIPPLER

<u>Scope:</u> Truck Tippler operation <u>Responsibility:</u> Engineer/SH

PPE:

- 1. Safety helmet
- 2. Safety shoe
- 3. Mask
- 4. Safety goggles
- 5. Gloves

TOOLS:

- 1. Screw driver
- 2. spanner set
- 3. Pipe Wrench

Hazard Analysis:

<u>Risks associated:</u> <u>Mitigating Measures</u>

PROCEDURE

- 1) Position the coal/additive stacker in required stockpile.
- 2) Clean the Permanent magnet on L11BC4/321BC7.
- 3) Check the condition of the belt before starting.
- 4) Starting stacker boom conveyor belt.
- 5) Inform to central control room to start all equipments in circuit
- 6) Coal crusher has to be started for big lumps crushing, if required.
- 7) Truck tippler bottom materials accumulation is to be cleaned before starting.

DALMIA CEMENT (B) LIMITED - Ariyalur MECHANICAL SOP Issue No. 02 Rev. No: 00 Effective Date: 1.11.2019 SOP/MEC/030 Issued By: M.R Approved By: HOD - MECHANICAL

Truck tippler operation

- 8) Bunker to be cleaned before starting.
- 9) Check the oil level in the Tippler Hydraulic tank.
- 10) Ensure No cleaning labor is standing above hopper grill.
- 11) Dust suppression to be stated at bunker in coal crusher for all materials except gypsum
- 12) After getting the GREEN signal, truck should be park in the platform
- 13) Truck front suspension is to be locked by front hooking arrangement.
- 14) Back lift is to be operated carefully.
- 15) Main lift is to be operated up to 45 to 50 degrees depending on the unloading materials.

Emergency / Emergency Shut OFF:

1. If any injury takes place, provide First aid and inform to the Safety department or Call Emergency number 3108/9865152222

Isolation Matrix: Not applicable.

JSA: Not applicable.