



**DALMIA CEMENT (B) LIMITED – CEMENT PLANT
ARIYALUR
SAFETY DEPARTMENT MANUAL**



Issue No. 01	Rev. No: 00	Effective Date: 01.11.2010	WI-39(PI-14; AM-7)
Issued By: M.R		Approved By: HOD -SAFETY	
USE OF FIRE EXTINGUISHER			

WI-39(PI-14; AM-7)

Hazards Involved: Caught in between, Slip & Fall

Selection of Personal Protective Equipments: Gloves and Mask.

Instruction:

Follow the PASS Method:

- P** - **Pull the Pin** at the top of the extinguisher. The pin releases a locking Mechanism and will allow you to discharge the extinguisher.
- A** - **Aim at the base of the fire**, not the flames. This is important - in order to put out the fire, you must extinguish the fuel.
- S** - **Strike the Knob**. This will release the extinguishing agent in the extinguisher.
- S** - **Sweep from side to side**. Using a sweeping motion, move the fire extinguisher back and forth until the fire is completely out. Operate the extinguisher from a safe distance, several feet away, and then move towards the fire once it starts to diminish. Be sure to read the instructions on your fire extinguisher - different fire extinguishers recommend operating them from different distances.
Remember: Aim at the base of the fire, not at the flames!!!!