

# DALMIA CEMENT (B) LIMITED -ARIYALUR MECHANICAL DEPARTMENT

Issue No. 02 Rev. No: 00 Effective Date: 01.11.2019 SOP/MECH/117

Issued By: M.R Approved By: HOD (MECHANICAL)

# **Scrap Handling After Work completion**

Scope : Scrap Handling after Work completion

Responsibility: Section Engineer - Mech.

Accountability: Section In-charge - Mech.

## PPE:

1. Helmet,

- 2. Safety shoe,
- 3. Safety belt,
- 4. Safety goggles.
- 5. Asbestos Gloves.

#### Tools:

- 1. chain block-1no
- 2. Web (Nylon) slings-2Nos.
- 3. Box Spanner set
- 4. Ring Spanner set

# Hazards:

### **Risks associated**

#### **Mitigating Measures**

Material may fall on anybody


: Isolate the area with Barricading tape.

#### Training needs:

- 1. Fire fighting
- 2. Emergency preparedness
- 3. Assembly procedure.

# **Procedure:**

- 1. After work completed, clear the generated scraps.
- 2. Worker should use the hand gloves before start to collect of scraps.
- 3. Small Scrap Collect in bags and get it down ground to thru Lift or Manually.
- 4. If material is huge use pipe chutes/EOT/Lift/Rope with pulley.
- 5. Barricade the area with prescribed Red & White tape as a caution of area Isolation.
- 6. Keep one watch person at ground floor to alert the people movement.



- 7. Load the material in the trolley/ tractor.
- 8. Trolley should be handled by the minimum two persons in load condition.
- 9. While pushing, pulling & turning the trolley, workers should be aware of slopes, Slippery area (water stagnation), etc.
- 10. The Scraps to be hand over to the store person with ISO format.