



DALMIA CEMENT (B) LIMITED – CEMENT PLANT
DPM
MECHANICAL DEPARTMENT



Issue No. 02	Rev. No:01	Effective Date: 22.05.2015	SOP/MECH/22
Issued By: S & P		Approved By: Head – Mech	
AIRSLIDE CLOTH REPLACEMENT			

Scope : This SOP is applicable to Safe working fo Airslide cloth Replacement

Responsibility : Section Engineer.

Accountability : Section Head-Mechanical

PPE:

1. Safety helmet,
2. Safety shoe,
3. Dust Mask,
4. Hand Gloves
5. Safety Goggles

Tools:

1. 1MT chain block-1no
2. Nylon Web slings- 2Nos.
3. Rope-2 nos
4. DE/ Ring Spanner set.
5. Clamp suitable to the width of Air slide cloth.
6. Hole Punch(Hole Bari)

Auxiliaries

1. Cutting Set

Hazards:

Risks associated

Body injury

Mitigating Measures

- 1.Safe and tested tools and tackles
2. on job training

Training needs:

1. Emergency preparedness
2. On job training

Line Clearance required for:



DALMIA CEMENT (B) LIMITED – CEMENT PLANT
DPM
MECHANICAL DEPARTMENT



Issue No. 02	Rev. No:01	Effective Date: 22.05.2015	SOP/MECH/22
Issued By: S & P		Approved By: Head – Mech	
AIRSLIDE CLOTH REPLACEMENT			

1. Connecting Equipments.
2. Related air slide blower.

Procedure:

1. Airslide box inside material clean with help of related blowers
2. Take electrical shutdown permit for connecting Equipments,
3. The Permit Paper should be with the person who is attending the job.
4. Trained Worker will be engaged for working with related PPE's.
5. Take General work permit and hot work permit to perform the job.
6. Use ppe's while working.
7. If cloth in damaged condition , Remove the air slide box air chambers
8. Remove the air slide blower connection pipe line
9. Remove the damaged cloth.
10. Replaced the new cloth.
11. Tension the new cloth with approximately 2% elongation in the air chamber with the help of chain block or any tensioning device.
12. Fix the bottom air chamber.
13. Top and bottom chambers covers to be tightened to avoid leakage.
14. Fix the air slide blower connecting pipeline
15. Clear the connecting drive and air slide blower line clearance.
16. Get the line clearance and inform to CCR to run the equipment.

Emergency Shut- off:



DALMIA CEMENT (B) LIMITED – CEMENT PLANT
DPM
MECHANICAL DEPARTMENT



Issue No. 02	Rev. No:01	Effective Date: 22.05.2015	SOP/MECH/22
Issued By: S & P		Approved By: Head – Mech	
AIRSLIDE CLOTH REPLACEMENT			

If body injury is there, First aid will be given and inform to the Safety department or Call Emergency number - 222/9865125176/9865177444.

Records/Annexure:

1. Refer Line clearance/permit in mechanical department.
2. JSA is enclosed below.

Job Safety Analysis	Job: Airslide cloth replacement	Date: 20/09/2012	Analysis by: Section engineer	Reviewed by: Section head
----------------------------	---------------------------------	------------------	----------------------------------	------------------------------



DALMIA CEMENT (B) LIMITED – CEMENT PLANT
DPM
MECHANICAL DEPARTMENT



Issue No. 02	Rev. No:01	Effective Date: 22.05.2015	SOP/MECH/22
Issued By: S & P		Approved By: Head – Mech	
AIRSLIDE CLOTH REPLACEMENT			

Title of employee doing job: Fitter	Supervisor: Section Engineer	Department: Mechanical	Section: Mills	Approved by: HOD
Req'd/recommended PPE: Safety Helmet, Safety shoe, Hand Gloves, Safety goggles. Nose mask.				
Sequence of Basic Job Steps	Potential Hazards	Recommended Safe Job Procedure	What Could Go Wrong	Corrective Action
Air slide box cleaning before starting work	Eye & nose Irritation	Use Nose Mask, Safety goggles' & Hand gloves while cleaning	Dust escape from the box and puffed eyes & nose	Workmen should use proper PPEs before entering the job
Air slide box bottom air champer removing work	Hand & body injury	Lock the airchamper with proper ropes and loosen the bolts with suitable spanner	Rope damaged and the box fall on hand, Spanner slipped and chance to fall	Ropes should be checked and suitable spanner to be used
Air slide blower connection pipe line removing work	Body injury	Use proper spanners only to avoid slip / shear of bolt and nut during loosen the fasteners	Spanners may slip and chance to fall	Use correct size and condition of spanner(prefer ring spanner)



DALMIA CEMENT (B) LIMITED – CEMENT PLANT

DPM

MECHANICAL DEPARTMENT



Issue No. 02 Rev. No:01 Effective Date: 22.05.2015 SOP/MECH/22

Issued By: S & P Approved By: Head – Mech

AIRSLIDE CLOTH REPLACEMENT

cloth changing work	Body injury	Use proper chainblocks,ropes, tools required to tension the cloth and fasteners fixing	Chain block slipped and hit the body,	Inspect the condition of lifting equipments. 1. Lifting ropes / Belts 2. Chain block a)Periodical replacement is recommended for ropes b)Use tested(with in the due date) Chain blocks c)Workmen should competent to lift the machines and tools
Air slide box bottom air chamber fixing work	Hand injury	Lift the box with proper ropes	Rope cut and fall on hand	check the Ropes and use min.2ropes
Air slide box bolt tightening work	Hand injury	Use proper spanners only to avoid slip / shear of bolt and nut during tightening	Spanners may slip and chance to fall bolt may shear / cut during load	Use correct size and condition of spanner



DALMIA CEMENT (B) LIMITED – CEMENT PLANT
DPM
MECHANICAL DEPARTMENT



Issue No. 02	Rev. No:01	Effective Date: 22.05.2015	SOP/MECH/22
Issued By: S & P		Approved By: Head – Mech	
AIRSLIDE CLOTH REPLACEMENT			

Air slide blower connecting pipeline re-fixing work	Body injury	Use proper spanners only to avoid slip / shear of bolt and nut during tightening	Spanners may slip and chance to fall downbolt may shear / cut during load	Use correct size and condition of spanner
Old air slide cloth and tools removed from the job location	Body injury	House keeping done after completion of work	Poor House keeping lead fall down	Housekeeping done after completion of work

HEAD MECHANICAL

HEAD TECHNICAL