

The sTeX3 Manual *

Michael Kohlhase, Dennis Müller
FAU Erlangen-Nürnberg
<http://kwarc.info/>

2022-04-24

Abstract

sTeX is a collection of L^AT_EX packages that allow to markup documents semantically without leaving the document format.

Running ‘pdflatex’ over sTeX-annotated documents formats them into normal-looking PDF. But sTeX also comes with a conversion pipeline into semantically annotated HTML5, which can host semantic added-value services that make the documents active (i.e. interactive and user-adaptive) and essentially turning L^AT_EX into a document format for (mathematical) knowledge management (MKM).

sTeX augments L^AT_EX with

- *semantic macros* that denote and distinguish between mathematical concepts, operators, etc. independent of their notational presentation,
- a powerful *module system* that allows for authoring and importing individual fragments containing document text and/or semantic macros, independent of – and without hard coding – directory paths relative to the current document, and
- a mechanism for exporting sTeX documents to (modular) XHTML, preserving all the semantic information for semantically informed knowledge management services.

This is the user manual for the sTeX package and associated software. It is primarily directed at end-users who want to use sTeX to author semantically enriched documents. For the full documentation, see [the sTeX documentation](#).

*Version 3.0 (last revised 2022-04-24)

Contents

1	What is sTeX?	2
2	Quickstart	3
2.1	Setup	3
2.1.1	Minimal Setup for the PDF-only Workflow	3
2.1.2	GIT-based Setup for the sTeX Development Version	3
2.1.3	sTeX Archives (Manual Setup)	4
2.1.4	The sTeX IDE	4
2.1.5	Manual Setup for Active Documents and Knowledge Management Services	4
2.2	A First sTeX Document	5
2.2.1	OMDoc/xhtml Conversion	8
3	Creating sTeX Content	10
3.1	How Knowledge is Organized in sTeX	10
3.2	sTeX Archives	11
3.2.1	The Local MathHub-Directory	11
3.2.2	The Structure of sTeX Archives	11
3.2.3	MANIFEST.MF-Files	12
3.2.4	Using Files in sTeX Archives Directly	13
3.3	Module, Symbol and Notation Declarations	14
3.3.1	The smodule-Environment	14
3.3.2	Declaring New Symbols and Notations	16
	Operator Notations	19
3.3.3	Argument Modes	19
	Mode-b Arguments	20
	Mode-a Arguments	20
	Mode-B Arguments	22
3.3.4	Type and Definiens Components	22
3.3.5	Precedences and Automated Bracketing	23
3.3.6	Variables	25
3.3.7	Variable Sequences	26
3.4	Module Inheritance and Structures	28
3.4.1	Multilinguality and Translations	28
3.4.2	Simple Inheritance and Namespaces	29
3.4.3	The mathstructure Environment	31
3.4.4	The copymodule Environment	34
3.4.5	The interpretmodule Environment	35
3.5	Primitive Symbols (The sTeX Metatheory)	35
4	Using sTeX Symbols	36
4.1	\symref and its variants	36
4.2	Marking Up Text and On-the-Fly Notations	37
4.3	Referencing Symbols and Statements	39

5	<code>\TeX</code> Statements	40
5.1	Definitions, Theorems, Examples, Paragraphs	40
5.2	Proofs	43
5.2.1	Introduction & Running Example	43
5.2.2	Proofs and Proof steps	44
5.2.3	Justifications	45
5.2.4	Proof Structure	45
5.2.5	Proof End Markers	46
6	Highlighting and Presentation Customizations	47
7	Additional Packages	49
7.1	Package Options	49
7.2	Inputting Standalone TIKZ Pictures	49
7.3	Limitations	50
7.4	Modular Document Structuring	50
7.4.1	Introduction	50
7.4.2	The User Interface	51
	Document Structure	51
	Ignoring Inputs	52
	Global Variables	52
7.5	Slides and Course Notes	53
7.5.1	Introduction	53
7.5.2	The User Interface	53
	Package Options	54
	Notes and Slides	54
	Header and Footer Lines of the Slides	55
	Frame Images	56
	Colors and Highlighting	56
	Excursions	56
	Limitations	57
7.6	Homework, Problems and Exams	57
7.6.1	Introduction	57
	Package Options	58
	Problems and Solutions	58
	Multiple Choice Blocks	59
	Including Problems	60
	Reporting Metadata	60
	Limitations	61
7.6.2	Package Options	61
7.6.3	Assignments	61
7.6.4	Typesetting Exams	61
7.6.5	Including Assignments	62



Boxes like this one contain implementation details that are mostly relevant for more advanced use cases, might be useful to know when debugging, or might be good to know to better understand how something works. They can easily be skipped on a first read.



Boxes like this one explain how some $\text{\texttt{\textbackslash}}\text{\textsf{S}}\text{\textsf{T}}\text{\textsf{E}}\text{\textsf{X}}$ concept relates to the MMT/OMDoc system, philosophy or language; see [MMT; Koh06] for introductions.

Chapter 1

What is sTeX?

Formal systems for mathematics (such as interactive theorem provers) have the potential to significantly increase both the accessibility of published knowledge, as well as the confidence in its veracity, by rendering the precise semantics of statements machine actionable. This allows for a plurality of added-value services, from semantic search up to verification and automated theorem proving. Unfortunately, their usefulness is hidden behind severe barriers to accessibility; primarily related to their surface languages reminiscent of programming languages and very unlike informal standards of presentation.

sTeX minimizes this gap between informal and formal mathematics by integrating formal methods into established and widespread authoring workflows, primarily L^AT_EX, via non-intrusive semantic annotations of arbitrary informal document fragments. That way formal knowledge management services become available for informal documents, accessible via an IDE for authors and via generated *active* documents for readers, while remaining fully compatible with existing authoring workflows and publishing systems.

Additionally, an extensible library of reusable document fragments is being developed, that serve as reference targets for global disambiguation, intermediaries for content exchange between systems and other services.

Every component of the system is designed modularly and extensibly, and thus lay the groundwork for a potential full integration of interactive theorem proving systems into established informal document authoring workflows.

The general sTeX workflow combines functionalities provided by several pieces of software:

- The sTeX package collection to use semantic annotations in L^AT_EX documents,
- RuS_{TE}X [RT] to convert `tex` sources to (semantically enriched) `xhtml`,
- The MMT system [MMT], that extracts semantic information from the thus generated `xhtml` and provides semantically informed added value services.

Chapter 2

Quickstart

2.1 Setup

There are two ways of using $\text{\texttt{sTeX}}$: as a

1. way of writing $\text{\texttt{L\text{A}TeX}}$ more modularly (object-oriented Math) for creating PDF documents or
2. foundation for authoring active documents in HTML5 instrumented with knowledge management services.

Both are legitimate and useful. The first requires a significantly smaller tool-chain, so we describe it first. The second requires a much more substantial (and experimental) toolchain of knowledge management systems. Both workflows profit from an integrated development environment (IDE), which (also) automates setup as far as possible (see [subsection 2.1.4](#)).

2.1.1 Minimal Setup for the PDF-only Workflow

In the best of all worlds, there is no setup, as you already have a new version of $\text{\texttt{T\text{E}XLive}}$ on your system as a $\text{\texttt{L\text{A}TeX}}$ enthusiast. If not now is the time to install it; see [\[TL\]](#). You can usually update $\text{\texttt{T\text{E}XLive}}$ via a package manager or the $\text{\texttt{T\text{E}XLive}}$ manager **$\text{\texttt{tlmgr}}$** .

Alternatively, you can install $\text{\texttt{sTeX}}$ from CTAN, the Comprehensive $\text{\texttt{T\text{E}X}}$ Archive Network; see [\[ST\]](#) for details.

2.1.2 GIT-based Setup for the $\text{\texttt{sTeX}}$ Development Version

If you want use the latest and greatest $\text{\texttt{sTeX}}$ packages, you can that have not even been released to CTAN, then you can directly clone them from the $\text{\texttt{sTeX}}$ development repository [\[sTeX\]](#) by the following command-line instructions:

```
cd <stexdir>
git clone https://github.com/slatex/sTeX.git
```

and keep it updated by pulling updates via `git pull` in the cloned $\text{\texttt{sTeX}}$ directory. Then update your `TEXINPUTS` environment variable, e.g. by placing the following line in your `.bashrc`:

¹NEW PART: MK: reorganized, we do not need the full MKM tool chain

```
export TEXINPUTS="$(TEXINPUTS):<sTeXDIR>//:"
```

2.1.3 sTeX Archives (Manual Setup)

Writing semantically annotated sTeX becomes much easier, if we can use well-designed libraries of already annotated content. sTeX provides such libraries as sTeX archives – i.e. GIT repositories at <https://gl.mathhub.info> – most prominently the SMGLoM libraries at <https://gl.mathhub.info/smgglom>.

To do so, we set up a **local MathHub** by creating a MathHub directory `<mhdir>`. Every sTeX archive as an **archive path** `<apath>` and a name `<archive>`. We can clone the sTeX archive by the following command-line instructions:

```
cd <mhdir>/<apath>
git clone https://gl.mathhub.info/smgglom/<archive>.git
```

Note that sTeX archives often depend on other archives, thus you should be prepared to clone these as well – e.g. if `pdflatex` reports missing files. To make sure that sTeX too knows where to find its archives, we need to set a global system variable `MATHHUB`, that points to your local MathHub-directory (see [section 3.2](#)).

```
export MATHHUB="<mhdir>"
```

2.1.4 The sTeX IDE

We are currently working on an sTeX IDE as an sTeX plugin for VScode; see [\[Sla\]](#). It will feature a setup procedure that automates the setup described above (and below). For additional functionality see the (now obsolete) plugin for sTeX 1 [\[SLS; Stb\]](#).

2.1.5 Manual Setup for Active Documents and Knowledge Management Services

Foregoing on the sTeX IDE, we will need several additional (on top of the minimal setup above) pieces of software; namely:

- **The Mmt System** available [here](#)². We recommend following the setup routine documented [here](#).

Following the setup routine (Step 3) will entail designating a **MathHub**-directory on your local file system, where the MMT system will look for sTeX/MMT content archives.

- **sTeX Archives** If we only care about L^AT_EX and generating pdfs, we do not technically need MMT at all; however, we still need the `MATHHUB` system variable to be set. Furthermore, MMT can make downloading content archives we might want to use significantly easier, since it makes sure that all dependencies of (often highly interrelated) sTeX archives are cloned as well.

Once set up, we can run `mmt` in a shell and download an archive along with all of its dependencies like this: `lmh install <name-of-repository>`, or a whole *group* of archives; for example, `lmh install smgglom` will download all `smgglom` archives.

- **RuSTeX** The MMT system will also set up RuSTeX for you, which is used to generate (semantically annotated) `xhtml` from tex sources. In lieu of using MMT, you can also download and use RuSTeX directly [here](#).

²EdNOTE: For now, we require the `sTeX`-branch, requiring manually compiling the MMT sources

2.2 A First sTeX Document

Having set everything up, we can write a first sTeX document. As an example, we will use the `smglom/calculus` and `smglom/arithmetics` archives, which should be present in the designated MathHub-folder, and write a small fragment defining the *geometric series*:

TODO: use some sTeX-archive instead of `smglom`, use a convergence-notion that includes the limit, mark-up the theorem properly

```

1 \documentclass{article}
2 \usepackage{stex,xcolor,stexthm}
3
4 \begin{document}
5 \begin{smodule}{GeometricSeries}
6   \importmodule[smglom/calculus]{series}
7   \importmodule[smglom/arithmetics]{realarith}
8
9   \symdef{geometricSeries}[name=geometric-series]{\comp{S}}
10
11   \begin{sdefinition}[for=geometricSeries]
12     The \definame{geometricSeries} is the \symname{?series}
13     \[\defeq{\geometricSeries}{\definiens{
14       \infinitesum{\svar{n}}{1}{
15         \realdivide[frac]{1}{
16           \realpower{2}{\svar{n}}
17         }
18       }}
19     \end{sdefinition}
20
21     \begin{sassertion}[name=geometricSeriesConverges,type=theorem]
22       The \symname{geometricSeries} \symname{converges} towards $1$.
23     \end{sassertion}
24 \end{smodule}
25 \end{document}

```

Compiling this document with `pdflatex` should yield the output

Definition 0.1. The **geometric series** is the **series**

$$S := \sum_{n=1}^{\infty} \frac{1}{2^n}.$$

Theorem 0.2. The **geometric series converges** towards 1.

Move your cursor over the various highlighted parts of the document – depending on your pdf viewer, this should yield some interesting (but possibly for now cryptic) information.

Remark 2.2.1:

Note that all of the highlighting, tooltips, coloring and the environment headers come from `stexthm` – by default, the amount of additional packages loaded is kept to a minimum and all the presentations can be customized, see [chapter 6](#).

Let's investigate this document in detail to understand the respective parts of the \TeX markup infrastructure:

```
\begin{smodule}{GeometricSeries}
...
\end{smodule}
```

smodule First, we open a new *module* called `GeometricSeries`. The main purpose of the `smodule` environment is to group the contents and associate it with a *globally unique* identifier (URI), which is computed from the name `GeometricSeries` and the document context. (Depending on your pdf viewer), the URI should pop up in a tooltip if you hover over the word **geometric series**.

```
\importmodule[smglom/calculus]{series}
\importmodule[smglom/arithmetics]{realarith}
```

\importmodule Next, we *import* two modules – `series` from the \TeX archive `smglom/calculus`, and `realarith` from the \TeX archive `smglom/arithmetics`. If we investigate these archives, we find the files `series.en.tex` and `realarith.en.tex` (respectively) in their respective source-folders, which contain the statements `\begin{smodule}{series}` and `\begin{smodule}{realarith}` (respectively).

The `\importmodule`-statements make all \TeX symbols and associated semantic macros (e.g. `\infinitesum`, `\realdive`, `\realpower`) in the imported module available to the current module `GeometricSeries`. The module `GeometricSeries` “exports” all of these symbols to all modules imports it via an `\importmodule{GeometricSeries}` instruction. Additionally it exports the local symbol `\geometricSeries`.

\usemodule If we only want to *use* the content of some module `Foo`, e.g. in remarks or examples, but none of the symbols in our current module actually *depend* on the content of `Foo`, we can use `\usemodule` instead – like `\importmodule`, this will make the module content available, but will *not* export it to other modules.

```
\symdef{GeometricSeries}[name=geometric-series]{\comp{S}}
```

\symdef Next, we introduce a new *symbol* with name `geometric-series` and assign it the semantic macro `\geometricSeries`. `\symdef` also immediately assigns this symbol a *notation*, namely `S`.

\comp The macro `\comp` marks the `S` in the notation as a *notational component*, as opposed to e.g. arguments to `\geometricSeries`. It is the notational components that get highlighted and associated with the corresponding symbol (i.e. in this case `geometricSeries`). Since `\geometricSeries` takes no arguments, we can wrap the whole notation in a `\comp`.

```

\begin{sdefinition}[for=geometricSeries]
...
\end{sdefinition}
\begin{sassertion}[name=geometricSeriesConverges,type=theorem]
...
\end{sassertion}

```

What follows are two \LaTeX -statements (e.g. definitions, theorems, examples, proofs, ...). These are semantically marked-up variants of the usual environments, which take additional optional arguments (e.g. `for=`, `type=`, `name=`). Since many \LaTeX templates predefine environments like `definition` or `theorem` with different syntax, we use `sdefinition`, `sassertion`, `sexample` etc. instead. You can customize these environments to e.g. simply wrap around some predefined `theorem`-environment. That way, we can still use `sassertion` to provide semantic information, while being fully compatible with (and using the document presentation of) predefined environments.

In our case, the `stexthm`-package patches e.g. `\begin{sassertion}[type=theorem]` to use a `theorem`-environment defined (as usual) using the `amsthm` package.

```
... is the \symname{?series}
```

`\symname`

The `\symname`-command prints the name of a symbol, highlights it (based on customizable settings) and associates the text printed with the corresponding symbol.

Note that the argument of `\symref` can be a local or imported symbol (here the `series` symbol is imported from the `series` module). \LaTeX tries to determine the full symbol URI from the argument. If there are name clashes in or with the imported symbols, the name of the exporting module can be prepended to the symbol name before the `?` character.

If you hover over the word `series` in the pdf output, you should see a tooltip showing the full URI of the symbol used.

`\symref`

The `\symname`-command is a special case of the more general `\symref`-command, which allows customizing the precise text associated with a symbol. `\symref` takes two arguments the first is the symbol name, and the second a variant verbalization of the symbol, e.g. an inflection variant, a different language or a synonym. In our example `\symname{?series}` abbreviates `\symref{?series}{series}`.

```
The \definame{geometricSeries} ...
```

`\definame`
`\definiendum`

The `sdefinition`-environment provides two additional macros, `\definame` and `\definiendum` which behave similarly to `\symname` and `\symref`, but explicitly mark the symbols as *being defined* in this environment, to allow for special highlighting.

```

\[\defeq{\geometricSeries}{\definiens{
  \infinitesum{\svar{n}}{1}{
    \realdivide[frac]{1}{
      \realpower{2}{\svar{n}}
    }
  }}
\].\]

```

The next snippet – set in a math environment – uses several semantic macros imported from (or recursively via) `series` and `realarithmetics`, such as `\defeq`, `\infinitesum`, etc. In math mode, using a semantic macro inserts its (default) definition. A semantic

macro can have several notations – in that case, we can explicitly choose a specific notation by providing its identifier as an optional argument; e.g. `\realdivide[frac]{a}{b}` will use the explicit notation named `frac` of the semantic macro `\realdivide`, which yields $\frac{a}{b}$ instead of a/b .

`\svar` The `\svar{n}` command marks up the `n` as a variable with name `n` and notation `n`.

`\definiens` The `sdefinition`-environment additionally provides the `\definiens`-command, which allows for explicitly marking up its argument as the *definiens* of the symbol currently being defined.

2.2.1 OMDoc/xhtml Conversion

So, if we run `pdflatex` on our document, then \TeX yields pretty colors and tooltips¹. But \TeX becomes a lot more powerful if we additionally convert our document to `xhtml` while preserving all the \TeX markup in the result.

TODO VSCode Plugin

Using `Ru\TeX [RT]`, we can convert the document to `xhtml` using the command `rustex -i /path/to/file.tex -o /path/to/outfile.xhtml`. Investigating the resulting file, we notice additional semantic information resulting from our usage of semantic macros, `\symref` etc. Below is the (abbreviated) snippet inside our `\definiens` block:

```
<mrow resource="" property="stex:definiens">
  <mrow resource="...?series?infinitesum" property="stex:OMBIND">
    <munderover displaystyle="true">
      <mo resource="...?series?infinitesum" property="stex:comp">\Sigma</mo>
      <mrow>
        <mrow resource="1" property="stex:arg">
          <mi resource="var://n" property="stex:OMV">n</mi>
        </mrow>
        <mo resource="...?series?infinitesum" property="stex:comp">=</mo>
        <mi resource="2" property="stex:arg">1</mi>
      </mrow>
      <mi resource="...?series?infinitesum" property="stex:comp">\infty</mi>
    </munderover>
    <mrow resource="3" property="stex:arg">
      <mfrac resource="...?realarith?division#frac#" property="stex:OMA">
        <mi resource="1" property="stex:arg">1</mi>
        <mrow resource="2" property="stex:arg">
          <msup resource="...realarith?exponentiation" property="stex:OMA">
            <mi resource="1" property="stex:arg">2</mi>
            <mrow resource="2" property="stex:arg">
              <mi resource="var://n" property="stex:OMV">n</mi>
            </mrow>
          </msup>
        </mrow>
      </mfrac>
    </mrow>
  </mrow>
</mrow>
```

¹...and hyperlinks for symbols, and indices, and allows reusing document fragments modularly, and...

...containing all the semantic information. The MMT system can extract from this the following OPENMATH snippet:

```
<OMBIND>
  <OMID name="...?series?infinitesum"/>
  <OMV name="n"/>
  <OMLIT name="1"/>
  <OMA>
    <OMS name="...?realarith?division"/>
    <OMLIT name="1"/>
    <OMA>
      <OMS name="...realarith?exponentiation"/>
      <OMLIT name="2"/>
      <OMV name="n"/>
    </OMA>
  </OMA>
</OMBIND>
```

...giving us the full semantics of the snippet, allowing for a plurality of knowledge management services – in particular when serving the **xhtml**.

Remark 2.2.2:

Note that the **html** when opened in a browser will look slightly different than the **pdf** when it comes to highlighting semantic content – that is because naturally **html** allows for much more powerful features than **pdf** does. Consequently, the **html** is intended to be served by a system like MMT, which can pick up on the semantic information and offer much more powerful highlighting, linking and similar features, and being customizable by *readers* rather than being prescribed by an author.

Additionally, not all browsers (most notably Chrome) support MATHML natively, and might require additional external JavaScript libraries such as MathJax to render mathematical formulas properly.

Chapter 3

Creating sTeX Content

We can use sTeX by simply including the package with `\usepackage{stex}`, or – primarily for individual fragments to be included in other documents – by using the sTeX document class with `\documentclass{stex}` which combines the `standalone` document class with the `stex` package.

Both the `stex` package and document class offer the following options:

lang (*<language>**) Languages to load with the `babel` package.

mathhub (*<directory>*) MathHub folder to search for repositories – this is not necessary if the `MATHHUB` system variable is set.

sms (*<boolean>*) use *persisted* mode (not yet implemented).

image (*<boolean>*) passed on to `tikzinput`.

debug (*<log-prefix>**) Logs debugging information with the given prefixes to the terminal, or all if `all` is given. Largely irrelevant for the majority of users.

3.1 How Knowledge is Organized in sTeX

sTeX content is organized on multiple levels:

1. sTeX **archives** (see [section 3.2](#)) contain individual `.tex`-files.
2. These may contain sTeX **modules**, introduced via `\begin{smodule}{ModuleName}`.
3. Modules contain sTeX **symbol declarations**, introduced via `\symdecl{symbolname}`, `\symdef{symbolname}` and some other constructions. Most symbols have a *notation* that can be used via a *semantic macro* `\symbolname` generated by symbol declarations.
4. sTeX **expressions** finally are built up from usages of semantic macros.

 M

 M

 T

- sTeX archives are simultaneously MMT archives, and the same directory structure is consequently used.

- sTeX modules correspond to OMDoc/MMT *theories*. `\importmodules` (and

$\hookrightarrow M \rightarrow$
 $\hookrightarrow M \rightarrow$
 $\hookrightarrow T \rightarrow$

similar constructions) induce MMT `includes` and other *theory morphisms*, thus giving rise to a *theory graph* in the OMDOC sense [RK13].

- Symbol declarations induce OMDOC/MMT *constants*, with optional (formal) *type* and *definiens* components.
- Finally, $\mathcal{S}\mathcal{T}\mathcal{E}\mathcal{X}$ expressions are converted to OMDOC/MMT terms, which use the abstract syntax (and XML encoding) of OPENMATH [Bus+04].

3.2 $\mathcal{S}\mathcal{T}\mathcal{E}\mathcal{X}$ Archives

3.2.1 The Local MathHub-Directory

`\usemodule`, `\importmodule`, `\inputref` etc. allow for including content modularly without having to specify absolute paths, which would differ between users and machines. Instead, $\mathcal{S}\mathcal{T}\mathcal{E}\mathcal{X}$ uses *archives* that determine the global namespaces for symbols and statements and make it possible for $\mathcal{S}\mathcal{T}\mathcal{E}\mathcal{X}$ to find content referenced via such URIs.

All $\mathcal{S}\mathcal{T}\mathcal{E}\mathcal{X}$ archives need to exist in the local MathHub-directory. $\mathcal{S}\mathcal{T}\mathcal{E}\mathcal{X}$ knows where this folder is via one of four means:

1. If the $\mathcal{S}\mathcal{T}\mathcal{E}\mathcal{X}$ package is loaded with the option `mathhub=/path/to/mathhub`, then $\mathcal{S}\mathcal{T}\mathcal{E}\mathcal{X}$ will consider `/path/to/mathhub` as the local MathHub-directory.
2. If the `mathhub` package option is *not* set, but the macro `\mathhub` exists when the $\mathcal{S}\mathcal{T}\mathcal{E}\mathcal{X}$ -package is loaded, then this macro is assumed to point to the local MathHub-directory; i.e. `\def\mathhub{/path/to/mathhub}\usepackage{stex}` will set the MathHub-directory as `path/to/mathhub`.
3. Otherwise, $\mathcal{S}\mathcal{T}\mathcal{E}\mathcal{X}$ will attempt to retrieve the system variable `MATHHUB`, assuming it will point to the local MathHub-directory. Since this variant needs setting up only *once* and is machine-specific (rather than defined in tex code), it is compatible with collaborating and sharing tex content, and hence recommended.
4. Finally, if all else fails, $\mathcal{S}\mathcal{T}\mathcal{E}\mathcal{X}$ will look for a file `~/.stex/mathhub.path`. If this file exists, $\mathcal{S}\mathcal{T}\mathcal{E}\mathcal{X}$ will assume that it contains the path to the local MathHub-directory. This method is recommended on systems where it is difficult to set environment variables.

3.2.2 The Structure of $\mathcal{S}\mathcal{T}\mathcal{E}\mathcal{X}$ Archives

An $\mathcal{S}\mathcal{T}\mathcal{E}\mathcal{X}$ archive `group/name` is stored in the directory `/path/to/mathhub/group/name`; e.g. assuming your local MathHub-directory is set as `/user/foo/MathHub`, then in order for the `smglom/calculus`-archive to be found by the $\mathcal{S}\mathcal{T}\mathcal{E}\mathcal{X}$ system, it needs to be in `/user/foo/MathHub/smglom/calculus`.

Each such archive needs two subdirectories:

- `/source` – this is where all your tex files go.
- `/META-INF` – a directory containing a single file `MANIFEST.MF`, the content of which we will consider shortly

An additional `lib`-directory is optional, and is where $\text{\texttt{S\TeX}}$ will look for files included via `\libinput`.

Additionally a *group* of archives `group/name` may have an additional archive `group/meta-inf`. If this `meta-inf`-archive has a `/lib`-subdirectory, it too will be searched by `\libinput` from all tex files in any archive in the `group/*-group`.

We recommend the following additional directory structure in the `source`-folder of an $\text{\texttt{S\TeX}}$ archive:

- `/source/mod/` – individual $\text{\texttt{S\TeX}}$ modules, containing symbol declarations, notations, and `\begin{sparagraph}[type=symdoc,for=...]` environments for “encyclopaedic” symbol documentations
- `/source/def/` – definitions
- `/source/ex/` – examples
- `/source/thm/` – theorems, lemmata and proofs; preferably proofs in separate files to allow for multiple proofs for the same statement
- `/source/snip/` – individual text snippets such as remarks, explanations etc.
- `/source/frag/` – individual document fragments, ideally only `\inputrefing` snippets, definitions, examples etc. in some desirable order
- `/source/tikz/` – tikz images, as individual `.tex`-files
- `/source/pic/` – image files.³

3.2.3 MANIFEST.MF-Files

The `MANIFEST.MF` in the `META-INF`-directory consists of key-value-pairs, informing $\text{\texttt{S\TeX}}$ (and associated software) of various properties of an archive. For example, the `MANIFEST.MF` of the `smglom/calculus`-archive looks like this:

```
id: smglom/calculus
source-base: http://mathhub.info/smglob/calculus
narration-base: http://mathhub.info/smglob/calculus
dependencies: smglom/arithmetic,smglom/sets,smglom/topology,
              smglom/mv,smglom/linear-algebra,smglom/algebra
responsible: Michael.Kohlhase@FAU.de
title: Elementary Calculus
teaser: Terminology for the mathematical study of change.
description: desc.html
```

Many of these are in fact ignored by $\text{\texttt{S\TeX}}$, but some are important:

`id`: The name of the archive, including its group (e.g. `smglom/calculus`),

`source-base` or

`ns`: The namespace from which all symbol and module URIs in this repository are formed, see (`TODO`),

³EdNOTE: MK: bisher habe ich immer PIC subdirs, soll ich das ändern?

narration-base: The namespace from which all document URIs in this repository are formed, see (TODO),

url-base: The URL that is formed as a basis for *external references*, see (TODO),

dependencies: All archives that this archive depends on. $\text{\texttt{STeX}}$ ignores this field, but MMT can pick up on them to resolve dependencies, e.g. for `lmh install`.

3.2.4 Using Files in $\text{\texttt{STeX}}$ Archives Directly

Several macros provided by $\text{\texttt{STeX}}$ allow for directly including files in repositories. These are:

$\text{\texttt{\backslash mhinput}}$	$\text{\texttt{\backslash mhinput}}[\text{Some/Archive}]\{\text{some/file}\}$ directly inputs the file <code>some/file</code> in the <code>source-</code> folder of <code>Some/Archive</code> .
--------------------------------------	---

$\text{\texttt{\backslash inputref}}$	$\text{\texttt{\backslash inputref}}[\text{Some/Archive}]\{\text{some/file}\}$ behaves like $\text{\texttt{\backslash mhinput}}$, but wraps the input in a <code>\begingroup ... \endgroup</code> . When converting to <code>xhtml</code> , the file is not input at all, and instead an <code>html</code> -annotation is inserted that references the file, e.g. for lazy loading.
---------------------------------------	--

In the majority of practical cases $\text{\texttt{\backslash inputref}}$ is likely to be preferred over $\text{\texttt{\backslash mhinput}}$ because it leads to less duplication in the generated `xhtml`.

$\text{\texttt{\backslash ifinput}}$	Both $\text{\texttt{\backslash mhinput}}$ and $\text{\texttt{\backslash inputref}}$ set $\text{\texttt{\backslash ifinput}}$ to “true” during input. This allows for selectively including e.g. bibliographies only if the current file is not being currently included in a larger document.
--------------------------------------	---

$\text{\texttt{\backslash addmhbibresource}}$	$\text{\texttt{\backslash addmhbibresource}}[\text{Some/Archive}]\{\text{some/file}\}$ searches for a file like $\text{\texttt{\backslash mhinput}}$ does, but calls $\text{\texttt{\backslash addbibresource}}$ to the result and looks for the file in the archive root directory directly, rather than the <code>source</code> directory. Typical invocations are
---	--

- $\text{\texttt{\backslash addmhbibresource}}\{\text{lib/refs.bib}\}$, which specifies a bibliography in the `lib` folder in the local archive or
- $\text{\texttt{\backslash addmhbibresource}}[\text{HW/meta-inf}]\{\text{lib/refs.bib}\}$ in another.

$\text{\texttt{\backslash libinput}}$	$\text{\texttt{\backslash libinput}}\{\text{some/file}\}$ searches for a file <code>some/file</code> in
---------------------------------------	---

- the `lib`-directory of the current archive, and
- the `lib`-directory of a `meta-inf`-archive in (any of) the archive groups containing the current archive

and include all found files in reverse order; e.g. $\text{\texttt{\backslash libinput}}\{\text{preamble}\}$ in a `.tex`-file in `smglom/calculus` will *first* input `.../smglom/meta-inf/lib/preamble.tex` and then `../smglom/calculus/lib/preamble.tex`.

$\text{\texttt{\backslash libinput}}$ will throw an error if *no* candidate for `some/file` is found.

`\libusepackage` `\libusepackage`[package-options]{some/file} searches for a file `some/file.sty` in the same way that `\libinput` does, but will call `\usepackage`[package-options]{path/to/some/file} instead of `\input`.
`\libusepackage` throws an error if not *exactly one* candidate for `some/file` is found.

Remark 3.2.1:

A good practice is to have individual \TeX fragments follow basically this document frame:

```
1 \documentclass{stex}
2 \libinput{preamble}
3 \begin{document}
4   ...
5   \ifinputref \else \libinput{postamble} \fi
6 \end{document}
```

Then the `preamble.tex` files can take care of loading the generally required packages, setting presentation customizations etc. (per archive or archive group or both), and `postamble.tex` can e.g. print the bibliography, index etc.

`\libusepackage` is particularly useful in `preamble.tex` when we want to use custom packages that are not part of \TeX Live. In this case we commit the respective packages in one of the `lib` folders and use `\libusepackage` to load them.

3.3 Module, Symbol and Notation Declarations

3.3.1 The `smodule`-Environment

`smodule` A new module is declared using the basic syntax

```
\begin{smodule}[options]{ModuleName}...\end{smodule}.
```

A module is required to declare any new formal content such as symbols or notations (but not variables, which may be introduced anywhere).

The `smodule`-environment takes several keyword arguments, all of which are optional:

`title` (*<token list>*) to display in customizations.

`type` (*<string>**) for use in customizations.

`deprecate` (*<module>*) if set, will throw a warning when loaded, urging to use *<module>* instead.

`id` (*<string>*) for cross-referencing.

`ns` (*<URI>*) the namespace to use. *Should not be used, unless you know precisely what you're doing.* If not explicitly set, is computed using `\stex_modules_current_namespace:`.

`lang` (*<language>*) if not set, computed from the current file name (e.g. `foo.en.tex`).

`sig` (*<language>*) if the current file is a translation of a file with the same base name but a different language suffix, setting `sig=<lang>` will preload the module from that language file. This helps ensuring that the (formal) content of both modules is (almost) identical across languages and avoids duplication.

`creators` ($\langle string \rangle^*$) names of the creators.
`contributors` ($\langle string \rangle^*$) names of contributors.
`srccite` ($\langle string \rangle$) a source citation for the content of this module.

\hookrightarrow M \rightarrow An \LaTeX module corresponds to an MMT/OMDoc *theory*. As such it
 \hookrightarrow M \rightarrow gets assigned a module URI (*universal resource identifier*) of the form
 \hookrightarrow T \hookrightarrow $\langle namespace \rangle ? \langle module-name \rangle$.

By default, opening a module will produce no output whatsoever, e.g.:

Example 1

Input:

```
1 \begin{smodule}[title={This is Some Module}]{SomeModule}
2   Hello World
3 \end{smodule}
```

Output:

Hello World

`\stexpatchmodule`

We can customize this behavior either for all modules or only for modules with a specific type using the command `\stexpatchmodule[optional-type]{begin-code}{end-code}`. Some optional parameters are then available in `\smodule*`-macros, specifically `\smoduletitle`, `\smoduletype` and `\smoduleid`.

For example:

Example 2

Input:

```
1 \stexpatchmodule[display]
2   {\textbf{Module (\smoduletitle)}\par}
3   {\par\noindent\textbf{End of Module (\smoduletitle)}}
4
5 \begin{smodule}[type=display,title={Some New Module}]{SomeModule2}
6   Hello World
7 \end{smodule}
```

Output:

Module (Some New Module)
Hello World
End of Module (Some New Module)

3.3.2 Declaring New Symbols and Notations

Inside an `smodule` environment, we can declare new \TeX symbols.

`\symdecl`

The most basic command for doing so is using `\symdecl{symbolname}`. This introduces a new symbol with name `symbolname`, arity 0 and semantic macro `\symbolname`.

The starred variant `\symdecl*{symbolname}` will declare a symbol, but not introduce a semantic macro. If we don't want to supply a notation (for example to introduce concepts like “abelian”, which is not something that has a notation), the starred variant is likely to be what we want.

\hookrightarrow `\symdecl` introduces a new OMDoc/MMT constant in the current module (\Rightarrow OMDoc/MMT theory). Correspondingly, they get assigned the URI `<module-URI>?<constant-name>`.

Without a semantic macro or a notation, the only meaningful way to reference a symbol is via `\symref`, `\symname` etc.

Example 3

Input:

```
1 \symdecl*{foo}
2 Given a \symname{foo}, we can...
```

Output:

Given a `foo`, we can...

Obviously, most semantic macros should take actual *arguments*, implying that the symbol we introduce is an *operator* or *function*. We can let `\symdecl` know the *arity* (i.e. number of arguments) of a symbol like this:

Example 4

Input:

```
1 \symdecl{binarysymbol}[args=2]
2 \symref{binarysymbol}{this} is a symbol taking two arguments.
```

Output:

`this` is a symbol taking two arguments.

So far we have gained exactly ... nothing by adding the arity information: we cannot do anything with the arguments in the text.

We will now see what we can gain with more machinery.

`\notation`

We probably want to supply a notation as well, in which case we can finally actually use the semantic macro in math mode. We can do so using the `\notation` command, like this:

Example 5

Input:

```
1 \notation{binarysymbol}{\text{First: }#1\text{; Second: }#2}
2 $\binarysymbol{a}{b}$
```

Output:

First: a ; Second: b

-  `M` → Applications of semantic macros, such as `\binarysymbol{a}{b}` are translated to
-  `M` → MMT/OMDOC as OMA-terms with head `<OMS name="...?binarysymbol"/>`.
-  `T` → Semantic macros with no arguments correspond to OMS directly.

`\comp`

For many semantic services e.g. semantic highlighting or **wikification** (linking user-visible notation components to the definition of the respective symbol they come from), we need to specify the notation components. Unfortunately, there is currently no way the \LaTeX engine can infer this by itself, so we have to specify it manually in the notation specification. We can do so with the `\comp` command.

We can introduce a new notation `highlight` for `\binarysymbol` that fixes this flaw, which we can subsequently use with `\binarysymbol[highlight]`:

Example 6

Input:

```
1 \notation{binarysymbol}[highlight]
2 {\comp{\text{First: }}#1\comp{\text{; Second: }}#2}
3 $\binarysymbol[highlight]{a}{b}$
```

Output:

First: a ; Second: b



Ideally, `\comp` would not be necessary: Everything in a notation that is *not* an argument should be a notation component. Unfortunately, it is computationally expensive to determine where an argument begins and ends, and the argument markers `#n` may themselves be nested in other macro applications or \LaTeX groups, making it ultimately almost impossible to determine them automatically while also remaining compatible with arbitrary highlighting customizations (such as tooltips, hyperlinks, colors) that users might employ, and that are ultimately invoked by `\comp`.

Note that it is required that

1. the argument markers `#n` never occur inside a `\comp`, and
2. no semantic arguments may ever occur inside a notation.

Both criteria are not just required for technical reasons, but conceptionally meaningful:

The underlying principle is that the arguments to a semantic macro represent *arguments to the mathematical operation* represented by a symbol. For example, a semantic macro `\addition{a}{b}` taking two arguments would represent *the actual addition of (mathematical objects) a and b*. It should therefore be impossible for *a* or *b* to be part of a notation component of `\addition`.



Similarly, a semantic macro can not conceptually be part of the notation of `\addition`, since a semantic macro represents a *distinct mathematical concept* with *its own semantics*, whereas notations are syntactic representations of the very symbol to which the notation belongs.

If you want an argument to a semantic macro to be a purely syntactic parameter, then you are likely somewhat confused with respect to the distinction between the precise *syntax* and *semantics* of the symbol you are trying to declare (which happens quite often even to experienced \LaTeX users), and might want to give those another thought - quite likely, the macro you aim to implement does not actually represent a semantically meaningful mathematical concept, and you will want to use `\def` and similar native \LaTeX macro definitions rather than semantic macros.

`\symdef`

In the vast majority of cases where a symbol declaration should come with a semantic macro, we will want to supply a notation immediately. For that reason, the `\symdef` command combines the functionality of both `\symdecl` and `\notation` with the optional arguments of both:

Example 7

Input:

```
1 \symdef{newbinarysymbol}[h1,args=2]
2   {\comp{\text{1.: }}#1\comp{\text{; 2.: }}#2}
3 $\newbinarysymbol{a}{b}$
```

Output:

```
1.: a; 2.: b
```

We just declared a new symbol `newbinarysymbol` with `args=2` and immediately provided it with a notation with identifier `h1`. Since `h1` is the *first* (and so far, only) notation supplied for `newbinarysymbol`, using `\newbinarysymbol` without optional argument defaults to this notation.

But one man's meat is another man's poison: it is very subjective what the “default notation” of an operator should be. Different communities have different practices. For instance, the complex unit is written as *i* in Mathematics and as *j* in electrical engineering.

So to allow modular specification and facilitate re-use of document fragments \LaTeX allows to re-set notation defaults.

$\backslash\text{setnotation}$

The first notation provided will stay the default notation unless explicitly changed – this is enabled by the $\backslash\text{setnotation}$ command: $\backslash\text{setnotation}\{\text{symbolname}\}\{\text{notation-id}\}$ sets the default notation of $\backslash\text{symbolname}$ to notation-id , i.e. henceforth, $\backslash\text{symbolname}$ behaves like $\backslash\text{symbolname}[\text{notation-id}]$ from now on.

Often, a default notation is set right after the corresponding notation is introduced – the starred version $\backslash\text{notation}^*$ for that reason introduces a new notation and immediately sets it to be the new default notation. So expressed differently, the *first* $\backslash\text{notation}$ for a symbol behaves exactly like $\backslash\text{notation}^*$, and $\backslash\text{notation}^*\{\text{foo}\}[\text{bar}]\{\dots\}$ behaves exactly like $\backslash\text{notation}\{\text{foo}\}[\text{bar}]\{\dots\}\backslash\text{setnotation}\{\text{foo}\}[\text{bar}]$.

Operator Notations

Once we have a semantic macro with arguments, such as $\backslash\text{newbinarysymbol}$, the semantic macro represents the *application* of the symbol to a list of arguments. What if we want to refer to the operator *itself*, though?

We can do so by supplying the $\backslash\text{notation}$ (or $\backslash\text{symdef}$) with an *operator notation*, indicated with the optional argument op= . We can then invoke the operator notation using $\backslash\text{symbolname}![\text{notation-identifier}]$. Since operator notations never take arguments, we do not need to use $\backslash\text{comp}$ in it, the whole notation is wrapped in a $\backslash\text{comp}$ automatically:

Example 8

Input:

```
1 \notation{newbinarysymbol}[ab, op={\text{a:}\cdot\text{; b:}\cdot}]
2 {\comp{\text{a:}}#1\comp{\text{; b:}}#2} \symname{newbinarysymbol} is also
3 occasionally written $\newbinarysymbol![ab]$
```

Output:

newbinarysymbol is also occasionally written $\text{a:} \cdot \text{; b:} \cdot$

\hookrightarrow $\backslash\text{symbolname}!$ is translated to OMDoc/MMT as $\langle\text{OMS name}=\dots?\text{symbolname}\rangle/$
 \hookrightarrow directly.

3.3.3 Argument Modes

The notations so far used *simple* arguments which we call *mode-i* arguments. Declaring a new symbol with $\backslash\text{symdecl}\{\text{foo}\}[\text{args}=3]$ is equivalent to writing $\backslash\text{symdecl}\{\text{foo}\}[\text{args}=iii]$, indicating that the semantic macro takes three mode-i arguments. However, there are three more argument modes which we will investigate now, namely mode-b, mode-a and mode-B arguments.

Mode-b Arguments

A mode-b argument represents a *variable* that is *bound* by the symbol in its application, making the symbol a *binding operator*. Typical examples of binding operators are e.g. sums \sum , products \prod , integrals \int , quantifiers like \forall and \exists , that λ -operator, etc.

\hookrightarrow Mode-b arguments behave exactly like mode-i arguments within T_EX, but applications of binding operators, i.e. symbols with mode-b arguments, are translated to OMBIND-terms in OMDoc/MMT, rather than OMA.

For example, we can implement a summation operator binding an index variable and taking lower and upper index bounds and the expression to sum over like this:

Example 9

Input:

```

1 \symdef{summation}[args=biii]
2   {\mathop{\comp{sum}}_{\#1\comp{=}\#2}^{\#3\#4}}
3   $\summation{\svar{x}}{1}{\svar{n}}{\svar{x}}^2$
    
```

Output:

$$\sum_{x=1}^n x^2$$

where the variable x is now *bound* by the `\summation`-symbol in the expression.

Mode-a Arguments

Mode-a arguments represent a *flexary argument sequence*, i.e. a sequence of arguments of arbitrary length. Formally, operators that take arbitrarily many arguments don't "exist", but in informal mathematics, they are ubiquitous. Mode-a arguments allow us to write e.g. `\addition{a,b,c,d,e}` rather than having to write something like `\addition{a}{\addition{b}{\addition{c}{\addition{d}{e}}}}`!

`\notation` (and consequently `\symdef`, too) take one additional argument for each mode-a argument that indicates how to "accumulate" a comma-separated sequence of arguments. This is best demonstrated on an example.

Let's say we want an operator representing quantification over an ascending chain of elements in some set, i.e. `\ascendingchain{S}{a,b,c,d,e}{t}` should yield $\forall a <_S b <_S c <_S d <_S e. t$. The "base"-notation for this operator is simply `{\comp{forall} \#2\comp{.},\#3}`, where `\#2` represents the full notation fragment *accumulated* from `{a,b,c,d,e}`.

The *additional* argument to `\notation` (or `\symdef`) takes the same arguments as the base notation and two *additional* arguments `\#1` and `\#2` representing successive pairs in the mode-a argument, and accumulates them into `\#2`, i.e. to produce $a <_S b <_S c <_S d <_S e$, we do `{\#1 \comp{<}}_{\#1} \#2`:

Example 10

Input:

```

1 \symdef{ascendingchain}[args=iai]
2   {\comp{\forall} #2\comp{. \,} #3}
3   {##1 \comp{<}_{#1} ##2}
4
5 Tadaa: $\ascendingchain{S}{a,b,c,d,e}{t}$

```

Output:

Tadaa: $\forall a <_S b <_S c <_S d <_S e. t$

If this seems overkill, keep in mind that you will rarely need the single-hash arguments #1,#2 etc. in the a-notation-argument. For a much more representative and simpler example, we can introduce flexary addition via:

Example 11

Input:

```

1 \symdef{addition}[args=a]{#1}{##1 \comp{+} ##2}
2
3 Tadaa: $\addition{a,b,c,d,e}$

```

Output:

Tadaa: $a+b+c+d+e$

The assoc-key We mentioned earlier that “formally”, flexary arguments don’t really “exist”. Indeed, formally, addition is usually defined as a binary operation, quantifiers bind a single variable etc.

Consequently, we can tell \LaTeX (or, rather, MMT/OMDOC) how to “resolve” flexary arguments by providing `\symdecl` or `\symdef` with an optional `assoc`-argument, as in `\symdecl{addition}[args=a,assoc=bin]`. The possible values for the `assoc`-key are:

bin: A binary, associative argument, e.g. as in `\addition`

binl: A binary, left-associative argument, e.g. $a^{b^{c^d}}$, which stands for $((a^b)^c)^d$

binr: A binary, right-associative argument, e.g. as in $A \rightarrow B \rightarrow C \rightarrow D$, which stands for $A \rightarrow (B \rightarrow (C \rightarrow D))$

pre: Successively prefixed, e.g. as in $\forall x, y, z. P$, which stands for $\forall x. \forall y. \forall z. P$

conj: Conjunctive, e.g. as in $a = b = c = d$ or $a, b, c, d \in A$, which stand for $a = d \wedge b = d \wedge c = d$ and $a \in A \wedge b \in A \wedge c \in A \wedge d \in A$, respectively

pwconj: Pairwise conjunctive, e.g. as in $a \neq b \neq c \neq d$, which stands for $a \neq b \wedge a \neq c \wedge a \neq d \wedge b \neq c \wedge b \neq d \wedge c \neq d$

As before, at the PDF level, this annotation is invisible (and without effect), but at the level of the generated OMDoc/MMT this leads to more semantical expressions.

Mode-B Arguments

Finally, mode-B arguments simply combine the functionality of both `a` and `b` - i.e. they represent an arbitrarily long sequence of variables to be bound, e.g. for implementing quantifiers:

Example 12

Input:

```
1 \symdef{quantforall}[args=Bi]
2   {\comp{\forall}#1\comp{.}#2}
3   {##1\comp,##2}
4
5 \$\quantforall{\svar{x},\svar{y},\svar{z}}{P}$
```

Output:

$\forall x,y,z.P$

3.3.4 Type and Definiens Components

`\symdecl` and `\symdef` take two more optional arguments. \TeX largely ignores them (except for special situations we will talk about later), but MMT can pick up on them for additional services. These are the `type` and `def` keys, which expect expressions in math-mode (ideally using semantic macros, of course!)

The `type` and `def` keys correspond to the `type` and `definiens` components of

- \hookrightarrow OMDOC/MMT constants.
- \rightarrow Correspondingly, the name “type” should be taken with a grain of salt, since
- \rightarrow OMDOC/MMT – being foundation-independent – does not a priori implement a fixed typing system.

The `type`-key allows us to provide additional information (given the necessary \TeX symbols), e.g. for addition on natural numbers:

Example 13

Input:

```
1 \symdef{Nat}[type=\set]{\comp{\mathbb N}}
2 \symdef{addition}[
3   type=\funtype{\Nat,\Nat}{\Nat},
4   op=+,
5   args=a
6 ]{#1}{##1 \comp+ ##2}
7
8 \symname{addition} is an operation $\funtype{\Nat,\Nat}{\Nat}$
```

Output:

`addition` is an operation $\mathbb{N} \times \mathbb{N} \rightarrow \mathbb{N}$

The `def`-key allows for declaring symbols as abbreviations:

Example 14

Input:

```
1 \symdef{successor}[
2   type=\funtype{\Nat}{\Nat},
3   def=\fun{\svar{x}}{\addition{\svar{x},1}},
4   op=\mathtt{succ},
5   args=1
6 ]{\comp{\mathtt{succ}{}#1\comp{}}}
7
8 The \symname{successor} operation $\funtype{\Nat}{\Nat}$
9 is defined as $\fun{\svar{x}}{\addition{\svar{x},1}}$
```

Output:

The `successor` operation $\mathbb{N} \rightarrow \mathbb{N}$ is defined as $x \mapsto x+1$

3.3.5 Precedences and Automated Bracketing

Having done `\addition`, the obvious next thing to implement is `\multiplication`. This is straight-forward in theory:

Example 15

Input:

```
1 \symdef{multiplication}[
2   type=\funtype{\Nat,\Nat}{\Nat},
3   op=\cdot,
4   args=a
5 ]{\#1}{\#1 \comp\cdot \#2}
6
7 \symname{multiplication} is an operation $\funtype{\Nat,\Nat}{\Nat}$
```

Output:

`multiplication` is an operation $\mathbb{N} \times \mathbb{N} \rightarrow \mathbb{N}$

However, if we *combine* `\addition` and `\multiplication`, we notice a problem:

Example 16

Input:

```
1 $\addition{a,\multiplication{b,\addition{c,\multiplication{d,e}}}}$
```

Output:

$a+b \cdot c+d \cdot e$

We all know that \cdot binds stronger than $+$, so the output $a+b\cdot c+d\cdot e$ does not actually reflect the term we wrote. We can of course insert parentheses manually

Example 17

Input:

```
1 $\addition{a,\multiplication{b,(\addition{c,\multiplication{d,e}})}}$
```

Output:

$$a+b\cdot(c+d\cdot e)$$

but we can also do better by supplying *precedences* and have \TeX insert parentheses automatically.

For that purpose, `\notation` (and hence `\symdef`) take an optional argument `prec=<opprec>;<argprec1>x...x<argprec n>`.

We will investigate the precise meaning of `<opprec>` and the `<argprec>`s shortly – in the vast majority of cases, it is perfectly sufficient to think of `prec=` taking a single number and having that be *the* precedence of the notation, where lower precedences (somewhat counterintuitively) bind stronger than higher precedences. So fixing our notations for `\addition` and `\multiplication`, we get:

Example 18

Input:

```
1 \notation{multiplication}[
2   op=\cdot,
3   prec=50
4 ]{#1}{##1 \comp\cdot ##2}
5 \notation{addition}[
6   op=+,
7   prec=100
8 ]{#1}{##1 \comp+ ##2}
9
10 $\addition{a,\multiplication{b,\addition{c,\multiplication{d,e}}}}$
```

Output:

$$a+b\cdot(c+d\cdot e)$$

Note that the precise numbers used for precedences are pretty arbitrary – what matters is which precedences are higher than which other precedences when used in conjunction.

`\infprec`
`\neginfprec`

It is occasionally useful to have “infinitely” high or low precedences to enforce or forbid automated bracketing entirely – for those purposes, `\infprec` and `\neginfprec` exist (which are implemented as the maximal and minimal integer values accordingly).

More precisely, each notation takes

1. One *operator precedence* and
2. one *argument precedence* for each argument.

By default, all precedences are 0, unless the symbol takes no argument, in which case the operator precedence is `\neginfprec` (negative infinity). If we only provide a single number, this is taken as both the operator precedence and all argument precedences.

$\text{\S}\text{\TeX}$ decides whether to insert parentheses by comparing operator precedences to a *downward precedence* p_d with initial value `\infprec`. When encountering a semantic macro, $\text{\S}\text{\TeX}$ takes the operator precedence p_{op} of the notation used and checks whether $p_{op} > p_d$. If so, $\text{\S}\text{\TeX}$ insert parentheses.

When $\text{\S}\text{\TeX}$ steps into an argument of a semantic macro, it sets p_d to the respective argument precedence of the notation used.

In the example above:



1. $\text{\S}\text{\TeX}$ starts out with $p_d = \text{\code{\infprec}}$.
2. $\text{\S}\text{\TeX}$ encounters `\addition` with $p_{op} = 100$. Since $100 \not> \text{\code{\infprec}}$, it inserts no parentheses.
3. Next, $\text{\S}\text{\TeX}$ encounters the two arguments for `\addition`. Both have no specifically provided argument precedence, so $\text{\S}\text{\TeX}$ uses $p_d = p_{op} = 100$ for both and recurses.
4. Next, $\text{\S}\text{\TeX}$ encounters `\multiplication{b,...}`, whose notation has $p_{op} = 50$.
5. We compare to the current downward precedence p_d set by `\addition`, arriving at $p_{op} = 50 \not> 100 = p_d$, so $\text{\S}\text{\TeX}$ again inserts no parentheses.
6. Since the notation of `\multiplication` has no explicitly set argument precedences, $\text{\S}\text{\TeX}$ uses the operator precedence for all arguments of `\multiplication`, hence sets $p_d = p_{op} = 50$ and recurses.
7. Next, $\text{\S}\text{\TeX}$ encounters the inner `\addition{c,...}` whose notation has $p_{op} = 100$.
8. We compare to the current downward precedence p_d set by `\multiplication`, arriving at $p_{op} = 100 > 50 = p_d$ – which finally prompts $\text{\S}\text{\TeX}$ to insert parentheses, and we proceed as before.

3.3.6 Variables

All symbol and notation declarations require a module with which they are associated, hence the commands `\symdecl`, `\notation`, `\symdef` etc. are disabled outside of `smodule`-environments.

Variables are different – variables are allowed everywhere, are not exported when the current module (if one exists) is imported (via `\importmodule` or `\usemodule`) and (also unlike symbol declarations) “disappear” at the end of the current \TeX group.

`\svar`

So far, we have always used variables using `\svar{n}`, which marks-up n as a variable with name `n`. More generally, `\svar[foo]{<texcode>}` marks-up the arbitrary `<texcode>` as representing a variable with name `foo`.

Of course, this makes it difficult to reuse variables, or introduce “functional” variables with arities > 0 , or provide them with a type or definiens.

`\vardef`

For that, we can use the `\vardef` command. Its syntax is largely the same as that of `\symdef`, but unlike symbols, variables have only one notation (TODO: so far?), hence there is only `\vardef` and no `\vardecl`.

Example 19

Input:

```

1 \vardef{varf}[
2   name=f,
3   type=\funtype{\Nat}{\Nat},
4   op=f,
5   args=1,
6   prec=0;\neginfprec
7 ]{\comp{f}#1}
8 \vardef{varn}[name=n,type=\Nat]{\comp{n}}
9 \vardef{varx}[name=x,type=\Nat]{\comp{x}}
10
11 Given a function $\varf!:\funtype{\Nat}{\Nat}$,
12 by $\addition{\varf!,\varn}$ we mean the function
13 $\fun{\varx}{\varf{\addition{\varx,\varn}}}$

```

Output:

Given a function $f : \mathbb{N} \rightarrow \mathbb{N}$, by $f+n$ we mean the function $x \mapsto f(x+n)$

(of course, “lifting” addition in the way described in the previous example is an operation that deserves its own symbol rather than abusing `\addition`, but... well.)

TODO: bind=forall/exists

3.3.7 Variable Sequences

Variable *sequences* occur quite frequently in informal mathematics, hence they deserve special support. Variable sequences behave like variables in that they disappear at the end of the current \TeX group and are not exported from modules, but their declaration is quite different.

`\varseq`

A variable sequence is introduced via the command `\varseq`, which takes the usual optional arguments `name` and `type`. It then takes a starting index, an end index and a *notation* for the individual elements of the sequence parametric in an index. Note that both the starting as well as the ending index may be variables.

This is best shown by example:

Example 20

Input:

```

1 \vardef{varn}[name=n,type=\Nat]{\comp{n}}
2 \varseq{seqa}[name=a,type=\Nat]{1}{\varn}{\comp{a}_{#1}}
3
4 The  $i$ th index of  $\seqa!$  is  $\seqa{i}$ .

```

Output:

The i th index of a_1, \dots, a_n is a_i .

Note that the syntax `\seqa!` now automatically generates a presentation based on the starting and ending index.

TODO: more notations for invoking sequences.

Notably, variable sequences are nicely compatible with `a`-type arguments, so we can do the following:

Example 21

Input:

```
1  $\addition{\seqa}$ 
```

Output:

$a_1 + \dots + a_n$

Sequences can be *multidimensional* using the `args`-key, in which case the notation's arity increases and starting and ending indices have to be provided as a comma-separated list:

Example 22

Input:

```

1 \vardef{varm}[name=m,type=\Nat]{\comp{m}}
2 \varseq{seqa}[
3   name=a,
4   args=2,
5   type=\Nat,
6 ]{1,1}{\varn,\varm}{\comp{a}_{#1}^{\#2}}
7
8  $\seqa!$  and  $\addition{\seqa}$ 

```

Output:

a_1^1, \dots, a_n^m and $a_1^1 + \dots + a_n^m$

We can also explicitly provide a “middle” segment to be used, like such:

Example 23

Input:

```

1 \varseq{seqa}[
2   name=a,
3   type=\Nat,
4   args=2,
5   mid={\comp{a}_{\varn}^1,\comp{a}_1^2,\ellipses,\comp{a}_{1}^{\varm}}
6 ]{1,1}{\varn,\varm}{\comp{a}_{\#1}^{\#2}}
7
8 $\seqa!$ and $\addition{\seqa}$

```

Output:

$$a_1^1, \dots, a_n^1, a_1^2, \dots, a_1^m, \dots, a_n^m \text{ and } a_1^1 + \dots + a_n^1 + a_1^2 + \dots + a_1^m + \dots + a_n^m$$

3.4 Module Inheritance and Structures

The sTeX features for modular document management are inherited from the OM-Doc/MMT model that organizes knowledge into a graph, where the nodes are theories (called modules in sTeX) and the edges are truth-preserving mappings (called theory morphisms in MMT). We have already seen modules/theories above.

Before we get into theory morphisms in sTeX we will see a very simple application of modules: managing multilinguality modularly.

3.4.1 Multilinguality and Translations

If we load the sTeX document class or package with the option `lang=<lang>`, sTeX will load the appropriate `babel` language for you – e.g. `lang=de` will load the `babel` language `ngerman`. Additionally, it makes sTeX aware of the current document being set in (in this example) *german*. This matters for reasons other than mere `babel`-purposes, though:

Every *module* is assigned a language. If no sTeX package option is set that allows for inferring a language, sTeX will check whether the current file name ends in e.g. `.en.tex` (or `.de.tex` or `.fr.tex`, or...) and set the language accordingly. Alternatively, a language can be explicitly assigned via `\begin{smodule}[lang=<language>]{Foo}`.

Technically, each `smodule`-environment induces *two* OMDoc/MMT theories:
 \hookrightarrow `\begin{smodule}[lang=<lang>]{Foo}` generates a theory `some/namespace?Foo` that only contains the “formal” part of the module – i.e. exactly the content that is exported when using `\importmodule`.
 \rightsquigarrow Additionally, MMT generates a *language theory* `some/namespace/Foo?<lang>` that includes `some/namespace?Foo` and contains all the other document content – variable declarations, includes for each `\usemodule`, etc.

Notably, the language suffix in a filename is ignored for `\usemodule`, `\importmodule` and in generating/computing URIs for modules. This however allows for providing *translations* for modules between languages without needing to duplicate content:

If a module `Foo` exists in e.g. english in a file `Foo.en.tex`, we can provide a file `Foo.de.tex` right next to it, and write `\begin{smodule}[sig=en]{Foo}`. The `sig`-key

then signifies, that the “signature” of the module is contained in the *english* version of the module, which is immediately imported from there, just like `\importmodule` would.

Additionally to translating the informal content of a module file to different languages, it also allows for customizing notations between languages. For example, the *least common multiple* of two numbers is often denoted as $\text{lcm}(a, b)$ in english, but is called *kleinstes gemeinsames Vielfaches* in german and consequently denoted as $\text{kgV}(a, b)$ there.

We can therefore imagine a german version of an lcm-module looking something like this:

```
1 \begin{smodule}[sig=en]{lcm}
2   \notation*{lcm}[de]{\comp{\mathtt{kgV}}{(#1,#2)}}
3
4   Das \symref{lcm}{kleinste gemeinsame Vielfache}
5    $\text{lcm}\{a,b\}$  von zwei Zahlen  $a,b$  ist...
6 \end{smodule}
```

If we now do `\importmodule{lcm}` (or `\usemodule{lcm}`) within a *german* document, it will also load the content of the german translation, including the `de`-notation for `\lcm`.

3.4.2 Simple Inheritance and Namespaces

`\importmodule`
`\usemodule`

`\importmodule`[Some/Archive]{path?ModuleName} is only allowed within an `smodule`-environment and makes the symbols declared in `ModuleName` available therein. Additionally the symbols of `ModuleName` will be exported if the current module is imported somewhere else via `\importmodule`.

`\usemodule` behaves the same way, but without exporting the content of the used module.

It is worth going into some detail how exactly `\importmodule` and `\usemodule` resolve their arguments to find the desired module – which is closely related to the *namespace* generated for a module, that is used to generate its URI.



Ideally, \LaTeX would use arbitrary URIs for modules, with no forced relationships between the *logical* namespace of a module and the *physical* location of the file declaring the module – like MMT does things.

Unfortunately, \TeX only provides very restricted access to the file system, so we are forced to generate namespaces systematically in such a way that they reflect the physical location of the associated files, so that \LaTeX can resolve them accordingly. Largely, users need not concern themselves with namespaces at all, but for completeness sake, we describe how they are constructed:

- If `\begin{smodule}{Foo}` occurs in a file `/path/to/file/Foo[.<lang>].tex` which does not belong to an archive, the namespace is `file://path/to/file`.
- If the same statement occurs in a file `/path/to/file/bar[.<lang>].tex`, the namespace is `file://path/to/file/bar`.

In other words: outside of archives, the namespace corresponds to the file URI with the filename dropped iff it is equal to the module name, and ignoring the (optional) language suffix.



If the current file is in an archive, the procedure is the same except that the initial segment of the file path up to the archive's `source`-folder is replaced by the archive's namespace URI.



Conversely, here is how namespaces/URIs and file paths are computed in import statements, exemplary `\importmodule`:

- `\importmodule{Foo}` outside of an archive refers to module `Foo` in the current namespace. Consequently, `Foo` must have been declared earlier in the same document or, if not, in a file `Foo[.<lang>].tex` in the same directory.
- The same statement *within* an archive refers to either the module `Foo` declared earlier in the same document, or otherwise to the module `Foo` in the archive's top-level namespace. In the latter case, it has to be declared in a file `Foo[.<lang>].tex` directly in the archive's `source`-folder.
- Similarly, in `\importmodule{some/path?Foo}` the path `some/path` refers to either the sub-directory and relative namespace path of the current directory and namespace outside of an archive, or relative to the current archive's top-level namespace and `source`-folder, respectively.

The module `Foo` must either be declared in the file `<top-directory>/some/path/Foo[.<lang>].tex`, or in `<top-directory>/some/path[.<lang>].tex` (which are checked in that order).

- Similarly, `\importmodule[Some/Archive]{some/path?Foo}` is resolved like the previous cases, but relative to the archive `Some/Archive` in the mathhub-directory.
- Finally, `\importmodule{full://uri?Foo}` naturally refers to the module `Foo` in the namespace `full://uri`. Since the file this module is declared in can not be determined directly from the URI, the module must be in memory already, e.g. by being referenced earlier in the same document.

Since this is less compatible with a modular development, using full URIs directly is strongly discouraged, unless the module is declared in the current file directly.

`\STEXexport`

`\importmodule` and `\usemodule` import all symbols, notations, semantic macros and (recursively) `\importmodules`. If you want to additionally export e.g. convenience macros and other (S_TE_X) code from a module, you can use the command `\STEXexport{<code>}` in your module. Then `<code>` is executed (both immediately and) every time the current module is opened via `\importmodule` or `\usemodule`.



Note, that `\newcommand` defines macros *globally* and throws an error if the macro already exists, potentially leading to low-level L^AT_EX errors if we put a `\newcommand` in an `\STEXexport` and the `<code>` is executed more than once in a document – which can happen easily.

A safer alternative is to use macro definition principles, that are safe to use even if the macro being defined already exists, and ideally are local to the current T_EX



group, such as `\def` or `\let`.

3.4.3 The `mathstructure` Environment

A common occurrence in mathematics is bundling several interrelated “declarations” together into *structures*. For example:

- A *monoid* is a structure $\langle M, \circ, e \rangle$ with $\circ : M \times M \rightarrow M$ and $e \in M$ such that...
- A *topological space* is a structure $\langle X, \mathcal{T} \rangle$ where X is a set and \mathcal{T} is a topology on X
- A *partial order* is a structure $\langle S, \leq \rangle$ where \leq is a binary relation on S such that...

This phenomenon is important and common enough to warrant special support, in particular because it requires being able to *instantiate* such structures (or, rather, structure *signatures*) in order to talk about (concrete or variable) *particular* monoids, topological spaces, partial orders etc.

`mathstructure` The `mathstructure` environment allows us to do exactly that. It behaves exactly like the `smodule` environment, but is itself only allowed inside an `smodule` environment, and allows for instantiation later on.

How this works is again best demonstrated by example:

Example 24

Input:

```
1 \begin{mathstructure}{monoid}
2   \symdef{universe}[type=\set]{\comp{U}}
3   \symdef{op}[
4     args=2,
5     type=\funtype{\universe,\universe}{\universe},
6     op=\circ
7   ]{\#1 \comp{\circ} \#2}
8   \symdef{unit}[type=\universe]{\comp{e}}
9 \end{mathstructure}
10
11 A \symname{monoid} is...
```

Output:

A `monoid` is...

Note that the `\symname{monoid}` is appropriately highlighted and (depending on your pdf viewer) shows a URI on hovering – implying that the `mathstructure` environment has generated a *symbol* `monoid` for us. It has not generated a semantic macro though, since we can not use the `monoid`-symbol *directly*. Instead, we can instantiate it, for example for integers:

Example 25

Input:

```

1 \symdef{Int}[type=\set]{\comp{\mathbb Z}}
2 \symdef{addition}[
3   type=\funtype{\Int,\Int}{\Int},
4   args=2,
5   op=+
6 ]{##1 \comp{+} ##2}
7 \symdef{zero}[type=\Int]{\comp{0}}
8
9 $\mathstruct{\Int,\addition!,\zero}$ is a \symname{monoid}.

```

Output:

$\langle \mathbb{Z}, +, 0 \rangle$ is a monoid.

So far, we have not actually instantiated monoid, but now that we have all the symbols to do so, we can:

Example 26

Input:

```

1 \instantiate{intmonoid}{monoid}{\mathbb{Z}_{+,0}}[
2   universe = Int ,
3   op = addition ,
4   unit = zero
5 ]
6
7 $\intmonoid{universe}$, $\intmonoid{unit}$ and $\intmonoid{op}\{a\}\{b\}$.
8
9 Also: $\intmonoid!$

```

Output:

\mathbb{Z} , 0 and $a+b$.
Also: $\mathbb{Z}_{+,0}$

\instantiate

So summarizing: `\instantiate` takes four arguments: The (macro-)name of the instance, a key-value pair assigning declarations in the corresponding `mathstructure` to symbols currently in scope, the name of the `mathstructure` to instantiate, and lastly a notation for the instance itself.

It then generates a semantic macro that takes as argument the name of a declaration in the instantiated `mathstructure` and resolves it to the corresponding instance of that particular declaration.

`\instantiate` and `mathstructure` make use of the *Theories-as-Types* paradigm \hookrightarrow (see [MRK18]):
 \hookrightarrow `mathstructure{<name>}` simply creates a nested theory with name `<name>-structure`. The *constant* `<name>` is defined as `Mod(<name>-structure)` – a *dependent record type with manifest fields*, the fields of which are generated

$\hookrightarrow M$ from (and correspond to) the constants in `<name>-structure`.
 $\hookrightarrow M$ `\instantiate` generates a constant whose definiens is a record term of type `Mod(<name>-structure)`, with the fields assigned based on the respective key-value-list.
 $\rightsquigarrow T$

Notably, `\instantiate` throws an error if not *every* declaration in the instantiated `mathstructure` is being assigned.

You might consequently ask what the usefulness of `mathstructure` even is.

`\varinstantiate`

The answer is that we can also instantiate a `mathstructure` with a *variable*. The syntax of `\varinstantiate` is equivalent to that of `\instantiate`, but all of the key-value-pairs are optional, and if not explicitly assigned (to a symbol *or* a variable declared with `\vardef`) inherit their notation from the one in the `mathstructure` environment.

This allows us to do things like:

Example 27

Input:

```

1 \varinstantiate{varM}{monoid}{M}
2
3 A \symname{monoid} is a structure
4 $\varM! := \mathstruct{\varM{universe}, \varM{op}!, \varM{unit}}$
5 such that
6 $\varM{op}!: \funtype{\varM{universe}, \varM{universe}}{\varM{universe}}$ ...

```

Output:

A `monoid` is a structure $M := \langle U, \circ, e \rangle$ such that $\circ : U \times U \rightarrow U$...

.

and

Example 28

Input:

```

1 \varinstantiate{varMb}{monoid}{M_2}[universe = Int]
2
3 Let $\varMb! := \mathstruct{\varMb{universe}, \varMb{op}!, \varMb{unit}}$
4 be a \symname{monoid} on $\Int$ ...

```

Output:

Let $M_2 := \langle \mathbb{Z}, \circ, e \rangle$ be a `monoid` on \mathbb{Z} ...

.

We will return to these two example later, when we also know how to handle the *axioms* of a monoid.

3.4.4 The copymodule Environment

TODO: explain

Given modules:

Example 29

Input:

```

1 \begin{smodule}{magma}
2   \symdef{universe}{\comp{\mathcal U}}
3   \symdef{operation}[args=2,op=\circ]{#1 \comp\circ #2}
4 \end{smodule}
5 \begin{smodule}{monoid}
6   \importmodule{magma}
7   \symdef{unit}{\comp e}
8 \end{smodule}
9 \begin{smodule}{group}
10  \importmodule{monoid}
11  \symdef{inverse}[args=1]{#1~{\comp{-1}}}
12 \end{smodule}

```

Output:

.

We can form a module for *rings* by “cloning” an instance of *group* (for addition) and *monoid* (for multiplication), respectively, and “glueing them together” to ensure they share the same universe:

Example 30

Input:

```

1 \begin{smodule}{ring}
2   \begin{copymodule}{group}{addition}
3     \renamedecl[name=universe]{universe}{runiverse}
4     \renamedecl[name=plus]{operation}{rplus}
5     \renamedecl[name=zero]{unit}{rzero}
6     \renamedecl[name=uminus]{inverse}{ruminus}
7   \end{copymodule}
8   \notation*{rplus}[plus,op=+,prec=60]{#1 \comp+ #2}
9   \notation*{rzero}[zero]{\comp0}
10  \notation*{ruminus}[uminus,op=-]{\comp- #1}
11  \begin{copymodule}{monoid}{multiplication}
12    \assign{universe}{\runiverse}
13    \renamedecl[name=times]{operation}{rtimes}
14    \renamedecl[name=one]{unit}{rone}
15  \end{copymodule}
16  \notation*{rtimes}[cdot,op=\cdot,prec=50]{#1 \comp\cdot #2}
17  \notation*{rone}[one]{\comp1}
18  Test: $\rtimes a\{rplus c\{rtimes d\}}$
19 \end{smodule}

```

Output:

Test: $a \cdot (c + d \cdot e)$

TODO: explain donotclone

3.4.5 The `interpretmodule` Environment

TODO: explain

Example 31

Input:

```
1 \begin{smodule}{int}
2   \syndef{Integers}{\comp{\mathbb Z}}
3   \syndef{plus}[args=2,op=+]{#1 \comp+ #2}
4   \syndef{zero}{\comp0}
5   \syndef{uminus}[args=1,op=-]{\comp-#1}
6
7   \begin{interpretmodule}{group}{intisgroup}
8     \assign{universe}{\Integers}
9     \assign{operation}{\plus!}
10    \assign{unit}{\zero}
11    \assign{inverse}{\uminus!}
12  \end{interpretmodule}
13 \end{smodule}
```

Output:

3.5 Primitive Symbols (The STEX Metatheory)

The `stex-metatheory` package contains STEX symbols so ubiquitous, that it is virtually impossible to describe any flexiformal content without them, or that are required to annotate even the most primitive symbols with meaningful (foundation-independent) “type”-annotations, or required for basic structuring principles (theorems, definitions). As such, it serves as the default meta theory for any STEX module.

We can also see the `stex-metatheory` as a foundation of mathematics in the sense of [Rab15], albeit an informal one (the ones discussed there are all formal foundations). The state of the `stex-metatheory` is necessarily incomplete, and will stay so for a long while: It arises as a collection of empirically useful symbols that are collected as more and more mathematics are encoded in STEX and are classified as foundational.

Formal foundations should ideally instantiate these symbols with their formal counterparts, e.g. `isa` corresponds to a typing operation in typed setting, or the \in -operator in set-theoretic contexts; `bind` corresponds to a universal quantifier in (n th-order) logic, or a Π in dependent type theories.

We make this theory part of the STEX collection rather than encoding it in STEX itself⁴

⁴EdNOTE: MK: why? continue

Chapter 4

Using \TeX Symbols

Given a symbol declaration `\symdecl{symbolname}`, we obtain a semantic macro `\symbolname`. We can use this semantic macro in math mode to use its notation(s), and we can use `\symbolname!` in math mode to use its operator notation(s). What else can we do?

4.1 `\symref` and its variants

`\symref`
`\symname`

We have already seen `\symname` and `\symref`, the latter being the more general.

`\symref{<symbolname>}{<code>}` marks-up `<code>` as referencing `<symbolname>`. Since quite often, the `<code>` should be (a variant of) the name of the symbol anyway, we also have `\symname{<symbolname>}`.

Note that `\symname` uses the *name* of a symbol, not its macroname. More precisely, `\symname` will insert the name of the symbol with “-” replaced by spaces. If a symbol does not have an explicit `name=` given, the two are equal – but for `\symname` it often makes sense to make the two explicitly distinct. For example:

Example 32

Input:

```
1 \symdef{Nat}[
2   name=natural-number,
3   type=\set
4 ]{\comp{\mathbb{N}}}
5
6 A \symname{Nat} is...
```

Output:

A natural number is...

`\symname` takes two additional optional arguments, `pre=` and `post=` that get prepended or appended respectively to the symbol name.

`\Symname`

Additionally, `\Symname` behaves exactly like `\symname`, but will capitalize the first letter of the name:

Example 33

Input:

```
1 \Symname[post=s]{Nat} are...
```

Output:

```
Natural numbers are...
```



This is as good a place as any other to explain how \TeX resolves a string `symbolname` to an actual symbol.

If `\symbolname` is a semantic macro, then \TeX has no trouble resolving `symbolname` to the full URI of the symbol that is being invoked.

However, especially in `\symname` (or if a symbol was introduced using `\symdecl*` without generating a semantic macro), we might prefer to use the *name* of a symbol directly for readability – e.g. we would want to write `A \symname{natural-number} is...` rather than `A \symname{Nat} is...`. \TeX attempts to handle this case thusly:

If `string` does *not* correspond to a semantic macro `\string` and does *not* contain a `?`, then \TeX checks all symbols currently in scope until it finds one, whose name is `string`. If `string` is of the form `pre?name`, \TeX first looks through all modules currently in scope, whose full URI ends with `pre`, and then looks for a symbol with name `name` in those. This allows for disambiguating more precisely, e.g. by saying `\symname{Integers?addition}` or `\symname{RealNumbers?addition}` in the case where several `additions` are in scope.

4.2 Marking Up Text and On-the-Fly Notations

We can also use semantic macros outside of text mode though, which allows us to annotate arbitrary text fragments.

Let us assume again, that we have `\symdef{addition}[args=2]{#1 \comp+ #2}`. Then we can do

Example 34

Input:

```
1 \addition{\comp{The sum of} \arg{\$svar{n}} \$} \comp{ and } \arg{\$svar{m}} \$}  
2 is...
```

Output:

```
The sum of  $n$  and  $m$  is...
```


...which marks up the text fragment as representing an *application* of the `addition`-symbol to two argument n and m .

\hookrightarrow M \rightarrow As expected, the above example is translated to OMDoc/MMT as an
 \rightarrow M \rightarrow OMA with `<OMS name="...?addition"/>` as head and `<OMV name="n"/>` and
 \rightarrow T \rightarrow `<OMV name="m"/>` as arguments.



Note the difference in treating “arguments” between math mode and text mode. In math mode the (in this case two) tokens/groups following the `\addition` macro are treated as arguments to the addition function, whereas in text mode the group following `\addition` is taken to be the ad-hoc presentation. We drill in on this now.

\arg

In text mode, every semantic macro takes exactly one argument, namely the text-fragment to be annotated. The `\arg` command is only valid within the argument to a semantic macro and marks up the *individual arguments* for the symbol.

We can also use semantic macros in text mode to invoke an operator itself instead of its application, with the usual syntax using `!`:

Example 35

Input:

```
1 \addition!{Addition} is...
```

Output:

```
Addition is...
```

Indeed, `\symbolname!{<code>}` is exactly equivalent to `\symref{symbolname}{<code>}` (the latter is in fact implemented in terms of the former).

`\arg` also allows us to switch the order of arguments around and “hide” arguments: For example, `\arg[3]{<code>}` signifies that `<code>` represents the *third* argument to the current operator, and `\arg*[i]{<code>}` signifies that `<code>` represents the *i*th argument, but it should not produce any output (it is exported in the `xhtml` however, so that MMT and other systems can pick up on it).⁵

Example 36

Input:

```
1 \addition{\comp{adding}
2   \arg[2]{\svar{k}$}
3   \arg*{\svar{n}}{\svar{m}}}} yields...
```

Output:

⁵EdNOTE: MK: I do not understand why we have to/want to give the second `arg*`; I think this must be elaborated on.

adding k yields...

Note that since the second `\arg` has no explicit argument number, it automatically represents the first not-yet-given argument – i.e. in this case the first one.⁶

The same syntax can be used in math mod as well. This allows us to spontaneously introduce new notations on the fly. We can activate it using the starred variants of semantic macros:

Example 37

Input:

```
1 Given $\addition{\svar{n}}{\svar{m}}$, then
2 $\addition*{
3   \arg*{\addition{\svar{n}}{\svar{m}}}
4   \comp{+}
5   \arg{\svar{k}}
6 }$ yields...
```

Output:

Given $n+m$, then $+k$ yields...

4.3 Referencing Symbols and Statements

TODO: references documentation

⁶EdNOTE: MK: I do not understand this at all.

Chapter 5

sTeX Statements

5.1 Definitions, Theorems, Examples, Paragraphs

As mentioned earlier, we can semantically mark-up *statements* such as definitions, theorems, lemmata, examples, etc.

The corresponding environments for that are:

- `sdefinition` for definitions,
- `sassertion` for assertions, i.e. propositions that are declared to be *true*, such as theorems, lemmata, axioms,
- `sexample` for examples and counterexamples, and
- `sparagraph` for “other” semantic paragraphs, such as comments, remarks, conjectures, etc.

The *presentation* of these environments can be customized to use e.g. predefined theorem-environments, see [chapter 6](#) for details.

All of these environments take optional arguments in the form of `key=value`-pairs. Common to all of them are the keys `id=` (for cross-referencing, see [section 4.3](#)), `type=` for customization (see [chapter 6](#)) and additional information (e.g. definition principles, “difficulty” etc), as well as `title=` (for giving the paragraph a title), and finally `for=`.

The `for=` key expects a comma-separated list of existing symbols, allowing for e.g. things like

Example 38

Input:

```
1 \begin{sexample}[
2   id=additionandmultiplication.ex,
3   for={addition,multiplication},
4   type={trivial,boring},
5   title={An Example}
6 ]
7   $\addition{2,3}$ is $5$, $\multiplication{2,3}$ is $6$.
8 \end{sexample}
```

Output:

Example 5.1.1 (An Example). $2+3$ is 5, $2\cdot 3$ is 6.

`\definiendum`
`\definame`
`\Definame`

`sdefinition` (and `sparagraph` with `type=symdoc`) introduce three new macros: `definiendum` behaves like `symref` (and `definame/Definame` like `symname/Symname`, respectively), but highlights the referenced symbol as *being defined* in the current definition.

$\hookrightarrow M \rightarrow$ The special `type=symdoc` for `sparagraph` is intended to be used for “informal definitions”, or encyclopedia-style descriptions for symbols.
 $\dashrightarrow M \dashrightarrow$ The MMT system can use those (in lieu of an actual `sdefinition` in scope) to present to users, e.g. when hovering over symbols.
 $\rightsquigarrow T \rightsquigarrow$

`\definiens`

Additionally, `sdefinition` (and `sparagraph` with `type=symdoc`) introduces `\definiens`[<optional sym which marks up <code> as being the explicit *definiens* of <optional symbolname> (in case `for=` has multiple symbols).

All four statement environments – i.e. `sdefinition`, `sassertion`, `sexample`, and `sparagraph` – also take an optional parameter `name=` – if this one is given a value, the environment will generate a *symbol* by that name (but with no semantic macro). Not only does this allow for `\symref` et al, it allows us to resume our earlier example for monoids much more nicely:⁷

Example 39

Input:

⁷EdNOTE: MK: we should reference the example explicitly here.

```

1 \begin{mathstructure}{monoid}
2   \symdef{universe}[type=\set]{\comp{U}}
3   \symdef{op}[
4     args=2,
5     type=\funtype{\universe,\universe}{\universe},
6     op=\circ
7   ]{#1 \comp{\circ} #2}
8   \symdef{unit}[type=\universe]{\comp{e}}
9
10  \begin{sparagraph}[type=symdoc,for=monoid]
11    A \definame{monoid} is a structure
12    $\mathstruct{\universe,\op!,\unit}$
13    where $\op!:\funtype{\universe}{\universe}$ and
14    $\inset{\unit}{\universe}$ such that
15
16    \begin{sassertion}[name=associative,
17      type=axiom,
18      title=Associativity]
19      $\op!$ is associative
20    \end{sassertion}
21    \begin{sassertion}[name=isunit,
22      type=axiom,
23      title=Unit]
24      $\equal{\op{\svar{x}}{\unit}}{\svar{x}}$
25      for all $\inset{\svar{x}}{\universe}$
26    \end{sassertion}
27  \end{sparagraph}
28 \end{mathstructure}
29
30 An example for a \symname{monoid} is...

```

Output:

A **monoid** is a structure $\langle U, \circ, e \rangle$ where $\circ : U \rightarrow U$ and $e \in U$ such that

Axiom 5.1.2 (Associativity). \circ is associative

Axiom 5.1.3 (Unit). $x \circ e = x$ for all $x \in U$

An example for a **monoid** is...

The main difference to before⁸ is that the two **sassertions** now have **name=** attributes. Thus the **mathstructure monoid** now contains two additional symbols, namely the axioms for associativity and that e is a unit. Note that both symbols do not represent the mere *propositions* that e.g. \circ is associative, but *the assertion that it is actually true* that \circ is associative.

If we now want to instantiate **monoid** (unless with a variable, of course), we also need to assign **associative** and **neutral** to analogous assertions. So the earlier example

```

1 \instantiate{intmonoid}{monoid}{\mathbb{Z}_{+,0}}[
2   universe = Int ,
3   op = addition ,
4   unit = zero
5 ]

```

⁸EDNOTE: MK: reference

...will not work anymore. We now need to give assertions that addition is associative and that zero is a unit with respect to addition.²

5.2 Proofs

5.2.1 Introduction & Running Example

The `stex-proof` package supplies macros and environment that allow to annotate the structure of mathematical proofs in \LaTeX document. This structure can be used by MKM systems for added-value services, either directly from the \LaTeX sources, or after translation.

We will go over the general intuition by way of a running example:

```

1 \begin{sproof}[id=simple-proof]
2   {We prove that  $\sum_{i=1}^n 2i-1 = n^2$  by induction over  $n$ }
3   \begin{spfcases}{For the induction we have to consider the following cases:}
4     \begin{spfcase}{$n=1$}
5       \begin{spfstep}[type=inline] then we compute  $1=1^2$  \end{spfstep}
6     \end{spfcase}
7     \begin{spfcase}{$n=2$}
8       \begin{spfcomment}[type=inline]
9         This case is not really necessary, but we do it for the
10        fun of it (and to get more intuition).
11      \end{spfcomment}
12      \begin{spfstep}[type=inline] We compute  $1+3=2^2=4$ . \end{spfstep}
13    \end{spfcase}
14    \begin{spfcase}{$n>1$}
15      \begin{spfstep}[type=assumption,id=ind-hyp]
16        Now, we assume that the assertion is true for a certain  $k \geq 1$ ,
17        i.e.  $\sum_{i=1}^k (2i-1) = k^2$ .
18      \end{spfstep}
19      \begin{spfcomment}
20        We have to show that we can derive the assertion for  $n=k+1$  from
21        this assumption, i.e.  $\sum_{i=1}^{k+1} (2i-1) = (k+1)^2$ .
22      \end{spfcomment}
23      \begin{spfstep}
24        We obtain  $\sum_{i=1}^{k+1} (2i-1) = \sum_{i=1}^k (2i-1) + 2(k+1) - 1$ 
25        \spfjust[method=arith:split-sum]{by splitting the sum}.
26      \end{spfstep}
27      \begin{spfstep}
28        Thus we have  $\sum_{i=1}^{k+1} (2i-1) = k^2 + 2k + 1$ 
29        \spfjust[method=fertilize]{by inductive hypothesis}.
30      \end{spfstep}
31      \begin{spfstep}[type=conclusion]
32        We can \spfjust[method=simplify]{simplify} the right-hand side to  $(k+1)^2$ , w
33        proves the assertion.
34      \end{spfstep}
35    \end{spfcase}
36    \begin{spfstep}[type=conclusion]
37      We have considered all the cases, so we have proven the assertion.
38    \end{spfstep}
39  \end{spfcases}
40 \end{sproof}

```

²Of course, \LaTeX can not check that the assertions are the “correct” ones – but if the assertions (both in monoid as well as those for addition and zero) are properly marked up, MMT can. **TODO: should**

This yields the following result:

Proof: We prove that $\sum_{i=1}^n 2i - 1 = n^2$ by induction over n

1. For the induction we have to consider the following cases:

1.1. $n = 1$: then we compute $1 = 1^2$ □

1.2. $n = 2$: This case is not really necessary, but we do it for the fun of it (and to get more intuition). We compute $1 + 3 = 2^2 = 4$ □

1.3. $n > 1$:

1.3.1. Now, we assume that the assertion is true for a certain $k \geq 1$, i.e. $\sum_{i=1}^k (2i - 1) = k^2$.

1.3.2. We have to show that we can derive the assertion for $n = k + 1$ from this assumption, i.e. $\sum_{i=1}^{k+1} (2i - 1) = (k + 1)^2$.

1.3.3. We obtain $\sum_{i=1}^{k+1} (2i - 1) = \sum_{i=1}^k (2i - 1) + 2(k + 1) - 1$ by splitting the sum.

1.3.4. Thus we have $\sum_{i=1}^{k+1} (2i - 1) = k^2 + 2k + 1$ by inductive hypothesis.

1.3.5. We can simplify the right-hand side to $(k + 1)^2$, which proves the assertion. □

1.4. We have considered all the cases, so we have proven the assertion. □

5.2.2 Proofs and Proof steps

sproof The **sproof** environment is the main container for proofs. It takes an optional **KeyVal** argument that allows to specify the **id** (identifier) and **for** (for which assertion is this a proof) keys. The regular argument of the **proof** environment contains an introductory comment, that may be used to announce the proof style. The **proof** environment contains a sequence of **spstep**, **spfcomment**, and **spfcases** environments that are used to markup the proof steps.

\spfidea The **\spfidea** macro allows to give a one-paragraph description of the proof idea.

\spfsketch For one-line proof sketches, we use the **\spfsketch** macro, which takes the same optional argument as **sproof** and another one: a natural language text that sketches the proof.

spfststep Regular proof steps are marked up with the **step** environment, which takes an optional **KeyVal** argument for annotations. A proof step usually contains a local assertion (the text of the step) together with some kind of evidence that this can be derived from already established assertions.

5.2.3 Justifications

justification This evidence is marked up with the `\spfjust` macro in the `stex-proofs` package. This environment totally invisible to the formatted result; it wraps the text in the proof step that corresponds to the evidence. The environment takes an optional `KeyVal` argument, which can have the `method` key, whose value is the name of a proof method (this will only need to mean something to the application that consumes the semantic annotations). Furthermore, the justification can contain “premises” (specifications to assertions that were used justify the step) and “arguments” (other information taken into account by the proof method).

\premise The `\premise` macro allows to mark up part of the text as reference to an assertion that is used in the argumentation. In the running example we have used the `\premise` macro to identify the inductive hypothesis.

\justarg The `\justarg` macro is very similar to `\premise` with the difference that it is used to mark up arguments to the proof method. Therefore the content of the first argument is interpreted as a mathematical object rather than as an identifier as in the case of `\premise`. In our example, we specified that the simplification should take place on the right hand side of the equation. Other examples include proof methods that instantiate. Here we would indicate the substituted object in a `\justarg` macro.

Note that both `\premise` and `\justarg` can be used with an empty second argument to mark up premises and arguments that are not explicitly mentioned in the text.

5.2.4 Proof Structure

subproof The `spfcases` environment is used to mark up a subproof. This environment takes an optional `KeyVal` argument for semantic annotations and a second argument that allows to specify an introductory comment (just like in the `proof` environment). The `method` key can be used to give the name of the proof method executed to make this subproof.

spfcases The `spfcases` environment is used to mark up a proof by cases. Technically it is a variant of the `subproof` where the `method` is `by-cases`. Its contents are `spfcase` environments that mark up the cases one by one.

spfcase The content of a `spfcases` environment are a sequence of case proofs marked up in the `pfcase` environment, which takes an optional `KeyVal` argument for semantic annotations. The second argument is used to specify the the description of the case under consideration. The content of a `spfcase` environment is the same as that of a `sproof`, i.e. `spfsteps`, `spfcomments`, and `spfcases` environments.

\spfcasesketch `\spfcasesketch` is a variant of the `spfcase` environment that takes the same arguments, but instead of the `spfsteps` in the body uses a third argument for a proof sketch.

spfcomment The `spfcomment` environment is much like a `step`, only that it does not have an object-level assertion of its own. Rather than asserting some fact that is relevant for the proof, it is used to explain where the proof is going, what we are attempting to to, or what we have achieved so far. As such, it cannot be the target of a `\premise`.

5.2.5 Proof End Markers

`\sproofend`

Traditionally, the end of a mathematical proof is marked with a little box at the end of the last line of the proof (if there is space and on the end of the next line if there isn't), like so:

The `stex-proofs` package provides the `\sproofend` macro for this.

`\sProofEndSymbol`

If a different symbol for the proof end is to be used (e.g. *q.e.d*), then this can be obtained by specifying it using the `\sProofEndSymbol` configuration macro (e.g. by specifying `\sProofEndSymbol{q.e.d}`).

Some of the proof structuring macros above will insert proof end symbols for sub-proofs, in most cases, this is desirable to make the proof structure explicit, but sometimes this wastes space (especially, if a proof ends in a case analysis which will supply its own proof end marker). To suppress it locally, just set `proofend={}` in them or use `\sProofEndSymbol{}`.

Chapter 6

Highlighting and Presentation Customizations

The environments starting with `s` (i.e. `smodule`, `sassertion`, `sexample`, `sdefinition`, `sparagraph` and `sproof`) by default produce no additional output whatsoever (except for the environment content of course). Instead, the document that uses them (whether directly or e.g. via `inputref`) can decide how these environments are supposed to look like.

The `stexthm` defines some default customizations that can be used, but of course many existing L^AT_EX templates come with their own `definition`, `theorem` and similar environments that authors are supposed (or even required) to use. Their concrete syntax however is usually not compatible with all the additional arguments that `gTEX` allows for semantic information.

Therefore we introduced the separate environments `sdefinition` etc. instead of using `definition` directly, and allow authors to specify how these environments should be styled via the commands `stexpatch*`.

```
\stexpatchmodule
\stexpatchdefinition
\stexpatchassertion
\stexpatchexample
\stexpatchparagraph
\stexpatchproof
```

All of these commands take one optional and two proper arguments, i.e.

```
\stexpatch*{<type>}{<begin-code>}{<end-code>}.
```

After `gTEX` reads and processes the optional arguments for these environments, (some of) their values are stored in the macros `\s*<field>` (i.e. `sexampleid`, `\sassertionname`, etc.). It then checks for all the values `<type>` in the `type=`-list, whether an `\stexpatch*{<type>}` for the current environment has been called. If it finds one, it uses that patches `<begin-code>` and `<end-code>` to mark up the current environment. If no patch for (any of) the type(s) is found, it checks whether and `\stexpatch*` was called without optional argument.

For example, if we want to use a predefined `theorem` environment for `sassertions` with `type=theorem`, we can do

```
1 \stexpatchassertion[theorem]{\begin{theorem}}{\end{theorem}}
```

...or, rather, since e.g. `theorem`-environments defined using `amsthm` take an optional title as argument, we can do:

```
1 \stexpatchassertion[theorem]
2   {\ifx\sassertiontitle\@empty
3     \begin{theorem}
```

```

4 \else
5   \begin{theorem}[\sassertiontitle]
6   \fi}
7 {\end{theorem}}

```

Or, if we want all `sdefinitions` to use a predefined `definition`-environment, we can do

```

1 \stexpatchdefinition
2 {\ifx\sdefinitiontitle\@empty
3   \begin{definition}
4   \else
5     \begin{definition}[\sdefinitiontitle]
6   \fi}
7 {\end{definition}}

```

`\compemph`
`\varemp`
`\symrefemph`
`\defemph`

Apart from the environments, we can control how \TeX highlights variables, notation components, `\symrefs` and `\definiendums`, respectively.

To do so, we simply redefine these four macros. For example, to highlight notation components (i.e. everything in a `\comp`) in blue, as in this document, we can do `\def\compemph#1{\textcolor{blue}{#1}}`. By default, `\compemph` et al do nothing.

`\compemph@uri`
`\varemp@uri`
`\symrefemph@uri`
`\defemph@uri`

For each of the four macros, there exists an additional macro that takes the full URI of the relevant symbol currently being highlighted as a second argument. That allows us to e.g. use pdf tooltips and links. For example, this document uses

```

1 \protected\def\symrefemph@uri#1#2{
2   \pdftooltip{
3     \srefsymuri{#2}{\symrefemph{#1}}
4   }{
5     URI:~\detokenize{#2}
6   }
7 }

```

By default, `\compemph@uri` is simply defined as `\compemph{#1}` (analogously for the other three commands).

Chapter 7

Additional Packages

7.1 Package Options

image

The behavior of the `tikzinput` package is determined by whether the `image` option is given. If it is not, then the `tikz` package is loaded, all other options are passed on to it and `\tikzinput{<file>}` inputs the TIKZ file `<file>.tex`; if not, only the `graphicx` package is loaded and `\tikzinput{<file>}` loads an image file `<file>.<ext>` generated from `<file>.tex`.

7.2 Inputting Standalone TIKZ Pictures

The selective input functionality of the `tikzinput` package assumes that the TIKZ pictures are externalized into a standalone picture file, such as the following one

```
1 \documentclass{standalone}
2 \usepackage{tikz}
3 \usetikzpackage{...}
4 \begin{document}
5   \begin{tikzpicture}
6     ...
7   \end{tikzpicture}
8 \end{document}
```

The `standalone` class is a minimal \LaTeX class that when loaded in a document that uses the `standalone` package: the preamble and the `document` environment are disregarded during loading, so they do not pose any problems. In effect, an `\input` of the file above only sees the `tikzpicture` environment, but the file itself is standalone in the sense that we can run \LaTeX over it separately, e.g. for generating an image file from it.

`\tikzinput`
`\ctikzinput`

This is exactly where the `tikzinput` package comes in: it supplies the `\tikzinput` macro, which – depending on the `image` option – either directly inputs the TIKZ picture (source) or tries to load an image file generated from it.

Concretely, if the `image` option is not set for the `tikzinput` package, then `\tikzinput[⟨opt⟩]{⟨file⟩}` disregards the optional argument `⟨opt⟩` and inputs `⟨file⟩.tex` via `\input` and resizes it to as specified in the `width` and `height` keys. If it is, `\tikzinput[⟨opt⟩]{⟨file⟩}` expands to `\includegraphics[⟨opt⟩]{⟨file⟩}`.

`\ctikzinput` is a version of `\tikzinput` that is centered.

`\mhtikzinput`
`\cmhtikzinput`

`\mhtikzinput` is a variant of `\tikzinput` that treats its file path argument as a relative path in a math archive in analogy to `\inputref`. To give the archive path, we use the `mhrepos=` key.

Again, `\cmhtikzinput` is a version of `\mhtikzinput` that is centered.

`\libusetikzlibrary`

Sometimes, we want to supply archive-specific TIKZ libraries in the `lib` folder of the archive or the `meta-inf/lib` of the archive group. Then we need an analogon to `\libinput` for `\usetikzlibrary`. The `stex-tikzinput` package provides the `libusetikzlibrary` for this purpose.

7.3 Limitations

1. We only listen to the `width` and `height` keys in the `tikz` case, the others are disregarded.

7.4 Modular Document Structuring

This package supplies an infrastructure for writing OMDoc documents in \LaTeX . This includes a simple structure sharing mechanism for \LaTeX that allows to move from a copy-and-paste document development model to a copy-and-reference model, which conserves space and simplifies document management. The augmented structure can be used by MKM systems for added-value services, either directly from the \LaTeX sources, or after translation.

7.4.1 Introduction

The `document-structure` package supplies macros and environments that allow to label document fragments and to reference them later in the same document or in other documents. In essence, this enhances the document-as-trees model to documents-as-directed-acyclic-graphs (DAG) model. This structure can be used by MKM systems for added-value services, either directly from the \LaTeX sources, or after translation. Currently, trans-document referencing provided by this package can only be used in the \LaTeX collection.

DAG models of documents allow to replace the “Copy and Paste” in the source document with a label-and-reference model where document are shared in the document source and the formatter does the copying during document formatting/presentation.

7.4.2 The User Interface

The document-structure package accepts the following options:

<code>class=<name></code>	load <code><name>.cls</code> instead of <code>article.cls</code>
<code>topsect=<sect></code>	The top-level sectioning level; the default for <code><sect></code> is <code>section</code>

Document Structure

sfragment The structure of the document is given by the **sfragment** environment just like in OM-DOC. In the L^AT_EX route, the **sfragment** environment is flexibly mapped to sectioning commands, inducing the proper sectioning level from the nesting of **sfragment** environments. Correspondingly, the **sfragment** environment takes an optional key/value argument for metadata followed by a regular argument for the (section) title of the sfragment. The optional metadata argument has the keys **id** for an identifier, **creators** and **contributors** for the Dublin Core metadata [DCM03]. The option **short** allows to give a short title for the generated section. If the title contains semantic macros, they need to be protected by `\protect`⁹, and we need to give the **loadmodules** key it needs no value. For instance we would have

```

1 \begin{smodule}{foo}
2   \symdef{bar}{B^a_r}
3   ...
4   \begin{sfragment}[id=sec.barderiv,loadmodules]
5     {Introducing $\protect\bar$ Derivations}

```

L^AT_EX automatically computes the sectioning level, from the nesting of **sfragment** environments.

But sometimes, we want to skip levels (e.g. to use a subsection* as an introduction for a chapter).

blindfragment Therefore the **document-structure** package provides a variant **blindfragment** that does not produce markup, but increments the sectioning level and logically groups document parts that belong together, but where traditional document markup relies on convention rather than explicit markup. The **blindfragment** environment is useful e.g. for creating frontmatter at the correct level. The example below shows a typical setup for the outer document structure of a book with parts and chapters.

```

1 \begin{document}
2 \begin{blindfragment}
3 \begin{blindfragment}
4 \begin{frontmatter}
5 \maketitle\newpage
6 \begin{sfragment}{Preface}
7 ... <<preface>> ...
8 \end{sfragment}
9 \clearpage\setcounter{tocdepth}{4}\tableofcontents\clearpage
10 \end{frontmatter}
11 \end{blindfragment}
12 ... <<introductory remarks>> ...
13 \end{blindfragment}
14 \begin{sfragment}{Introduction}
15 ... <<intro>> ...

```

⁹EdNOTE: MK: still?

```

16 \end{sfragment}
17 ... <<more chapters>> ...
18 \bibliographystyle{alpha}\bibliography{kwarc}
19 \end{document}

```

Here we use two levels of `blindfragment`:

- The outer one groups the introductory parts of the book (which we assume to have a sectioning hierarchy topping at the part level). This `blindfragment` makes sure that the introductory remarks become a “chapter” instead of a “part”.
- The inner one groups the frontmatter³ and makes the preface of the book a section-level construct.¹⁰

`\skipfragment`

The `\skipfragment` “skips an `sfragment`”, i.e. it just steps the respective sectioning counter. This macro is useful, when we want to keep two documents in sync structurally, so that section numbers match up: Any section that is left out in one becomes a `\skipfragment`.

`\currentsectionlevel`
`\CurrentSectionLevel`

The `\currentsectionlevel` macro supplies the name of the current sectioning level, e.g. “chapter”, or “subsection”. `\CurrentSectionLevel` is the capitalized variant. They are useful to write something like “In this `\currentsectionlevel`, we will...” in an `sfragment` environment, where we do not know which sectioning level we will end up.

Ignoring Inputs

`\prematurestop`
`\afterprematurestop`

For prematurely stopping the formatting of a document, \TeX provides the `\prematurestop` macro. It can be used everywhere in a document and ignores all input after that – backing out of the `sfragment` environment as needed. After that – and before the implicit `\end{document}` it calls the internal `\afterprematurestop`, which can be customized to do additional cleanup or e.g. print the bibliography.

`\prematurestop` is useful when one has a driver file, e.g. for a course taught multiple years and wants to generate course notes up to the current point in the lecture. Instead of commenting out the remaining parts, one can just move the `\prematurestop` macro. This is especially useful, if we need the rest of the file for processing, e.g. to generate a theory graph of the whole course with the already-covered parts marked up as an overview over the progress; see `import_graph.py` from the `lmhtools` utilities [LMH].

Global Variables

Text fragments and modules can be made more re-usable by the use of global variables. For instance, the admin section of a course can be made course-independent (and therefore re-usable) by using variables (actually token registers) `courseAcronym` and `courseTitle`

³We shied away from redefining the `frontmatter` to induce a `blindfragment`, but this may be the “right” way to go in the future.

¹⁰EdNOTE: MK: We need a substitute for the “Note that here the `display=flow` on the `sfragment` environment prevents numbering as is traditional for prefaces.”

instead of the text itself. The variables can then be set in the \LaTeX preamble of the course notes file.

$\backslash\text{setSGvar}$ $\backslash\text{useSGvar}$	$\backslash\text{setSGvar}\{\langle vname \rangle\}\{\langle text \rangle\}$ to set the global variable $\langle vname \rangle$ to $\langle text \rangle$ and $\backslash\text{useSGvar}\{\langle vname \rangle\}$ to reference it.
--	---

$\backslash\text{ifSGvar}$	With $\backslash\text{ifSGvar}$ we can test for the contents of a global variable: the macro call $\backslash\text{ifSGvar}\{\langle vname \rangle\}\{\langle val \rangle\}\{\langle ctext \rangle\}$ tests the content of the global variable $\langle vname \rangle$, only if (after expansion) it is equal to $\langle val \rangle$, the conditional text $\langle ctext \rangle$ is formatted.
----------------------------	--

7.5 Slides and Course Notes

We present a document class from which we can generate both course slides and course notes in a transparent way.

7.5.1 Introduction

The `notesslides` document class is derived from `beamer.cls` [Tana], it adds a “notes version” for course notes that is more suited to printing than the one supplied by `beamer.cls`.

7.5.2 The User Interface

The `notesslides` class takes the notion of a slide frame from Till Tantau’s excellent `beamer` class and adapts its notion of frames for use in the \LaTeX and OMDoc. To support semantic course notes, it extends the notion of mixing frames and explanatory text, but rather than treating the frames as images (or integrating their contents into the flowing text), the `notesslides` package displays the slides as such in the course notes to give students a visual anchor into the slide presentation in the course (and to distinguish the different writing styles in slides and course notes).

In practice we want to generate two documents from the same source: the slides for presentation in the lecture and the course notes as a narrative document for home study. To achieve this, the `notesslides` class has two modes: *slides mode* and *notes mode* which are determined by the package option.

Package Options

<code>slides</code>	<p>The <code>notesslides</code> class takes a variety of class options:</p> <ul style="list-style-type: none"> • The options <code>slides</code> and <code>notes</code> switch between slides mode and notes mode (see Section ??). • If the option <code>sectocframes</code> is given, then for the <code>sfragments</code>, special frames with the <code>sfragment</code> title (and number) are generated. • If the option <code>frameimages</code> is set, then slide mode also shows the <code>\frameimage</code>-generated frames (see section ??). If also the <code>fiboxed</code> option is given, the slides are surrounded by a box.
<code>notes</code>	
<code>sectocframes</code>	
<code>frameimages</code>	
<code>fiboxed</code>	

Notes and Slides

<code>frame,note</code>	<p>Slides are represented with <code>theframe</code> just like in the <code>beamer</code> class, see [Tanb] for details. The <code>notesslides</code> class adds the <code>rownote</code> environment for encapsulating the course note fragments.⁴</p>
-------------------------	--



Note that it is essential to start and end the `notes` environment at the start of the line – in particular, there may not be leading blanks – else L^AT_EX becomes confused and throws error messages that are difficult to decipher.

By interleaving the `frame` and `note` environments, we can build course notes as shown here:

```

1 \ifnotes\maketitle\else
2 \frame[noframenumbering]\maketitle\fi
3
4 \begin{note}
5   We start this course with ...
6 \end{note}
7
8 \begin{frame}
9   \frametitle{The first slide}
10  ...
11 \end{frame}
12 \begin{note}
13   ... and more explanatory text
14 \end{note}
15
16 \begin{frame}
17   \frametitle{The second slide}
18   ...
19 \end{frame}
20 ...

```

⁴MK: it would be very nice, if we did not need this environment, and this should be possible in principle, but not without intensive L^AT_EX trickery. Hints to the author are welcome.

`\ifnotes`

Note the use of the `\ifnotes` conditional, which allows different treatment between `notes` and `slides` mode – manually setting `\notesttrue` or `\notesfalse` is strongly discouraged however.



We need to give the title frame the `noframenumbers` option so that the frame numbering is kept in sync between the slides and the course notes.



The `beamer` class recommends not to use the `allowframebreaks` option on frames (even though it is very convenient). This holds even more in the `notesslides` case: At least in conjunction with `\newpage`, frame numbering behaves funnily (we have tried to fix this, but who knows).

`\inputref*`

If we want to transclude a the contents of a file as a note, we can use a new variant `\inputref*` of the `\inputref` macro: `\inputref*{foo}` is equivalent to `\begin{note}\inputref{foo}\end{note}`.

`n,nexample,nsproof,nassertion`

There are some environments that tend to occur at the top-level of `note` environments. We make convenience versions of these: e.g. the `nparagraph` environment is just an `sparagraph` inside a `note` environment (but looks nicer in the source, since it avoids one level of source indenting). Similarly, we have the `nfragment`, `ndefinition`, `nexample`, `nsproof`, and `nassertion` environments.

Header and Footer Lines of the Slides

`\setslidelogo`

The default logo provided by the `notesslides` package is the \TeX logo it can be customized using `\setslidelogo{<logo name>}`.

`\setsource`

The default footer line of the `notesslides` package mentions copyright and licensing. In the `beamer` class, `\source` stores the author's name as the copyright holder . By default it is *Michael Kohlhase* in the `notesslides` package since he is the main user and designer of this package. `\setsource{<name>}` can change the writer's name.

`\setlicensing`

For licensing, we use the Creative Commons Attribution-ShareAlike license by default to strengthen the public domain. If package `hyperref` is loaded, then we can attach a hyperlink to the license logo. `\setlicensing[<url>]{<logo name>}` is used for customization, where `<url>` is optional.

Frame Images

Sometimes, we want to integrate slides as images after all – e.g. because we already have a PowerPoint presentation, to which we want to add \LaTeX notes.

`\frameimage`
`\mhframeimage`

In this case we can use `\frameimage[⟨opt⟩]{⟨path⟩}`, where `⟨opt⟩` are the options of `\includegraphics` from the `graphicx` package [CR99] and `⟨path⟩` is the file path (extension can be left off like in `\includegraphics`). We have added the `label` key that allows to give a frame label that can be referenced like a regular `beamer` frame.

The `\mhframeimage` macro is a variant of `\frameimage` with repository support. Instead of writing

```
1 \frameimage{\MathHub{fooMH/bar/source/baz/foobar}}
```

we can simply write (assuming that `\MathHub` is defined as above)

```
1 \mhframeimage[fooMH/bar]{baz/foobar}
```


Note that the `\mhframeimage` form is more semantic, which allows more advanced document management features in `MathHub`.

If `baz/foobar` is the “current module”, i.e. if we are on the `MathHub` path `...MathHub/fooMH/bar...`, then stating the repository in the first optional argument is redundant, so we can just use

```
1 \mhframeimage{baz/foobar}
```

Colors and Highlighting

`\textwarning`

The `\textwarning` macro generates a warning sign: 

Excursions

In course notes, we sometimes want to point to an “excursion” – material that is either presupposed or tangential to the course at the moment – e.g. in an appendix. The typical setup is the following:

```
1 \excursion{founif}{../ex/founif}{We will cover first-order unification in}
2 ...
3 \begin{appendix}\printexcursions\end{appendix}
```

`\excursion`

The `\excursion{⟨ref⟩}{⟨path⟩}{⟨text⟩}` is syntactic sugar for

```
1 \begin{nparagraph}[title=Excursion]
2   \activateexcursion{founif}{../ex/founif}
3   We will cover first-order unification in \sref{founif}.
4 \end{nparagraph}
```

`\activateexcursion`
`\printexcursion`
`\excursionref`

Here `\activateexcursion{<path>}` augments the `\printexcursions` macro by a call `\inputref{<path>}`. In this way, the `\printexcursions` macro (usually in the appendix) will collect up all excursions that are specified in the main text.

Sometimes, we want to reference – in an excursion – part of another. We can use `\excursionref{<label>}` for that.

`\excursiongroup`

Finally, we usually want to put the excursions into an `sfragment` environment and add an introduction, therefore we provide the a variant of the `\printexcursions` macro: `\excursiongroup[id=<id>,intro=<path>]` is equivalent to

```
1 \begin{note}
2 \begin{sfragment}[id=<id>]{Excursions}
3   \inputref{<path>}
4   \printexcursions
5 \end{sfragment}
6 \end{note}
```

Limitations

In this section we document known limitations. If you want to help alleviate them, please feel free to contact the package author. Some of them are currently discussed in the \TeX GitHub repository [\[sTeX\]](#).

1. when option `book` which uses `\pagestyle{headings}` is given and semantic macros are given in the `sfragment` titles, then they sometimes are not defined by the time the heading is formatted. Need to look into how the headings are made. This is a problem of the underlying `omdoc` package.

7.6 Homework, Problems and Exams

7.6.1 Introduction

The `problem` package supplies an infrastructure that allows specify problem. Problems are text fragments that come with auxiliary functions: hints, notes, and solutions⁵. Furthermore, we can specify how long the solution to a given problem is estimated to take and how many points will be awarded for a perfect solution.

Finally, the `problem` package facilitates the management of problems in small files, so that problems can be re-used in multiple environment.

⁵for the moment multiple choice problems are not supported, but may well be in a future version

Package Options

solutions	The problem package takes the options solutions (should solutions be output?), notes (should the problem notes be presented?), hints (do we give the hints?), gnotes (do we show grading notes?), pts (do we display the points awarded for solving the problem?), min (do we display the estimated minutes for problem solving). If these are specified, then the corresponding auxiliary parts of the problems are output, otherwise, they remain invisible.
boxed	The boxed option specifies that problems should be formatted in framed boxes so that they are more visible in the text. Finally, the test option signifies that we are in a test situation, so this option does not show the solutions (of course), but leaves space for the students to solve them.
test	

Problems and Solutions

problem The main environment provided by the **problem** package is (surprise surprise) the **problem** environment. It is used to mark up problems and exercises. The environment takes an optional KeyVal argument with the keys **id** as an identifier that can be reference later, **pts** for the points to be gained from this exercise in homework or quiz situations, **min** for the estimated minutes needed to solve the problem, and finally **title** for an informative title of the problem.

```

1 \usepackage[solutions,hints,pts,min]{problem}
2 \begin{document}
3   \begin{sproblem}[id=elephants,pts=10,min=2,title=Fitting Elephants,name=elephants]
4     How many Elephants can you fit into a Volkswagen beetle?
5   \begin{hint}
6     Think positively, this is simple!
7   \end{hint}
8   \begin{exnote}
9     Justify your answer
10  \end{exnote}
11  \begin{solution}[for=elephants,height=3cm]
12    Four, two in the front seats, and two in the back.
13  \begin{gnote}
14    if they do not give the justification deduct 5 pts
15  \end{gnote}
16  \end{solution}
17  \end{sproblem}
18 \end{document}

```

The result of formatting this problem is

Problem 7.6.1 (Fitting Elephants)

How many Elephants can you fit into a Volkswagen beetle?

Hint: Think positively, this is simple!

Note: Justify your answer

Solution: Four, two in the front seats, and two in the back.

solution The **solution** environment can be used to specify a solution to a problem. If the package option **solutions** is set or **\solutionstrue** is set in the text, then the solution will be presented in the output. The **solution** environment takes an optional KeyVal argument with the keys **id** for an identifier that can be referenced **for** to specify which problem this is a solution for, and **height** that allows to specify the amount of space to be left in test situations (i.e. if the **test** option is set in the **\usepackage** statement).

hint, exnote, gnote The **hint** and **exnote** environments can be used in a **problem** environment to give hints and to make notes that elaborate certain aspects of the problem. The **gnote** (grading notes) environment can be used to document situations that may arise in grading.

\startsolutions
\stopsolutions

Sometimes we would like to locally override the **solutions** option we have given to the package. To turn on solutions we use the **\startsolutions**, to turn them off, **\stopsolutions**. These two can be used at any point in the documents.

\ifsolutions

Also, sometimes, we want content (e.g. in an exam with master solutions) conditional on whether solutions are shown. This can be done with the **\ifsolutions** conditional.

Multiple Choice Blocks

mcb Multiple choice blocks can be formatted using the **mcb** environment, in which single choices are marked up with **\mcc** macro.

\mcc

\mcc[*<keyvals>*]{*<text>*} takes an optional key/value argument *<keyvals>* for choice meta-data and a required argument *<text>* for the proposed answer text. The following keys are supported

- **T** for true answers, **F** for false ones,
- **Ttext** the verdict for true answers, **Ftext** for false ones, and
- **feedback** for a short feedback text given to the student.

```

1 \begin{sproblem}[title=Functions,name=functions1]
2   What is the keyword to introduce a function definition in python?
3   \begin{mcb}
4     \mcc[T]{def}
5     \mcc[F,feedback=that is for C and C++){function}
6     \mcc[F,feedback=that is for Standard ML]{fun}
7     \mcc[F,Ftext=Noooooooooo,feedback=that is for Java]{public static void}
8   \end{mcb}
9 \end{sproblem}

```

This results in

Problem 7.6.2 (Functions)

What is the keyword to introduce a function definition in python?

☐ **def**
(**true**)

- ☐ `function`
(**false**) (*that is for C and C++*)
- ☐ `fun`
(**false**) (*that is for Standard ML*)
- ☐ `public static void`
(**false**) (*that is for Java*)

Problem 7.6.3 (Functions)

What is the keyword to introduce a function definition in python?

- ☐ `def`
(**true**)
- ☐ `function`
(**false**) (*that is for C and C++*)
- ☐ `fun`
(**false**) (*that is for Standard ML*)
- ☐ `public static void`
(**false**) (*that is for Java*)

Including Problems

`\includeproblem`

The `\includeproblem` macro can be used to include a problem from another file. It takes an optional `KeyVal` argument and a second argument which is a path to the file containing the problem (the macro assumes that there is only one problem in the include file). The keys `title`, `min`, and `pts` specify the problem title, the estimated minutes for solving the problem and the points to be gained, and their values (if given) overwrite the ones specified in the `problem` environment in the included file.

Reporting Metadata

The sum of the points and estimated minutes (that we specified in the `pts` and `min` keys to the `problem` environment or the `\includeproblem` macro) to the log file and the screen after each run. This is useful in preparing exams, where we want to make sure that the students can indeed solve the problems in an allotted time period.

The `\min` and `\pts` macros allow to specify (i.e. to print to the margin) the distribution of time and reward to parts of a problem, if the `pts` and `pts` package options are set. This allows to give students hints about the estimated time and the points to be awarded.

Limitations

In this section we document known limitations. If you want to help alleviate them, please feel free to contact the package author. Some of them are currently discussed in the \LaTeX GitHub repository [\[sTeX\]](#).

1. none reported yet

The `wexam` package and class supplies an infrastructure that allows to format nice-looking assignment sheets by simply including problems from problem files marked up with the `roblem` package. It is designed to be compatible with `problems.sty`, and inherits some of the functionality.

7.6.2 Package Options

`solutions`
`notes`
`hints`
`gnotes`
`pts`
`min`

The `wexam` package and class take the options `solutions`, `notes`, `hints`, `gnotes`, `pts`, `min`, and `boxed` that are just passed on to the `problems` package (cf. its documentation for a description of the intended behavior).

7.6.3 Assignments

`assignment`
`number`

`title`
`type`
`given`
`due`

This package supplies the `assignment` environment that groups problems into assignment sheets. It takes an optional KeyVal argument with the keys `number` (for the assignment number; if none is given, 1 is assumed as the default or — in multi-assignment documents — the ordinal of the `assignment` environment), `title` (for the assignment title; this is referenced in the title of the assignment sheet), `type` (for the assignment type; e.g. “quiz”, or “homework”), `given` (for the date the assignment was given), and `due` (for the date the assignment is due).

7.6.4 Typesetting Exams

`multiple`

`test`

`\testspace`
`\testnewpage`
`\testemptypage`

`testheading`
`duration`
`min`
`reqpts`

Furthermore, the `hwexam` package takes the option `multiple` that allows to combine multiple assignment sheets into a compound document (the assignment sheets are treated as section, there is a table of contents, etc.).

Finally, there is the option `test` that modifies the behavior to facilitate formatting tests. Only in `test` mode, the macros `\testspace`, `\testnewpage`, and `\testemptypage` have an effect: they generate space for the students to solve the given problems. Thus they can be left in the \LaTeX source.

`\testspace` takes an argument that expands to a dimension, and leaves vertical space accordingly. `\testnewpage` makes a new page in `test` mode, and `\testemptypage` generates an empty page with the cautionary message that this page was intentionally left empty.

Finally, the `\testheading` takes an optional keyword argument where the keys `duration` specifies a string that specifies the duration of the test, `min` specifies the equivalent in number of minutes, and `reqpts` the points that are required for a perfect grade.


```

1 \title{320101 General Computer Science (Fall 2010)}
2 \begin{testheading}[duration=one hour,min=60,reqpts=27]
3   Good luck to all students!
4 \end{testheading}

```

Will result in
formats to

Name:

Matriculation Number:

320101 General Computer Science (Fall 2010)

2022-04-24

You have one hour (sharp) for the test;

Write the solutions to the sheet.

The estimated time for solving this exam is 58 minutes, leaving you 2 minutes for revising your exam.

You can reach 30 points if you solve all problems. You will only need 27 points for a perfect score, i.e. 3 points are bonus points.

You have ample time, so take it slow and avoid rushing to mistakes!

Different problems test different skills and knowledge, so do not get stuck on one problem.

	To be used for grading, do not write here											
prob.	7.6.1	7.6.2	7.6.3	1.1	2.1	2.2	2.3	3.1	3.2	3.3	Sum	grade
total				4	4	6	6	4	4	2	30	
reached												

good luck

7.6.5 Including Assignments

`\inputassignment` The `\inputassignment` macro can be used to input an assignment from another file. It takes an optional KeyVal argument and a second argument which is a path to the file containing the problem (the macro assumes that there is only one `assignment` environment in the included file). The keys `number`, `title`, `type`, `given`, and `due` are just as for the `assignment` environment and (if given) overwrite the ones specified in the `assignment` environment in the included file.

References

- [Bus+04] Stephen Buswell et al. *The Open Math Standard, Version 2.0*. Tech. rep. The OpenMath Society, 2004. URL: <http://www.openmath.org/standard/om20>.
- [CR99] David Carlisle and Sebastian Rathz. *The graphicx package*. Part of the T_EX distribution. The Comprehensive T_EX Archive Network. 1999. URL: <https://www.tug.org/texlive/devsrc/Master/texmf-dist/doc/latex/graphics/graphicx.pdf>.
- [DCM03] The DCMI Usage Board. *DCMI Metadata Terms*. DCMI Recommendation. Dublin Core Metadata Initiative, 2003. URL: <http://dublincore.org/documents/dcmi-terms/>.
- [Koh06] Michael Kohlhase. *OMDoc – An open markup format for mathematical documents [Version 1.2]*. LNAI 4180. Springer Verlag, Aug. 2006. URL: <http://omdoc.org/pubs/omdoc1.2.pdf>.
- [LMH] *LMH Scripts*. URL: <https://github.com/sLaTeX/lmhtools>.
- [MMT] *MMT – Language and System for the Uniform Representation of Knowledge*. Project web site. URL: <https://uniformal.github.io/> (visited on 01/15/2019).
- [MRK18] Dennis Müller, Florian Rabe, and Michael Kohlhase. “Theories as Types”. In: *9th International Joint Conference on Automated Reasoning*. Ed. by Didier Galmiche, Stephan Schulz, and Roberto Sebastiani. Springer Verlag, 2018. URL: <https://kwarc.info/kohlhase/papers/ijcar18-records.pdf>.
- [Rab15] Florian Rabe. “The Future of Logic: Foundation-Independence”. In: *Logica Universalis* 10.1 (2015). 10.1007/s11787-015-0132-x; Winner of the Contest “The Future of Logic” at the World Congress on Universal Logic, pp. 1–20.
- [RK13] Florian Rabe and Michael Kohlhase. “A Scalable Module System”. In: *Information & Computation* 0.230 (2013), pp. 1–54. URL: <https://kwarc.info/frabe/Research/mmt.pdf>.
- [RT] *sLaTeX/RusTeX*. URL: <https://github.com/sLaTeX/RusTeX> (visited on 04/22/2022).
- [Sla] *sLaTeX/sTeX-IDE*. URL: <https://github.com/slatex/sTeX-IDE> (visited on 04/22/2022).
- [Sib] *sLaTeX/stexls-vscode-plugin*. URL: <https://github.com/slatex/stexls-vscode-plugin> (visited on 04/22/2022).
- [SLS] *sLaTeX/stexls*. URL: <https://github.com/slatex/stexls> (visited on 04/22/2022).
- [ST] *sTeX – An Infrastructure for Semantic Preloading of LaTeX Documents*. URL: <https://ctan.org/pkg/stex> (visited on 04/22/2022).
- [sTeX] *sTeX: A semantic Extension of TeX/LaTeX*. URL: <https://github.com/sLaTeX/sTeX> (visited on 05/11/2020).
- [Tana] Till Tantau. *beamer – A LaTeX class for producing presentations and slides*. URL: <http://ctan.org/pkg/beamer> (visited on 01/07/2014).
- [Tanb] Till Tantau. *User Guide to the Beamer Class*. URL: <http://ctan.org/macros/latex/contrib/beamer/doc/beameruserguide.pdf>.
- [TL] *TeX Live*. URL: <http://www.tug.org/texlive/> (visited on 12/11/2012).