

**BLG520E Cryptography
2nd Project**

1. Build three different block ciphers with the following properties

- (a) They are substitution-permutation networks (SPNs) with 16-bit block length.
- (b) They include four rounds.
- (c) The key schedules for all the block ciphers is performed by using a 16-bit linear feedback shift register (LFSR) [2] as shown in Eq. 1 and 2.

Master key: $K_0 = [k_{0,15} \ k_{0,14} \ k_{0,13} \ k_{0,12} \ k_{0,11} \ k_{0,10} \ k_{0,9} \ k_{0,8} \ k_{0,7} \ k_{0,6} \ k_{0,5} \ k_{0,4} \ k_{0,3} \ k_{0,2} \ k_{0,1} \ k_{0,0}]$

i -th round key:

$$k_{i,15} = k_{i-1,0} \oplus k_{i-1,2} \oplus k_{i-1,4} \oplus k_{i-1,5} \quad (1)$$

$$k_{i,j} = k_{i-1,j+1} \quad (2)$$

Block Cipher 1:

SBox:	z	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F
	$\pi_S(z)$	1	9	6	D	7	3	5	F	2	C	E	A	4	B	8	0

Permutation:	z	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
	$\pi_P(z)$	15	11	7	3	14	10	6	2	13	9	5	1	12	8	4	0

Block Cipher 2: SBox: $\pi_S(z) = \begin{cases} 0 & \text{if } z = 0 \\ z^{-1} \bmod 17 & \text{if } 1 \leq z \leq 15 \end{cases}$,

SBox:	z	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F
	$\pi_S(z)$	0	1	9	6	D	7	3	5	F	2	C	E	A	4	B	8

Permutation:	z	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
	$\pi_P(z)$	15	11	7	3	14	10	6	2	13	9	5	1	12	8	4	0

Block Cipher 3: SBox: $\pi_S(z) = \begin{cases} 0 & \text{if } z = 0 \\ z^{-1} \bmod 17 & \text{if } 1 \leq z \leq 15 \end{cases}$,

SBox:	z	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F
	$\pi_S(z)$	0	1	9	6	D	7	3	5	F	2	C	E	A	4	B	8

Permutation:	z	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
	$\pi_P(z)$	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0

2. Choose a random key. Produce some random or chosen plaintext, ciphertext pairs for all the three different block ciphers.
3. Doğançan Davutoğlu, Muhammed Güneş, Ömer Faruk Birgül, Yunus Emre Eryılmaz, Burak Karamete, Enes Yasin Akman, Havva Betül Kulaksız, Ezgi Hasret Açıkgöz will apply linear cryptanalysis [5, 1, 3] to above block ciphers.
4. Fethi Okta, Furkan Can, Yasin Yılmaz, Burak Bozdağ, Şükrü Sezer, Şenay Yeldan, Şevval Yıldız, Valentin L'Homel will apply differential cryptanalysis [4, 3] to above block ciphers.
5. Compare and discuss the results for all the block ciphers.

References

- [1] Alex Biryukov and Christophe De Cannière. *Linear Cryptanalysis for Block Ciphers*, pages 351–354. Springer US, Boston, MA, 2005.
- [2] S. Gaonkar. Design of 8 bit, 16 bit and 32 bit lfsr for pn sequence generation using VHDL. *International Journal of Technical Research and Applications*, 31:305–308, 2015. e-ISSN: 2320-8163.
- [3] H. M. Heys. *A Tutorial on Linear and Differential Cryptanalysis*.
- [4] X. Lai, J.L. Massey, and S. Murphy. Markov ciphers and differential cryptanalysis. In D. W. Davies, editor, *Advances in Cryptology: Proceedings of EUROCRYPT'91*, volume 547 of *Lecture Notes in Computer Science*, pages 17– 38, Brighton, UK, April 1991. Springer-Verlag.
- [5] M. Matsui. Linear cryptanalysis method for DES cipher. In T. Helleseht, editor, *Advances in Cryptology: Proceedings of EUROCRYPT'93*, volume 765 of *Lecture Notes in Computer Science*, pages 386–397, Lofthus, Norway, May 23-27 1993. Springer-Verlag.