

LabPower UPS

Data Center Uninterruptible Power Supply

Kabellab products are meticulously designed for easy installation while maintaining the highest quality with an aesthetically pleasing design. Kabellab combines innovative design with technology to create efficient products that achieve maximum impact. These are Kabellab's guiding principles.



1978 - 2017
IN LOVING MEMORY OF TLM



MDU 30X Modules






30kVA to 300kVA Modular UPS



3 Phase Power System



Lithium Battery power System



LabPower-MDU 3P RM600/100X

The **LabPower-MDU 30-300kVA** 3-in, 3-out UPS features a modular design and N+X parallel redundancy, with capacity per module ranging from 30kVA to 300kVA. This flexible configuration allows users to gradually expand and customize their power protection. The series effectively addresses nearly all power issues—including outages, overvoltage, undervoltage, voltage sags, oscillations, high-voltage pulses, fluctuations, surges, harmonic distortion, electromagnetic interference, frequency variations, and other common power disturbances—ensuring reliable and stable operation for critical loads.



Applications

The LabPower-MDU product provides versatile power protection solutions across diverse sectors, ensuring safety, stability, and dependability. Its environmentally friendly design makes it suitable for critical applications such as data centers, financial institutions, government and corporate data rooms, healthcare facilities, educational institutions, and other environments that demand uninterrupted, high-quality power supply.



Performance Features

Digital control

All components of this UPS series utilize digital control, resulting in outstanding performance metrics. The control system is highly stable and reliable, ensuring consistent and dependable operation.

High power density modular design

Each module has a capacity of 30KVA and occupies a height of 2U. The UPS modules support hot-swappable design, allowing online addition or removal without causing downtime, thus enabling "zero" maintenance time.

N+X parallel redundancy

Redundant modules exceeding two ensure a system availability of 99.999%, with an MTBF (Mean Time Between Failures) surpassing 250,000 hours. Battery packs can be shared seamlessly across four cabinets within the setup.

Smart Battery Management

Users can configure the charging current, with seamless automatic switching between constant current, constant voltage, and floating charging modes. The system supports 30 to 50 batteries for flexible capacity management.

Safe and convenient maintenance

In emergency situations, the system can switch to the maintenance bypass power supply, allowing maintenance personnel to perform safe online maintenance. Pressing the EPO button initiates an emergency shutdown, and the system also features a remote emergency shutdown (REPO) function for added safety and control.



1978 - 2017
IN LOVING MEMORY OF TLM



Website at www.kabellab.com

The Kabellab Logo is designed by Kabellab Technologies Company. Third-party trademarks mentioned are the property of their respective owners.

Specifications

Models			RM90/30X	RM150/30X	RM300/30X
Normal Capacity	Cabinet		30~90kW	30~150kW	30~300kW
	Module		30kW		
Maximum Number of Modules			3	5	10
Input	Mode		3 Phase 4 Wires and Ground		
	Nominal voltage		380/400V/415Vac		
	Voltage range		138~485Vac		
	Frequency range		40~70Hz		
	Power factor		≥0.99		
	THDi		≤3% (100% nonlinear load)		
	Bypass range		Max.voltage: 220V: +25 %(optional+10%, +15%, +20%); 230V: +20 %(optional +10%, +15%); 240V: +15 % (optional +10%); Min.voltage: -45%(optional -20%, -30%)		
			Bypass frequency protection range: ±10%		
	Power Walking In		Yes		
	Bypass back irrigation		Bypass back irrigation		
	Generator access		Yes		
Output	Phase		3 Phase 4 Wires and Ground		
	Rated Voltage		380/400V/415Vac		
	Power Factor		1		
	Voltage Regulation		±1%		
	Frequency(Hz)	Utility mode	±1%,±2%,±4%,±5%,±10%of the rated frequency(optional)		
		Battery mode	(50/60±0.1%)Hz		
	Crest Factor		3:1		
	THD		≤2%with linear load,≤5%with non linear load		
	Efficiency		96%		
	Overload		≤110%,to bypass after 60min;≤125%,to bypass after 10min;≤150%,to bypass after 1min		
Battery	Voltage		±180V/±192V/±204V/±216V/±228V/±240/±252/±264/±276/±288/±300 Vdc (30/32/34/36/38/40/42/44/46/48/50 sections, amount to 30~50 sections are optional)		
	Charge Current	Cabinet	Max 30A	Max 50A	Max 100A
		Module	Max 10A		
Transfer Time			Utility to Battery:0ms;Utility to bypass:0ms		
Protection	Alarm		overload,utility abnormal,UPS fault,battery low,etc		
	Protection		short circuit,overload,over temperature,battery low,fan fault alarm		
Communication			RS232, RS485, Intelligent slot x 2, Dry Contact, SNMP		
Physical	Dimension (DxWxH) mm	UPS Cabinet	850x600x1350	850x600x1350	850x600x2000
		UPS Module	620x440x86 (mm)		
	N.W 9kg)	UPS Cabinet	160	170	275
		UPS Module	21		
Standards			EN62040-1,EN62040-2		



Lithium Battery power System




LabPower serves as an OEM for lithium batteries sourced from another factory, offering a comprehensive solution for lithium iron phosphate battery systems tailored for UPS and energy storage applications. Featuring a broad voltage range of 96V to 1000V, this system ensures adaptability across various scenarios. Renowned for its safety and reliability, it finds applicability in UPS, home storage, industrial, commercial energy storage, and various other fields.



Features

- Safety, reliability, and longevity assured
- Modular and standardized design for seamless integration
- Dual control for precise charge and discharge management
- Gap-free power supply for uninterrupted operation
- Comprehensive CAN/RS485/LAN interface for seamless communication
- Intuitive visualization via touch screen interface
- Scalability with support for up to 20 parallel units
- Efficient operation and maintenance, including remote maintenance capabilities



Specifications

Voltage range(V)	300~432
Cell	3.2V50Ah
PACK	1P15S
Parallel & Series	1P120S
Rated voltage(V)	384
Rated capacity(Ah)	50
Rated energy (kWh)	19.2
Max output power(kW)	76.8
Max discharge current(A)	200
Max charge current(A)	50
Discharge cut-off voltage(V)	300
Max charge voltage(V)	432
Advise back-up time(min)	15
Cycles(25°C,0.5C/1C,100%DOD)	>2500
Working temperature(°C)	0~40
Working humidity	<95%R.H(non-condensing)
Communication	CAN2.0/RS485/DO
Pack dimention(W*D*H,mm)	440*470*133
Cabinet dimention(W*D*H,mm)	600*800*2000
Cabinet count	1
Protection level	IP20
System weight(kg)	Approx. 385
Certification	UL/CE/UN38.3

