

LabPower UPS

Data Center Uninterruptible Power Supply

Kabellab products are meticulously designed for easy installation while maintaining the highest quality with an aesthetically pleasing design. Kabellab combines innovative design with technology to create efficient products that achieve maximum impact. These are Kabellab's guiding principles.



1978 - 2017
IN LOVING MEMORY OF TLM





1kVA to 10kVA






Single Phase Power System



Acid Battery power System

RTA



1~10kVA High Frequency Rack or Tower UPS

LabPower-RTA Uninterruptible Power Supply (UPS) systems are crafted to deliver unrivaled power stability and efficiency. Equipped with true double-conversion technology, these systems provide clean, consistent power, safeguarding your equipment from voltage variations. The wide input voltage range (110-300VAC) guarantees flexibility in unpredictable power conditions.

For enhanced efficiency, our 1-3 KVA models include an ECO mode for energy savings, while 6K and 10K models feature adjustable charging currents and an emergency power-off function for tailored control and safety. Engineered for versatility, models up to 6KVA offer a dual Rack-Tower design and a hot-swappable battery setup to ensure seamless operation and maintenance. Additionally, generator compatibility across 1KR, 2KR, and 3KR models ensures reliable backup during outages.

Choose our UPS systems for comprehensive power protection tailored to your unique requirements. For further details and customization options, reach out to our sales team.



Applications

Our comprehensive solution is designed to provide optimal support for small to medium-sized data centers, IT machine rooms, financial institutions, traffic dispatch centers, security monitoring, and a variety of related facilities. Its versatile nature ensures seamless integration into diverse environments, enhancing both operational efficiency and reliability. By focusing on the unique needs of each industry, our solution offers unmatched performance and flexibility, making it the perfect choice for a broad spectrum of applications.



Features

Our cutting-edge Uninterruptible Power Supply (UPS) systems are meticulously engineered to deliver superior power protection and efficiency for various applications. Experience unparalleled reliability and performance with our feature-rich solutions:

- True Double-Conversion Technology
- Input Power Factor Correction
- Output Power Factor of 0.8
- Wide Input Voltage Range (110-300VAC)
- ECO Mode for Energy Saving
- Rack-Tower 2-in-1 Design
- Hot-Swappable Battery Design



1978 - 2017
IN LOVING MEMORY OF TLM



Website at www.kabellab.com

The Kabellab Logo is designed by Kabellab Technologies Company. Third-party trademarks mentioned are the property of their respective owners.

Model			LabPower™-1KR	LabPower™-2KR	LabPower™-3KR	LabPower™-6KR	LabPower™-10KR			
Part Number			KBL-LPW-RSP1	KBL-LPW-RSP2	KBL-LPW-RSP3	KBL-LPW-RSP6	KBL-LPW-RSP10			
Capacity (kVA)			1000VA/800W	2000VA/1600W	3000VA/2400W	6000VA/4800W	10000VA/8000W			
Phase			Single Phase with Ground							
INPUT	Nominal Voltage		110/115/120/127VAC or 208/220/230/240VAC			208/220/230/240VAC				
	Input Voltage Range		55-145 VAC or 110-300 VAC at 50% load 85-140 VAC or 160-280 VAC at 100% load			110-300 VAC ± 3% at 50% Load 176-300 VAC ± 3% at 100% Load				
	Frequency Range		40Hz ~ 70 Hz			46Hz ~ 54 Hz or 56Hz ~ 64 Hz				
	Power Factor		≥0.99 @ Nominal Voltage (100% load)							
OUTPUT	Output Voltage		110/115/120/127VAC or 208/220/230/240VAC			208/220/230/240VAC				
	Voltage Regulation		± 1%			± 1%				
	Frequency Range (Synchronized Range)		47~ 53 Hz or 57 ~ 63 Hz			46Hz ~ 54 Hz or 56Hz ~ 64 Hz				
	Frequency Range (Batt. Mode)		50 Hz ± 0.25 Hz or 60Hz ± 0.3 Hz			50 Hz ± 0.1 Hz or 60 Hz ± 0.1 Hz				
	Current Crest Ratio		3:1							
	Harmonic Distortion		≤3 % THD (Linear Load), ≤6 % THD (Non-linear Load)			≤3 % THD (Linear Load), ≤5 % THD (Non-linear Load)				
	TRANSFER TIME	AC Mode to Battery Mode	Zero			0 ms				
		Inverter to Bypass	4 ms (Typical)			0 ms				
	Waveform (Batt. Mode)		Pure Sinewave							
EFFICIENCY	AC Mode		88%	89%	90%	92%	93%			
	Battery Mode		83%	87%	88%	90%	91%			
BATTERY	Standard Model	Battery Type	12V/9AH				12V/9AH			
		Numbers	2	4	6	16	20	16	20	
		Typical Recharge Time	4 hours recover to 90% capacity				9 hours recover to 90% capacity			
		Charging Current	1.0A				1A/2A (Adjustable)			
		Charging Voltage (DC) ±1%	27.4	54.7	82.1	218.4	273	218.4	273	
	Long-run Model	Battery Type	Depending on the capacity of external batteries				Depending on applications			
		Numbers	2	3	4	6	8	6	8	16 - 20 pcs (Adjustable)
		Charging Current (Max)	1.0A/2.0A/4.0A/6.0 A				1A/2A/4A/6A (6A is available for 16pcs batts)			
		Charging Voltage (DC) ±1%	27.4	41	54.7	82	109.4	82.1	109.4	218.4 VDC ± 1% (Based on 16pcs batts)
	PHYSICAL	UPS Standard Model	Dimension DxWxH (mm)	310x438x88 (2U)		410x438x88 (2U)		500x438x88 (2U)		500x438x133 (3U)
Net Weight (kgs)			9		12		14.2		15	18
Battery Pakcs		Dimension DxWxH (mm)	310x438x88 (2U)		410x438x88 (2U)		630x438x88 (2U)		438X715X86 (2U)	438X715X86 (2U)
		Net Weight (kgs)	12		19		29.3		50	50
OTHERS	Humidity		20-90 % RH @ 0- 40°C (non-condensing)			0-95 % RH @ 0- 40°C (non-condensing)				
	Noise Level		Less than 50dB @ 1 Meter			<55dB@1 meter		<58dB@1 meter		
	Smart RS-232 / USB		Supports Windows® 2000/2003/XP/Vista/2008, Windows® 7/8/10, Linux and MAC							
	Optional SNMP		Power management from SNMP manager and web browser							

