



LabActiv-REVO 8F

Industrial Managed Switch 8 x SFP Slot, 2 x Gigabit POE+

8 x SFP Slot



Overview

LabActiv-REVO 8F is our new generation management type industrial Ethernet switch series of products, it supports 10 SFP ports, the aluminum metal case with IP40 protection equipment, strong anti vibration card base, extreme temperature adaptability and good EMC performance of EMC, to ensure that in the harsh environment the long-term stable and reliable, safe use. **LabActiv-REVO 8F** supports the proprietary M-Ring ring protection protocol, healing time can be less than 20ms, VLAN, QinQ, STP/RSTP, support QoS, ACL multicast, rich two layer exchange function, while providing CLI, Telnet, SSH, Http, Https and other management and network management software based on SNMPv1/v2c/v3. BH600-C628FI has wide range of applications, including campus, rail transport, electricity, petroleum, petrochemical, banking, water, metallurgy, public security, military, civil aviation, etc., by the user's trust and praise. work devices such as IP cameras and wireless access points between remote locations.

Features and Benefits

- **8xSFP Port, 1000Base-X**
- **2-port 10/100/1000BASE-T RJ45** with auto MDI / MDI-X function
- Support cable fault detection, a key to restart and restore the factory function
- Support Ethernet ring network protocol ERPS, support for private M-RING ring protection protocol, the protection of switching time can be less than 20ms
- Based on port aggregation, linear protection based on G.8031 protocol and the protection of the ring network based on G.8032 protocol
- Support spanning tree (STP) and fast spanning tree (RSTP) protocol and multi spanning tree (MSTP) protocol, port support hybrid redundancy network
- Support VLAN 802.1Q, basic QinQ and flexible QinQ, support up to VLAN 4K table entry
- Support for rich OAM, including 802.3ah standards in line with the EFM and 802.1ag, Y.1731 standard CFM
- Support port based, 802.1P, DSCP, MAC address, ID VLAN, Type QOS and other Ethernet services
- Supports 256 ACL access control rules
- Support for speed limits based on port, VLAN, and port +VLAN
- Support RMON, effectively improve the network monitoring and forecasting ability
- Supports RADIUS, TACACS+, IEEE802.1X, HTTPS and SSH and other network security functions
- Support the broken fiber alarm; support Dying Gasp remote equipment fail alarm
- Support relay output alarm function
- Support port loop detection

Compliance

EMI:

FCC Part15 Subpart B Class A
EN 55022 Class A

EMS:

IEC 61000-4-2 ESD, IEC 61000-4-3 RS
IEC 61000-4-4 EFT, IEC 61000-4-5 Surge
IEC 61000-4-6 CS, IEC 61000-4-8
IEC 61000-4-11

Collision

IEC 60068-2-27



1978 - 2017
IN LOVING MEMORY OF TLM



Website at **www.kabellab.com**

Kabellab and the Kabellab Logo are designed of Kabellab Technologies Company. Third party trademarks mentioned are the property of their respective owners. The use of ward partner does not imply a partnership relationship between Kabellab and any other company. Since 2009, Kabellab established by Brian and owned the Kabellab products development and design. Kabellab has appointed agent/partners in few country, which are Brunei Darussalm, Malaysia, Taiwan, Philippine & China.

Technical Specifications

Perimeter	
IEEE Standard	IEEE 802.3 10BASE-T
	IEEE 802.3u 100BASE-TX/100BASE-FX
	IEEE 802.3z Gigabit SX/LX
	IEEE 802.3ab Gigabit 1000T
	IEEE 802.3x flow control and back pressure
	IEEE 802.3az Energy Efficient Ethernet
	IEEE 802.3ad port trunk with LACP
	IEEE 802.3ah Configuring Ethernet OAM
	IEEE 802.1D Spanning Tree Protocol
	IEEE 802.1x Port Authentication Network Control
	IEEE 802.1Q VLAN tagging
	IEEE 1588
Packet buffer	4Mbits
Maximum packet length	Up to 10K Bytes
MAC address table	8K
Transmission mode	Store and Forward (full/half duplex mode)
Exchange property	Delay time: < 7μs
	Backplane bandwidth: 56Gbps
	Packet forwarding rate: 14880 (64 Byte)

Interface	
Connector	16xRJ45 PoE+ 30W
Optical Port	4xSFP Slot Dual Mode, Auto Detection

Power Information	
Power access mode	Phoenix terminal, DC seat
Input Power	DC 48-57V
Overload protection	Yes
Power reverse	Support
Power Consumption	Full-load<15W (Not use PoE)
LED Indicators PWR	Power Status
LED Indicators Link/Act	Data LINK Status
LED Indicators Fiber	Fiber LINK Status

Environment	
Operating Temperature	-40°C to 80°C
Storage Temperature	-40°C to 80°C
Relative Humidity	5% to 90% non-condensing
MTBF	500,000 hours

Physical	
Protection grade	IP40 Aluminum Case
Cooling mode	Natural cooling, no fan design
Dimension (WxDxH)	160(L) x 130(W) x 70(H) mm
Weight	1000g
Mounting Options	DIN-RAIL / Wall-Mount

Order Information	
Part Number	Description
KA-RV1604	LabActiv-REVO 16 Industrial Media Converter 4xSFP, 16xGigabit PoE+ 30W, Din Rail
KA-MM01G-SX	LabActiv-SFP SX 1.2Gbps 850nm Dual Fiber Transceiver, Industrial Grade 550M
KA-SM01G-LX	LabActiv-SFP LX 1.2Gbps 1310nm Dual Fiber Transceiver, Industrial Grade 20KM



1978 - 2017
IN LOVING MEMORY OF TLM



Website at **www.kabellab.com**

Kabellab and the Kabellab Logo are designed of Kabellab Technologies Company. Third party trademarks mentioned are the property of their respective owners. The use of ward partner does not imply a partnership relationship between Kabellab and any other company. Since 2009, Kabellab established by Brian and owned the Kabellab products development and design. Kabellab has appointed agent/partners in few country, which are Brunei Darussalm, Malaysia, Taiwan, Filippine & China.