



LabActiv-REVO 4

Industrial Managed Switch 4 x Gigabit POE+, 2 x SFP Slot

4 x **30W** Each port



Overview

LabActiv-REVO 4 is a new generation industrial Managed switch with 4-Port 10/100/1000Base-T 802.3at PoE+ and 2-Port 100/1000Base-X SFP that provide stable and reliable Ethernet transmission, with high quality design and reliability. The industrial switch complies with various characteristics such as mini size, no fan, low power consumption, high reliability and stability, and easy to maintain. With dual power input design, LabActiv-REVO 4 can offer redundant mechanisms for critical applications that need always-on connections. It can also operate either at standard operating temperature range -40 to 80°C. Housed in rugged DIN rail or wall mountable IP40 enclosures, these switches are perfect choices for harsh environments, such as industrial networking, intelligent transportation systems (ITS) and are also suitable for many military and utility market applications where environmental conditions exceed commercial product specifications.

Features and Benefits

- **4-port 10/100/1000BASE-T RJ45** with auto MDI / MDI-X function
- **2xSFP Port, 100Base-FX or 1000Base-X** dual mode (auto detection)
- 100/1000BASE-X mini-GBIC/SFP slots for SFP type auto detection
- Support 16K bytes giant frame, compatible with various extension protocol
- Support IEEE802.3az energy efficient Ethernet technology
- Electric 4KV surge protection, easy to use in outdoor environment
- Power input polarity protection design, no worry about wrong operation
- DHCP RFC 1541, 1542
- DIN trail /Wall mounting

Compliance

EMI:

FCC Part15 Subpart B Class A
EN 55022 Class A

EMS:

IEC 61000-4-2 ESD, IEC 61000-4-3 RS
IEC 61000-4-4 EFT, IEC 61000-4-5 Surge
IEC 61000-4-6 CS, IEC 61000-4-8
IEC 61000-4-11

Collision

IEC60068-2-27

Software Features:

- Redundant network: STP/RSTP
- Multicast: IGMP Snooping V1/V2
- VLAN: IEEE 802.1Q 4K VLAN, QinQ
- Link Aggregation: manual
- Management Function: CLI/WEB/SNMP
- Diagnostic Maintenance: Port mirroring, Ping
- Alarm management: 1-way relay alarm output, RMON, SNMP Trap
- Security: DHCP Snooping, User hierarchical management
- Data control Port-based ingress/egress speed limit, Full duplex IEEE 802.3x, half duplex back-pressure flow control. Broadcast storm suppression, Unknown-Multicast suppression and Unknown-Unicast suppression



1978 - 2017
IN LOVING MEMORY OF TLM



Website at www.kabellab.com

Kabellab and the Kabellab Logo are designed of Kabellab Technologies Company. Third party trademarks mentioned are the property of their respective owners. The use of ward partner does not imply a partnership relationship between Kabellab and any other company. Since 2009, Kabellab established by Brian and owned the Kabellab products development and design. Kabellab has appointed agent/partners in few country, which are Brunei Darussalm, Malaysia, Taiwan, Philippine & China.

Technical Specifications

Perimeter	
IEEE Standard	IEEE 802.1x authentication
	IEEE 802.1q-Tagging
	IEEE 802.1p-Queueing Layer 2 QoS/CoS with min. 4 Queues per Port
	IEEE 802.1w RSTP rapid spanning tree
	IEEE 802.3ad Trunking
	IEEE 802.3x flow control
	IEEE 802.1D Spanning Tree
	IEEE 802.1ab LLDP
Packet buffer	4Mbits
Maximum packet length	Up to 1532Bytes
MAC address table	16K
Transmission mode	Store and Forward (full/half duplex mode)
Exchange property	Delay time: < 7μs
	Backplane bandwidth: 20Gbps
	Packet forwarding rate: 14.88Mpps

PoE	
PoE Standard	4x IEEE 802.3af /IEEE 802.3at PoE
Power budget	Max. PoE output power budget 30W

Interface	
Connector	4xRJ45 PoE+ 30W
Optical Port	2xSFP Slot Dual Mode, Auto Detection

Power Information	
Power access mode	Phoenix terminal, DC seat
Input Power	DC 48-57V
Overload protection	Yes
Power reverse	Support
Power Consumption	Full-load<15W (Not use PoE)
LED Indicators PWR	Power Status
LED Indicators Link/Act	Data LINK Status
LED Indicators Fiber	Fiber LINK Status

Environment	
Operating Temperature	-40°C to 80°C
Storage Temperature	-40°C to 80°C
Relative Humidity	5% to 90% non-condensing
MTBF	100,000 hours

Physical	
Protection grade	IP40 Aluminum Case
Cooling mode	Natural cooling, no fan design
Dimension (WxDxH)	138(L) x 106(W) x 41(H) mm
Weight	600g
Mounting Options	DIN-RAIL / Wall-Mount

Order Information	
Part Number	Description
KA-RV4002	LabActiv-REVO 4 Industrial Media Converter 2xSFP, 4xGigabit PoE+ 30W, Din Rail
KA-MM01G-SX	LabActiv-SFP SX 1.2Gbps 850nm Dual Fiber Transceiver, Industrial Grade 550M
KA-SM01G-LX	LabActiv-SFP LX 1.2Gbps 1310nm Dual Fiber Transceiver, Industrial Grade 20KM



1978 - 2017
IN LOVING MEMORY OF TLM



Website at www.kabellab.com

Kabellab and the Kabellab Logo are designed of Kabellab Technologies Company. Third party trademarks mentioned are the property of their respective owners. The use of ward partner does not imply a partnership relationship between Kabellab and any other company. Since 2009, Kabellab established by Brian and owned the Kabellab products development and design. Kabellab has appointed agent/partners in few country, which are Brunei Darussalm, Malaysia, Taiwan, Filippine & China.