


DRILL CHART: TOP to BOTTOM				
ALL UNITS ARE IN MILS				
FIGURE	FINISHED_SIZE	TOLERANCE_DRILL	PLATED	QTY
⊙	40.0	+3.0/-3.0	PLATED	11
⊕	93.0	+3.0/-3.0	NON-PLATED	2



- NOTES: (UNLESS OTHERWISE SPECIFIED)
- 1.FABRICATE PER IPC-6012B TYPE 2 CLASS 3
- 2.MATERIAL:

BASE MATERIAL : FR4 Tg 180
- 3.BOARD THICKNESS: 1.6 MM +/-5% TOL.
- 4.FINISHED CU THICKNESS FOR ALL LAYERS : 2 OZ.
- 5.NO OF LAYERS: 2
- 6.SURFACE FINISH: ENIG FINISH
- 7.SOLDERMASK CLEARANCE IS GIVEN SAME AS PAD SIZE EXCEPT FIDUCIALS.

VENDOR SHALL MODIFY THE MASK CLEARANCE AS PER THE REQUIRED MANUFACTURING TOLERANCE

COLOR:GREEN
- 8.SILKSCREEN:SINGLE SIDE WITH PERMANENT NON CONDUCTIVE WHITE EPOXY INK

SILKSCREEN MAY BE TRIMMED OFF ANY SOLDERED ENTITY.
- 9.BOW AND TWIST NOT TO EXCEED 0.180MM (0.007") PER INCH AS MEASURED PER IPC-TM-650.
- 10.100%CONTINUITY TESTING USING DATABASE NETLIST SHALL BE PERFORMED.
- 11.VENDOR SHOULD FOLLOW ROHS COMPLAINT PROCESS FOR MANUFACTURING.