Project name: Poker

Possible advanced topics: Version control and Build Systems (Gradle / Maven),

#	Name	How to Demo	Notes
1	Open the program to the selection screen	Make a selection screen with a play button, possibly a button to a settings menu, quit button would also be nice	Settings are optional, includes starting money and “big blind”
2	Open the board	After clicking play button, open the board and display a deal button to start the game	
3	Deal cards	Deal cards, there's an option to toggle show and hide cards for each player. Betting begins for the first player. (Call, fold and raise options appear). The “big blind” is subtracted from the players and added to the pot.	
4	First betting cycle	After the first player has betted, the second player gets the option to do the same. If this player raises the first player gets the option to respond. (if he raises again, the second player gets the chance to respond etc.)	If anyone folds, game chooses the other player as the winner and skip to 9
5	Flop	After both players are done betting, the deal button appears again and after pressing, the 3 flop cards are shown and the players get the chance to bet again.	
6	Turn	After a repeat of 4, and all the players are done betting, the deal button appears and after being pressed, the turn card gets shown and the players get the chance to bet again	
7	River	After a repeat of 4, and all the players are done betting, the deal button appears and after being pressed, the river card gets shown and the players get the chance to bet again	

8	Game!	After all players are done betting, a “SHOW WINNER” button appears.	
9	Pot to winner	After clicking the show winner button (or someone folding), a winner gets chosen and the pot money gets given to that player.	
10	Next game	The board gets reset we get a repeat of 3-10	This is important to make sure the game continues with the carried money from the previous game.
11	Match winner	After a player runs out of money, and loses the game, the other player gets declared as the winner.	Win conditions implementation required us to find out the order of poker hands.
12	Special cases	If during a betting round, one player cannot match the bet raised by the other player, the money is returned back to the other player and the round continues as per the poker rules.	Required to change the logic by adding some if else statements
13	Raise edge case	The player cannot raise more money than they have, so we need to add a case for that as well to prevent the raise button from applying	
14	Hiding buttons	The buttons will be hidden when they're not in use, for example when its player 1’s turn, the buttons for player 2 will be hidden and vice versa.	Needed to implement
15	Creating all the classes	We divided all the code into classes such as the main screen where the board all the above steps will take place, we had classes for cards, player, pokerGame	Creating multiple files and making sure the variables all able to be accessed by different files in the same package.
16	Cards class	We created a class that has a hashmap containing all the cards and a number, so when we call method to randomly generate number it picks a random card.	

17	Player class	It has the player class that has values like playermoney, the players cards and the methods to show cards of the players and change the money of the player.	
18	Winner, PokerGame and GameRunner classes	Winner class has the methods to determine the winner using the cards of the table and the pair each player has, poker game contains methods for the actual game, game runner creates the poker game.	
19	GUI	Make sure there are buttons displaying all the actions such as raise, call and fold and the pot money and the money each player has.	Used netbeans palette to make things a bit easier and to save time.