

Assignment Title: - No. 1

Create a static web page which defines all text formatting tags of HTML in tabular format.

Name: - Piyush Rajendra Waghmare

PRN: - 123B1B284

DIV: - D4

Objectives: -

- To design and develop a static web page using HTML and CSS.
- To understand and demonstrate HTML text formatting tags.
- To differentiate between semantic and presentation tags.
- To display HTML formatting tags in a clear tabular format.
- To visualize the actual output of each text formatting tag.

Outcomes: -

- Successfully created a well-styled static webpage using internal CSS.
- Learned the usage and purpose of common HTML text formatting tags.

- Understood the difference between semantic tags (,) and presentation tags (, <i>).
- Gained practical knowledge of how formatting tags affect text appearance and meaning.
- Improved understanding of HTML documentation and reference table design.

Theory Concept in brief: -

HTML text formatting tags are used to enhance the appearance, structure, and meaning of text on a web page. These tags help in highlighting important content, emphasizing text, displaying quotations, showing deleted or inserted content, and representing mathematical expressions.

Text formatting tags are classified into:

- Presentation tags such as and <i>, which focus only on appearance.
- Semantic tags such as and , which provide meaning and importance to the text.

Using semantic tags improves accessibility, SEO, and readability of web content.

Dataset Used: -

- No external dataset was used.
- The content displayed on the webpage is manually created sample text.
- Example strings and text values are used to demonstrate the functionality of each HTML tag.

Program Code with output Screenshot: -

File Name : - Index.html

<!DOCTYPE html>

<html lang="en">

<head>

<meta charset="UTF-8">

<meta name="viewport" content="width=device-width, initial-scale=1.0">

<title>HTML Text Formatting Tags</title>

<style>

body {

font-family: Arial, sans-serif;

margin: 20px;

background-color: #f4f4f9;

```
color: #333;  
}
```

```
h1 {  
color: #2c3e50;  
text-align: center;  
border-bottom: 2px solid #3498db;  
padding-bottom: 10px;  
}
```

```
h2 {  
color: #2c3e50;  
border-bottom: 1px dashed #3498db;  
padding-bottom: 5px;  
margin-top: 40px;  
}
```

```
table {  
width: 100%;  
border-collapse: collapse;  
margin-top: 20px;  
box-shadow: 0 4px 8px rgba(0, 0, 0, 0.1);
```

```
background-color: #fff;  
}
```

```
th, td {  
border: 1px solid #ddd;  
padding: 12px;  
text-align: left;  
}
```

```
th {  
background-color: #3498db;  
color: white;  
font-weight: bold;  
text-transform: uppercase;  
}
```

```
tr:nth-child(even) {  
background-color: #f2f8ff;  
}
```

```
tr:hover {  
background-color: #e9f5ff;
```

_____}

_____ .code-tag {

_____ font-family: 'Courier New', monospace;

_____ background-color: #ecf0f1;

_____ padding: 2px 5px;

_____ border-radius: 4px;

_____ color: #c0392b;

_____ font-weight: bold;

_____ }

_____ .example-output {

_____ color: #27ae60;

_____ font-weight: 500;

_____ }

_____ #sample-output {

_____ background-color: #ffffff;

_____ padding: 20px;

_____ border: 1px solid #ccc;

_____ border-radius: 8px;

_____ margin-top: 20px;

```
box-shadow: 0 2px 4px rgba(0,0,0,0.05);  
}
```

```
blockquote {  
margin: 15px 0;  
padding: 10px 20px;  
border-left: 5px solid #e74c3c;  
background-color: #fcecec;  
font-style: italic;  
}
```

```
</style>
```

```
</head>
```

```
<body>
```

```
<h1>HTML Text Formatting Tags Reference</h1>
```

```
<table>
```

```
<thead>
```

```
<tr>
```

```
<th>Tag</th>
```

```
<th>Description</th>
```

Example Code	Result
<pre></pre>	
<pre> text (Presentation).</pre>	 text (Presentation).
<pre><code class="code-tag">Bold Text</code></pre>	Bold Text
<pre><td class="example-output">Bold Text</td></pre>	Bold Text
<pre></tr></pre>	
<pre><tr></pre>	
<pre><td class="code-tag"></pre>	
<pre><td>Defines important text (Semantic).</td></pre>	Defines important text (Semantic).
<pre><td><code class="code-tag">Important Text</code></pre>	Important Text
<pre><td class="example-output">Important Text</td></pre>	Important Text
<pre></tr></pre>	
<pre><tr></pre>	

<td class="code-tag"><i></td>

<td>**Italic** text (Presentation).</td>

<td><code class="code-tag"><i>Italic
Text</i></code></td>

<td class="example-output"><i>Italic Text</i></td>

</tr>

<tr>

<td class="code-tag"></td>

<td>Defines **emphasized** text (Semantic).</td>

<td><code class="code-
tag">Emphasized Text</code></td>

<td class="example-output">Emphasized
Text</td>

</tr>

<tr>

<td class="code-tag"><mark></td>

<td>Defines **highlighted** text.</td>

<td><code class="code-
tag"><mark>Highlighted
Text</mark></code></td>

<td class="example-output"><mark>Highlighted
Text</mark></td>

</tr>

<u><tr></u>	
<u><td class="code-tag">&lt;small&gt;</td></u>	
<u><td>Renders text one size **smaller**.</td></u>	
<u><td><code class="code-tag">&lt;small&gt;Smaller Text&lt;/small&gt;</code></td></u>	
<u><td class="example-output"><small>Smaller Text</small></td></u>	
<u></tr></u>	
<u><tr></u>	
<u><td class="code-tag">&lt;del&gt;</td></u>	
<u><td>Defines **deleted** text (Strikethrough).</td></u>	
<u><td><code class="code-tag">&lt;del&gt;Deleted Text&lt;/del&gt;</code></td></u>	
<u><td class="example-output">Deleted Text</td></u>	
<u></tr></u>	
<u><tr></u>	
<u><td class="code-tag">&lt;ins&gt;</td></u>	
<u><td>Defines **inserted** text (Underline).</td></u>	
<u><td><code class="code-tag">&lt;ins&gt;Inserted Text&lt;/ins&gt;</code></td></u>	
<u><td class="example-output"><ins>Inserted Text</ins></td></u>	

</tr>

<tr>

<td class="code-tag"><sub></td>

<td>Defines ****subscripted**** text (e.g.,
\$\\text{H} 2\\text{O}\$).</td>

<td><code class="code-
tag">H<sub>2</sub>O</code></td>

<td class="example-
output">H₂O</td>

</tr>

<tr>

<td class="code-tag"><sup></td>

<td>Defines ****superscripted**** text (e.g.,
\$\\text{x}^2\$).</td>

<td><code class="code-
tag">x<sup>2</sup></code></td>

<td class="example-output">x²</td>

</tr>

<tr>

<td class="code-tag"><abbr></td>

<td>Defines an ****abbreviation**** (use `title`).</td>

<td><code class="code-tag"><abbr
title="HyperText Markup
Language">HTML</abbr></code></td>

<td class="example-output"><abbr
title="HyperText Markup Language">HTML</abbr></td>

</tr>

<tr>

<td class="code-tag"><code></td>

<td>Defines a piece of **computer code**.</td>

<td><code class="code-
tag"><code>console.log()</code></code></td>

<td class="example-
output"><code>console.log()</code></td>

</tr>

<tr>

<td class="code-tag"><blockquote></td>

<td>Defines a section that is **quoted** (Block-
level).</td>

<td><code class="code-
tag"><blockquote>...</blockquote></code></td>
≥

<td class="example-output">See section
below.</td>

</tr>

<tr>

<td class="code-tag"><q></td>

<td>Defines a **short inline quotation**.</td>

<td><code class="code-tag"><q>Inline
Quote</q></code></td>

<td class="example-output"><q>Inline
Quote</q></td>

</tr>

</tbody>

</table>

—
<h2>Sample Case Demonstration: Semantic and
Presentation Tags in Use</h2>

—
<div id="sample-output">

<p>

Today, we're issuing a

strong correction

to an old post. We had initially printed the water
formula as

H²O

(using a

deleted 2

but it should, of course, be H₂O
(subscript and superscript).

This specific error was

<small>small</small>

and easily fixed).

</p>

<p>

To emphasize the importance of accuracy
in all technical fields, we'd like to

<q>quote the famous programming dictum: Keep it
Simple, Stupid</q>.

The original programmer's note included the
abbreviation

<abbr title="Keep It Simple, Stupid">KISS</abbr>,

followed by the

<code>code snippet: if (error != true)</code>.

<mark>Mark that last point well.</mark>

This simple principle, though sometimes delivered in
a very

bold

and slightly <i>italic</i> way, remains paramount.

A final note: we have

<ins>inserted this sentence</ins>

_____ to confirm the update.

_____ </p>

_____ <p>

_____ The article concludes with a longer quote from the
_____ lead scientist:

_____ </p>

_____ <blockquote>

_____ "The mistake with H2O was a regrettable oversight.
_____ We must always strive for semantic correctness, using
_____ for importance and for emphasis,
_____ rather than just and <i> for appearance
_____ alone. This incident serves as a good reminder."

_____ </blockquote>

_____ </div>

_____ </body>

_____ </html>

HTML Text Formatting Tags Reference

Tag	Description	Example Code	Result
<code></code>	“Bold” text (Presentation).	<code>Bold Text</code>	Bold Text
<code></code>	Defines “important” text (Semantic).	<code>Important Text</code>	Important Text
<code><i></code>	“Italic” text (Presentation).	<code><i>Italic Text</i></code>	<i>Italic Text</i>
<code></code>	Defines “emphasized” text (Semantic).	<code>Emphasized Text</code>	<i>Emphasized Text</i>
<code><mark></code>	Defines “highlighted” text.	<code><mark>Highlighted Text</mark></code>	Highlighted Text
<code><small></code>	Renders text one size “smaller” .	<code><small>Smaller Text</small></code>	Smaller Text
<code></code>	Defines “deleted” text (Strikethrough).	<code>Deleted Text</code>	Deleted Text
<code><ins></code>	Defines “inserted” text (Underline).	<code><ins>Inserted Text</ins></code>	<u>Inserted Text</u>
<code><sub></code>	Defines “subscripted” text (e.g., H_2O).	<code>H<sub>2</sub></code></code>	H_2O
<code><sup></code>	Defines “superscripted” text (e.g., x^2).	<code>x<sup>2</sup></code></code>	x^2
<code><abbr></code>	Defines an “abbreviation” (use <code>title</code>).	<code><abbr title="HyperText Markup Language">HTML</abbr></code>	<u>HTML</u>
<code><code></code>	Defines a piece of “computer code” .	<code><code>console.log()</code></code>	<code>console.log()</code>
<code><blockquote></code>	Defines a section that is “quoted” (Block-level).	<code><blockquote>...</blockquote></code>	See section below.

<abbr>	Defines an “abbreviation” (use <code>title</code>).	<abbr title="HyperText Markup Language">HTML</abbr>	HTML
<code>	Defines a piece of “computer code” .	<code>console.log()</code>	console.log()
<blockquote>	Defines a section that is “quoted” (Block-level).	<blockquote>...</blockquote>	See section below.
<q>	Defines a “short inline quotation” .	<q>Inline Quote</q>	“Inline Quote”

Sample Case Demonstration: Semantic and Presentation Tags in Use

Today, we're issuing a **strong correction** to an old post. We had initially printed the water formula as H²O (using a ~~deleted-2~~ but it should, of course, be H₂O (subscript and superscript). This specific error was small and easily fixed).

To *emphasize* the importance of accuracy in all technical fields, we'd like to "quote the famous programming dictum: Keep it Simple, Stupid". The original programmer's note included the abbreviation KISS, followed by the code snippet: `if (error != true)`. **Mark that last point well.** This simple principle, though sometimes delivered in a very **bold** and slightly *italic* way, remains paramount. A final note: we have inserted this sentence to confirm the update.

The article concludes with a longer quote from the lead scientist:

"The mistake with H₂O was a regrettable oversight. We must always strive for semantic correctness, using `<strong>` for importance and `<em>` for emphasis, rather than just `<b>` and `<i>` for appearance alone. This incident serves as a good reminder."

Conclusion: -

This experiment demonstrates the effective use of HTML text formatting tags through a structured and visually appealing static web page.

By presenting the tags in a table along with descriptions, code examples, and rendered output, the webpage serves as a quick reference guide for HTML learners.

The implementation highlights the importance of using semantic HTML for better web standards, accessibility, and maintainability.