

Autonomous Vehicle Lane Detection System Using Convolutional Neural Networks

Payal Sengar¹, Piyush Jain², Prabhat Dubey³

Palak Bhatnagar⁴, Pawanesh Pandey⁵

⁶

^{1,2,3,4,5}Department of Artificial Intelligence and Machine Learning, Noida Institute of Engineering and Technology, Greater Noida, Uttar Pradesh

ABSTRACT

Autonomous driving systems rely heavily on accurate lane detection to ensure safe and reliable navigation. Traditional computer vision techniques often struggle under varying lighting conditions, occlusions, and complex road scenarios. In this paper, we propose a deep learning-based approach for real-time lane detection and steering direction prediction using a U-Net convolutional neural network architecture. The model is trained on the TuSimple dataset, where lane annotations are converted into binary segmentation masks to enable pixel-wise classification.

The proposed system integrates an encoder-decoder structure with skip connections to effectively capture both spatial and contextual features. To enhance segmentation performance, a hybrid loss function combining Binary Cross-Entropy and Dice loss is employed, improving robustness against class imbalance. The trained model demonstrates high accuracy in detecting lane boundaries and generating precise segmentation masks.

Furthermore, the system extends beyond lane detection by incorporating a steering decision module that analyzes the predicted lane regions to determine driving direction (left, right, or straight). The model is also deployed in a real-time video processing pipeline, demonstrating its practical applicability in dynamic driving environments. Experimental results indicate that the proposed approach achieves reliable performance and can serve as a foundation for advanced driver assistance systems (ADAS) and autonomous vehicles.

1. INTRODUCTION

1.1 Lane Detection in Autonomous Driving

Lane detection is a fundamental component of modern autonomous driving systems and Advanced Driver Assistance Systems (ADAS). It enables vehicles to identify road boundaries and maintain proper lane discipline, ensuring safe and efficient navigation. Accurate lane detection is essential for tasks such as lane keeping, lane departure warning, and path planning. However, detecting lanes in real-world scenarios is challenging due to varying lighting conditions, occlusions, shadows, road curvature, and worn-out lane markings.

Traditional computer vision techniques, such as edge detection and Hough Transform, have been widely used for lane detection. However, these methods often fail to perform reliably in complex environments because they rely heavily on handcrafted features and predefined rules. As a result, there is a growing need for more robust and adaptive approaches.

In recent years, deep learning techniques have significantly improved the performance of lane detection systems. Convolutional Neural Networks (CNNs), especially segmentation-based models like U-Net, have demonstrated high accuracy in extracting lane features from images. These models learn complex spatial patterns directly from data, making them more effective in handling real-world variations. Despite these advancements, achieving real-time performance while maintaining accuracy remains a key challenge in autonomous systems.

1.2 Importance of Lane Detection and Real-Time Decision Making

Accurate and real-time lane detection plays a critical role in enhancing road safety and reducing accidents. A reliable lane detection system not only identifies lane boundaries but also assists in making driving decisions such as steering direction. By analyzing the detected lane regions, an intelligent system can determine whether the vehicle should move left, right, or continue straight.

Real-time processing is essential for practical deployment in autonomous vehicles, as decisions must be made instantly based on continuously changing road conditions. Any delay or inaccuracy in detection can lead to unsafe driving behavior. Therefore, integrating lane detection with decision-making mechanisms is crucial for building efficient and reliable autonomous systems.

Furthermore, such systems can be deployed in driver assistance technologies to support human drivers, especially in scenarios involving long-distance driving, fatigue, or low visibility conditions. With the advancement of deep learning and computational power, developing real-time lane detection systems has become more feasible and scalable.

1.3 Importance of Accurate Lane Detection and Real-Time Monitoring

Accurate lane detection plays a crucial role in improving road safety and reducing traffic accidents. Early and precise identification of lane boundaries enables autonomous vehicles and driver assistance systems to maintain proper lane discipline, thereby preventing unintended lane departures and collisions. Reliable lane detection not only enhances passenger safety but also reduces the overall economic burden caused by road accidents and traffic disruptions.

Modern lane detection systems utilize camera-based sensors and deep learning models to continuously monitor road conditions and detect lane markings in real time. These systems are designed to function under diverse environmental conditions, including varying lighting, shadows, and road textures. By leveraging advanced techniques such as convolutional neural networks, lane detection can be performed with high accuracy even in complex scenarios.

Real-time monitoring is essential because road environments are highly dynamic. The ability to process video frames instantly and make immediate decisions—such as adjusting steering direction (left, right, or straight)—significantly enhances the effectiveness of autonomous driving systems. Timely detection ensures that corrective actions can be taken before a potential hazard occurs.

However, challenges such as poor lane visibility, occlusions, faded markings, and lack of standardized road infrastructure can affect system performance, especially in developing regions. Therefore, continuous improvement in detection algorithms, data quality, and system robustness is necessary to ensure reliable deployment in real-world conditions.

1.4 Machine Learning in Autonomous Lane Detection

Machine Learning is a rapidly advancing field of artificial intelligence that enables systems to learn from data and improve their performance without being explicitly programmed. In the context of autonomous driving, machine learning plays a vital role in enabling vehicles to understand and interpret visual information from road environments. It allows systems to automatically identify patterns such as lane markings, road boundaries, and driving paths, which are essential for safe navigation.

The learning process begins with the collection of relevant data, such as road images and annotated lane information from datasets like TuSimple. This data is then preprocessed to generate suitable inputs, including resized images and corresponding segmentation masks that highlight lane regions. A deep learning model, such as a Convolutional Neural Network (CNN) based U-Net architecture, is trained on this data to perform pixel-wise classification of lane markings.

During training, the model learns both spatial and contextual features of lanes under varying conditions, including different lighting, shadows, and road textures. After training, the model is evaluated using validation data to measure its accuracy and generalization capability. In this work, a hybrid loss function combining Binary Cross-Entropy and Dice loss is used to improve segmentation performance and handle class imbalance effectively.

Machine learning techniques used in this project fall under the category of supervised learning, where the model learns from labeled data. The trained model is further integrated into a real-time system to process video frames and assist in determining steering direction. This demonstrates how machine learning can be effectively applied to build intelligent and reliable autonomous driving systems.




Figure 1: Autonomous Vehicle Lane Detection System using Deep Learning Architecture

1.5 Role of Machine Learning in Autonomous Driving Systems

Machine learning plays a crucial role in enhancing the capabilities of autonomous driving systems by enabling accurate perception and decision-making based on visual data. In this work, deep learning techniques are utilized to perform lane detection using image-based features extracted from road scenes. Unlike traditional approaches that rely on handcrafted features, machine learning models can automatically learn complex spatial patterns, improving detection accuracy under diverse environmental conditions.

The proposed system leverages a Convolutional Neural Network (CNN), specifically a U-Net architecture, to perform lane segmentation. By training on annotated datasets such as TuSimple, the model learns to identify lane markings at a pixel level, providing more precise

and reliable results compared to conventional methods. The integration of deep learning with image processing allows the system to handle challenges such as shadows, varying lighting conditions, and road curvature.

Furthermore, the model is extended to support decision-making by analyzing detected lane regions to determine steering direction. This demonstrates the potential of machine learning not only for perception tasks but also for assisting in real-time driving decisions. Such non-invasive, vision-based techniques reduce dependency on expensive sensors and contribute to the development of cost-effective autonomous systems.

However, the proposed approach has certain limitations. The performance of the model depends on the quality and diversity of the training dataset, and it may struggle in scenarios with heavily faded lane markings or extreme weather conditions. Additionally, real-time deployment requires optimization to ensure low latency and high efficiency. Despite these challenges, the use of machine learning in lane detection provides a strong foundation for building intelligent and scalable autonomous driving solutions.

2. LITERATURE REVIEW

In recent years, significant research has been conducted in the field of autonomous driving, particularly in lane detection and road scene understanding. Traditional approaches relied heavily on image processing techniques such as edge detection, color thresholding, and Hough Transform to identify lane boundaries. While these methods are computationally efficient, they often fail under challenging conditions such as shadows, varying illumination, occlusions, and worn-out lane markings.

In paper [1], a classical computer vision-based approach for lane detection was proposed using edge detection and Hough Transform techniques. The method performed well under controlled conditions but showed limitations in complex environments due to its dependence on handcrafted features and sensitivity to noise.

In paper [2], the authors introduced a deep learning-based approach using convolutional neural networks (CNNs) for lane detection. The model was trained on large-scale datasets and demonstrated improved accuracy compared to traditional methods. However, the approach focused primarily on feature extraction and lacked precise pixel-level segmentation, which limited its performance in detailed lane boundary detection.

In paper [3], a segmentation-based method using Fully Convolutional Networks (FCNs) was proposed to achieve pixel-wise classification of lane markings. The results showed significant improvement in detecting lane regions accurately. However, the model required high computational resources and struggled with real-time implementation.

In paper [4], an advanced deep learning architecture incorporating attention mechanisms and multi-scale feature extraction was introduced to enhance lane detection performance. The model achieved high accuracy in complex driving scenarios by focusing on relevant regions of the image. Despite its effectiveness, the model had increased computational complexity, making it less suitable for real-time applications.

In paper [5], researchers explored the use of U-Net architecture for lane segmentation. The encoder-decoder structure with skip connections enabled the model to capture both spatial and contextual information effectively. The results demonstrated high segmentation accuracy, especially in challenging scenarios. However, the model's performance depended heavily on the quality and diversity of the training dataset.

In paper [6], real-time lane detection systems were developed by integrating deep learning models with video processing pipelines. These systems demonstrated the feasibility of deploying lane detection models in practical scenarios. However, challenges such as latency, hardware constraints, and robustness under extreme weather conditions remained unresolved.

In paper [7], various machine learning and deep learning techniques, including Support Vector Machines (SVM), Random Forest, and CNN-based models, were compared for lane detection tasks. The study concluded that deep learning models significantly outperform traditional machine learning approaches in terms of accuracy and adaptability to complex environments.

Overall, the literature indicates that while traditional methods provide simplicity and efficiency, deep learning approaches, particularly segmentation-based models like U-Net, offer superior performance in lane detection tasks. However, challenges such as real-time processing, dataset limitations, and robustness under diverse conditions still need to be addressed.

Table 1: Comparison of Existing Lane Detection Approaches

Ref	Method	Dataset	Performance	Limitation
[1]	Edge + Hough Transform	Road Images	Good in simple cases	Fails in complex scenes
[2]	CNN-based Detection	Large-scale dataset	Improved accuracy	No pixel-level precision
[3]	FCN Segmentation	Lane datasets	High accuracy	High computation cost

[4]	Attention-based CNN	Multi-scenario data	Robust performance	Complex architecture
[5]	U-Net	TuSimple	High segmentation accuracy	Data dependent
[6]	Real-time DL systems	Video data	Practical implementation	Latency issues
[10]	ML vs DL comparison	Multiple datasets	DL performs best	Resource intensive

In lane detection tasks, the dataset is often highly imbalanced, as the number of pixels belonging to lane markings is significantly smaller compared to background pixels. This imbalance can bias the model during training, leading to poor detection of lane regions while favoring background classification. As a result, the model may achieve high overall accuracy but fail to accurately segment lane boundaries.

To address this issue, techniques such as data augmentation and specialized loss functions are commonly used. In this work, a hybrid loss function combining Binary Cross-Entropy and Dice loss is employed to handle class imbalance effectively and improve segmentation performance. While such approaches enhance the model's ability to detect lane pixels, challenges still remain in accurately capturing thin and faint lane markings.

Therefore, future research should focus on improving imbalance-handling strategies, incorporating more diverse datasets, and using advanced evaluation metrics that better reflect real-world performance of lane detection systems

3. KEY FINDINGS AND OPEN RESEARCH CHALLENGES:

1. Weak Generalization because of constraints of the datasets

Most existing studies on lane detection are trained and evaluated on specific datasets such as TuSimple or similar benchmarks. While these models often achieve high accuracy in controlled environments, their performance may degrade when applied to real-world scenarios with different road conditions, lighting variations, weather changes, and diverse traffic environments. This limitation arises due to the lack of diverse and large-scale datasets that represent real-world variability.

Additionally, many models are trained on relatively clean and well-annotated data, which does not fully capture challenges such as faded lane markings, occlusions, shadows, and irregular road structures. As a result, the generalization capability of these models remains limited when deployed in practical autonomous driving systems.

To address this issue, future research should focus on developing and utilizing large-scale, diverse, and multi-environment datasets. Incorporating data from different geographical regions, weather conditions, and road types can significantly improve model robustness. Furthermore, techniques such as data augmentation, domain adaptation, and transfer learning can be explored to enhance generalization and ensure reliable performance in real-world applications.

2. Obvious Benefit of Data-Driven Learning Models

Recent studies have consistently demonstrated that deep learning and data-driven approaches significantly outperform traditional computer vision techniques in lane detection tasks. Unlike conventional methods that rely on handcrafted features and predefined rules, data-driven models such as Convolutional Neural Networks (CNNs) are capable of learning complex, non-linear patterns directly from image data. This allows them to adapt effectively to variations in road conditions, lighting, shadows, and lane structures.

The ability of these models to capture both spatial and contextual information makes them highly suitable for pixel-level tasks such as lane segmentation. Architectures like U-Net further enhance performance by combining low-level and high-level features through skip connections, resulting in more accurate and detailed lane detection.

As a result, data-driven deep learning models are becoming the foundation of modern autonomous driving systems and Advanced Driver Assistance Systems (ADAS). Their superior accuracy, adaptability, and scalability make them essential for building reliable real-time lane detection and decision-support systems.

3. Limited Utilization of Multimodal Information

Most existing lane detection approaches primarily rely on a single source of data, typically RGB camera images, to identify lane markings. While image-based methods have shown strong performance, the absence of multimodal data integration limits the system's ability to fully understand complex driving environments. Factors such as poor lighting conditions, shadows, occlusions, and faded lane markings can significantly affect the reliability of vision-only systems.

The lack of frameworks that combine multiple data sources—such as camera images, LiDAR, radar, or GPS information—restricts the robustness and accuracy of lane detection models. Integrating heterogeneous data sources can provide complementary information, enabling better perception and decision-making in challenging scenarios.

Therefore, future research should focus on developing multimodal approaches that fuse data from different sensors to enhance lane detection performance. Such integration can improve system reliability, especially in adverse conditions, and contribute to the advancement of more intelligent and resilient autonomous driving systems.

4. High Dependence on Preprocessing and Data Preparation

Lane detection models are highly dependent on preprocessing steps such as image resizing, normalization, and accurate generation of lane segmentation masks. The quality of these preprocessing techniques directly affects the performance of the deep learning model. For instance, improper mask generation or loss of important spatial details during resizing can lead to inaccurate lane predictions.

Although techniques such as data augmentation, normalization, and advanced loss functions (e.g., Dice loss and Binary Cross-Entropy) help improve model performance, there is still a lack of standardized preprocessing pipelines across different studies. Variations in preprocessing methods can lead to inconsistent results and make it difficult to fairly compare different models.

Furthermore, the effectiveness of the model also depends on how well the input data represents real-world conditions. Insufficient diversity in preprocessing strategies may limit the model's ability to generalize across different environments.

Therefore, developing standardized and robust preprocessing and data preparation techniques is essential for improving the reliability, consistency, and performance of lane detection systems in real-world autonomous driving applications.

4. Class Imbalance and Pixel Distribution Challenges

In lane detection tasks, the dataset is inherently imbalanced, as the number of pixels representing lane markings is significantly smaller compared to background pixels. This imbalance can bias the model during training, causing it to favor background prediction while failing to accurately detect thin and less prominent lane regions.

Various techniques, such as data augmentation and specialized loss functions, are used to address this issue. In particular, loss functions like Dice loss combined with Binary Cross-Entropy help improve the model's ability to focus on minority lane pixels. However, while these approaches enhance detection performance, their impact on false positives—such as incorrectly identifying non-lane regions as lanes—remains a challenge.

Additionally, there is a lack of standardized evaluation metrics that fully capture real-world performance, especially in complex driving conditions. Metrics like accuracy alone may not reflect the model's effectiveness in detecting fine lane structures.

Therefore, future research should focus on developing more robust imbalance-handling techniques and adopting comprehensive evaluation metrics to ensure reliable and accurate lane detection in real-world autonomous driving scenarios.

5. Limited Focus on Early Detection and Proactive Decision Support

Most existing lane detection systems primarily focus on identifying lane boundaries in already visible and well-defined road conditions. Relatively less attention has been given to detecting early signs of potential driving risks, such as faded lane markings, partially occluded lanes, or poorly structured road boundaries. This limitation reduces the ability of such systems to support proactive decision-making and prevent potential hazards before they fully develop.

A more advanced approach should focus on predictive and anticipatory capabilities, where the system can identify subtle patterns indicating possible lane deviations or unsafe road conditions in advance. Incorporating temporal information from consecutive frames and enhancing sensitivity to weak lane features can significantly improve early detection of driving risks.

Therefore, future research should emphasize developing intelligent models that not only detect clear lane markings but also recognize early indicators of unsafe conditions. Such advancements can enhance the reliability of autonomous systems and contribute to safer and more proactive driving assistance technologies.

6. Increasing Importance of Model Transparency and Interpretability

The need for explainable artificial intelligence (XAI) in autonomous driving systems is increasingly being recognized. As lane detection models are used in safety-critical applications, it is essential to understand how these models make predictions and decisions. Interpretability techniques such as saliency maps, Grad-CAM, and feature visualization are increasingly used to analyze model behavior and highlight the regions of the input image that most influence lane detection. This improves transparency and builds trust in the system.

Explainable models also allow developers and engineers to better understand the strengths and limitations of the algorithm, making it easier to debug errors and improve performance. Furthermore, the use of open and interpretable models enables validation against real-world driving scenarios and ensures that the system behaves reliably under different conditions.

Overall, integrating explainable AI techniques into lane detection systems enhances their reliability, safety, and usability, making them more suitable for deployment in real-world autonomous driving applications.

7. Limited Integration of Explainability in Real-Time Decision Making

Despite advancements in interpretability techniques for deep learning models, many existing lane detection systems limit their use to visualization and post-analysis rather than integrating them into real-time driving decisions. While methods such as saliency maps and Grad-CAM help in understanding which regions of an image influence model predictions, their direct impact on improving steering decisions or system behavior is still not fully explored.

The connection between model explanations and actionable driving responses—such as lane correction, steering adjustments, or safety alerts—remains an open research area. Simply visualizing important regions is not sufficient unless these insights are effectively incorporated into the decision-making pipeline of autonomous systems.

Therefore, future research should focus on integrating explainability techniques directly into real-time systems, enabling models not only to detect lanes but also to justify and refine their decisions. This can enhance system reliability, improve debugging, and support the development of safer and more intelligent autonomous driving solutions.

8. Improved Performance with Domain-Specific Visual Features

Studies have shown that lane detection models achieve better performance when trained on domain-specific and visually meaningful features such as lane markings, road boundaries, curvature patterns, and texture variations of the road surface. Models that effectively capture these features through deep learning architectures, such as convolutional neural networks,

demonstrate higher accuracy compared to those relying on minimal or handcrafted features.

By learning spatial and contextual information directly from road images, these models are able to align their predictions with real-world driving scenarios. Features such as lane continuity, edge alignment, and geometric structure contribute significantly to accurate lane segmentation and reliable steering decisions.

Furthermore, models that incorporate these meaningful visual cues tend to be more consistent with actual road conditions and driving behavior. This alignment enhances the robustness and reliability of the system, making it more suitable for real-world deployment in autonomous driving and advanced driver assistance systems.

9. Need for Real-World Deployment-Oriented Solutions

Despite achieving strong performance in experimental and benchmark settings, many lane detection models are not thoroughly evaluated under real-world driving conditions. Factors such as varying weather conditions, inconsistent road quality, lighting changes, and dynamic traffic environments can significantly impact model performance. Additionally, challenges related to computational efficiency and latency make it difficult to deploy complex deep learning models in real-time systems.

For practical implementation, lane detection systems must be reliable, scalable, and capable of operating efficiently on embedded hardware with limited computational resources. Real-time performance is critical, as even small delays in detection and decision-making can affect driving safety.

Therefore, future research should focus on developing deployment-ready solutions that balance accuracy with efficiency. Emphasis should be placed on optimizing models for real-time inference, improving robustness under diverse conditions, and ensuring seamless integration into autonomous vehicles and Advanced Driver Assistance Systems (ADAS). Such advancements are essential for transitioning from experimental models to real-world, production-level autonomous driving systems.

4. DISCUSSION

Table 2. Core research areas and proposed solutions using machine learning

Research Focus	Studies	Problem	The Proposed Solution
Accuracy	[3], [6], [11]	Single models make errors.	Use U-Net for accurate lane detection
Efficiency	[4], [9], [12]	Too much confusing data.	Use ROI-based preprocessing for efficiency
Reliability	[7], [8]	Limited lane data affects performance.	Use data augmentation for better accuracy
Visual Detail	[1], [2]	Faded lanes are hard to detect.	Use deep learning for fine segmentation
Trust	[3], [4]	Model decisions are hard to understand.	Use visual outputs for model explanation

Table 2 demonstrates the improvement in model accuracy, efficiency, and reliability using deep learning techniques, preprocessing methods, and data augmentation. The table also

highlights how convolutional neural networks can enhance lane detection and support decision-making through clear visual outputs. Overall, these methods improve the performance and robustness of real-time lane detection systems.

CONCLUSION

Autonomous driving remains a major focus in modern transportation systems globally, with significant challenges in real-world environments where poor lighting conditions, occlusions, and faded lane markings lead to inaccurate detection in many cases. Lane detection should be performed at the earliest stage of visual processing because accurate identification of road boundaries increases driving safety, reduces accidents, and improves navigation efficiency. In this regard, deep learning has become a powerful tool to support lane detection and decision-making through the effective analysis of large volumes of road and video data.

System reliability and safety are also critical during the implementation of deep learning technologies in autonomous driving. Visual data captured from cameras is highly sensitive to environmental conditions, and therefore, artificial intelligence systems must be designed to ensure robustness, accuracy, and consistency in performance. Proper validation, testing, and safety measures must be established so that machine learning-based driving systems become reliable and practical for real-world applications.

This paper has presented a systematic study of deep learning-based lane detection methods and evaluated their effectiveness in improving detection accuracy and performance. The findings indicate that advanced models such as Convolutional Neural Networks, U-Net architectures, and hybrid deep learning approaches consistently perform better compared to traditional computer vision techniques. Furthermore, detection performance is improved by using effective preprocessing techniques, such as image resizing, normalization, and lane mask generation, along with diverse datasets representing real-world driving conditions. Explainable AI techniques are also gaining importance, although their integration into real-time autonomous systems remains limited. Additionally, challenges such as handling complex road scenarios, improving model generalization, and achieving real-time performance still require further attention.

Finally, deep learning-based lane detection systems demonstrate strong potential in enabling safe navigation, real-time decision-making, and intelligent transportation systems. Future research should focus on practical deployment of optimized and interpretable models, integration of multimodal sensor data, and development of robust systems capable of performing reliably across diverse real-world environments.

FUTURE SCOPE

Building upon the current deep learning-based framework, future research will focus on the development of a transformer-driven, explainable lane detection system that leverages both image and sensor-based data. Specifically, hybrid architectures combining Convolutional Neural Networks (CNNs) with Vision Transformers (ViT) will be explored to effectively model spatial features from road images alongside contextual driving information. Cross-validation strategies, such as k-fold validation and data augmentation techniques, will be rigorously applied to ensure model robustness, reduce overfitting, and provide reliable performance across diverse and complex driving environments.

To enhance interpretability, advanced explainable AI techniques, including attention map visualization, Grad-CAM, and feature attribution methods, will be integrated into the deep learning framework to provide both global and local explanations of lane detection results. Furthermore, multimodal fusion mechanisms will be designed to combine camera data with additional inputs such as LiDAR, radar, and GPS information into a unified perception model. The study will also explore domain adaptation and transfer learning to improve model generalization across different road conditions and geographical environments. Finally, the proposed system will aim for real-world deployment through the development of an interpretable, real-time decision-support system for autonomous vehicles, validated using large-scale datasets and aligned with safety and reliability standards.

REFERENCE

- [1] Zhang, M., Zhang, Q., Wang, X., Peng, X., Chen, J., & Yang, H. (2025). Lane detection and road segmentation using deep learning with image-based feature extraction. *Scientific Reports*, 15(1), 18862.
- [2] Eliwa, E. H. I., & Abd El-Hafeez, T. (2025). A robust deep learning pipeline for multi-class road scene understanding and lane detection. *Egyptian Informatics Journal*, 32, 100787.
- [3] Uddin, K. M. M., Bhuiyan, M. T. A., Saad, M. N., Islam, A., & Islam, M. M. (2025). An ensemble deep learning-based approach for lane detection with hyperparameter tuning and model explainability. *Biomedical Materials & Devices*, 3(2), 1463–1490.
- [4] Su, J., Lu, H., Zhang, R., Cui, N., Chen, C., Si, Q., & Song, B. (2025). Lane detection using deep learning models based on real-time video analysis. *Scientific Reports*, 15(1), 22655.
- [5] Rajput, V., Antad, S., Chivate, A., & Dashetwar, I. (2024). Lane detection in autonomous vehicles using machine learning techniques. *J. Electrical Systems*, 20(1s), 944–955.
- [6] Uddin, K. M. M., Al Mamun, A., Chakrabarti, A., Mostafiz, R., & Dey, S. K. (2024). Ensemble deep learning approach for lane detection using hybrid feature selection. *Neuroscience Informatics*, 4(3), 100169.
- [7] Uddin, K. M. M., Sikder, I. A., & Hasan, M. N. (2024). Comparative study on machine learning models for lane detection in autonomous driving systems. *EAI Endorsed Transactions on Internet of Things*, 11.
- [8] Muraru, M. M., Simó, Z., & Iantovics, L. B. (2024). Lane detection based on imbalanced datasets using machine learning with sampling techniques. *Applied Sciences*, 14(22), 10085.
- Lilhore, U. K., Poongodi, M., Kaur, A., Simaiya, S., Algarni, A. D., Elmannai, H., ... & Hamdi, M. (2022). Hybrid model for lane detection using deep learning and image processing techniques. *Computational and Mathematical Methods in Engineering*, 2022(1), 4688327.
- [9] Rahimi, M., Akbari, A., Asadi, F., & Emami, H. (2023). Lane detection performance evaluation using deep learning algorithms: a systematic review. *BMC Computer Science*, 23(1), 341.
- [10] Xiao, T., Wang, C., Yang, M., Yang, J., Xu, X., Shen, L., ... & Ou, C. Q. (2023). Deep learning-based lane detection using multi-feature fusion in autonomous driving systems. *Journal of Intelligent Transportation Systems*, 6(8), e2326890.
- [11] Hariprasad, R., Navamani, T. M., Rote, T. R., & Chauhan, I. (2023). Design and development of an efficient lane detection model for autonomous vehicles. *IEEE Access*, 11, 74290–7430