

Alertmanager configuration

We manage our Alertmanager configuration here using jsonnet. The resultant Kubernetes secret object is uploaded, and is consumed by the Prometheus operator deployment.

The CI jobs for this are run on `ops.gitlab.net` where the variables are configured. See: https://ops.gitlab.net/gitlab-com/runbooks/-/settings/ci_cd

Variables

ALERTMANAGER_SECRETS_FILE

Type: File

Value: A jsonnet file, based on the dummy-secrets.jsonnet template.

CI Jobs

These jobs run in a CI pipeline, view the `.gitlab-ci.yml` to determine how this is configured.

To run a manual deploy, you will need a local secrets file with the filename exported in the `ALERTMANAGER_SECRETS_FILE` variable.

For the production alertmanger, this content is stored in vault at `ops-gitlab-net/gitlab-com/runbooks/ops/`

Then run:

```
kubectl apply --namespace monitoring --filename k8s_alertmanager_secret.yaml
```

- Generate the `alertmanager.yml` file.
`./generate.sh`
- Validate the `alertmanager.yml` looks reasonable.
- The contents of this file are visible as a base64 encoded secret, in the manifest `k8s_alertmanager_secret.yaml`.
- When this secret is uploaded to a namespace containing a prometheus operator and an Alertmanager CRD (which these days is only the ops GKE cluster's monitoring namespace), Alertmanager's config will automatically be updated.