

PostgreSQL HA

This page has historically been about PostgreSQL HA with repmgr. These parts have been removed since we switched to Patroni. Still valid information has been retained.

Consul

Health

- Show consul members. Any error can indicate an issue with consul. Can be run from any node connected to the consul cluster. If cluster issues are expected, run from consul servers to check.

```
# /opt/gitlab/embedded/bin/consul members
```

Commands

- To force an update to `/var/opt/gitlab/consul/databases.ini` on the pgbouncer server

```
# gitlab-ctl restart consul
```

Pgbouncer

Health

- `/var/opt/gitlab/consul/databases.ini` should exist, and it should have a value for `host=XXXXXX`
- Connect to the admin console with `gitlab-ctl pgb-console` – Password should be in 1 Password

- Check database configuration. Check `host` column, and `current_connections` first

```
pgbouncer=# show databases;
```

name	host	port	database	force_user	pool_size
gitlabhq_production	PRIMRAY_HOST	5432	gitlabhq_production		
pgbouncer		6432	pgbouncer	pgbouncer	

(2 rows)

- Check for client connections

```
pgbouncer=# show clients;
```

type	user	database	state	addr	port	local_addr
C	gitlab	gitlabhq_production	active	127.0.0.1	58448	127.0.0.1
...						

- Check for server connections

```
pgbouncer=# show servers;
 type | user | database | state | addr | port | local_addr
-----+-----+-----+-----+-----+-----+-----
  S    | gitlab | gitlabhq_production | idle | PRIMARY_HOST | 5432 | PGBOUNCER_HOS
...

```

PostgreSQL

Health

- Connect to the db console

```
# gitlab-psql -d gitlabhq_production
```

- Check if a node thinks it is a primary or a standby

```
# gitlab-psql -d template1
template1# select * from pg_is_in_recovery();
...
```

f indicates the node is a primary t indicates the node is a standby

- If replication isn't working, check that the replication slots exist and are active. If restart_lsn does not equal pg_current_xlog_location, there is some replication lag.

```
“shell # gitlab-psql -d template1 template1=# select * from
pg_replication_slots ; select * from pg_current_xlog_location();
slot_name | plugin | slot_type | datoid | database | active | ac-
tive_pid | xmin | catalog_xmin | restart_lsn | confirmed_flush_lsn
-----+-----+-----+-----+-----+-----+-----
patroni_04_db_gprd_c_gitlab_production_internal | | physical | | | t |
28881 | | AD/59000060 | ...

```

pg_current_xlog_location
AD/5C000060
(1 row)