

Topology Service Rest

- Service Overview
- **Alerts:** <https://alerts.gitlab.net/#!/alerts?filter=%7Btype%3D%22topology-rest%22%2C%20tier%3D%22sv%22%7D>
- **Label:** gitlab-com/gl-infra/production~“Service::TopologyServiceRest”

Logging

- stg
- prod

Summary

The Topology Service implements a limited set of functions responsible for providing essential features for Cells to operate.

Deployment and service configuration is managed in a separate topology-service-deployer repository.

Deployment configuration including scaling is managed using a Runway service manifest in the topology-service-deployer repository (see `runway.yml` in `.runway/*`).

Configuration for the service is managed in `config.toml`, which is provided as an environment variable as part of deployment in the topology-service-deployer repository (see the `CONFIG_TOML` environment variable defined in `env-*.yaml` in `.runway/*`). Details on the configuration syntax found [here](#).

Architecture

Topology service is a Go container deployed using Runway. It sits in its own GCP project and responds to router requests for information pertaining to Cells.

More detailed documentation found [here](#).

Scalability

Topology service is deployed using Runway and its scaling is handled by Cloud Run and configured as part of Runway deployment ([doc](#)).

Availability

Topology service is deployed to multiple regions. In future, when storing data, the storage system (Cloud Spanner) will also be configured in multiple regions.

Security/Compliance

Currently, no customer data is stored in Cells or in the topology service and is available as a public endpoint.

Monitoring/Alerting

Topology service is deployed using Runway, which supports observability by integrating with the monitoring stack. You can see the metrics via the general Runway Service Metrics dashboard.

Breakglass

- Topology Service Access Procedure