

Mimir recording rules

This directory contains the source files that will generate the recording rules on the directory mimir-rules.

Mimir uses the so called tenant as an abstraction to a set of series (our recording rules). Each tenant is isolated from each other, allowing us to parallelize work as see fit to scale.

At GitLab, we use a combination of cluster, environment, service, and filename as a tenant. The helper function `separateMimirRecordingFiles` provides the building blocks to split the rules by tenants, generating the recording rule files with a valid unique name that works as a namespace for each rule group.

Targeting specific tenants per service

A service can target a specific Mimir tenant. Simply provide the tenant names in the service definition, for example:

```
“diff -git a/metrics-catalog/services/thanos.jsonnet b/metrics-catalog/services/thanos.jsonnet
index a1a24d18f..9ce5d73b1 100644 — a/metrics-catalog/services/thanos.jsonnet
+++ b/metrics-catalog/services/thanos.jsonnet  @@ -23,6  +23,7  @@ local
thanosServiceSelector = { type: ‘thanos’, namespace: ‘thanos’ }; metricsCata-
log.serviceDefinition({ type: ‘thanos’, tier: ‘inf’, + tenants: [‘gitlab-ops’],
tags: [‘golang’, ‘thanos’], ““
```

This configuration will allow outputting recording rules only to the tenant(s) listed.

Further reading

- Grafana Mimir official docs