

DOMAIN WINTER WINNING CAMP

Student Name: Piyush Bhardwaj

UID: 22BCS11108

Branch: CSE

Section/Group: 22BCS_IOT-639/B


VERY EASY

1. Binary Tree Inorder Traversal

Given the root of a binary tree, return the inorder traversal of its nodes' values. **Example**

1:

Input: root = [1,null,2,3] **Output:** [1,3,2] **Explanation:**



CODE:

```
#include <iostream>
#include <vector> using
namespace std; struct
TreeNode {
    int val;
    TreeNode *left;
    TreeNode *right;
    TreeNode(int x) : val(x), left(nullptr), right(nullptr) {}
};

void inorder(TreeNode* root, vector<int>& result) {
```

```
if (!root) return;    inorder(root->left, result);
result.push_back(root->val);    inorder(root->right, result);
}
```

```
vector<int> inorderTraversal(TreeNode* root) {
    vector<int> result;
    inorder(root, result);    return result;
}
```

```
int main() {
    // Create tree: [1, null, 2, 3]
    TreeNode* root = new TreeNode(1);    root-
>right = new TreeNode(2);    root->right-
>left = new TreeNode(3);
```

```
    vector<int> result = inorderTraversal(root);
    for (int val : result) {        cout << val << " ";
    }
    cout << endl;

    return 0;
}
```

1 3 2


2.Binary Tree Preorder Traversal

Given the root of a binary tree, return the preorder traversal of its nodes' values.

Example 1:

Input: root = [1,null,2,3] **Output:**

[1,2,3] **Explanation:**



CODE:

```
#include <iostream> #include
<vector> using
namespace std;

struct TreeNode {
    int val;
    TreeNode *left;
    TreeNode *right;
    TreeNode(int x) : val(x), left(nullptr), right(nullptr) { } };


void preorder(TreeNode* root, vector<int>& result) {
    if (!root) return;    result.push_back(root->val);
    preorder(root->left, result);    preorder(root->right, result);
}

vector<int> preorderTraversal(TreeNode* root) {
    vector<int> result;    preorder(root, result);    return
    result;
}

int main() {
    // Create tree: [1, null, 2, 3]
    TreeNode* root = new TreeNode(1);    root-
>right = new TreeNode(2);    root->right-
>left = new TreeNode(3);

    vector<int> result = preorderTraversal(root);
    for (int val : result) {        cout << val << " ";
    }
    cout << endl;

    return 0; }
```



1 2 3

3. Binary Tree - Sum of All Nodes

Given the root of a binary tree, you need to find the sum of all the node values in the binary tree.

Example 1:

Input: root = [5, 2, 6, 1, 3, 4, 7]

Output: 28

Explanation: The sum of all nodes is $5 + 2 + 6 + 1 + 3 + 4 + 7 = 28$.

CODE:

```
#include <iostream>
using namespace std;

struct TreeNode {
    int val;
    TreeNode *left;
    TreeNode *right;
    TreeNode(int x) : val(x), left(nullptr), right(nullptr) { } };

int sumOfAllNodes(TreeNode* root) {
    if (!root) return 0;
    return root->val + sumOfAllNodes(root->left) + sumOfAllNodes(root->right); }

int main() {
    // Create tree: [5, 2, 6, 1, 3, 4, 7]
    TreeNode* root = new TreeNode(5);
    root->left = new TreeNode(2);    root->right
    = new TreeNode(6);    root->left->left = new
    TreeNode(1);    root->left->right = new
    TreeNode(3);    root->right->left = new
    TreeNode(4);    root->right->right =
    new TreeNode(7);

    cout << "Sum of all nodes: " << sumOfAllNodes(root) << endl;

    return 0;
}
```

```
Sum of all nodes: 28
```

Easy:

1. Same Tree

Two binary trees are considered the same if they are structurally identical, and the nodes have the same value.

Example 1:

Input: p = [1,2,3], q = [1,2,3]

Output: true CODE:

```
#include <iostream>
```

```
using namespace std;
```

```
struct TreeNode {
```

```
int val;
```

```
    TreeNode* left;
```

```
    TreeNode* right;
```

```
    TreeNode(int x) : val(x), left(nullptr), right(nullptr) {}
```

```
};
```

```
bool isSameTree(TreeNode* p, TreeNode* q) {    if (!p && !q) return true;
```

```
// Both trees are empty    if (!p || !q || p->val != q->val) return false; //
```

```
Structure or value mismatch    return isSameTree(p->left, q->left) &&
```

```
isSameTree(p->right, q->right); }
```

```
int main() {
```

```
    // Create tree p: [1, 2, 3]
```

```
    TreeNode* p = new TreeNode(1);    p->
```

```
>left = new TreeNode(2);    p->
```

```
>right = new TreeNode(3);
```

```
    // Create tree q: [1, 2, 3]
```

```
    TreeNode* q = new TreeNode(1);    q->
```

```
>left = new TreeNode(2);    q->
```

```
>right = new TreeNode(3);
```

```
    cout << (isSameTree(p, q) ? "true" : "false") << endl;
```


```
    return 0; }.
```



2. Invert Binary Tree

Given the root of a binary tree, invert the tree, and return its root

Example 1:



Input: root = [4,2,7,1,3,6,9] **Output:**
[4,7,2,9,6,3,1]

CODE:

```
#include <iostream>
```

```
using namespace std;
```

```
struct TreeNode {
    int val;
    TreeNode* left;
    TreeNode* right;
    TreeNode(int x) : val(x), left(nullptr), right(nullptr) {} };
```

```
TreeNode* invertTree(TreeNode* root) {
    if (!root) return nullptr;    swap(root->left, root->right);
    // Swap left and right child
    invertTree(root->left);    invertTree(root->right);
    return root;
}
```

```
void preorderTraversal(TreeNode* root) {
    if (!root) return;    cout <<
    root->val << " ";
    preorderTraversal(root->left);
    preorderTraversal(root->right);
}
```

```
int main() {
    // Create tree: [4, 2, 7, 1, 3, 6, 9]
    TreeNode* root = new TreeNode(4);
    root->left = new TreeNode(2);    root->right
    = new TreeNode(7);    root->left->left = new
    TreeNode(1);    root->left->right = new
    TreeNode(3);    root->right->left = new
    TreeNode(6);    root->right->right =
    new TreeNode(9);
```

```
root = invertTree(root);

preorderTraversal(root); // Expected output: 4 7 9 6 2 3 1
cout << endl;


return 0; }
```

4 7 9 6 2 3 1

3. Path Sum

Given a binary tree and a sum, return true if the tree has a root-to-leaf path such that adding up all the values along the path equals the given sum. Return false if no such path can be found.

Example 1:



Input: root = [5,4,8,11,null,13,4,7,2,null,null,null,1], targetSum = 22

Output: true

Explanation: The root-to-leaf path with the target sum is shown.

CODE:

```
#include <iostream>
using namespace std;

struct TreeNode {
    int val;
    TreeNode* left;
    TreeNode* right;
    TreeNode(int x) : val(x), left(nullptr), right(nullptr) { }
};
```

```
bool hasPathSum(TreeNode* root, int targetSum) {    if (!root) return false;    if (!root->left &&
!root->right) return root->val == targetSum; // Check if leaf    return hasPathSum(root->left,
targetSum - root->val) || hasPathSum(root->right, targetSum - root->val);
}
```

```
int main() {
    // Create tree: [5, 4, 8, 11, null, 13, 4, 7, 2, null, null, 1]
    TreeNode* root = new TreeNode(5);    root->left = new
    TreeNode(4);    root->right = new TreeNode(8);    root->left-
    >left = new TreeNode(11);    root->left->left->left = new
    TreeNode(7);    root->left->left->right = new
    TreeNode(2);    root->right->left = new
    TreeNode(13);    root->right->right = new
    TreeNode(4);    root->right->right->right =
    new TreeNode(1);

    int targetSum = 22;
    cout << (hasPathSum(root, targetSum) ? "true" : "false") << endl;

    return 0;
}
```

true

Medium:

1. Construct Binary Tree from Preorder and Inorder Traversal

Given two integer arrays preorder and inorder where preorder is the preorder traversal of a binary tree and inorder is the inorder traversal of the same tree, construct and return the binary tree.

Example 1:

Input: preorder = [3,9,20,15,7], inorder = [9,3,15,20,7] **Output:**
[3,9,20,null,null,15,7]

CODE:

```
#include <iostream>
#include <unordered_map> #include
<vector> using
namespace std;

struct TreeNode {
    int val;
```



```
TreeNode* left;
TreeNode* right;
TreeNode(int x) : val(x), left(nullptr), right(nullptr) { } };

TreeNode* buildTreeHelper(vector<int>& preorder, int preStart, int preEnd,
vector<int>& inorder, int inStart, int inEnd,
unordered_map<int, int>& inMap) {    if (preStart > preEnd || inStart > inEnd)
return nullptr;

    TreeNode* root = new TreeNode(preorder[preStart]);    int
inRoot = inMap[root->val];
    int numsLeft = inRoot - inStart;

    root->left = buildTreeHelper(preorder, preStart + 1, preStart + numsLeft, inorder, inStart, inRoot -
1, inMap);
    root->right = buildTreeHelper(preorder, preStart + numsLeft + 1, preEnd, inorder, inRoot + 1,
inEnd, inMap);

    return root;
}

TreeNode* buildTree(vector<int>& preorder, vector<int>& inorder) {
unordered_map<int, int> inMap;
    for (int i = 0; i < inorder.size(); i++) inMap[inorder[i]] = i;    return
buildTreeHelper(preorder, 0, preorder.size() - 1, inorder, 0, inorder.size() - 1, inMap); }

void printInorder(TreeNode* root) {
if (!root) return;
printInorder(root->left);    cout << root->val
<< " ";    printInorder(root->right);
}

int main() {    vector<int> preorder = {3,
9, 20, 15, 7};    vector<int> inorder = {9,
3, 15, 20, 7};

    TreeNode* root = buildTree(preorder, inorder);

    printInorder(root); // Output: 9 3 15 20 7
cout << endl;

    return 0;
}
```

}

9 3 15 20 7

2. Construct Binary Tree from Inorder and Postorder Traversal

Given two integer arrays inorder and postorder where inorder is the inorder traversal of a binary tree and postorder is the postorder traversal of the same tree, construct and return the binary tree.

Example 1:

Input: inorder = [9,3,15,20,7], postorder = [9,15,7,20,3] **Output:**
[3,9,20,null,null,15,7]

CODE:

```
#include <iostream>
#include <unordered_map> #include
<vector> using
namespace std;

struct TreeNode {
    int val;
    TreeNode* left;
    TreeNode* right;
    TreeNode(int x) : val(x), left(nullptr), right(nullptr) { };
    TreeNode* buildTreeHelper(vector<int>& inorder, int inStart, int inEnd,
vector<int>& postorder, int postStart, int postEnd, unordered_map<int,
int>& inMap) {
        if (inStart > inEnd || postStart > postEnd) return nullptr;

        TreeNode* root = new TreeNode(postorder[postEnd]);
        int inRoot = inMap[root->val];
        int numsLeft = inRoot - inStart;

        root->left = buildTreeHelper(inorder, inStart, inRoot - 1, postorder, postStart, postStart + numsLeft
- 1, inMap);    root->right = buildTreeHelper(inorder, inRoot + 1, inEnd, postorder, postStart +
numsLeft, postEnd - 1, inMap);

        return root;
    }
}
```

```
TreeNode* buildTree(vector<int>& inorder, vector<int>& postorder) {
unordered_map<int, int> inMap;
    for (int i = 0; i < inorder.size(); i++) inMap[inorder[i]] = i;

    return buildTreeHelper(inorder, 0, inorder.size() - 1, postorder, 0, postorder.size() - 1, inMap); }

void printInorder(TreeNode* root) {
if (!root) return;
printInorder(root->left);    cout << root->val
<< " ";    printInorder(root->right);
}

int main() {    vector<int> inorder = {9, 3,
15, 20, 7};    vector<int> postorder = {9,
15, 7, 20, 3};

    TreeNode* root = buildTree(inorder, postorder);

    printInorder(root); // Output: 9 3 15 20 7
    cout << endl;

    return 0;
}
```



3. Sum Root to Leaf Numbers

You are given the root of a binary tree containing digits from 0 to 9 only.


Each root-to-leaf path in the tree represents a number.

For example, the root-to-leaf path 1 -> 2 -> 3 represents the number 123.

Return the total sum of all root-to-leaf numbers. Test cases are generated so that the answer will fit in a 32-bit integer.

A leaf node is a node with no children.

Example 1:



Input: root = [1,2,3] **Output:** 25 **Explanation:**

The root-to-leaf path 1->2 represents the number 12.

The root-to-leaf path 1->3 represents the number 13.

Therefore, sum = 12 + 13 = 25.

CODE:

```
#include <iostream>
```

```
using namespace std;
```

```
struct TreeNode {
```

```
    int val;
```

```
    TreeNode* left;
```

```
    TreeNode* right;
```

```
    TreeNode(int x) : val(x), left(nullptr), right(nullptr) {} };
```

```
int sumNumbersHelper(TreeNode* root, int currentSum) {    if
```

```
(!root) return 0;
```

```
    currentSum = currentSum * 10 + root->val;    if (!root->left  
&& !root->right) return currentSum; // Leaf node
```

```
    return sumNumbersHelper(root->left, currentSum) + sumNumbersHelper(root->right,  
currentSum);
```

```
}
```

```
int sumNumbers(TreeNode* root) {
```

```
return sumNumbersHelper(root, 0);
```

```
}
```

```
int main() {
```

```
    TreeNode* root = new TreeNode(1);    root->
```

```
left = new TreeNode(2);    root->
```

```
right = new TreeNode(3);
```

```
    cout << sumNumbers(root) << endl; // Output: 25
```

```
    return 0;
```

```
}
```


Hard:

1. Binary Tree Right Side View

Given the root of a binary tree, imagine yourself standing on the right side of it, return the values of the nodes you can see ordered from top to bottom.

Example 1:

Input: root = [1,2,3,null,5,null,4] **Output:** [1,3,4]



Explanation:

CODE:

```
#include <iostream>
```

```
#include <vector> #include
```

```
<queue> using
```

```
namespace std;
```

```
struct TreeNode {
```

```
    int val;
```

```
    TreeNode* left;
```

```
    TreeNode* right;
```

```
    TreeNode(int x) : val(x), left(nullptr), right(nullptr) {} };
```

```
vector<int> rightSideView(TreeNode* root) {
```

```
    vector<int> result;
```

```
    if (!root) return result;
```

```
    queue<TreeNode*> q;    q.push(root);
```

```

        while (!q.empty()) {            int
levelSize = q.size();                for (int i = 0;
i < levelSize; i++) {                TreeNode*
current = q.front();                q.pop();
        // Add the last node of the current level to the result        if
(i == levelSize - 1) result.push_back(current->val);

        if (current->left) q.push(current->left);
if (current->right) q.push(current->right);
        }    }
return result;
}

int main() {
    TreeNode* root = new TreeNode(1);
    root->left = new TreeNode(2);    root->right
= new TreeNode(3);    root->left->right =
new TreeNode(5);    root->right->right =
new TreeNode(4);

    vector<int> result = rightSideView(root);
for (int val : result) {        cout << val << "
";
    }
    // Output: 1 3 4    return
0;
}

```

1 3 4


2. Binary Tree Maximum Path Sum

A path in a binary tree is a sequence of nodes where each pair of adjacent nodes in the sequence has an edge connecting them. A node can only appear in the sequence at most once. Note that the path does not need to pass through the root.

The path sum of a path is the sum of the node's values in the path.

Given the root of a binary tree, return the maximum path sum of any non-empty path.

Example 1:



Input: root = [1,2,3]

Output: 6

Explanation: The optimal path is 2 -> 1 -> 3 with a path sum of 2 + 1 + 3 = 6.

CODE:

```
#include <iostream> #include
<climits> using
namespace std;
```

```
struct TreeNode {
    int val;
    TreeNode* left;
    TreeNode* right;
    TreeNode(int x) : val(x), left(nullptr), right(nullptr) {}
};
```

```
int maxPathSumHelper(TreeNode* root, int& maxSum) {    if
(!root) return 0;
```

```
    // Compute maximum path sums for left and right subtrees    int leftMax
= max(0, maxPathSumHelper(root->left, maxSum));    int rightMax =
max(0, maxPathSumHelper(root->right, maxSum));
```

```
    // Update the overall maximum path sum    maxSum = max(maxSum,
leftMax + rightMax + root->val);
```

```
    // Return the maximum path sum including the current node    return
max(leftMax, rightMax) + root->val;
}
```

```
int maxPathSum(TreeNode* root) {    int
maxSum = INT_MIN;
maxPathSumHelper(root, maxSum);
    return maxSum;
}
```

```
int main() {
```

```
TreeNode* root = new TreeNode(1);    root->
>left = new TreeNode(2);    root->
>right = new TreeNode(3);

    cout << maxPathSum(root) << endl; // Output: 6
    return 0;
}
```

6

Very Hard:


1. Count Paths That Can Form a Palindrome in a Tree

You are given a tree (i.e. a connected, undirected graph that has no cycles) rooted at node 0 consisting of n nodes numbered from 0 to $n - 1$. The tree is represented by a 0-indexed array `parent` of size n , where `parent[i]` is the parent of node i . Since node 0 is the root, `parent[0] == -1`. You are also given a string `s` of length n , where `s[i]` is the character assigned to the edge between i and `parent[i]`. `s[0]` can be ignored.

Return the number of pairs of nodes (u, v) such that $u < v$ and the characters assigned to edges on the path from u to v can be rearranged to form a palindrome.

A string is a palindrome when it reads the same backwards as forwards.

Example 1:



Input: `parent = [-1,0,0,1,1,2]`, `s = "acaabc"` **Output:** 8

Explanation: The valid pairs are:

- All the pairs (0,1), (0,2), (1,3), (1,4) and (2,5) result in one character which is always a palindrome.
- The pair (2,3) result in the string "aca" which is a palindrome.
- The pair (1,5) result in the string "cac" which is a palindrome.

- The pair (3,5) result in the string "acac" which can be rearranged into the palindrome "acca".

CODE:

```
#include <iostream>
#include <vector>
#include <unordered_map> #include
<unordered_set> using
namespace std;

// Helper function to perform DFS and count palindromic paths
void dfs(int node, int mask, const vector<vector<int>>& graph, const string& s, unordered_map<int,
int>& count, int& result) {
    // Update result based on the current mask    result
    += count[mask];    for (int i = 0; i <
    26; ++i) {        result += count[mask
    ^ (1 << i)];
    }
    // Increment the count for the current mask
    count[mask]++;

    // Recur for child nodes    for
    (int child : graph[node]) {
        dfs(child, mask ^ (1 << (s[child] - 'a')), graph, s, count, result);    }

    // Decrement the count to backtrack    count[mask]--;
    ;
    }

int countPalindromePaths(vector<int>& parent, string s) {
    int n = parent.size();    vector<vector<int>> graph(n);    for
    (int i = 1; i < n; ++i) {
        graph[parent[i]].push_back(i);
    }

    unordered_map<int, int> count;
    count[0] = 1; // Initial mask (no characters)    int
    result = 0;
    dfs(0, 0, graph, s, count, result);
    return result;
}

int main() {
    vector<int> parent = {-1, 0, 0, 1, 1, 2};
```

```
string s = "acaabc";
cout << countPalindromePaths(parent, s) << endl; // Output: 8
return 0;
}
```


8

2. Longest Path With Different Adjacent Characters

You are given a tree (i.e. a connected, undirected graph that has no cycles) rooted at node 0 consisting of n nodes numbered from 0 to $n - 1$. The tree is represented by a 0-indexed array `parent` of size n , where `parent[i]` is the parent of node i . Since node 0 is the root, `parent[0] == -1`. You are also given a string `s` of length n , where `s[i]` is the character assigned to node i .

Return the length of the longest path in the tree such that no pair of adjacent nodes on the path have the same character assigned to them.

Example 1:



Input: `parent = [-1,0,0,1,1,2], s = "abacbe"`

Output: 3

Explanation: The longest path where each two adjacent nodes have different characters in the tree is the path: 0 -> 1 -> 3. The length of this path is 3, so 3 is returned. It can be proven that there is no longer path that satisfies the conditions.

CODE:

```
from collections import defaultdict
```

```
def longestPath(parent, s):    n
    = len(parent)
    adj = defaultdict(list)
```

```
    # Build the adjacency list of the tree    for
    i in range(1, n):        adj[parent[i]].append(i)
```

```
    # This will store the longest path starting from each node    longest
    = [0] * n
```

```
def dfs(node):
    first_max, second_max = 0, 0

    # Explore all the children of the current node
    for child in adj[node]:
        child_path =
        dfs(child)

        # Only consider the child's path if the characters are different
        if s[child] != s[node]:
            if child_path > first_max:
                second_max = first_max
                first_max
                = child_path
            elif child_path >
            second_max:
                second_max = child_path

        # The longest path that passes through this node is the sum of first_max and second_max + 1
        (for the current node itself)
        longest[node] = first_max + 1
        #
        Return the length of the longest path for the
        subtree rooted at this node
        return first_max + 1

    # Start DFS from the root (node 0)
    dfs(0)

    # The answer is the longest path in the tree
    return
    max(longest)

# Example usage
parent = [-1, 0, 0, 1, 1, 2]
s = "abacbe"
print(longestPath(parent, s)) # Output: 3
```